

Brussels, 11.11.2013 COM(2013) 776 final

ANNEXES 1 to 2

## **ANNEXES**

to the

## **Proposal for a COUNCIL REGULATION**

suspending the autonomous Common Customs Tariff duties on certain agricultural and industrial products and repealing Regulation (EU) No 1344/2011

EN EN

## ANNEX I

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 0710 21 00	10	Peas in pods, of the species <i>Pisum sativum</i> of the variety <i>Hortense axiphium</i> , frozen, of a thickness of not more than 6 mm, to be used, in their pods, in the manufacture of prepared meals <sup>(1)(2)</sup>	0 %	31.12.2018
ex 0710 80 95	50	Bamboo shoots, frozen, not put up for retail sale	0 %	31.12.2018
ex 0711 59 00	11	Mushrooms, excluding mushrooms of the genera <i>Agaricus, Calocybe, Clitocybe, Lepista, Leucoagaricus, Leucopaxillus, Lyophyllum</i> and <i>Tricholoma</i> , provisionally preserved in brine, in sulphur water, or in other preservative solutions, but unsuitable in that state for immediate consumption, for the food-canning industry (1)	0 %	31.12.2016
ex 0712 32 00 ex 0712 33 00 ex 0712 39 00	10 10 31	Mushrooms, excluding mushrooms of the genus <i>Agaricus</i> , dried, whole or in identifiable slices or pieces, for treatment other than simple repacking for retail sale (1)(2)	0 %	31.12.2018
ex 0804 10 00	30	Dates, fresh or dried, for use in the manufacture (excluding packing) of products of drink or food industries	0 %	31.12.2018
ex 0810 40 50	10	Cranberries of the species <i>Vaccinium macrocarpon</i> , fresh, for use in the manufacture (excluding packing) of products of drink or food industries	0 %	31.12.2018
0811 90 50 0811 90 70 ex 0811 90 95	70	Fruit of the genus <i>Vaccinium</i> , uncooked or cooked by steaming or boiling in water, frozen, not containing added sugar or other sweetening matter	0 %	31.12.2018
ex 0811 90 95	20	Boysenberries, frozen, not containing added sugar, not put up for retail sale	0 %	31.12.2018
ex 0811 90 95	30	Pineapple (Ananas comosus), in pieces, frozen	0 %	31.12.2018
ex 0811 90 95	40	Rose-hips, uncooked or cooked by steaming or boiling in water, frozen, not containing added sugar or other sweetening matter	0 %	31.12.2018
ex 1511 90 19 ex 1511 90 91 ex 1513 11 10 ex 1513 19 30 ex 1513 21 10 ex 1513 29 30	10 10 10 10 10 10	Palm oil, coconut (copra) oil, palm kernel oil, for the manufacture of:  — industrial monocarboxylic fatty acids of subheading 3823 19 10,  — methyl esters of fatty acids of heading 2915 or 2916,  — fatty alcohols of subheadings 2905 17, 2905 19 and 3823 70 used for the manufacture of cosmetics, washing products or pharmaceutical products,  — fatty alcohols of subheading 2905 16, pure or mixed, used for the manufacture of cosmetics, washing products or pharmaceutical products,  — stearic acid of subheading 3823 11 00 or  — goods of heading 3401	0 %	31.12.2018
ex 1515 90 99	92	Vegetable oil, refined, containing by weight 35 % or more but not more than 50 % of arachidonic acid or 35 % or more but not more than 50 % of docosahexaenoic acid	0 %	31.12.2018
ex 1516 20 96	20	Jojoba oil, hydrogenated and interesterified, without any further chemical modification and not subjected to any texturisation process	0 %	31.12.2014
ex 1517 90 99	10	Vegetable oil, refined, containing by weight 25 % or more but not more than 50 % arachidonic acid or 12 % or more but not more than 50 % docosahexaenoic acid and standardized with high oleic sunflower oil (HOSO)	0 %	31.12.2016
ex 1902 30 10 ex 1903 00 00	10 20	Transparent noodles, cut in pieces, obtained from beans ( <i>Vigna radiata</i> (L.) Wilczek), not put up for retail sale	0 %	31.12.2018
ex 2005 91 00	10	Bamboo shoots, prepared or preserved, in immediate packings of a net content of more than 5 kg	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 2007 99 50 ex 2007 99 50	81 91	Acerola puree concentrate, obtained by cooking:  — of the Genus <i>Malpighia spp.</i> ,  — with a sugar content by weight of more than 13 % but not more than 30 % for use in the manufacture of products of food and drink industry	9 % (3)	31.12.2017
ex 2007 99 50 ex 2007 99 50	82 92	Acidified banana puree concentrate, obtained by cooking:  — of the Genus <i>Musa cavendish</i> ,  — with a sugar content by weight of more than 13 % but not more than 30 % for use in the manufacture of products of food and drink industry	11.5 % (3)	31.12.2017
ex 2007 99 50 ex 2007 99 50 ex 2007 99 93	83 93 10	Mango puree concentrate, obtained by cooking:  — of the Genus Mangifera spp.,  — with a sugar content by weight of not more than 30 % for use in the manufacture of products of food and drink industry  (1)	6 % (3)	31.12.2017
ex 2007 99 50 ex 2007 99 50	84 94	Papaya puree concentrate, obtained by cooking:  — of the Genus <i>Carica spp.</i> ,  — with a sugar content by weight of more than 13 % but not more than 30 % for use in the manufacture of products of food and drink industry	7.8 % (3)	31.12.2017
ex 2007 99 50 ex 2007 99 50	85 95	Guava puree concentrate, obtained by cooking:  — of the Genus <i>Psidium spp.</i> ,  — with a sugar content by weight of more than 13 % but not more than 30 % for use in the manufacture of products of food and drink industry	6 % (3)	31.12.2017
ex 2008 93 91	20	Sweetened dried cranberries, excluding packing alone as processing, for the manufacture of products of food processing industries	0 %	31.12.2017
ex 2008 99 48	94	Mango puree:  — not from concentrate,  — of the genus <i>Mangifera</i> ,  — of a Brix value of 14 or more, but not more than 20 used in the manufacture of products of drink industry	6 %	31.12.2015
ex 2008 99 49 ex 2008 99 99	30 40	Seedless boysenberry puree not containing added spirit, whether or not containing added sugar	0 %	31.12.2014
ex 2008 99 49 ex 2008 99 99	70 11	Blanched vine leaves of the genus <i>Karakishmish</i> , in brine, containing by weight:  — more than 6 % of salt concentration,  — 0,1 % or more but not more than 1,4 % of acidity expressed as citric acid monohydrate and  — whether or not but not more than 2 000 mg/kg of sodium benzoate according CODEX STAN 192-1995 for use in the manufacture of stuffed vine leaves with rice	0 %	31.12.2017
ex 2009 41 92 ex 2009 41 99	20 70	Pineapple juice:  — not from concentrate,  — of the genus <i>Ananas</i> ,  — of a Brix value of 11 or more but not more than 16, used in the manufacture of products of drink industry  (1)	8 %	31.12.2015

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 2009 49 30	91	Pineapple juice, other than in powder form:  — with a Brix value of more than 20 but not more than 67,  — a value of more than € 30 per 100 kg net weight,  — containing added sugars used in the manufacture of products of food or drink industry  (1)	0 %	31.12.2014
ex 2009 81 31	10	Cranberry juice concentrate:  — of a Brix value of 40 or more but not more than 66,  — in immediate packings of a content of 50 litres or more	0 %	31.12.2014
ex 2009 89 79	20	Frozen boysenberry juice concentrate with a Brix value of 61 or more, but not more than 67, in immediate packing of a content of 50 litres or more	0 %	31.12.2016
ex 2009 89 79	30	Frozen acerola juice concentrate:  — with a Brix value of more than 48 but not more than 67,  — in immediate packings of a content of 50 litres or more	0 %	31.12.2018
ex 2009 89 79	85	Acai berry juice concentrate:  — of the species Euterpe oleracea,  — frozen,  — not sweetened,  — not in powder form,  — of a Brix value of 23 or more but not more than 32, in immediate packings of a content of 10 kg or more	0 %	31.12.2016
ex 2009 89 99	93	Untreated frozen coconut water, in immediate packing of a content of 50 litres or more	0 %	31.12.2016
ex 2106 10 20	10	Soya protein isolate, containing by weight 6,6 % or more but not more than 8,6 % of calcium phosphate	0 %	31.12.2018
ex 2106 90 92	45	Preparation containing by weight:  — more than 30 % but not more than 35 % licorice extract,  — more than 65 % but not more than 70 % tricaprylin, standardized by weight to 3 % or more but not more than 4 % glabridin	0 %	31.12.2016
ex 2519 90 10	10	Fused magnesia with a purity by weight of 97 % or more	0 %	31.12.2016
ex 2804 50 90	10	Tellurium of a purity by weight of 99,99 % or more, but not more than 99,999 % by weight (CAS RN 13494-80-9)	0 %	31.12.2018
2804 70 00		Phosphorus	0 %	31.12.2018
ex 2805 19 90	10	Lithium metal of a purity by weight of 99,7 % or more (CAS RN 7439-93-2)	0 %	31.12.2017
ex 2805 30 10	10	Alloy of cerium and other rare-earth metals, containing by weight 47 % or more of cerium	0 %	31.12.2018
ex 2805 30 90 ex 2805 30 90 ex 2805 30 90	45 55 65	Rare-earth metals, scandium and yttrium, of a purity by weight of 95 % or more	0 %	31.12.2015
ex 2811 19 80	10	Sulphamidic acid (CAS RN 5329-14-6)	0 %	31.12.2018
ex 2811 19 80	20	Hydrogen iodide (CAS RN 10034-85-2)	0 %	31.12.2016
ex 2811 19 80	30	Phosphorous acid (CAS RN 10294-56-1)/phosphonic acid (CAS RN 13598-36-2) used as an ingredient for production of additives used in poly(vinyl chloride) industry (1)	0 %	31.12.2017
ex 2811 22 00	10	Silicon dioxide (CAS RN 7631-86-9) in the form of powder, for use in the manufacture of high performance liquid chromatography columns (HPLC) and	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		sample preparation cartridges		
ex 2811 22 00	30	Balls of porous white silica of a particle size of more than 1 $\mu m$ for use in the manufacture of cosmetic products $^{(1)}$	0 %	31.12.2016
ex 2812 90 00	10	Nitrogen trifluoride (CAS RN 7783-54-2)	0 %	31.12.2018
ex 2816 40 00	10	Barium hydroxide (CAS RN 17194-00-2)	0 %	31.12.2017
ex 2818 10 91	10	Sintered corundum with micro crystalline structure, containing by weight: — 94 % or more, but not more than 98,5 % of $\alpha$ -Al <sub>2</sub> O <sub>3</sub> (CAS RN 1344-28-1), — 2 % ( $\pm$ 1,5 %) of magnesium spinel (CAS RN 1309-48-4), — 1 % ( $\pm$ 0,6 %) of yttrium oxide (CAS RN 1314-36-9), and	0 %	31.12.2015
		— either 2 % (± 1,2 %) of lanthanum oxide (CAS RN 1312-81-8) — or 2 % (± 1,2 %) of lanthanum oxide (CAS RN 1312-81-8) and neodymium oxide (CAS RN 1313-97-9) with less than 50 % of the total weight having a particle size of more than 10 mm		
ex 2818 20 00	10	Activated alumina with a specific surface area of at least 350 m <sup>2</sup> /g	0 %	31.12.2014
ex 2818 30 00	10	Aluminium hydroxide oxide in the form of pseudo-boehmite	4 %	31.12.2018
2819 10 00		Chromium trioxide (CAS RN 1333-82-0)	0 %	31.12.2016
ex 2819 90 90	10	Dichromium trioxide for use in metallurgy (CAS RN 1308-38-9)	0 %	31.12.2016
ex 2823 00 00	10	Titanium dioxide (CAS RN 13463-67-7):  — of a purity by weight of 99,9 % or more,  — with an average grain-size of 1,2 μm or more but not more than 1,8 μm  — with a specific surface of 5,0 m²/g or more, but not more than 7,5 m²/g	0 %	31.12.2017
ex 2823 00 00	20	Titanium dioxide (CAS RN 13463-67-7) with a purity by weight of 99,7 % or more and containing by weight:  — not more than 0,005 % of potassium and sodium combined (expressed as elemental sodium and elemental potassium),  — not more than 0,01 % of phosphorus (expressed as elemental phosphorus), for use in the metallurgy	0 %	31.12.2017
ex 2825 10 00	10	Hydroxylammonium chloride (CAS RN 5470-11-1)	0 %	31.12.2017
ex 2825 50 00	20	Copper (I or II) oxide containing by weight 78 % or more of copper and not more than 0,03 % of chloride	0 %	31.12.2018
ex 2825 60 00	10	Zirconium dioxide (CAS RN 1314-23-4)	0 %	31.12.2017
ex 2826 19 90	10	Tungsten hexafluoride with a purity of 99,9 % by weight or more (CAS RN 7783-82-6)	0 %	31.12.2015
ex 2826 90 80	15	Lithium hexafluorophosphate (CAS RN 21324-40-3)	0 %	31.12.2016
ex 2827 39 85	10	Copper monochloride of a purity by weight of 96 % or more but not more than 99 % (CAS RN 7758-89-6)	0 %	31.12.2018
ex 2827 39 85	20	Antimony pentachloride of a purity by weight of 99 % or more (CAS RN 7647-18-9)	0 %	31.12.2016
ex 2827 39 85	30	Manganese dichloride (CAS RN 7773-01-5)	0 %	31.12.2014
ex 2827 49 90	10	Hydrated zirconium dichloride oxide	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 2830 10 00	10	Disodium tetrasulphide, containing by weight 38 % or less of sodium calculated on the dry weight	0 %	31.12.2018
ex 2833 29 80	20	Manganese sulphate monohydrate (CAS RN 10034-96-5)	0 %	31.12.2018
ex 2833 29 80	30	Zirconium sulphate (CAS RN 14644-61-2)	0 %	31.12.2015
ex 2835 10 00	10	Sodium hypophosphite monohydrate (CAS RN 10039-56-2)	0 %	31.12.2017
ex 2836 91 00	20	Lithium carbonate, containing one or more of the following impurities at the concentrations indicated:  — 2 mg/kg or more of arsenic,  — 200 mg/kg or more of calcium,  — 200 mg/kg or more of chlorides,  — 20 mg/kg or more of iron,  — 150 mg/kg or more of magnesium,  — 20 mg/kg or more of heavy metals,  — 300 mg/kg or more of potassium,  — 300 mg/kg or more of sodium,  — 200 mg/kg or more of sulphates, determined according to the methods specified in the European Pharmacopæia	0 %	31.12.2018
ex 2836 99 17	20	Zirconium (IV) basic carbonate (CAS RN 15667-84-2)	0 %	31.12.2018
ex 2837 19 00	20	Copper cyanide (CAS RN 544-92-3)	0 %	31.12.2018
ex 2837 20 00	10	Tetrasodium hexacyanoferrate (II) (CAS RN 13601-19-9)	0 %	31.12.2016
ex 2837 20 00	20	Ammonium iron (III) hexacyanoferrate (II) (CAS RN 25869-00-5)	0 %	31.12.2017
ex 2839 19 00	10	Disodium disilicate (CAS RN 13870-28-5)	0 %	31.12.2017
ex 2839 90 00	20	Calcium silicate (CAS RN 1344-95-2)	0 %	31.12.2018
2841 30 00		Sodium dichromate (CAS RN 10588-01-9)	0 %	31.12.2018
ex 2841 80 00	10	Diammonium wolframate (ammonium paratungstate) (CAS RN 11120-25-5)	0 %	31.12.2017
ex 2841 90 85	10	Lithium cobalt(III) oxide with a cobalt content of at least 59 % (CAS RN 12190-79-3)	0 %	31.12.2017
ex 2841 90 85	20	Potassium titanium oxide in powder form with a purity of 99 % or more (CAS RN 12056-51-8)	0 %	31.12.2018
ex 2842 10 00	10	Synthetic Beta Zeolite powder	0 %	31.12.2018
ex 2842 10 00	20	Synthetic Chabasite Zeolite Powder	0 %	31.12.2014
ex 2842 90 10	10	Sodium selenate (CAS RN 13410-01-0)	0 %	31.12.2014
ex 2843 29 00	10	Silver oxide, nitrate- and carbonate-free, with a silver content of at least 99,99 % by weight of the metal content, for the manufacture of silver oxide batteries (1)	0 %	31.12.2016
2845 10 00		Heavy water (deuterium oxide) (Euratom) (CAS RN 7789-20-0)	0 %	31.12.2018
2845 90 10		Deuterium and compounds thereof; hydrogen and compounds thereof, enriched in deuterium; mixtures and solutions containing these products ( <i>Euratom</i> )	0 %	31.12.2018
ex 2845 90 90	10	Helium-3 (CAS RN 14762-55-1)	0 %	31.12.2016
ex 2845 90 90	20	Water enriched at a level of 95 % or more by weight with oxygen-18 (CAS RN 14314-42-2)	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 2845 90 90	30	(13C)Carbon monoxide (CAS RN 1641-69-6)	0 %	31.12.2016
ex 2845 90 90	40	Iron boride enriched at a level of more than 95 % by weight with boron-10 (CAS RN 200513-39-9)	0 %	31.12.2018
ex 2846 10 00 ex 3824 90 97	10 48	Rare-earth concentrate containing by weight 60 % or more but not more than 95 % of rare-earth oxides and not more than 1 % each of zirconium oxide, aluminium oxide or iron oxide, and having a loss on ignition of 5 % or more by weight	0 %	31.12.2018
ex 2846 10 00	20	Dicerium tricarbonate, whether or not hydrated (CAS RN 537-01-9)	0 %	31.12.2018
ex 2846 10 00	30	Cerium lanthanum carbonate, whether or not hydrated	0 %	31.12.2018
ex 2846 10 00	40	Cerium lanthanum neodymium praseodymium carbonate, whether or not hydrated	0 %	31.12.2014
2846 90 00		Compounds, inorganic or organic, of rare-earth metals, of yttrium or of scandium or of mixtures of these metals, other than those of subheading 2846 10 00	0 %	31.12.2018
ex 2848 00 00	10	Phosphine (CAS RN 7803-51-2)	0 %	31.12.2018
ex 2850 00 20	10	Silane (CAS RN 7803-62-5)	0 %	31.12.2018
ex 2850 00 20	20	Arsine (CAS RN 7784-42-1)	0 %	31.12.2018
ex 2850 00 20	30	Titanium nitride with a particle size of not more than 250 nm (CAS RN 25583-20-4)	0 %	31.12.2017
ex 2850 00 20	40	Germanium tetrahydride (CAS RN 7782-65-2)	0 %	31.12.2016
ex 2850 00 20	50	Sodium tetrahydroborate (CAS 16940-66-2) with:  — a purity by weight of 98 % or more and  — not more than 10ppm iron for use as an additive in the manufacture of oxygen barrier polymer articles	0 %	31.12.2017
ex 2850 00 60	10	Sodium azide (CAS RN 26628-22-8)	0 %	31.12.2018
ex 2853 00 90	10	Chlorosulphonyl isocyanate (CAS RN 1189-71-5)	0 %	31.12.2016
ex 2903 39 90	10	Carbon tetrafluoride (tetrafluoromethane) (CAS RN 75-73-0)	0 %	31.12.2018
ex 2903 39 90	15	Perfluoro(4-methyl-2-pentene) (CAS RN 84650-68-0)	0 %	31.12.2016
ex 2903 39 90	25	2,3,3,3-Tetrafluoroprop-1-ene (CAS RN 754-12-1)	0 %	31.12.2017
ex 2903 39 90	30	Perfluoroethane (CAS RN 76-16-4)	0 %	31.12.2018
ex 2903 39 90	40	1,1-Difluoroethane (CAS RN 75-37-6)	0 %	31.12.2018
ex 2903 39 90	50	1,1,1,3,3-Pentafluoropropane (CAS RN 460-73-1)	0 %	31.12.2018
ex 2903 39 90	70	1,1,1,2-Tetrafluoroethane, certified odourless containing a maximum:  — 600 ppm by weight of 1,1,2,2-tetrafluoroethane,  — 2 ppm by weight of pentafluoroethane,  — 2 ppm by weight of chlorodifluoromethane,  — 2 ppm by weight of chloropentafluoroethane,  — 2 ppm by weight of dichlorodifluoromethane for use in the manufacture of pharmaceutical grade propellant for medical metred dose inhalers (CAS RN 811-97-2)	0 %	31.12.2016
ex 2903 39 90	75	Trans-1,3,3,3-tetrafluoroprop-1-ene (CAS RN 1645-83-6)	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 2903 39 90	80	Hexafluoropropene (CAS RN 116-15-4)	0 %	31.12.2016
ex 2903 77 30	10	1,1,1-Trichlorotrifluoroethane (CAS RN 354-58-5)	0 %	31.12.2018
ex 2903 77 90	10	Chlorotrifluoroethylene (CAS RN 79-38-9)	0 %	31.12.2016
ex 2903 89 90	10	1,6,7,8,9,14,15,16,17,17,18,18-Dodecachloropentacyclo [12.2.1.1 <sup>6,9</sup> .0 <sup>2,13</sup> .0 <sup>5,10</sup> ]octadeca-7,15-diene (CAS RN 13560-89-9)	0 %	31.12.2018
ex 2903 89 90	30	Octafluorocyclopentene (CAS RN 559-40-0)	0 %	31.12.2016
ex 2903 89 90	40	Hexabromocyclododecane	0 %	31.12.2016
ex 2903 89 90	50	Chlorocyclopentane (CAS RN 930-28-9)	0 %	31.12.2017
ex 2903 99 90	20	1,2-Bis(pentabromophenyl)ethane (CAS RN 84852-53-9)	0 %	31.12.2018
ex 2903 99 90	40	2,6-Dichlorotoluene, of a purity by weight of 99 % or more and containing:  — 0,001 mg/kg or less of tetrachlorodibenzodioxines,  — 0,001 mg/kg or less of tetrachlorodibenzofurans,  — 0,2 mg/kg or less of tetrachlorobiphenyls	0 %	31.12.2018
ex 2903 99 90	50	Fluorobenzene (CAS RN 462-06-6)	0 %	31.12.2018
ex 2903 99 90	70	α,α,α',α'-Tetrachloro-o-xylen (CAS RN 25641-99-0)	0 %	31.12.2015
ex 2903 99 90	80	1-Bromo-3,4,5-trifluorobenzene (CAS RN 138526-69-9)	0 %	31.12.2018
ex 2903 99 90	85	2-Bromo-9H-fluorene (CAS RN 1133-80-8)	0 %	31.12.2018
ex 2904 10 00	30	Sodium <i>p</i> -styrenesulphonate (CAS RN 2695-37-6)	0 %	31.12.2014
ex 2904 10 00	50	Sodium 2-methylprop-2-ene-1-sulphonate (CAS RN 1561-92-8)	0 %	31.12.2014
ex 2904 20 00	10	Nitromethane (CAS RN 75-52-5)	0 %	31.12.2015
ex 2904 20 00	20	Nitroethane (CAS RN 79-24-3)	0 %	31.12.2015
ex 2904 20 00	30	1-Nitropropane (CAS RN 108-03-2)	0 %	31.12.2015
ex 2904 20 00	40	2-Nitropropane (CAS RN 79-46-9)	0 %	31.12.2014
ex 2904 90 40	10	Trichloronitromethane, for the manufacture of goods of subheading 3808 92 (CAS RN 76-06-2)	0 %	31.12.2014
ex 2904 90 95	20	1-Chloro-2,4-dinitrobenzene (CAS RN 97-00-7)	0 %	31.12.2014
ex 2904 90 95	30	Tosyl chloride (CAS RN 98-59-9)	0 %	31.12.2014
ex 2904 90 95	40	4-Chlorobenzenesulphonyl chloride (CAS RN 98-60-2)	0 %	31.12.2017
ex 2904 90 95	50	Ethanesulphonyl chloride (CAS RN 594-44-5)	0 %	31.12.2018
ex 2905 19 00	11	Potassium tert-butanolate (CAS RN 865-47-4), whether or not in the form of a solution in tetrahydrofuran according to note 1e to Chapter 29 of the CN	0 %	31.12.2018
ex 2905 19 00	30	2,6-Dimethylheptan-4-ol (CAS RN 108-82-7)	0 %	31.12.2018
ex 2905 19 00	40	2,6-Dimethylheptan-2-ol (CAS RN 13254-34-7)	0 %	31.12.2014

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 2905 19 00	70	Titanium tetrabutanolate (CAS RN 5593-70-4)	0 %	31.12.2017
ex 2905 19 00	80	Titanium tetraisopropoxide (CAS RN 546-68-9)	0 %	31.12.2017
ex 2905 19 00	85	Titanium tetraethanolate (CAS RN 3087-36-3)	0 %	31.12.2018
ex 2905 29 90	10	3,5-Dimethylhex-1-yn-3-ol (CAS RN 107-54-0)	0 %	31.12.2014
ex 2905 29 90	20	Dec-9-en-1-ol (CAS RN 13019-22-2)	0 %	31.12.2014
ex 2905 29 90	30	Dodeca-8,10-dien-1-ol (CAS RN 33956-49-9)	0 %	31.12.2015
ex 2905 39 95	10	Propane-1,3-diol (CAS RN 504-63-2)	0 %	31.12.2015
ex 2905 39 95	20	Butane-1,2-diol (CAS RN 584-03-2)	0 %	31.12.2016
ex 2905 39 95	30	2,4,7,9-Tetramethyl-4,7-decanediol (CAS RN 17913-76-7)	0 %	31.12.2016
ex 2905 39 95	40	Decane-1,10-diol (CAS RN 112-47-0)	0 %	31.12.2017
ex 2905 39 95	50	2-Methyl-2-propylpropane-1,3-diol (CAS RN 78-26-2)	0 %	31.12.2018
ex 2905 49 00	10	Ethylidynetrimethanol (CAS RN 77-85-0)	0 %	31.12.2014
ex 2905 59 98	20	2,2,2-Trifluoroethanol (CAS RN 75-89-8)	0 %	31.12.2014
2906 11 00		Menthol (CAS RN 1490-04-6)	0 %	31.12.2018
ex 2906 19 00	10	Cyclohex-1,4-ylenedimethanol (CAS RN 105-08-8)	0 %	31.12.2018
ex 2906 19 00	20	4,4'-Isopropylidenedicyclohexanol (CAS RN 80-04-6)	0 %	31.12.2018
ex 2906 29 00	10	2,2'-( <i>m</i> -Phenylene)dipropan-2-ol (CAS RN 1999-85-5)	0 %	31.12.2014
ex 2906 29 00	20	1-Hydroxymethyl-4-methyl-2,3,5,6-tetrafluorobenzene (CAS RN 79538-03-7)	0 %	31.12.2018
ex 2906 29 00	30	2-Phenylethanol (CAS RN 60-12-8)	0 %	31.12.2017
ex 2907 15 90	10	2-Naphthol (CAS RN 135-19-3)	0 %	31.12.2016
ex 2907 19 90	10	2,3,5-Trimethylphenol (CAS RN 697-82-5)	0 %	31.12.2014
ex 2907 19 90	20	Biphenyl-4-ol (CAS RN 92-69-3)	0 %	31.12.2018
ex 2907 21 00	10	Resorcinol (CAS RN 108-46-3)	0 %	31.12.2018
ex 2907 23 00	10	4,4'-Isopropylidenediphenol (CAS RN 80-05-7)	0 %	31.12.2017
ex 2907 29 00	15	6,6'-Di-tert-butyl-4,4'-butylidenedi-m-cresol (CAS RN 85-60-9)	0 %	31.12.2018
ex 2907 29 00	20	4,4'-(3,3,5-Trimethylcyclohexylidene)diphenol (CAS RN 129188-99-4)	0 %	31.12.2018
ex 2907 29 00	30	4,4',4"-Ethylidynetriphenol (CAS RN 27955-94-8)	0 %	31.12.2018
ex 2907 29 00	35	4-[2-(4-Hydroxy-3-prop-2-enylphenyl)propan-2-yl]-2-prop-2-enylphenol (CAS RN 1745-89-7)	0 %	31.12.2016
ex 2907 29 00	40	2,3,5-Trimethylhydroquinone (CAS RN 700-13-0)	0 %	31.12.2016
ex 2907 29 00	45	2-Methylhydroquinone (CAS RN 95-71-6)	0 %	31.12.2016

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 2907 29 00	50	6,6',6"-Tricyclohexyl-4,4',4"-butane-1,1,3-triyltri( <i>m</i> -cresol) (CAS RN 111850-25-0)	0 %	31.12.2018
ex 2907 29 00	55	Biphenyl-2,2'-diol (CAS RN 1806-29-7)	0 %	31.12.2017
ex 2907 29 00	70	2,2',2",6,6',6"-Hexa- <i>tert</i> -butyl- <i>a</i> , <i>a</i> ', <i>a</i> "-(mesitylene-2,4,6-triyl)tri- <i>p</i> -cresol (CAS RN 1709-70-2)	0 %	31.12.2018
ex 2907 29 00	85	Phloroglucinol whether or not hydrated	0 %	31.12.2018
ex 2908 19 00	10	Pentafluorophenol (CAS RN 771-61-9)	0 %	31.12.2018
ex 2908 19 00	20	4,4'-(Perfluoroisopropylidene)diphenol (CAS RN 1478-61-1)	0 %	31.12.2018
ex 2908 99 00	30	4-Nitrophenol (CAS RN 100-02-7)	0 %	31.12.2018
ex 2908 99 00	40	4,5-Dihydroxynaphthalene-2,7-disulphonic acid (CAS RN 148-25-4)	0 %	31.12.2017
ex 2909 19 90	20	Bis(2-chloroethyl) ether (CAS RN 111-44-4)	0 %	31.12.2018
ex 2909 19 90	30	Mixture of isomers of nonafluorobutyl methyl ether or nonafluorobutyl ethyl ether, of a purity by weight of 99 % or more	0 %	31.12.2018
ex 2909 19 90	50	3-Ethoxy-perfluoro-2-methylhexane (CAS RN 297730-93-9)	0 %	31.12.2016
ex 2909 19 90	60	1-Methoxyheptafluoropropane (CAS RN 375-03-1)	0 %	31.12.2018
ex 2909 20 00	10	8-Methoxycedrane (CAS RN 19870-74-7)	0 %	31.12.2016
ex 2909 30 38	10	Bis(pentabromophenyl) ether (CAS RN 1163-19-5)	0 %	31.12.2018
ex 2909 30 38	20	1,1'-Propane-2,2-diylbis[3,5-dibromo-4-(2,3-dibromopropoxy)benzene] (CAS RN 21850-44-2)	0 %	31.12.2016
ex 2909 30 90	10	2-(Phenylmethoxy)naphthalene (CAS RN 613-62-7)	0 %	31.12.2014
ex 2909 30 90	20	1,2-Bis(3-methyl-phenoxy)ethane (CAS RN 54914-85-1)	0 %	31.12.2014
ex 2909 30 90	30	3,4,5-Trimethoxytoluene (CAS RN 6443-69-2)	0 %	31.12.2015
ex 2909 50 00	10	4-(2-Methoxyethyl)phenol (CAS RN 56718-71-9)	0 %	31.12.2018
ex 2909 50 00	20	Ubiquinol (CAS RN 992-78-9)	0 %	31.12.2015
ex 2909 60 00	10	Bis(α,α-dimethylbenzyl) peroxide (CAS RN 80-43-3)	0 %	31.12.2018
ex 2909 60 00	20	1,4-Di(2-tert-butylperoxyisopropyl)benzene (CAS RN 25155-25-3)	0 %	31.12.2016
ex 2910 90 00	15	1,2-Epoxycyclohexane (CAS RN 286-20-4)	0 %	31.12.2018
ex 2910 90 00	30	2,3-Epoxypropan-1-ol (glycidol) (CAS RN 556-52-5)	0 %	31.12.2018
ex 2910 90 00	80	Allyl glycidyl ether (CAS RN 106-92-3)	0 %	31.12.2016
ex 2912 29 00	40	(2E,4E,6E,8E,10E,12E)-2,7,11-Trimethyl-13-(2,6,6-trimethyl-1-cyclohexen-1-yl)-2,4,6,8,10,12-tridecahexaenal (CAS RN 1638-05-7)	0 %	31.12.2016
ex 2912 29 00	50	4-Isobutylbenzaldehyde (CAS RN 40150-98-9)	0 %	31.12.2017
ex 2912 29 00	60	3,4-Dimethylbenzaldehyde (CAS RN 5973-71-7)	0 %	31.12.2018
ex 2912 49 00	10	3-Phenoxybenzaldehyde (CAS RN 39515-51-0)	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 2912 49 00	20	4-Hydroxybenzaldehyde (CAS RN 123-08-0)	0 %	31.12.2017
ex 2912 49 00	30	Salicylaldehyde (CAS RN 90-02-8)	0 %	31.12.2015
ex 2914 19 90	20	Heptan-2-one (CAS RN 110-43-0)	0 %	31.12.2017
ex 2914 19 90	30	3-Methylbutanone (CAS RN 563-80-4)	0 %	31.12.2017
ex 2914 19 90	40	Pentan-2-one (CAS RN 107-87-9)	0 %	31.12.2017
ex 2914 29 00	20	Cyclohexadec-8-enone (CAS RN 3100-36-5)	0 %	31.12.2018
ex 2914 29 00	30	(R)-p-Mentha-1(6),8-dien-2-one (CAS RN 6485-40-1)	0 %	31.12.2015
ex 2914 29 00	40	Camphor	0 %	31.12.2018
ex 2914 29 00	50	trans-β-Damascone (CAS RN 23726-91-2)	0 %	31.12.2016
ex 2914 39 00	30	Benzophenone (CAS RN 119-61-9)	0 %	31.12.2017
ex 2914 39 00	50	4-Phenylbenzophenone (CAS RN 2128-93-0)	0 %	31.12.2018
ex 2914 39 00	60	4-Methylbenzophenone (CAS RN 134-84-9)	0 %	31.12.2018
ex 2914 39 00	70	Benzil (CAS RN 134-81-6)	0 %	31.12.2017
ex 2914 39 00	80	4'-Methylacetophenone (CAS RN 122-00-9)	0 %	31.12.2017
ex 2914 50 00	20	3'-Hydroxyacetophenone (CAS RN 121-71-1)	0 %	31.12.2015
ex 2914 50 00	25	4'-Methoxyacetophenone (CAS RN 100-06-1)	0 %	31.12.2018
ex 2914 50 00	30	2'-Hydroxyacetophenone (CAS RN 118-93-4)	0 %	31.12.2018
ex 2914 50 00	36	2,7-Dihydroxy-9-fluorenone (CAS RN 42523-29-5)	0 %	31.12.2018
ex 2914 50 00	40	4-(4-Hydroxyphenyl)butan-2-one (CAS RN 5471-51-2)	0 %	31.12.2016
ex 2914 50 00	45	3,4-Dihydroxybenzophenone (CAS RN 10425-11-3)	0 %	31.12.2017
ex 2914 50 00	60	2,2-Dimethoxy-2-phenylacetophenone (CAS RN 24650-42-8)	0 %	31.12.2017
ex 2914 50 00	70	16α,17α-Epoxy-3β-hydroxypregn-5-en-20-one (CAS RN 974-23-2)	0 %	31.12.2017
ex 2914 50 00	80	2',6'-Dihydroxyacetophenone (CAS RN 699-83-2)	0 %	31.12.2018
ex 2914 69 90	10	2-Ethylanthraquinone (CAS RN 84-51-5)	0 %	31.12.2018
ex 2914 69 90	20	2-Pentylanthraquinone (CAS RN 13936-21-5)	0 %	31.12.2014
ex 2914 69 90	30	1,4-Dihydroxyanthraquinone (CAS RN 81-64-1)	0 %	31.12.2018
ex 2914 69 90	40	<i>p</i> -Benzoquinone (CAS RN 106-51-4)	0 %	31.12.2016
ex 2914 70 00	20	2,4'-Difluorobenzophenone (CAS RN 342-25-6)	0 %	31.12.2017
ex 2914 70 00	40	Perfluoro(2-methylpentan-3-one) (CAS RN 756-13-8)	0 %	31.12.2018
ex 2914 70 00	50	3'-Chloropropiophenone (CAS RN 34841-35-5)	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 2914 70 00	60	4'-tert-Butyl-2',6'-dimethyl-3',5'-dinitroacetophenone (CAS RN 81-14-1)	0 %	31.12.2015
ex 2914 70 00	70	4-Chloro-4'-hydroxybenzophenone (CAS RN 42019-78-3)	0 %	31.12.2016
ex 2915 29 00	10	Antimony triacetate (CAS RN 6923-52-0)	0 %	31.12.2018
ex 2915 39 00	20	Isopentyl acetate (CAS RN 123-92-2)	0 %	31.12.2017
ex 2915 39 00	40	tert-Butyl acetate (CAS RN 540-88-5)	0 %	31.12.2018
ex 2915 39 00	50	3-Acetylphenyl acetate (CAS RN 2454-35-5)	0 %	31.12.2014
ex 2915 39 00	60	Dodec-8-enyl acetate (CAS RN 28079-04-1)	0 %	31.12.2015
ex 2915 39 00	65	Dodeca-7,9-dienyl acetate (CAS RN 54364-62-4)	0 %	31.12.2015
ex 2915 39 00	70	Dodec-9-enyl acetate (CAS RN 16974-11-1)	0 %	31.12.2015
ex 2915 39 00	75	Isobornyl acetate (CAS RN 125-12-2)	0 %	31.12.2016
ex 2915 39 00	80	1-Phenylethyl acetate (CAS RN 93-92-5)	0 %	31.12.2016
ex 2915 39 00	85	2-tert-Butylcyclohexyl acetate (CAS RN 88-41-5)	0 %	31.12.2018
ex 2915 60 19	10	Ethyl butyrate (CAS RN 105-54-4)	0 %	31.12.2017
ex 2915 90 70	30	3,3-Dimethylbutyryl chloride (CAS RN 7065-46-5)	0 %	31.12.2017
ex 2915 90 70	40	Nonanoic acid (pelargonic acid) (CAS RN 112-05-0)	0 %	31.12.2018
ex 2915 90 70	50	Allyl heptanoate (CAS RN 142-19-8)	0 %	31.12.2014
ex 2915 90 70	55	Triethyl orthoformate (CAS RN 122-51-0)	0 %	31.12.2018
ex 2915 90 70	60	Ethyl-6,8-dichlorooctanoate (CAS RN 1070-64-0)	0 %	31.12.2015
ex 2915 90 70	70	Cobalt borate neodecanoate complexes, with a purity by weight of 92 % or more (CAS RN 68457-13-6)	0 %	31.12.2016
ex 2915 90 70	75	2,2-Dimethylbutyryl chloride (CAS RN 5856-77-9)	0 %	31.12.2017
ex 2915 90 70	80	Ethyl difluoroacetate (CAS RN 454-31-9)	0 %	31.12.2016
ex 2916 12 00	10	2-tert-Butyl-6-(3-tert-butyl-2-hydroxy-5-methylbenzyl)-4-methylphenyl acrylate (CAS RN 61167-58-6)	0 %	31.12.2018
ex 2916 12 00	40	2,4-Di- <i>tert</i> -pentyl-6-[1-(3,5-di- <i>tert</i> -pentyl-2-hydroxyphenyl)ethyl]phenylacrylate (CAS RN 123968-25-2)	0 %	31.12.2018
ex 2916 12 00	70	2-(2-Vinyloxyethoxy)ethyl acrylate (CAS RN 86273-46-3)	0 %	31.12.2017
ex 2916 13 00	10	Hydroxyzinc methacrylate powder (CAS RN 63451-47-8)	0 %	31.12.2014
ex 2916 13 00	20	Zinc dimethacrylate, in the form of powder (CAS RN 13189-00-9)	0 %	31.12.2018
ex 2916 14 00	10	2,3-Epoxypropyl methacrylate (CAS RN 106-91-2)	0 %	31.12.2018
ex 2916 19 95	20	Methyl 3,3-dimethylpent-4-enoate (CAS RN 63721-05-1)	0 %	31.12.2018
ex 2916 19 95	40	Sorbic acid for use in the manufacture of animal feeds (CAS RN 110-44-1)	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		(1)		
ex 2916 20 00	50	Ethyl 2,2-dimethyl-3-(2-methylpropenyl)cyclopropanecarboxylate (CAS RN 97-41-6)	0 %	31.12.2018
ex 2916 20 00	60	3-Cyclohexylpropionic acid (CAS RN 701-97-3)	0 %	31.12.2015
ex 2916 31 00	10	Benzyl benzoate (CAS RN 120-51-4)	0 %	31.12.2016
ex 2916 39 90	10	2,3,4,5-Tetrafluorobenzoic acid (CAS RN 1201-31-6)	0 %	31.12.2016
ex 2916 39 90	15	2-Chloro-5-nitrobenzoic acid (CAS RN 2516-96-3)	0 %	31.12.2016
ex 2916 39 90	20	3,5-Dichlorobenzoyl chloride (CAS RN 2905-62-6)	3.6 %	31.12.2018
ex 2916 39 90	25	2-Methyl-3-(4-Fluorophenyl)-propionyl chloride (CAS RN 1017183-70-8)	0 %	31.12.2015
ex 2916 39 90	30	2,4,6-Trimethylbenzoyl chloride (CAS RN 938-18-1)	0 %	31.12.2015
ex 2916 39 90	35	Methyl 4-tert-butylbenzoate (CAS RN 26537-19-9)	0 %	31.12.2018
ex 2916 39 90	38	6-Bromonaphthalene-2-carboxylic acid (CAS RN 5773-80-8)	0 %	31.12.2018
ex 2916 39 90	45	2-Chlorobenzoic acid (CAS RN 118-91-2)	0 %	31.12.2016
ex 2916 39 90	50	3,5-Dimethylbenzoyl chloride (CAS RN 6613-44-1)	0 %	31.12.2018
ex 2916 39 90	55	4-tert-Butylbenzoic acid (CAS RN 98-73-7)	0 %	31.12.2017
ex 2916 39 90	60	4-Ethylbenzoyl chloride (CAS RN 16331-45-6)	0 %	31.12.2018
ex 2916 39 90	70	Ibuprofen (INN) (CAS RN 15687-27-1)	0 %	31.12.2018
ex 2916 39 90	75	m-Toluic acid (CAS RN 99-04-7)	0 %	31.12.2017
ex 2916 39 90	85	(2,4,5-Trifluorophenyl)acetic acid (CAS RN 209995-38-0)	0 %	31.12.2017
ex 2917 11 00	20	Bis(p-methylbenzyl) oxalate (CAS RN 18241-31-1)	0 %	31.12.2018
ex 2917 11 00	30	Cobalt oxalate (CAS RN 814-89-1)	0 %	31.12.2014
ex 2917 19 10	10	Dimethyl malonate (CAS RN 108-59-8)	0 %	31.12.2014
ex 2917 19 10	20	Diethyl malonate (CAS RN 105-53-3)	0 %	31.12.2017
ex 2917 19 90	20	Sodium 1,2-bis(cyclohexyloxycarbonyl)ethanesulphonate (CAS RN 23386-52-9)	0 %	31.12.2018
ex 2917 19 90	30	Ethylene brassylate (CAS RN 105-95-3)	0 %	31.12.2014
ex 2917 19 90	50	Tetradecanedioic acid (CAS RN 821-38-5)	0 %	31.12.2015
ex 2917 19 90	70	Itaconic acid (CAS RN 97-65-4)	0 %	31.12.2018
ex 2917 20 00	30	1,4,5,6,7,7-Hexachloro-8,9,10-trinorborn-5-ene-2,3-dicarboxylic anhydride (CAS RN 115-27-5)	0 %	31.12.2018
ex 2917 20 00	40	3-Methyl-1,2,3,6-tetrahydrophthalic anhydride (CAS RN 5333-84-6)	0 %	31.12.2018
ex 2917 34 00	10	Diallyl phthalate (CAS RN 131-17-9)	0 %	31.12.2018
ex 2917 39 95	20	Dibutyl-1,4-benzenedicarboxylate (CAS RN 1962-75-0)	0 %	31.12.2015

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 2917 39 95	30	Benzene-1,2:4,5-tetracarboxylic dianhydride (CAS RN 89-32-7)	0 %	31.12.2015
ex 2918 16 00	20	Calcium digluconate monohydrate (CAS RN 66905-23-5) for use in the manufacture of calcium gluconate lactate (CAS RN 11116-97-5)	0 %	31.12.2018
ex 2918 19 98	20	L-Malic acid (CAS RN 97-67-6)	0 %	31.12.2018
ex 2918 29 00	10	Monohydroxynaphthoic acids	0 %	31.12.2018
ex 2918 29 00	35	Propyl 3,4,5-trihydroxybenzoate (CAS RN 121-79-9)	0 %	31.12.2017
ex 2918 29 00	50	Hexamethylene bis[3-(3,5-di- <i>tert</i> -butyl-4-hydroxyphenyl)propionate] (CAS RN 35074-77-2)	0 %	31.12.2018
ex 2918 29 00	60	Methyl-, ethyl-, propyl- or butyl esters of 4-hydroxybenzoic acid or their sodium salts (CAS RN 35285-68-8, 99-76-3, 5026-62-0, 94-26-8, 94-13-3, 35285-69-9, 120-47-8, 36457-20-2 or 4247-02-3)	0 %	31.12.2016
ex 2918 30 00	30	Methyl-2-benzoylbenzoate (CAS RN 606-28-0)	0 %	31.12.2018
ex 2918 30 00	50	Ethyl acetoacetate (CAS RN 141-97-9)	0 %	31.12.2017
ex 2918 99 90	10	3,4-Epoxycyclohexylmethyl 3,4-epoxycyclohexanecarboxylate (CAS RN 2386-87-0)	0 %	31.12.2018
ex 2918 99 90	15	Ethyl 2,3-epoxy-3-phenylbutyrate (CAS RN 77-83-8)	0 %	31.12.2017
ex 2918 99 90	20	Methyl 3-methoxyacrylate (CAS RN 5788-17-0)	0 %	31.12.2014
ex 2918 99 90	30	Methyl 2-(4-hydroxyphenoxy)propionate (CAS RN 96562-58-2)	0 %	31.12.2018
ex 2918 99 90	40	trans-4-Hydroxy-3-methoxycinnamic acid (CAS RN 1135-24-6)	0 %	31.12.2018
ex 2918 99 90	50	Methyl 3,4,5-trimethoxybenzoate (CAS RN 1916-07-0)	0 %	31.12.2018
ex 2918 99 90	60	3,4,5-Trimethoxybenzoic acid (CAS RN 118-41-2)	0 %	31.12.2018
ex 2918 99 90	70	Allyl-(3-methylbutoxy)acetate (CAS RN 67634-00-8)	0 %	31.12.2014
ex 2918 99 90	80	Sodium 5-[2-chloro-4-(trifluoromethyl)phenoxy]-2-nitrobenzoate (CAS RN 62476-59-9)	0 %	31.12.2016
ex 2919 90 00	10	2,2'-Methylenebis(4,6-di- <i>tert</i> -butylphenyl) phosphate, monosodium salt (CAS RN 85209-91-2)	0 %	31.12.2018
ex 2919 90 00	30	Aluminium hydroxybis[2,2'-methylenebis(4,6-di- <i>tert</i> -butylphenyl)phosphate] (CAS RN 151841-65-5)	0 %	31.12.2018
ex 2919 90 00	40	Tri-n-hexylphosphate (CAS RN 2528-39-4)	0 %	31.12.2018
ex 2919 90 00	50	Triethyl phosphate (CAS RN 78-40-0)	0 %	31.12.2016
ex 2920 19 00	10	Fenitrothion (ISO) (CAS RN 122-14-5)	0 %	31.12.2018
ex 2920 19 00	20	Tolclofos-methyl (ISO) (CAS RN 57018-04-9)	0 %	31.12.2018
ex 2920 90 10	10	Diethyl sulphate (CAS RN 64-67-5)	0 %	31.12.2018
ex 2920 90 10	20	Diallyl 2,2'-oxydiethyl dicarbonate (CAS RN 142-22-3)	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 2920 90 10	40	Dimethyl carbonate (CAS RN 616-38-6)	0 %	31.12.2018
ex 2920 90 10	50	Di-tert-butyl dicarbonate (CAS RN 24424-99-5)	0 %	31.12.2018
ex 2920 90 10	60	2,4-Di- <i>tert</i> -butyl-5-nitrophenyl methyl carbonate (CAS RN 873055-55-1)	0 %	31.12.2017
2920 90 30		Trimethyl phosphite (CAS RN 121-45-9)	0 %	31.12.2018
2920 90 40		Triethyl phosphite (CAS RN 122-52-1)	0 %	31.12.2016
ex 2920 90 85	10	O,O'-Dioctadecyl pentaerythritol bis(phosphite) (CAS RN 3806-34-6)	0 %	31.12.2018
ex 2920 90 85	20	Tris(methylphenyl)phosphite (CAS RN 25586-42-9)	0 %	31.12.2015
ex 2920 90 85	30	2,2'-[[3,3',5,5'-Tetrakis(1,1-dimethylethyl)[1,1'-biphenyl]-2,2'-diyl]bis(oxy)]bis[biphenyl-1,3,2-dioxaphosphepine], (CAS RN 138776-88-2)	0 %	31.12.2015
ex 2920 90 85	40	Bis(2,4-dicumylphenyl)pentaerythritol diphosphite (CAS RN 154862-43-8)	0 %	31.12.2015
ex 2920 90 85	50	Fosetyl-aluminium (CAS RN 39148-24-8)	0 %	31.12.2018
ex 2920 90 85	60	Bis(neopentylglycolato)diboron (CAS RN 201733-56-4)	0 %	31.12.2018
ex 2921 19 50 ex 2929 90 00	10 20	Diethylamino-triethoxysilane (CAS RN 35077-00-0)	0 %	31.12.2014
ex 2921 19 60	10	2-(N,N-Diethylamino)ethyl chloride hydrochloride (CAS RN 869-24-9)	0 %	31.12.2017
ex 2921 19 99	20	Ethyl(2-methylallyl)amine (CAS RN 18328-90-0)	0 %	31.12.2018
ex 2921 19 99	30	Allylamine (CAS RN 107-11-9)	0 %	31.12.2018
ex 2921 19 99	60	Tetrakis(ethylmethylamino) zirconium (IV), (CAS RN 175923-04-3)	0 %	31.12.2018
ex 2921 19 99	70	N,N-Dimethyloctylamine – boron trichloride (1:1) (CAS RN 34762-90-8)	0 %	31.12.2017
ex 2921 29 00	20	Tris[3-(dimethylamino)propyl]amine (CAS RN 33329-35-0)	0 %	31.12.2018
ex 2921 29 00	30	Bis[3-(dimethylamino)propyl]methylamine (CAS RN 3855-32-1)	0 %	31.12.2018
ex 2921 29 00	40	Decamethylenediamine (CAS RN 646-25-3)	0 %	31.12.2015
ex 2921 29 00	50	N'-[3-(Dimethylamino)propyl]- $N$ , $N$ -dimethylpropane-1,3-diamine, (CAS RN 6711-48-4)	0 %	31.12.2016
ex 2921 30 99	30	1,3-Cyclohexanedimethanamine (CAS RN 2579-20-6)	0 %	31.12.2015
ex 2921 30 99	40	Cyclopropylamin (CAS RN 765-30-0)	0 %	31.12.2017
ex 2921 42 00	15	4-Amino-3-nitrobenzenesulphonic acid (CAS RN 616-84-2)	0 %	31.12.2018
ex 2921 42 00	20	3-Chloroaniline (CAS RN 108-42-9)	0 %	31.12.2018
ex 2921 42 00	25	Sodium hydrogen 2-aminobenzene-1,4-disulphonate (CAS RN 24605-36-5)	0 %	31.12.2018
ex 2921 42 00	35	2-Nitroaniline (CAS RN 88-74-4)	0 %	31.12.2018
ex 2921 42 00	45	2,4,5-Trichloroaniline (CAS RN 636-30-6)	0 %	31.12.2018
ex 2921 42 00	50	3-Aminobenzenesulfonic acid (CAS RN 121-47-1)	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 2921 42 00	70	2-Aminobenzene-1,4-disulfonic acid (CAS RN 98-44-2)	0 %	31.12.2014
ex 2921 42 00	80	4-Chloro-2-nitroaniline (CAS RN 89-63-4)	0 %	31.12.2018
ex 2921 42 00	82	2-Chloro-4-nitroaniline (CAS RN 121-87-9)	0 %	31.12.2015
ex 2921 42 00	85	3,5-Dichloroaniline (CAS RN 626-43-7)	0 %	31.12.2018
ex 2921 42 00	86	2,5-Dichloroaniline of a purity by weight of 99,5 % or more (CAS RN 95-82-9)	0 %	31.12.2017
ex 2921 42 00	87	N-Methylaniline (CAS RN 100-61-8)	0 %	31.12.2017
ex 2921 42 00	88	3,4-Dichloroaniline-6-sulphonic acid (CAS RN 6331-96-0)	0 %	31.12.2017
ex 2921 43 00	20	4-Amino-6-chlorotoluene-3-sulphonic acid (CAS RN 88-51-7)	0 %	31.12.2018
ex 2921 43 00	30	3-Nitro- <i>p</i> -toluidine (CAS RN 119-32-4)	0 %	31.12.2018
ex 2921 43 00	40	4-Aminotoluene-3-sulphonic acid (CAS RN 88-44-8)	0 %	31.12.2018
ex 2921 43 00	50	4-Aminobenzotrifluoride (CAS RN 455-14-1)	0 %	31.12.2015
ex 2921 43 00	60	3-Aminobenzotrifluoride (CAS RN 98-16-8)	0 %	31.12.2015
ex 2921 43 00	70	N-Ethyl-m-toluidine (CAS RN 102-27-2)	0 %	31.12.2016
ex 2921 43 00	80	6-Chloro-α,α,α-trifluoro-m-toluidine (CAS RN 121-50-6)	0 %	31.12.2017
ex 2921 44 00	20	Diphenylamine (CAS RN 122-39-4)	0 %	31.12.2018
ex 2921 45 00	10	Sodium hydrogen 3-aminonaphthalene-1,5-disulphonate (CAS RN 4681-22-5)	0 %	31.12.2014
ex 2921 45 00	20	2-Aminonaphthalene-1,5-disulphonic acid (CAS RN 117-62-4) or one of its sodium salts (CAS RN 19532-03-7) or (CAS RN 62203-79-6)	0 %	31.12.2018
ex 2921 45 00	40	1-Naphthylamine (CAS RN 134-32-7)	0 %	31.12.2014
ex 2921 45 00	50	7-Aminonaphthalene-1,3,6-trisulphonic acid (CAS RN 118-03-6)	0 %	31.12.2018
ex 2921 49 00	20	Pendimethalin (ISO) (CAS RN 40487-42-1)	3.5 %	31.12.2018
ex 2921 49 00	40	N-1-Naphthylaniline (CAS RN 90-30-2)	0 %	31.12.2018
ex 2921 49 00	60	N-Benzyl-N-ethylaniline (CAS RN 92-59-1)	0 %	31.12.2014
ex 2921 49 00	70	2-Chlorobenzylamine (CAS RN 89-97-4)	0 %	31.12.2015
ex 2921 49 00	80	4-Heptafluoroisopropyl-2-methylaniline (CAS RN 238098-26-5)	0 %	31.12.2015
ex 2921 49 00	85	4-Isopropylaniline (CAS RN 99-88-7)	0 %	31.12.2017
ex 2921 51 19	20	Toluene diamine (TDA), containing by weight 78 % or more but not more than 82 % of 4-methyl-m-phenylenediamine and 18 % or more but not more than 22 % of 2-methyl-m-phenylenediamine, and with a residual tar content of not more than 0,23 % by weight	0 %	31.12.2018
ex 2921 51 19	30	2-Methyl- <i>p</i> -phenylenediamine sulphate (CAS RN 615-50-9)	0 %	31.12.2018
ex 2921 51 19	40	<i>p</i> -Phenylenediamine (CAS RN 106-50-3)	0 %	31.12.2016
ex 2921 51 19	50	Mono- and dichloroderivatives of <i>p</i> -phenylenediamine and <i>p</i> -diaminotoluene	0 %	31.12.2014

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 2921 51 19	60	2,4-Diaminobenzenesulphonic acid (CAS RN 88-63-1)	0 %	31.12.2018
ex 2921 59 90	10	Mixture of isomers of 3,5-diethyltoluenediamine	0 %	31.12.2018
ex 2921 59 90	30	3,3'-Dichlorobenzidine dihydrochloride (CAS RN 612-83-9)	0 %	31.12.2017
ex 2921 59 90	40	4,4'-Diaminostilbene-2,2'-disulphonic acid (CAS RN 81-11-8)	0 %	31.12.2018
ex 2921 59 90	50	N-Ethyl-N',N'-dimethyl-N-phenyl-ethylene-1,2-diamine (CAS RN 27692-91-7)	0 %	31.12.2014
ex 2921 59 90	60	(2R,5R)-1,6-Diphenylhexane-2,5-diamine dihydrochloride (CAS RN 1247119-31-8)	0 %	31.12.2017
ex 2922 19 85	20	2-(2-Methoxyphenoxy)ethylamine hydrochloride (CAS RN 64464-07-9)	0 %	31.12.2017
ex 2922 19 85	25	Titanium bis(triethanolamine)diisopropoxide (CAS RN 36673-16-2)	0 %	31.12.2017
ex 2922 19 85	30	N,N,N',N'-Tetramethyl-2,2'-oxybis(ethylamine) (CAS RN 3033-62-3)	0 %	31.12.2018
ex 2922 19 85	40	2-(Dimethylamino)ethyl benzoate (CAS RN 2208-05-1)	0 %	31.12.2014
ex 2922 19 85	45	2-[2-Hydroxyethyl(octadecyl)amino]ethanol (CAS RN 10213-78-2)	0 %	31.12.2016
ex 2922 19 85	50	2-(2-Methoxyphenoxy)ethylamine (CAS RN 1836-62-0)	0 %	31.12.2018
ex 2922 19 85	60	N,N,N'-trimethyl-N'-(2-hydroxy-ethyl) 2,2'-oxybis(ethylamine), (CAS RN 83016-70-0)	0 %	31.12.2018
ex 2922 19 85	65	trans-4-Aminocyclohexanol (CAS RN 27489-62-9)	0 %	31.12.2018
ex 2922 19 85	70	D-(-)-threo-2-amino-1-(p-nitrophenyl)propane-1,3-diol (CAS RN 716-61-0)	0 %	31.12.2016
ex 2922 19 85	75	2-Ethoxyethylamine (CAS RN 110-76-9)	0 %	31.12.2018
ex 2922 19 85	80	N-[2-[2-(Dimethylamino)ethoxy]ethyl]-N-methyl-1,3-propanediamine, (CAS RN 189253-72-3)	0 %	31.12.2014
ex 2922 19 85	85	(1S,4R)-cis-4-Amino-2-cyclopentene-1-methanol-D-tartrate (CAS RN 229177-52-0)	0 %	31.12.2018
ex 2922 21 00	10	2-Amino-5-hydroxynaphthalene-1,7-disulphonic acid (CAS RN 6535-70-2)	0 %	31.12.2018
ex 2922 21 00	30	6-Amino-4-hydroxynaphthalene-2-sulphonic acid (CAS RN 90-51-7)	0 %	31.12.2014
ex 2922 21 00	40	7-Amino-4-hydroxynaphthalene-2-sulphonic acid (CAS RN 87-02-5)	0 %	31.12.2018
ex 2922 21 00	50	Sodium hydrogen 4-amino-5-hydroxynaphthalene-2,7-disulphonate, (CAS RN 5460-09-3)	0 %	31.12.2014
ex 2922 21 00	60	4-Amino-5-hydroxynaphthalene-2,7-disulphonic acid with a purity by weight of 80 % or more (CAS RN 90-20-0)	0 %	31.12.2018
ex 2922 29 00	20	3-Aminophenol (CAS RN 591-27-5)	0 %	31.12.2018
ex 2922 29 00	25	5-Amino-o-cresol (CAS RN 2835-95-2)	0 %	31.12.2018
ex 2922 29 00	45	Anisidines	0 %	31.12.2018
ex 2922 29 00	55	3-Amino-4-hydroxybenzenesulphonic acid (CAS RN 98-37-3)	0 %	31.12.2014

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 2922 29 00	65	4-Trifluoromethoxyaniline (CAS RN 461-82-5)	0 %	31.12.2014
ex 2922 29 00	70	4-Nitro- <i>o</i> -anisidine (CAS RN 97-52-9)	0 %	31.12.2018
ex 2922 29 00	75	4-(2-Aminoethyl)phenol (CAS RN 51-67-2)	0 %	31.12.2015
ex 2922 29 00	80	3-Diethylaminophenol (CAS RN 91-68-9)	0 %	31.12.2018
ex 2922 29 00	85	4-Benzyloxyaniline hydrochloride (CAS RN 51388-20-6)	0 %	31.12.2018
ex 2922 39 00	10	1-Amino-4-bromo-9,10-dioxoanthracene-2-sulphonic acid and its salts	0 %	31.12.2018
ex 2922 39 00	20	2-Amino-5-chlorobenzophenone (CAS RN 719-59-5)	0 %	31.12.2015
ex 2922 39 00	70	p-[(2-Chloroethyl)ethylamino]benzaldehyde (CAS RN 2643-07-4)	0 %	31.12.2016
ex 2922 43 00	10	Anthranilic acid (CAS RN 118-92-3)	0 %	31.12.2018
ex 2922 49 85	10	Ornithine aspartate (INNM) (CAS RN 3230-94-2)	0 %	31.12.2018
ex 2922 49 85	15	DL-Aspartic acid used for the manufacture of food-integrators, (CAS RN 617-45-8)	0 %	31.12.2014
ex 2922 49 85	20	3-Amino-4-chlorobenzoic acid (CAS RN 2840-28-0)	0 %	31.12.2017
ex 2922 49 85	40	Norvaline	0 %	31.12.2018
ex 2922 49 85	45	Glycine (CAS RN 56-40-6)	0 %	31.12.2015
ex 2922 49 85	50	D-(-)-Dihydrophenylglycine (CAS RN 26774-88-9)	0 %	31.12.2014
ex 2922 49 85	60	Ethyl-4-dimethylaminobenzoate (CAS RN 10287-53-3)	0 %	31.12.2017
ex 2922 49 85	70	2-Ethylhexyl-4-dimethylaminobenzoate (CAS RN 21245-02-3)	0 %	31.12.2018
ex 2922 50 00	20	1-[2-Amino-1-(4-methoxyphenyl)-ethyl]-cyclohexanol hydrochloride, (CAS RN 130198-05-9)	0 %	31.12.2014
ex 2922 50 00	70	2-(1-Hydroxycyclohexyl)-2-(4-methoxyphenyl)ethylammonium acetate	0 %	31.12.2018
ex 2923 90 00	10	Tetramethylammonium hydroxide, in the form of an aqueous solution containing 25 % ( $\pm$ 0,5 %) by weight of tetramethylammonium hydroxide	0 %	31.12.2018
ex 2923 90 00	25	Tetrakis(dimethylditetradecylammonium) molybdate, (CAS RN 117342-25-3)	0 %	31.12.2018
ex 2923 90 00	45	Tetrabutylammonium hydroxide in the form of an aqueous solution containing 55 % ( $\pm$ 1 %) by weight of tetrabutylammonium hydroxide, (CAS RN 2052-49-5)	0 %	31.12.2014
ex 2923 90 00	70	Tetrapropylammonium hydroxide, in the form of an aqueous solution containing:  — 40 % (± 2 %) by weight of tetrapropylammonium hydroxide,  — 0,3 % by weight or less of carbonate,  — 0,1 % by weight or less of tripropylamine,  — 500 mg/kg or less of bromide and  — 25 mg/kg or less of potassium and sodium taken together	0 %	31.12.2018
ex 2923 90 00	75	Tetraethylammonium hydroxide, in the form of an aqueous solution containing:  — 35 % (± 0,5 %) by weight of tetraethylammonium hydroxide,  — not more than 1 000 mg/kg of chloride,  — not more than 2 mg/kg of iron and  — not more than 10 mg/kg of potassium	0 %	31.12.2015
ex 2923 90 00	80	Diallyldimethylammonium chloride, in the form of an aqueous solution containing	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		by weight 63 % or more but not more than 67 % of diallyldimethylammonium chloride, (CAS RN 7398-69-8)		
ex 2924 19 00	10	2-Acrylamido-2-methylpropanesulphonic acid (CAS RN 15214-89-8) or its sodium salt (CAS RN 5165-97-9), or its ammonium salt (CAS RN 58374-69-9)	0 %	31.12.2018
ex 2924 19 00	30	Methyl 2-acetamido-3-chloropropionate (CAS RN 87333-22-0)	0 %	31.12.2018
ex 2924 19 00	40	N-(1,1-Dimethyl-3-oxobutyl)acrylamide (CAS RN 2873-97-4)	0 %	31.12.2018
ex 2924 19 00	50	Acrylamide (CAS RN 79-06-1)	0 %	31.12.2018
ex 2924 19 00	60	N,N-Dimethylacrylamide (CAS RN 2680-03-7)	0 %	31.12.2016
ex 2924 19 00	70	Methylcarbamate (CAS RN 598-55-0)	0 %	31.12.2018
ex 2924 19 00	80	Tetrabutylurea (CAS RN 4559-86-8)	0 %	31.12.2017
ex 2924 21 00	10	4,4'-Dihydroxy-7,7'-ureylenedi(naphthalene-2-sulfonic acid) and its sodium salts	0 %	31.12.2018
ex 2924 21 00	20	(3-Aminophenyl)urea hydrochloride (CAS RN 59690-88-9)	0 %	31.12.2018
ex 2924 29 98	10	Alachlor (ISO), (CAS RN 15972-60-8)	0 %	31.12.2018
ex 2924 29 98	12	4-(Acetylamino)-2-aminobenzenesulphonic acid (CAS RN 88-64-2)	0 %	31.12.2018
ex 2924 29 98	15	Acetochlor (ISO), (CAS RN 34256-82-1)	0 %	31.12.2018
ex 2924 29 98	20	2-Chloro- <i>N</i> -(2-ethyl-6-methylphenyl)- <i>N</i> -(propan-2-yloxymethyl)acetamide, (CAS RN 86763-47-5)	0 %	31.12.2014
ex 2924 29 98	27	2-Bromo-4-fluoroacetanilide (CAS RN 1009-22-9)	0 %	31.12.2016
ex 2924 29 98	40	N,N'-1,4-Phenylenebis[3-oxobutyramide], (CAS RN 24731-73-5)	0 %	31.12.2015
ex 2924 29 98	45	Propoxur (ISO) (CAS RN 114-26-1)	0 %	31.12.2015
ex 2924 29 98	50	N,N'-(2,5-Dichloro-1,4-phenylene)bis[3-oxobutyramide], (CAS RN 42487-09-2)	0 %	31.12.2015
ex 2924 29 98	51	Methyl 2-amino-4-[[(2,5-dichlorophenyl)amino]carbonyl]benzoate (CAS RN 59673-82-4)	0 %	31.12.2017
ex 2924 29 98	53	4-Amino-N-[4-(aminocarbonyl)phenyl]benzamide (CAS RN 74441-06-8)	0 %	31.12.2017
ex 2924 29 98	55	N,N'-(2,5-Dimethyl-1,4-phenylene)bis[3-oxobutyramide], (CAS RN 24304-50-5)	0 %	31.12.2015
ex 2924 29 98	60	N,N'-(2-Chloro-5-methyl-1,4-phenylene)bis[3-oxobutyramide], (CAS RN 41131-65-1)	0 %	31.12.2015
ex 2924 29 98	63	N-Ethyl-2-(isopropyl)-5-methylcyclohexanecarboxamide (CAS RN 39711-79-0)	0 %	31.12.2016
ex 2924 29 98	65	2-(4-Hydroxyphenyl)acetamide (CAS RN 17194-82-0)	0 %	31.12.2018
ex 2924 29 98	75	3-Amino- <i>p</i> -anisanilide (CAS RN 120-35-4)	0 %	31.12.2018
ex 2924 29 98	80	5'-Chloro-3-hydroxy-2',4'-dimethoxy-2-naphthanilide (CAS RN 92-72-8)	0 %	31.12.2018
ex 2924 29 98	85	p-Aminobenzamide (CAS RN 2835-68-9)	0 %	31.12.2018
ex 2924 29 98	86	Anthranilamide of a purity by weight of 99,5 % or more (CAS RN 88-68-6)	0 %	31.12.2017

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 2924 29 98	87	Paracetamol (INN) (CAS RN 103-90-2)	0 %	31.12.2018
ex 2924 29 98	88	5'-Chloro-3-hydroxy-2'-methyl-2-naphthanilide (CAS RN 135-63-7)	0 %	31.12.2018
ex 2924 29 98	89	Flutolanil (ISO) (CAS RN 66332-96-5)	0 %	31.12.2018
ex 2924 29 98	91	3-Hydroxy-2'-methoxy-2-naphthanilide (CAS RN 135-62-6)	0 %	31.12.2018
ex 2924 29 98	92	3-Hydroxy-2-naphthanilide (CAS RN 92-77-3)	0 %	31.12.2014
ex 2924 29 98	93	3-Hydroxy-2'-methyl-2-naphthanilide (CAS RN 135-61-5)	0 %	31.12.2018
ex 2924 29 98	94	2'-Ethoxy-3-hydroxy-2-naphthanilide (CAS RN 92-74-0)	0 %	31.12.2018
ex 2924 29 98	97	1,1-Cyclohexanediacetic acid monoamide (CAS RN 99189-60-3)	0 %	31.12.2018
ex 2925 11 00	20	Saccharin and its sodium salt	0 %	31.12.2018
ex 2925 19 95	10	N-Phenylmaleimide (CAS RN 941-69-5)	0 %	31.12.2018
ex 2925 19 95	20	4,5,6,7-Tetrahydroisoindole-1,3-dione (CAS RN 4720-86-9)	0 %	31.12.2017
ex 2925 19 95	30	N,N'-(m-Phenylene)dimaleimide (CAS RN 3006-93-7)	0 %	31.12.2017
ex 2925 29 00	10	Dicyclohexylcarbodiimide (CAS RN 538-75-0)	0 %	31.12.2018
ex 2925 29 00	20	N-[3-(Dimethylamino)propyl]-N'-ethylcarbodiimide hydrochloride (CAS RN 25952-53-8)	0 %	01.01.2018
ex 2926 90 95	13	alpha-Bromo-o-toluonitrile (CAS RN 22115-41-9)	0 %	31.12.2018
ex 2926 90 95	20	2-(m-Benzoylphenyl)propiononitrile (CAS RN 42872-30-0)	0 %	31.12.2014
ex 2926 90 95	25	2,2-Dibromo-3-nitrilopropionamide (CAS RN 10222-01-2)	0 %	31.12.2016
ex 2926 90 95	30	2-Amino-3-(3,4-dimethoxyphenyl)-2-methylpropanenitrile hydrochloride, (CAS RN 2544-13-0)	0 %	31.12.2015
ex 2926 90 95	50	Alkyl or alkoxyalkyl esters of cyanoacetic acid	0 %	31.12.2018
ex 2926 90 95	55	Methyl-2-cyano-2-phenylbutyrate (CAS RN 24131-07-5)	0 %	31.12.2016
ex 2926 90 95	60	Cyanoacetic acid in crystalline form (CAS RN 372-09-8)	0 %	31.12.2014
ex 2926 90 95	61	m-(1-Cyanoethyl)benzoic acid (CAS RN 5537-71-3)	0 %	31.12.2016
ex 2926 90 95	63	1-(Cyanoacetyl)-3-ethylurea (CAS RN 41078-06-2)	0 %	31.12.2014
ex 2926 90 95	64	Esfenvalerate of a purity by weight of 83 % or more in a mixture of its own isomers (CAS RN 66230-04-4)	0 %	31.12.2014
ex 2926 90 95	65	Malononitrile (CAS RN 109-77-3)	0 %	31.12.2018
ex 2926 90 95	70	Methacrylonitrile (CAS RN 126-98-7)	0 %	31.12.2014
ex 2926 90 95	74	Chlorothalonil (ISO) (CAS RN 1897-45-6)	0 %	31.12.2014
ex 2926 90 95	75	Ethyl 2-cyano-2-ethyl-3-methylhexanoate (CAS RN 100453-11-0)	0 %	31.12.2014
ex 2926 90 95	80	Ethyl 2-cyano-2-phenylbutyrate (CAS RN 718-71-8)	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 2926 90 95	86	Ethylenediaminetetraacetonitrile (CAS RN 5766-67-6)	0 %	31.12.2018
ex 2926 90 95	89	Butyronitrile (CAS RN 109-74-0)	0 %	31.12.2018
ex 2927 00 00	10	2,2'-Dimethyl-2,2'-azodipropionamidine dihydrochloride	0 %	31.12.2018
ex 2927 00 00	20	4-Anilino-2-methoxybenzenediazonium hydrogen sulphate (CAS RN 36305-05-2)	0 %	31.12.2018
ex 2927 00 00	30	4'-Aminoazobenzene-4-sulphonic acid (CAS RN 104-23-4)	0 %	31.12.2018
ex 2927 00 00	70	Tetrasodium 3,3'-[azoxybis[(2-methoxy-4,1-phenylene)azo]]bis[4,5-dihydroxynaphthalene-2,7-disulphonate], (CAS RN 83968-64-3)	0 %	31.12.2014
ex 2927 00 00	80	4-[(2,5-Dichlorophenyl)azo]-3-hydroxy-2-naphthoic acid (CAS RN 51867-77-7)	0 %	31.12.2017
ex 2928 00 90	10	3,3'-Bis(3,5-di- <i>tert</i> -butyl-4-hydroxyphenyl)- <i>N,N</i> '-bipropionamide (CAS RN 32687-78-8)	0 %	31.12.2018
ex 2928 00 90	25	Acetaldehyde oxime in an aqueous solution (CAS RN 107-29-9)	0 %	31.12.2015
ex 2928 00 90	30	N-Isopropylhydroxylamine (CAS RN 5080-22-8)	0 %	31.12.2016
ex 2928 00 90	35	2-Chloro-N-methoxy-N-methylacetamide (CAS RN 67442-07-3)	0 %	31.12.2018
ex 2928 00 90	40	O-Ethylhydroxylamine, in the form of an aqueous solution (CAS RN 624-86-2)	0 %	31.12.2018
ex 2928 00 90	45	Tebufenozide (ISO) (CAS RN 112410-23-8)	0 %	31.12.2018
ex 2928 00 90	55	Aminoguanidinium hydrogen carbonate (CAS RN 2582-30-1)	0 %	31.12.2018
ex 2928 00 90	60	Adipohydrazide (CAS RN 1071-93-8)	0 %	31.12.2018
ex 2928 00 90	70	Butanone oxime (CAS RN 96-29-7)	0 %	31.12.2018
ex 2928 00 90	75	Metaflumizone (ISO) (CAS RN 139968-49-3)	0 %	31.12.2016
ex 2928 00 90	80	Cyflufenamid (ISO) (CAS RN 180409-60-3)	0 %	31.12.2018
ex 2928 00 90	85	Daminozide (ISO) with a purity by weight of 99 % or more (CAS RN 1596-84-5)	0 %	31.12.2016
ex 2929 10 00	10	Methylenedicyclohexyl diisocyanates (CAS RN 28605-81-4)	0 %	31.12.2018
ex 2929 10 00	15	3,3'-Dimethylbiphenyl-4,4'-diyl diisocyanate (CAS RN 91-97-4)	0 %	31.12.2014
ex 2929 10 00	20	Butyl isocyanate (CAS RN 111-36-4)	0 %	31.12.2017
ex 2929 10 00	40	<i>m</i> -Isopropenyl- <i>α</i> , <i>α</i> -dimethylbenzyl isocyanate (CAS RN 2094-99-7)	0 %	31.12.2018
ex 2929 10 00	50	<i>m</i> -Phenylenediisopropylidene diisocyanate (CAS RN 2778-42-9)	0 %	31.12.2018
ex 2929 10 00	55	2,5 (and 2,6)-Bis(isocyanatomethyl)bicyclo[2.2.1]heptane (CAS RN 74091-64-8)	0 %	31.12.2015
ex 2929 10 00	60	Trimethylhexamethylene diisocyanate, mixed isomers	0 %	31.12.2018
ex 2929 10 00	80	1,3-Bis(isocyanatomethyl)benzene (CAS RN 3634-83-1)	0 %	31.12.2016
ex 2930 20 00	10	Prosulfocarb (ISO) (CAS RN 52888-80-9)	0 %	31.12.2017
ex 2930 20 00	20	2-Isopropylethylthiocarbamate (CAS RN 141-98-0)	0 %	31.12.2016
ex 2930 90 99	10	2,3-Bis((2-mercaptoethyl)thio)-1-propanethiol (CAS RN 131538-00-6)	0 %	31.12.2015

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 2930 90 99	13	Mercaptamine hydrochloride (CAS RN 156-57-0)	0 %	31.12.2016
ex 2930 90 99	14	4-(Methylthio)benzaldehyde (CAS RN 3446-89-7)	0 %	31.12.2018
ex 2930 90 99	15	Ethoprophos (ISO) (CAS RN 13194-48-4)	0 %	31.12.2018
ex 2930 90 99	17	2-(3-Aminophenylsulphonyl)ethyl hydrogen sulphate (CAS RN 2494-88-4)	0 %	31.12.2018
ex 2930 90 99	18	1-Methyl-5-[3-methyl-4-[4-[(trifluoromethyl)thio]phenoxy]phenyl]biuret (CAS RN 106310-17-2)	0 %	31.12.2016
ex 2930 90 99	20	2-Methoxy-N-[2-nitro-5-(phenylthio)phenyl]acetamide (CAS RN 63470-85-9)	0 %	31.12.2015
ex 2930 90 99	23	Dimethyl [(methylsulphanyl)methylylidene]biscarbamate (CAS RN 34840-23-8)	0 %	31.12.2018
ex 2930 90 99	25	Thiophanate-methyl (ISO), (CAS RN 23564-05-8)	0 %	31.12.2018
ex 2930 90 99	30	4-(4-Isopropoxyphenylsulphonyl)phenol (CAS RN 95235-30-6)	0 %	31.12.2018
ex 2930 90 99	35	Glutathione (CAS RN 70-18-8)	0 %	31.12.2016
ex 2930 90 99	40	3,3'-Thiodi(propionic acid) (CAS RN 111-17-1)	0 %	31.12.2018
ex 2930 90 99	45	2-[(p-Aminophenyl)sulphonyl]ethyl hydrogen sulphate (CAS RN 2494-89-5)	0 %	31.12.2018
ex 2930 90 99	50	[S-(R*,R*)]-2-Amino-1-[4-(methylthio)-phenyl]-1,3-propanediol, (CAS RN 23150-35-8)	0 %	31.12.2015
ex 2930 90 99	55	Thiourea (CAS RN 62-56-6)	0 %	31.12.2015
ex 2930 90 99	60	Methyl phenyl sulphide (CAS RN 100-68-5)	0 %	31.12.2018
ex 2930 90 99	62	Zinc bis(benzenesulfinate) (CAS RN 24308-84-7)	0 %	31.12.2014
ex 2930 90 99	64	3-Chloro-2-methylphenyl methyl sulphide (CAS RN 82961-52-2)	0 %	31.12.2014
ex 2930 90 99	65	Pentaerythritol tetrakis(3-mercaptopropionate) (CAS RN 7575-23-7)	0 %	31.12.2015
ex 2930 90 99	66	Diphenyl sulphide (CAS RN 139-66-2)	0 %	31.12.2017
ex 2930 90 99	67	3-Bromomethyl-2-chloro-4-(methylsulphonyl)-benzoic acid (CAS RN 120100-05-2)	0 %	31.12.2018
ex 2930 90 99	68	Clethodim (ISO) (CAS RN 99129-21-2)	0 %	31.12.2017
ex 2930 90 99	77	4-[4-(2-Propenyloxy)phenylsulphonyl]phenol (CAS RN 97042-18-7)	0 %	31.12.2018
ex 2930 90 99	78	4-Mercaptomethyl-3,6-dithia-1,8-octanedithiol (CAS RN 131538-00-6)	0 %	31.12.2016
ex 2930 90 99	80	Captan (ISO) (CAS RN 133-06-2)	0 %	31.12.2018
ex 2930 90 99	81	Disodium hexamethylene-1,6-bisthiosulfate dihydrate (CAS RN 5719-73-3)	3 %	31.12.2014
ex 2930 90 99	83	Methyl-p-tolyl sulphone (CAS RN 3185-99-7)	0 %	31.12.2017
ex 2930 90 99	84	2-Chloro-4-(methylsulphonyl)benzoic acid (CAS RN 53250-83-2)	0 %	31.12.2014
ex 2930 90 99	87	3-Sulphinobenzoic acid (CAS RN 15451-00-0)	0 %	31.12.2018
ex 2930 90 99	89	Potassium- or sodium-salt of O-ethyl-, O-isopropyl-, O-butyl-, O-isobutyl- or O-pentyl-dithiocarbonates	0 %	31.12.2016

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 2931 90 90	05	Butylethylmagnesium (CAS RN 62202-86-2), in the form of a solution in heptane	0 %	31.12.2018
ex 2931 90 90	10	Diethylmethoxyborane (CAS RN 7397-46-8), whether or not in the form of a solution in tetrahydrofuran according to note 1e to Chapter 29 of the CN	0 %	31.12.2015
ex 2931 90 90	14	Sodium diisobutyldithiophosphinate (CAS RN 13360-78-6) in an aqueous solution	0 %	31.12.2017
ex 2931 90 90	15	Triethylborane (CAS RN 97-94-9)	0 %	31.12.2015
ex 2931 90 90	18	Trioctylphosphine oxide (CAS RN 78-50-2)	0 %	31.12.2016
ex 2931 90 90	20	Methylcyclopentadienyl manganese tricarbonyl containing not more than 4,9 % by weight of cyclopentadienyl manganese tricarbonyl, (CAS RN 12108-13-3)	0 %	31.12.2014
ex 2931 90 90	24	Methyl tris (2-pentanoneoxime) silane (CAS RN 37859-55-5)	0 %	31.12.2014
ex 2931 90 90	30	Diethylborane isopropoxide (CAS RN 74953-03-0)	0 %	31.12.2015
ex 2931 90 90	35	(Z)-Prop-1-en-1-ylphosphonic acid (CAS RN 25383-06-6)	0 %	31.12.2017
ex 2931 90 90	40	N-(Phosphonomethyl)iminodiacetic acid (CAS RN 5994-61-6)	0 %	31.12.2014
ex 2931 90 90	50	Bis(2,4,4-trimethylpentyl)phosphinic acid (CAS RN 83411-71-6)	0 %	31.12.2018
ex 2931 90 90	55	Dimethyl[dimethylsilyldiindenyl]hafnium (CAS RN 220492-55-7)	0 %	31.12.2014
ex 2931 90 90	70	N,N-Dimethylanilinium tetrakis(pentafluorophenyl)borate (CAS RN 118612-00-3)	0 %	31.12.2014
ex 2931 90 90	72	Phenylphosphonic dichloride (CAS RN 824-72-6)	0 %	31.12.2016
ex 2931 90 90	75	Tetrakis(hydroxymethyl)phosphonium chloride (CAS RN 124-64-1)	0 %	31.12.2016
ex 2931 90 90	86	Mixture of the isomers 9-icosyl-9-phosphabicyclo[3.3.1]nonane and 9-icosyl-9-phosphabicyclo[4.2.1]nonane	0 %	31.12.2018
ex 2931 90 90	87	Tris(4-methylpentan-2-oximino)methylsilane (CAS RN 37859-57-7)	0 %	31.12.2018
ex 2931 90 90	89	Tetrabutylphosphonium acetate in the form of an aqueous solution (CAS RN 30345-49-4)	0 %	31.12.2014
ex 2931 90 90	91	Trimethylsilane (CAS RN 993-07-7)	0 %	31.12.2016
ex 2931 90 90	92	Trimethylborane (CAS RN 593-90-8)	0 %	31.12.2014
ex 2931 90 90	96	3-(Hydroxyphenylphosphinoyl)propionic acid (CAS RN 14657-64-8)	0 %	31.12.2018
ex 2932 13 00	10	Tetrahydrofurfuryl alcohol (CAS RN 97-99-4)	0 %	31.12.2018
ex 2932 19 00	40	Furan (CAS RN 110-00-9) of a purity by weight of 99 % or more	0 %	31.12.2014
ex 2932 19 00	41	2,2 di(tetrahydrofuryl)propane (CAS RN 89686-69-1)	0 %	31.12.2014
ex 2932 19 00	45	1,6-Dichloro-1,6-dideoxy-β-D-fructofuranosyl-4-chloro-4 deoxy-α-D-galactopyranoside, (CAS RN 56038-13-2)	0 %	31.12.2014
ex 2932 19 00	50	2-Methylfuran (CAS RN 534-22-5)	0 %	31.12.2015
ex 2932 19 00	70	Furfurylamine (CAS RN 617-89-0)	0 %	31.12.2014
ex 2932 19 00	75	Tetrahydro-2-methylfuran (CAS RN 96-47-9)	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 2932 19 00	80	5-Nitrofurfurylidene di(acetate) (CAS RN 92-55-7)	0 %	31.12.2016
ex 2932 20 90	10	2'-Anilino-6'-[ethyl(isopentyl)amino]-3'-methylspiro[isobenzofuran-1(3H),9'-xanthen]-3-one (CAS RN 70516-41-5)	0 %	31.12.2018
ex 2932 20 90	15	Coumarin (CAS RN 91-64-5)	0 %	31.12.2016
ex 2932 20 90	20	Ethyl 6'-(diethylamino)-3-oxo-3 <i>H</i> -spiro[2-benzofuran-1,9'-xanthene]-2'-carboxylate (CAS RN 154306-60-2)	0 %	31.12.2017
ex 2932 20 90	35	6'-Diethylamino-3'-methyl-2'-(2,4-xylidino)spiro[isobenzofuran-1(3 <i>H</i> ),9'-xanthen]-3-one (CAS RN 36431-22-8)	0 %	31.12.2018
ex 2932 20 90	40	(S)-(-)-α-Amino-γ-butyrolactonehydrobromide (CAS RN 15295-77-9)	0 %	31.12.2017
ex 2932 20 90	55	6-Dimethylamino-3,3-bis(4-dimethylaminophenyl)phthalide (CAS RN 1552-42-7)	0 %	31.12.2018
ex 2932 20 90	60	6'-(Diethylamino)-3'-methyl-2'-(phenylamino)-spiro[isobenzofuran-1(3 <i>H</i> ),9'-[9 <i>H</i> ]xanthen]-3-one (CAS RN 29512-49-0)	0 %	31.12.2016
ex 2932 20 90	70	3',6'-Bis(ethylamino)-2',7'-dimethylspiro[isobenzofuran-1(3 <i>H</i> ),9'-[9 <i>H</i> ]-xanthen]-3-one, (CAS RN 41382-37-0)	0 %	31.12.2018
ex 2932 20 90	71	6'-(Dibutylamino)-3'-methyl-2'-(phenylamino)-spiro[isobenzofuran-1(3 <i>H</i> ),9'-[9 <i>H</i> ]xanthen]-3-one (CAS RN 89331-94-2)	0 %	31.12.2016
ex 2932 20 90	72	2'-[Bis(phenylmethyl)amino]-6'-(diethylamino)-spiro[isobenzofuran-1(3H),9'-[9H]xanthen]-3-one (CAS RN 34372-72-0)	0 %	31.12.2016
ex 2932 20 90	80	Gibberellic acid with a minimum purity by weight of 88 % (CAS RN 77-06-5)	0 %	31.12.2018
ex 2932 20 90	84	Decahydro-3a,6,6,9a-tetramethylnaphth [2,1-b] furan-2 (1H)-one (CAS RN 564-20-5)	0 %	31.12.2018
ex 2932 99 00	10	Bendiocarb (ISO) (CAS RN 22781-23-3)	0 %	31.12.2018
ex 2932 99 00	15	1,3,4,6,7,8-Hexahydro-4,6,6,7,8,8-hexamethylindeno[5,6-c]pyran (CAS RN 1222-05-5)	0 %	31.12.2016
ex 2932 99 00	20	Ethyl-2-methyl-1,3-dioxolane-2-acetate (CAS RN 6413-10-1)	0 %	31.12.2016
ex 2932 99 00	25	1-(2,2-Difluorobenzo[d][1,3]dioxol-5-yl)cyclopropanecarboxylic acid (CAS RN 862574-88-7)	0 %	31.12.2017
ex 2932 99 00	35	1,2,3-Trideoxy-4,6:5,7-bis-O-[(4-propylphenyl)methylene]-nonitol, (CAS RN 882073-43-0)	0 %	31.12.2018
ex 2932 99 00	40	1,3:2,4-Bis-O-(3,4-dimethylbenzylidene)-D-glucitol (CAS RN 135861-56-2)	0 %	31.12.2018
ex 2932 99 00	45	2-Butylbenzofuran (CAS RN 4265-27-4)	0 %	31.12.2018
ex 2932 99 00	50	7-Methyl-3,4-dihydro-2 <i>H</i> -1,5-benzodioxepin-3-one (CAS RN 28940-11-6)	0 %	31.12.2015
ex 2932 99 00	55	6-Fluoro-3,4-dihydro-2H-1-benzopyran-2-carboxylic acid (CAS RN 99199-60-7)	0 %	31.12.2018
ex 2932 99 00	70	1,3:2,4-bis-O-Benzylidene-D-glucitol (CAS RN 32647-67-9)	0 %	31.12.2016
ex 2932 99 00	75	3-(3,4-Methylenedioxyphenyl)-2-methylpropanal (CAS RN 1205-17-0)	0 %	31.12.2016
ex 2932 99 00	80	1,3:2,4-bis-O-(4-Methylbenzylidene)-D-glucitol (CAS RN 32647-67-9)	0 %	31.12.2016
ex 2933 19 90	30	3-Methyl-1-p-tolyl-5-pyrazolone (CAS RN 86-92-0)	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 2933 19 90	40	Edaravone (INN) (CAS RN 89-25-8)	0 %	31.12.2018
ex 2933 19 90	50	Fenpyroximate (ISO) (CAS RN 134098-61-6)	0 %	31.12.2014
ex 2933 19 90	60	Pyraflufen-ethyl (ISO) (CAS RN 129630-19-9)	0 %	31.12.2014
ex 2933 19 90	70	4,5-Diamino-1-(2-hydroxyethyl)-pyrazolsulphate (CAS RN 155601-30-2)	0 %	31.12.2018
ex 2933 19 90	80	3-(4,5-Dihydro-3-methyl-5-oxo-1 <i>H</i> -pyrazol-1-yl)benzenesulphonic acid (CAS RN 119-17-5)	0 %	31.12.2017
ex 2933 19 90	85	Allyl 5-amino-4-(2-methylphenyl)-3-oxo-2,3-dihydro-1H-1-pyrazolcarbothioate (CAS RN 473799-16-5)	0 %	31.12.2017
ex 2933 21 00	50	1-Bromo-3-chloro-5,5-dimethylhydantoin (CAS RN 16079-88-2)	0 %	31.12.2016
ex 2933 21 00	60	DL-p-Hydroxyphenylhydantoin (CAS RN 2420-17-9)	0 %	31.12.2016
ex 2933 21 00	70	α-(4-Methoxybenzoyl)- $α$ -(1-benzyl-5-ethoxy-3-hydantoinyl)-2-chloro-5-dodecyloxycarbonylacetanilide, (CAS RN 70950-45-7)	0 %	31.12.2016
ex 2933 21 00	80	5,5-Dimethylhydantoin (CAS RN 77-71-4)	0 %	31.12.2015
ex 2933 29 90	15	Ethyl 4-(1-hydroxy-1-methylethyl)-2-propylimidazole-5-carboxylate (CAS RN 144689-93-0)	0 %	31.12.2018
ex 2933 29 90	25	Prochloraz (ISO) (CAS RN 67747-09-5)	0 %	31.12.2018
ex 2933 29 90	35	1-Trityl-4-formylimidazole (CAS RN 33016-47-6)	0 %	31.12.2018
ex 2933 29 90	40	Triflumizole (ISO) (CAS RN 68694-11-1)	0 %	31.12.2014
ex 2933 29 90	45	Prochloraz copper chloride (ISO) (CAS RN 156065-03-1)	0 %	31.12.2018
ex 2933 29 90	50	1,3-Dimethylimidazolidin-2-one (CAS RN 80-73-9)	0 %	31.12.2018
ex 2933 29 90	60	1-Cyano-2-methyl-1-[2-(5-methylimidazol-4-ylmethylthio)ethyl]isothiourea (CAS RN 52378-40-2)	0 %	31.12.2016
ex 2933 29 90	70	Cyazofamid (ISO) (CAS RN 120116-88-3)	0 %	31.12.2016
ex 2933 29 90	80	Imazalil (ISO) (CAS RN 35554-44-0)	0 %	31.12.2017
ex 2933 39 99	12	2,3-Dichloropyridine (CAS RN 2402-77-9)	0 %	31.12.2017
ex 2933 39 99	15	Pyridine-2,3-dicarboxylic acid (CAS RN 89-00-9)	0 %	31.12.2018
ex 2933 39 99	18	6-Chloro-3-nitropyridin-2-ylamine (CAS RN 27048-04-0)	0 %	31.12.2017
ex 2933 39 99	20	Copper pyrithione powder (CAS RN 14915-37-8)	0 %	31.12.2014
ex 2933 39 99	24	2-Chloromethyl-4-methoxy-3,5-dimethylpyridine hydrochloride (CAS RN 86604-75-3)	0 %	31.12.2014
ex 2933 39 99	25	Imazethapyr (ISO) (CAS RN 81335-77-5)	0 %	31.12.2018
ex 2933 39 99	30	Fluazinam (ISO) (CAS RN 79622-59-6)	0 %	31.12.2014
ex 2933 39 99	32	2-(Chloromethyl)-3,4-dimethoxypyridine hydrochloride (CAS RN 72830-09-2)	0 %	31.12.2016
ex 2933 39 99	35	Aminopyralid (ISO) (CAS RN 150114-71-9)	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 2933 39 99	37	Aqueous solution of pyridine-2-thiol-1-oxide, sodium salt (CAS RN 3811-73-2)	0 %	31.12.2016
ex 2933 39 99	40	2-Chloropyridine (CAS RN 109-09-1)	0 %	31.12.2018
ex 2933 39 99	42	2,2,6,6-Tetramethylpiperidine (CAS RN 768-66-1)	0 %	31.12.2016
ex 2933 39 99	45	5-Difluoromethoxy-2-[[(3,4-dimethoxy-2-pyridyl)methyl]thio]-1 <i>H</i> -benzimidazole, (CAS RN 102625-64-9)	0 %	31.12.2014
ex 2933 39 99	47	(-)-trans-4-(4'-Fluorophenyl)-3-hydroxymethyl-N-methylpiperidine (CAS RN 105812-81-5)	0 %	31.12.2014
ex 2933 39 99	48	Flonicamid (ISO) (CAS RN 158062-67-0)	0 %	31.12.2014
ex 2933 39 99	49	2-[[[3-Methyl-4-(2,2,2-trifluoroethoxy)-2-pyridinyl]methyl]thio]-1 <i>H</i> -benzimidazole, (CAS RN 103577-40-8)	0 %	31.12.2015
ex 2933 39 99	50	N-Fluoro-2,6-dichloropyridinium tetrafluoroborate (CAS RN 140623-89-8)	0 %	31.12.2016
ex 2933 39 99	53	3-Bromopyridine (CAS RN 626-55-1)	0 %	31.12.2018
ex 2933 39 99	55	Pyriproxyfen (ISO) of a purity by weight of 97 % or more (CAS RN 95737-68-1)	0 %	31.12.2014
ex 2933 39 99	57	Tert-butyl 3-(6-amino-3-methylpyridin-2-yl)benzoate (CAS RN 1083057-14-0)	0 %	31.12.2017
ex 2933 39 99	60	2-Fluoro-6-(trifluoromethyl)pyridine (CAS RN 94239-04-0)	0 %	31.12.2018
ex 2933 39 99	63	2-Aminomethyl-3-chloro-5-trifluoromethylpyridine hydrochloride (CAS RN 326476-49-7)	0 %	31.12.2018
ex 2933 39 99	65	Acetamiprid (ISO) (CAS RN 135410-20-7)	0 %	31.12.2018
ex 2933 39 99	67	(1R,3S,4S)-tert-Butyl 3-(6-bromo-1H-benzo[d]imidazol-2-yl)-2-azabicyclo[2.2.1]heptane-2-carboxylate (CAS RN 1256387-74-2)	0 %	31.12.2018
ex 2933 39 99	70	2,3-Dichloro-5-trifluoromethylpyridine (CAS RN 69045-84-7)	0 %	31.12.2016
ex 2933 39 99	72	5,6-Dimethoxy-2-[(4-piperidinyl)methyl]indan-1-one (CAS RN 120014-30-4)	0 %	31.12.2016
ex 2933 39 99	77	Imazamox (ISO) (CAS RN 114311-32-9)	0 %	31.12.2018
ex 2933 39 99	85	2-Chloro-5-chloromethylpyridine (CAS RN 70258-18-3)	0 %	31.12.2015
ex 2933 49 10	10	Quinmerac (ISO) (CAS RN 90717-03-6)	0 %	31.12.2018
ex 2933 49 10	20	3-Hydroxy-2-methylquinoline-4-carboxylic acid (CAS RN 117-57-7)	0 %	31.12.2018
ex 2933 49 10	30	Ethyl 4-oxo-1,4-dihydroquinoline-3-carboxylate (CAS RN 52980-28-6)	0 %	31.12.2017
ex 2933 49 90	30	Quinoline (CAS RN 91-22-5)	0 %	31.12.2015
ex 2933 49 90	40	Isoquinoline (CAS RN 119-65-3)	0 %	31.12.2015
ex 2933 49 90	60	5,6,7,8-Tetrahydroquinoline (CAS RN 10500-57-9)	0 %	31.12.2014
ex 2933 49 90	70	Quinolin-8-ol (CAS RN 148-24-3)	0 %	31.12.2018
ex 2933 52 00	10	Malonylurea (barbituric acid) (CAS RN 67-52-7)	0 %	31.12.2016
ex 2933 59 95	15	Sitagliptin phosphate monohydrate (CAS RN 654671-77-9)	0 %	01.07.2014

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 2933 59 95	17	N,N'-(4,6-Dichloropyrimidine-2,5-diyl)diformamide (CAS RN 116477-30-6)	0 %	31.12.2018
ex 2933 59 95	20	2,4-Diamino-6-chloropyrimidine (CAS RN 156-83-2)	0 %	31.12.2018
ex 2933 59 95	23	6-Chloro-3-methyluracil (CAS RN 4318-56-3)	0 %	31.12.2018
ex 2933 59 95	27	2-[(2-Amino-6-oxo-1,6-dihydro-9H-purin-9-yl)methoxy]-3-hydroxypropylacetate (CAS RN 88110-89-8)	0 %	31.12.2018
ex 2933 59 95	30	Mepanipyrim (ISO) (CAS RN 110235-47-7)	0 %	31.12.2018
ex 2933 59 95	45	1-[3-(Hydroxymethyl)pyridin-2-yl]-4-methyl-2-phenylpiperazine (CAS RN 61337-89-1)	0 %	31.12.2014
ex 2933 59 95	50	2-(2-Piperazin-1-ylethoxy)ethanol (CAS RN 13349-82-1)	0 %	31.12.2014
ex 2933 59 95	55	Thiopental (INNM) (CAS RN 76-75-5)	0 %	31.12.2014
ex 2933 59 95	60	2,6-Dichloro-4,8-dipiperidinopyrimido[5,4-d]pyrimidine (CAS RN 7139-02-8)	0 %	31.12.2018
ex 2933 59 95	65	1-Chloromethyl-4-fluoro-1,4-diazoniabicyclo[2.2.2]octane bis(tetrafluoroborate), (CAS RN 140681-55-6)	0 %	31.12.2014
ex 2933 59 95	70	N-(4-Ethyl-2,3-dioxopiperazin-1-ylcarbonyl)-D-2-phenylglycine (CAS RN 63422-71-9)	0 %	31.12.2018
ex 2933 59 95	72	Triacetylganciclovir (CAS RN 86357-14-4)	0 %	31.12.2016
ex 2933 59 95	75	(2R,3S/2S,3R)-3-(6-Chloro-5-fluoro pyrimidin-4-yl)-2-(2,4-difluorophenyl)-1-(1 <i>H</i> -1,2,4-triazol-1-yl)butan-2-ol hydrochloride, (CAS RN 188416-20-8)	0 %	31.12.2014
ex 2933 59 95	77	3-(Trifluoromethyl)-5,6,7,8-tetrahydro[1,2,4]triazolo[4,3-a]pyrazine hydrochloride (1:1) (CAS RN 762240-92-6)	0 %	31.12.2017
ex 2933 69 80	25	1,3,5-Triazine-2,4,6-triamine monophosphate (CAS RN 20208-95-1)	0 %	31.12.2016
ex 2933 69 80	40	Troclosene sodium (INNM) (CAS RN 2893-78-9)	0 %	31.12.2016
ex 2933 69 80	50	1,3,5-Tris(2,3-dibromopropyl)-1,3,5-triazinane-2,4,6-trione (CAS RN 52434-90-9)	0 %	31.12.2018
ex 2933 69 80	55	Terbutryn (ISO) (CAS RN 886-50-0)	0 %	31.12.2015
ex 2933 69 80	60	Cyanuric acid (CAS RN 108-80-5)	0 %	31.12.2015
ex 2933 69 80	80	Tris(2-hydroxyethyl)-1,3,5-triazinetrione (CAS RN 839-90-7)	0 %	31.12.2018
ex 2933 79 00	30	5-Vinyl-2-pyrrolidone (CAS RN 7529-16-0)	0 %	31.12.2017
ex 2933 79 00	50	6-Bromo-3-methyl-3H-dibenz(f,ij)isoquinoline-2,7-dione (CAS RN 81-85-6)	0 %	31.12.2018
ex 2933 79 00	60	3,3-Pentamethylene-4-butyrolactam (CAS RN 64744-50-9)	0 %	31.12.2014
ex 2933 79 00	70	(S)-N-[(Diethylamino)methyl]-alpha-ethyl-2-oxo-1-pyrrolidineacetamide L-(+)-tartrate, (CAS RN 754186-36-2)	0 %	31.12.2015
ex 2933 99 80	10	2-(2 <i>H</i> -Benzotriazol-2-yl)-4,6-di- <i>tert</i> -butylphenol (CAS RN 3846-71-7)	0 %	31.12.2018
ex 2933 99 80	13	5-Difluoromethoxy-2-mercapto-1-H-benzimidazole (CAS RN 97963-62-7)	0 %	31.12.2016
ex 2933 99 80	15	2-(2H-Benzotriazol-2-yl)-4,6-di-tert-pentylphenol (CAS RN 25973-55-1)	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 2933 99 80	18	4,4'-[(9-Butyl-9H-carbazol-3-yl)methylene]bis[N-methyl-N-phenylaniline] (CAS RN 67707-04-4)	0 %	31.12.2017
ex 2933 99 80	20	2-(2 <i>H</i> -Benzotriazol-2-yl)-4,6-bis(1-methyl-1-phenylethyl)phenol (CAS RN 70321-86-7)	0 %	31.12.2018
ex 2933 99 80	22	(2S)-2-Benzyl- <i>N</i> , <i>N</i> -dimethylaziridine-1-sulfonamide (CAS RN 902146-43-4)	0 %	31.12.2017
ex 2933 99 80	24	1,3-Dihydro-5,6-diamino-2 <i>H</i> -benzimidazol-2-one (CAS RN 55621-49-3)	0 %	31.12.2017
ex 2933 99 80	28	<i>N</i> -(2,3-Dihydro-2-oxo-1H-benzimidazol-5-yl)-3-hydroxynaphthalene-2-carboxamide (CAS RN 26848-40-8)	0 %	31.12.2017
ex 2933 99 80	30	Quizalofop-P-ethyl (ISO) (CAS RN 100646-51-3)	0 %	31.12.2018
ex 2933 99 80	32	5-[4'-(Bromomethyl)biphenyl-2-yl]-2-trityl-2 <i>H</i> -tetrazole (CAS RN 133051-88-4)	0 %	31.12.2014
ex 2933 99 80	35	1,3,3-Trimethyl-2-methyleneindoline (CAS RN 118-12-7)	0 %	31.12.2014
ex 2933 99 80	37	8-Chloro-5,10-dihydro-11 <i>H</i> -dibenzo [ <i>b,e</i> ] [1,4]diazepin-11-one (CAS RN 50892-62-1)	0 %	31.12.2014
ex 2933 99 80	40	trans-4-Hydroxy-L-proline (CAS RN 51-35-4)	0 %	31.12.2018
ex 2933 99 80	43	2,3-Dihydro-1 <i>H</i> -pyrrole[3,2,1-ij]quinoline (CAS RN 5840-01-7)	0 %	31.12.2017
ex 2933 99 80	45	Maleic hydrazide (ISO) (CAS RN 123-33-1)	0 %	31.12.2018
ex 2933 99 80	47	Paclobutrazol (ISO) (CAS RN 76738-62-0)	0 %	31.12.2017
ex 2933 99 80	50	Metconazole (ISO) (CAS RN 125116-23-6)	3.2 %	31.12.2018
ex 2933 99 80	53	Potassium (S)-5-(tert-butoxycarbonyl)-5-azaspiro[2.4]heptane-6-carboxylate (CUS 0133723-1)	0 %	31.12.2018
ex 2933 99 80	55	Pyridaben (ISO) (CAS RN 96489-71-3)	0 %	31.12.2014
ex 2933 99 80	57	2-(5-Methoxyindol-3-yl)ethylamine (CAS RN 608-07-1)	0 %	31.12.2018
ex 2933 99 80	62	1H-Indole-6-carboxylic acid (CAS RN 1670-82-2)	0 %	31.12.2018
ex 2933 99 80	64	((3R)-1-{(1R,2R)-2-[2-(3,4-Dimethoxyphenyl) ethoxy]cyclohexyl}pyrrolidin-3-ol.hydrochloride, (CAS RN 748810-28-8)	0 %	31.12.2015
ex 2933 99 80	67	Candesartan ethyl ester (INNM) (CAS RN 139481-58-6)	0 %	31.12.2016
ex 2933 99 80	71	10-Methoxyiminostilbene (CAS RN 4698-11-7)	0 %	31.12.2018
ex 2933 99 80	72	1,4,7-Trimethyl-1,4,7-Triazacyclononane	0 %	31.12.2018
ex 2933 99 80	74	Imidazo[1,2-b] pyridazine-hydrochloride (CAS RN 18087-70-2)	0 %	31.12.2018
ex 2933 99 80	76	Manganese(2+), bis(octahydro-1,4,7-trimethyl-1H-1,4,7-triazonine-N1,N4,N7)tri-μ-oxodi-, acetate (1:2) (CAS RN 916075-10-0)	0 %	31.12.2014
ex 2933 99 80	78	3-Amino-3-azabicyclo (3.3.0) octane hydrochloride (CAS RN 58108-05-7)	0 %	31.12.2018
ex 2933 99 80	81	1,2,3-Benzotriazole (CAS RN 95-14-7)	0 %	31.12.2016
ex 2933 99 80	82	Tolytriazole (CAS RN 29385-43-1)	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 2933 99 80	88	2,6-Dichloroquinoxaline (CAS RN 18671-97-1)	0 %	31.12.2014
ex 2933 99 80	89	Carbendazim (ISO) (CAS RN 10605-21-7)	0 %	31.12.2018
ex 2934 10 00	10	Hexythiazox (ISO) (CAS RN 78587-05-0)	0 %	31.12.2018
ex 2934 10 00	15	4-Nitrophenyl thiazol-5-ylmethyl carbonate (CAS RN 144163-97-3)	0 %	31.12.2017
ex 2934 10 00	20	2-(4-Methylthiazol-5-yl)ethanol (CAS RN 137-00-8)	0 %	31.12.2018
ex 2934 10 00	25	(S)-Ethyl-2-(3-((2-isopropylthiazol-4-yl)methyl)-3-methylureido)-4-morpholinobutanoate oxalate (CAS RN 1247119-36-3)	0 %	31.12.2017
ex 2934 10 00	35	(2-Isopropylthiazol-4-yl)- <i>N</i> -methylmethanamine dihydrochloride (CAS RN 1185167-55-8)	0 %	31.12.2017
ex 2934 10 00	40	(Z)-2-(2-tert-butoxycarbonylaminothiazol-4-yl)-2-pentenoic acid (CAS RN 86978-24-7)	0 %	31.12.2018
ex 2934 10 00	60	Fosthiazate (ISO) (CAS RN 98886-44-3)	0 %	31.12.2014
ex 2934 10 00	70	2-(Formylamino)-4-thiazoleacetyl chloride, hydrochloride (CAS RN 372092-18-7)	0 %	31.12.2016
ex 2934 10 00	80	3,4-Dichloro-5-carboxyisothiazole (CAS RN 18480-53-0)	0 %	31.12.2016
ex 2934 20 80	20	S-1,3-Benzothiazol-2-yl (2Z)-(5-amino-1,2,4-thiadiazol-3-yl)(methoxyimino)ethanethioate (CAS RN 89604-91-1)	0 %	31.12.2016
ex 2934 20 80	30	2-[[(Z)-[1-(2-Amino-4-thiazolyl)-2-(2-benzothiazolylthio)-2-oxoethylidene]amino]oxy]-acetic acid, methyl ester (CAS RN 246035-38-1)	0 %	31.12.2016
ex 2934 20 80	40	1,2-Benzisothiazol-3(2H)-one (Benzisothiazolinone (BIT)) (CAS RN 2634-33-5)	0 %	31.12.2017
ex 2934 20 80	50	S-(1,3-Benzothiazol-2-yl)-(Z)-2-(2-aminothiazol-4-yl)-2-(acetyloxyimino)thioacetate, (CAS RN 104797-47-9)	0 %	31.12.2018
ex 2934 20 80	60	Benzothiazol-2-yl-(Z)-2-trityloxyimino-2-(2-aminothiazole-4-yl)-thioacetate (CAS RN 143183-03-3)	0 %	31.12.2015
ex 2934 20 80	70	N,N-Bis(1,3-benzothiazol-2-ylsulphanyl)-2-methylpropan-2-amine (CAS RN 3741-80-8)	0 %	31.12.2015
ex 2934 30 90	10	2-Methylthiophenothiazine (CAS RN 7643-08-5)	0 %	31.12.2017
ex 2934 99 90	11	Methyl 3-{1,4-dioxaspiro[4.5]dec-8-yl[(trans-4-methylcyclohexyl)carbonyl]amino}-5-iodothiophene-2-carboxylate (CAS RN 1026785-65-8)	0 %	31.12.2018
ex 2934 99 90	12	Dimethomorph (ISO) (CAS RN 110488-70-5)	0 %	31.12.2018
ex 2934 99 90	13	Buprofezin (ISO) of a purity by weight of 98,5 % or more (CAS RN 953030-84-7)	0 %	31.12.2018
ex 2934 99 90	14	Ethyl N-{[1-methyl-2-({[4-(5-oxo-4,5-dihydro-1,2,4-oxadiazol-3-yl)phenyl]amino}methyl)-1H-benzimidazol-5-yl]carbonyl}-N-pyridin-2-yl-balaninate (CAS RN 872728-84-2)	0 %	31.12.2017
ex 2934 99 90	15	Carboxin (ISO) (CAS RN 5234-68-4)	0 %	31.12.2018
ex 2934 99 90	17	Methyl(1,8-diethyl-1,3,4,9-tetrahydropyrano[3,4-b]indol-1-yl)acetate (CAS RN 122188-02-7)	0 %	31.12.2016
ex 2934 99 90	18	3,3-bis(2-Methyl-1-octyl-1H-indol-3-yl)phthalide (CAS RN 50292-95-0)	0 %	31.12.2017

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 2934 99 90	20	Thiophene (CAS RN 110-02-1)	0 %	31.12.2014
ex 2934 99 90	22	7-[4-(Diethylamino)-2-ethoxyphenyl]-7-(2-methyl-1-octyl-1H-indol-3-yl) furo[3,4-b]pyridin-5(7H)-one (CAS RN 87563-89-1)	0 %	31.12.2017
ex 2934 99 90	23	Bromuconazole (ISO) with a purity by weight of 96 % or more (CAS RN 116255-48-2)	0 %	31.12.2016
ex 2934 99 90	25	2,4-Diethyl-9 <i>H</i> -thioxanthen-9-one (CAS RN 82799-44-8)	0 %	31.12.2015
ex 2934 99 90	28	11-(Piperazin-1-yl)dibenzo[b,f][1,4]thiazepine dihydrochloride (CAS RN 111974-74-4)	0 %	31.12.2016
ex 2934 99 90	30	Dibenzo[b,f][1,4]thiazepin-11(10H)-one (CAS RN 3159-07-7)	0 %	31.12.2014
ex 2934 99 90	33	[2,2'-Thio-bis(4-tert-octylphenolato)]-n-butylamine nickel (CAS RN 14516-71-3)	0 %	31.12.2016
ex 2934 99 90	35	Dimethenamide (ISO) (CAS RN 87674-68-8)	0 %	31.12.2018
ex 2934 99 90	37	4-Propan-2-ylmorpholine (CAS RN 1004-14-4)	0 %	31.12.2017
ex 2934 99 90	40	2-Thiophene ethylamine (CAS RN 30433-91-1)	0 %	31.12.2015
ex 2934 99 90	43	Clopidogrel acid hydrochloride (CAS RN 144750-42-5)	0 %	31.12.2016
ex 2934 99 90	45	Tris(2,3-epoxypropyl)-1,3,5-triazinanetrione (CAS RN 2451-62-9)	0 %	31.12.2018
ex 2934 99 90	48	Propan-2-ol 2-methyl-4-(4-methylpiperazin-1-yl)-10 <i>H</i> -thieno[2,3-b][1,5]benzodiazepine (1:2) dihydrate (CAS RN 864743-41-9)	0 %	31.12.2016
ex 2934 99 90	50	10-[1,1'-Biphenyl]-4-yl-2-(1-methylethyl)-9-oxo-9 <i>H</i> -thioxanthenium hexafluorophosphate, (CAS RN 591773-92-1)	0 %	31.12.2015
ex 2934 99 90	55	Olmesartan medoxomil (INN) (CAS RN 144689-63-4)	0 %	31.12.2018
ex 2934 99 90	60	DL-Homocysteine thiolactone hydrochloride (CAS RN 6038-19-3)	0 %	31.12.2018
ex 2934 99 90	66	Tetrahydrothiophene-1,1-dioxide (CAS RN 126-33-0)	0 %	31.12.2018
ex 2934 99 90	72	1-[3-(5-Nitro-2-furyl)allylideneamino]imidazolidine-2,4-dione (CAS RN 1672-88-4)	0 %	31.12.2018
ex 2934 99 90	74	2-Isopropylthioxanthone (CAS RN 5495-84-1)	0 %	31.12.2017
ex 2934 99 90	75	(4 <i>R-cis</i> )-1,1-Dimethylethyl-6-[2[2-(4-fluorophenyl)-5-(1-isopropyl)-3-phenyl-4-[(phenylamino)carbonyl]-1 <i>H</i> -pyrrol-1-yl]ethyl]-2,2-dimethyl-1,3-dioxane-4-acetate (CAS RN 125971-95-1)	0 %	31.12.2016
ex 2934 99 90 ex 3204 20 00	76 10	2,5-Thiophenediylbis(5-tert-butyl-1,3-benzoxazole) (CAS RN 7128-64-5)	0 %	31.12.2016
ex 2934 99 90	77	Potassium 5-methyl-1,3,4-oxadiazole-2-carboxylate (CAS RN 888504-28-7)	0 %	31.12.2016
ex 2934 99 90	79	Thiophen-2-ethanol (CAS RN 5402-55-1)	0 %	31.12.2018
ex 2934 99 90	83	Flumioxazin (ISO) of a purity by weight of 96 % or more (CAS RN 103361-09-7)	0 %	31.12.2014
ex 2934 99 90	84	Etoxazole (ISO) of a purity by weight of 94,8 % or more (CAS RN 153233-91-1)	0 %	31.12.2014
ex 2934 99 90	85	N2-[1-(S)-Ethoxycarbonyl-3-phenylpropyl]-N6-trifluoroacetyl-L-lysyl-N2-carboxy anhydride (CAS RN 126586-91-2)	0 %	31.12.2015

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 2934 99 90	86	Dithianon (ISO) (CAS RN 3347-22-6)	0 %	31.12.2015
ex 2934 99 90	87	2,2'-(1,4-Phenylene)bis(4H-3,1-benzoxazin-4-one) (CAS RN 18600-59-4)	0 %	31.12.2015
ex 2935 00 90	15	Flupyrsulfuron-methyl-sodium (ISO) (CAS RN 144740-54-5)	0 %	31.12.2018
ex 2935 00 90	17	6-Methyl-4-oxo-5,6-dihydro-4H-thieno[2,3-b]thiopyran-2-sulfonamide (CAS RN 120279-88-1)	0 %	31.12.2018
ex 2935 00 90	20	Toluenesulphonamides	0 %	31.12.2018
ex 2935 00 90	23	N-[4-(2-Chloroacetyl)phenyl]methanesulphonamide (CAS RN 64488-52-4)	0 %	31.12.2016
ex 2935 00 90	25	Triflusulfuron-methyl (ISO) (CAS RN 126535-15-7)	0 %	31.12.2018
ex 2935 00 90	27	Methyl (3R,5S,6E)-7-{4-(4-fluorophenyl)-6-isopropyl-2-[methyl(methylsulfonyl)amino]pyrimidin-5-yl}-3,5-dihydroxyhept-6-enoate (CAS RN 147118-40-9)	0 %	31.12.2016
ex 2935 00 90	28	N-Fluorobenzenesulphonimide (CAS RN 133745-75-2)	0 %	31.12.2018
ex 2935 00 90	30	Mixture of isomers consisting of N-ethyltoluene-2-sulphonamide and N-ethyltoluene-4-sulphonamide	0 %	31.12.2014
ex 2935 00 90	35	Chlorsulfuron (ISO) (CAS RN 64902-72-3)	0 %	31.12.2018
ex 2935 00 90	40	Imazosulfuron (ISO), of a purity by weight of 98 % or more (CAS RN 122548-33-8)	0 %	31.12.2015
ex 2935 00 90	42	Penoxsulam (ISO) (CAS RN 219714-96-2)	0 %	31.12.2015
ex 2935 00 90	45	Rimsulfuron (ISO) (CAS RN 122931-48-0)	0 %	31.12.2018
ex 2935 00 90	48	(3R,5S,6E)-7-[4-(4-Fluorophenyl)-2-[methyl(methylsulfonyl)amino]-6-(propan-2-yl)pyrimidin-5-yl]-3,5-dihydroxyhept-6-enoic acid 1-[(R)-(4-chlorophenyl)(phenyl)methyl]piperazine (1:1) (CAS RN 1235588-99-4)	0 %	31.12.2016
ex 2935 00 90	50	4,4'-Oxydi(benzenesulphonohydrazide) (CAS RN 80-51-3)	0 %	31.12.2018
ex 2935 00 90	53	2,4-Dichloro-5-sulphamoylbenzoic acid (CAS RN 2736-23-4)	0 %	31.12.2014
ex 2935 00 90	55	Thifensulfuron-methyl (ISO) (CAS RN 79277-27-3)	0 %	31.12.2018
ex 2935 00 90	63	Nicosulphuron (ISO), of a purity by weight of 91 % or more (CAS RN 111991-09-4)	0 %	31.12.2014
ex 2935 00 90	65	Tribenuron-methyl (ISO) (CAS RN 101200-48-0)	0 %	31.12.2018
ex 2935 00 90	75	Metsulfuron-methyl (ISO) (CAS RN 74223-64-6)	0 %	31.12.2018
ex 2935 00 90	77	[[4-[2-[[(3-Ethyl-2,5-dihydro-4-methyl-2-oxo-1 <i>H</i> -pyrrol-1-yl)carbonyl]amino] ethyl]phenyl]sulfonyl]-carbamic acid ethyl ester, (CAS RN 318515-70-7)	0 %	31.12.2014
ex 2935 00 90	82	<i>N</i> -(5,7-Dimethoxy[1,2,4]triazolo[1,5-a]pyrimidin-2-yl)-2-methoxy-4-(trifluoromethyl)pyridine-3-sulphonamide, (CAS RN 422556-08-9)	0 %	31.12.2014
ex 2935 00 90	85	N-[4-(Isopropylaminoacetyl)phenyl]methanesulphonamide hydrochloride	0 %	31.12.2018
ex 2935 00 90	88	N-(2-(4-Amino-N-ethyl-m-toluidino)ethyl)methanesulphonamide sesquisulphate monohydrate, (CAS RN 25646-71-3)	0 %	31.12.2018
ex 2935 00 90	89	3-(3-Bromo-6-fluoro-2-methylindol-1-ylsulphonyl)- <i>N,N</i> -dimethyl-1,2,4-triazol-1-	0 %	31.12.2016

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		sulphonamide (CAS RN 348635-87-0)		
ex 2938 90 30	10	Ammonium glycyrrhizate (CAS RN 53956-04-0)	0 %	31.12.2015
ex 2938 90 90	10	Hesperidin (CAS RN 520-26-3)	0 %	31.12.2018
ex 2938 90 90	20	Ethylvanillin beta-D-glucopyranoside (CAS RN 122397-96-0)	0 %	31.12.2018
ex 2941 20 30	10	Dihydrostreptomycin sulphate (CAS RN 5490-27-7)	0 %	31.12.2016
ex 3102 50 00	10	Natural sodium nitrate	0 %	31.12.2017
3201 20 00		Wattle extract	0 %	31.12.2018
ex 3201 90 90	20	Tanning extracts derived from gambier and myrobalan fruits	0 %	31.12.2018
ex 3204 11 00	20	Dye C.I. Disperse Yellow 241 (CAS RN 83249-52-9), with a purity of 97 % or more as determined by high pressure liquid chromatography	0 %	31.12.2015
ex 3204 11 00	30	Preparation of dispersion dyes, containing:  — C.I. Disperse Orange 61,  — C.I. Disperse Blue 291:1,  — C.I. Disperse Violet 93:1,  — C.I. Disperse Red 54	0 %	31.12.2015
ex 3204 11 00	40	Dye C.I. Disperse Red 60 (CAS RN 17418-58-5)	0 %	31.12.2016
ex 3204 11 00	50	Dye C.I. Disperse Blue 72 (CAS RN 81-48-1)	0 %	31.12.2016
ex 3204 11 00	60	Dye C.I. Disperse Blue 359 (CAS RN 213328-78-0)	0 %	31.12.2016
ex 3204 11 00	70	Dye C.I. Disperse Red 343 (CAS RN 99035-78-6)	0 %	31.12.2017
ex 3204 11 00	80	Dye preparation, non-ionogenic, containing:  — N-[5-(acetylamino)-4-[(2-chloro-4,6-dinitrophenyl)azo]-2-methoxyphenyl]- 2-oxo-2-(phenylmethoxy)ethyl-β-alanine (CAS RN 159010-67-0)  — N-[4-[(2-cyano-4-nitrophenyl)azo]phenyl]-N-methyl-2-(1,3-dihydro-1,3-dioxo-2H-isoindol-2-yl)ethyl-β-alanine (CAS RN 170222-39-6) and  — N-[2-chloro-4-[(4-nitrophenyl)azo]phenyl]-2-[2-(1,3-dihydro-1,3-dioxo-2H-isoindol-2-yl)ethoxy]-2-oxoethyl-β-alanine (CAS RN 371921-34-5)	0 %	31.12.2017
ex 3204 12 00	10	Dye C.I. Acid Blue 9 (CAS RN 3844-45-9)	0 %	31.12.2016
ex 3204 12 00	20	Dye preparation, anionic, containing by weight 75 % or more of disodium-7-((4-chloro-6-(dodecylamino)-1,3,5-triazin-2-yl)amino)-4-hydroxy-3-((4-((4-sulfophenyl)azo))-2-naphthalenesulfonate (CAS RN 145703-76-0)	0 %	31.12.2017
ex 3204 12 00	30	Acid dye preparation, anionic, containing:  — lithium-amino-4-(4-tert-butylanilino)anthraquinone-2-sulfonate (CAS RN 125328-86-1),  — C.I. Acid Green 25 (CAS RN 4403-90-1) and  — C.I. Acid Blue 80 (CAS RN 4474-24-2)	0 %	31.12.2017
ex 3204 12 00	40	Liquid dye preparation containing anionic acid dye C.I. Acid Blue 182 (CAS RN 12219-26-0)	0 %	31.12.2018
ex 3204 13 00	10	Dye C.I. Basic Red 1 (CAS RN 989-38-8)	0 %	31.12.2016
ex 3204 13 00	20	(2,2'-(3,3'-Dioxidobiphenyl-4,4'-diyldiazo)bis(6-(4-(3-(diethylamino)propylamino)-6-(3-(diethylammonio)propylamino)-1,3,5-triazin-2-ylamino)-3-sulfonato-1-naphtholato))dicopper(II) acetate lactate (CAS RN 159604-94-1)	0 %	31.12.2017
ex 3204 13 00	30	Dye C.I. Basic Blue 7 (CAS RN 2390-60-5)	0 %	31.12.2017

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 3204 13 00	40	Dye C.I. Basic Violet 1 (CAS RN 603-47-4)/(CAS RN 8004-87-3)	0 %	31.12.2017
ex 3204 15 00	10	Dye C.I. Vat Orange 7 (C.I. Pigment Orange 43) (CAS RN 4424-06-0)	0 %	31.12.2017
ex 3204 15 00	60	Dyestuff C.I. Vat Blue 4 (CAS RN 81-77-6)	0 %	31.12.2018
ex 3204 17 00	10	Dye C.I. Pigment Yellow 81 (CAS RN 22094-93-5)	0 %	31.12.2018
ex 3204 17 00	15	Dye C.I. Pigment Green 7 (CAS RN 1328-53-6)	0 %	31.12.2016
ex 3204 17 00	20	Dye C.I. Pigment Blue 15:3 (CAS RN 147-14-8)	0 %	31.12.2016
ex 3204 17 00	25	Dye C.I. Pigment Yellow 14 (CAS RN 5468-75-7)	0 %	31.12.2016
ex 3204 17 00	30	Dye C.I. Pigment Yellow 97 (CAS RN 12225-18-2)	0 %	31.12.2017
ex 3204 17 00	35	Dye C.I. Pigment Red 202 (CAS RN 3089-17-6)	0 %	31.12.2016
ex 3204 17 00	40	Dye C.I. Pigment Yellow 120 (CAS RN 29920-31-8)	0 %	31.12.2014
ex 3204 17 00	50	Dye C.I. Pigment Yellow 180 (CAS RN 77804-81-0)	0 %	31.12.2014
ex 3204 17 00	60	Dye C.I. Pigment Red 53:1 (CAS RN 5160-02-1)	0 %	31.12.2016
ex 3204 17 00	65	Dye C.I. Pigment Red 53 (CAS RN 2092-56-0)	0 %	31.12.2016
ex 3204 17 00	70	Dye C.I. Pigment Yellow 13 (CAS RN 5102-83-0)	0 %	31.12.2016
ex 3204 17 00	75	Dye C.I. Pigment Orange 5 (CAS RN 3468-63-1)	0 %	31.12.2017
ex 3204 17 00	80	Dye C.I. Pigment Red 207 (CAS RN 71819-77-7)	0 %	31.12.2017
ex 3204 17 00	85	Dye C.I. Pigment Blue 61 (CAS RN 1324-76-1)	0 %	31.12.2017
ex 3204 17 00	88	Dye C.I. Pigment Violet 3 (CAS RN 1325-82-2)	0 %	31.12.2017
ex 3204 19 00	11	Photochromic dye, 3-(4-butoxyphenyl-6,7-dimethoxy-3-(4-methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo[h]indeno[2,1-f]chromene-11-carbonitrile	0 %	31.12.2014
ex 3204 19 00	21	Photochromic dye, 4-(3-(4-butoxyphenyl)-6-methoxy-3-(4-methoxyphenyl)-13,13-dimethyl-11-(trifluoromethyl)-3,13-dihydrobenzo[h]indeno[2,1-f]chromen-7-yl)morpholine (CAS RN 1021540-64-6)	0 %	31.12.2014
ex 3204 19 00	31	Photochromic dye, <i>N</i> -hexyl -6,7-dimethoxy-3,3-bis(4-methoxyphenyl)-13,13-dimethyl-3,13-dihydrobenzo[ <i>h</i> ]indeno[2,1- <i>f</i> ]chromene-11-carboxamide	0 %	31.12.2014
ex 3204 19 00	41	Photochromic dye, 4,4'-(13,13-dimethyl-3,13-dihydrobenzo[h]indeno[2,1-f]chromene-3,3-diyl)diphenol	0 %	31.12.2014
ex 3204 19 00	43	Photochromic dye, bis(2-(4-(7-methoxy-3-(4-methoxyphenyl)-11-phenyl-13, 13-dipropyl-3, 13-dihydrobenzo[h]indeno[2,1-f]chromen-3-yl)phenoxy)ethyl) decanedioate (CUS 0133724-2)	0 %	31.12.2018
ex 3204 19 00	47	Photochromic dye, 4-(4-(13,13-dimethyl-3,11-diphenyl-3,13-dihydrobenzo[h]indeno[2,1-f]chromen-3-yl)phenyl)morpholine (CUS 0133726-4)	0 %	31.12.2018
ex 3204 19 00	51	Photochromic dye, 4-(4-(6,11-difluoro-13,13-dimethyl-3-phenyl-3,13-dihydrobenzo[h]indeno[2,1-f] ]chromen-3-yl)phenyl)morpholine (CAS RN 1360882-72-6)	0 %	31.12.2014

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 3204 19 00	53	Photochromic dye, 3-(4-butoxyphenyl)-3-(4-fluorophenyl)-6,7-dimethoxy-13,13-dimethyl-3,13-dihydrobenzo[h]indeno[2,1-f]chromene-11-carbonitrile (CUS 0133725-3)	0 %	31.12.2018
ex 3204 19 00	55	Photochromic dye, 4, 4'-(7-methoxy-11-phenyl-13, 13-dipropyl-3, dihydrobenzo[h]indeno[2, 1-f]chromene-3, 3-diyl)diphenol (CUS 0133728-6)	0 %	31.12.2018
ex 3204 19 00	57	Photochromic dye, bis(2-{4-[11-cyano-3-(4-fluorophenyl)-6,7-dimethoxy-13,13-dimethyl-3, 13-dihydrobenzo[h]indeno[2,1-f]chromen-3-yl]phenoxy}ethyl) decanedioate (CUS 0133729-7)	0 %	31.12.2018
ex 3204 19 00	61	Photochromic dye, 3-(4-butoxyphenyl)-6,7-dimethoxy-3-(4-methoxyphenyl)-13,13-dimethyl-11-(trifluoromethyl)-3,13-dihydrobenzo[h]indeno[2,1-f]chromene (CAS RN 1021540-61-3)	0 %	31.12.2014
ex 3204 19 00	63	Photochromic dye, 1-{4-(6-methoxy-3-(4-methoxyphenyl)-13,13-dimethyl-3, 13-dihydrobenzo[h]indeno[2,1-f]chromen-3-yl)phenyl}piperidine (CUS 0133727-5)	0 %	31.12.2018
ex 3204 19 00	70	Dye C.I. Solvent Red 49 (CAS RN 509-34-2)	0 %	31.12.2018
ex 3204 19 00	71	Dye C.I. Solvent Brown 53 (CAS RN 64696-98-6)	0 %	31.12.2015
ex 3204 19 00	73	Dye C.I. Solvent Blue 104 (CAS RN 116-75-6) with a purity of 97 % or more determined by high pressure liquid chromatography	0 %	31.12.2015
ex 3204 19 00	77	Dye C.I. Solvent Yellow 98 (CAS RN 27870-92-4)	0 %	31.12.2016
ex 3204 19 00	84	Dye C.I. Solvent Blue 67 (CAS RN 12226-78-7)	0 %	31.12.2017
ex 3204 19 00	85	Dye C.I. Solvent Red HPR	0 %	31.12.2017
ex 3204 20 00	20	Dye C.I. Fluorescent Brightener 71 (CAS RN 16090-02-1)	0 %	31.12.2016
ex 3204 20 00	30	Dye C.I. Fluorescent Brightener 351 (CAS RN 38775-22-3)	0 %	31.12.2016
ex 3204 20 00	40	Disodium 5-[[4-anilino-6-[2-hydroxyethyl(methyl)amino]-1,3,5-triazin-2-yl]amino]-2-[(E)-2-[4-[[4-anilino-6-[2-hydroxyethyl(methyl)amino]-1,3,5-triazin-2-yl]amino]-2-sulfonatophenyl]ethenyl]benzenesulphonate (CAS RN 13863-31-5)	0 %	31.12.2018
ex 3205 00 00	10	Aluminium lakes prepared from dyes for use in the manufacture of pigments for the pharmaceutical industry	0 %	31.12.2018
ex 3205 00 00	20	Dye C.I. Carbon Black 7 Lake	0 %	31.12.2016
ex 3206 11 00	10	Titanium dioxide coated with isopropoxytitanium triisostearate, containing by weight 1,5 % or more but not more than 2,5 % of isopropoxytitanium triisostearate	0 %	31.12.2018
ex 3206 19 00	10	Preparation containing by weight:  — 72 % (± 2 %) of mica (CAS RN 12001-26-2) and  — 28 % (± 2 %) of titanium dioxide (CAS RN 13463-67-7)	0 %	31.12.2016
ex 3206 42 00	10	Lithopone (CAS RN 1345-05-7)	0 %	31.12.2018
3206 50 00		Inorganic products of a kind used as luminophores	0 %	31.12.2018
ex 3207 30 00	10	Preparation containing:  — not more than 85 % by weight of silver,  — not less than 2 % by weight of palladium,	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		barium titanate,     terpineol, and     ethyl cellulose,     used for screen printing in the manufacture of multilayer ceramic capacitors		
ex 3207 40 85	20	Glass flakes coated with silver, of an average diameter of 40 ( $\pm$ 10) $\mu m$	0 %	31.12.2018
ex 3207 40 85	40	Glass flakes (CAS RN 65997-17-3):  — of a thickness of 0,3 μm or more but not more than 10 μm, and  — coated with titanium dioxide (CAS RN 13463-67-7) or iron oxide (CAS RN 18282-10-5)	0 %	31.12.2017
ex 3208 10 90 ex 3707 90 90	10 60	Anti-reflection coating, consisting of an ester based polymer modified with a chromophore group, in the form of a solution of either 2-methoxy-1-propanol, 2-methoxy-1-methylethyl acetate or methyl-2-hydroxyisobutyrate, containing by weight not more than 10 % of polymer	0 %	31.12.2018
ex 3208 20 10	10	Copolymer of <i>N</i> -vinylcaprolactam, <i>N</i> -vinyl-2-pyrrolidone and dimethylaminoethyl methacrylate, in the form of a solution in ethanol containing by weight 34 % or more but not more than 40 % of copolymer	0 %	31.12.2018
ex 3208 20 10	20	Immersion topcoat solution containing by weight 0,5 % or more but not more than 15 % of acrylate-methacrylate-alkenesulphonate copolymers with fluorinated side chains, in a solution of n-butanol and/or 4-methyl-2-pentanol and/or diisoamylether	0 %	31.12.2018
ex 3208 90 19	10	Copolymer of maleic acid and methyl vinyl ether, monoesterified with ethyl and/or isopropyl and/or butyl groups, in the form of a solution in ethanol, ethanol and butanol, isopropanol or isopropanol and butanol	0 %	31.12.2018
ex 3208 90 19 ex 3902 90 90	15 94	Modified, chlorinated polyolefins, whether or not in a solution or dispersion	0 %	31.12.2018
ex 3208 90 19 ex 3208 90 91	25 20	Tetrafluoroethylene copolymer in butylacetate solution with a content of solvent of 50 % ( $\pm$ 2 %) by weight	0 %	31.12.2017
ex 3208 90 19	35	Silicones containing 50 % by weight or more of xylene of a kind used for the manufacture of long term surgical implants	0 %	31.12.2018
ex 3208 90 19	40	Polymer of methylsiloxane, in the form of a solution in a mixture of acetone, butanol, ethanol and isopropanol, containing by weight 5 % or more but not more than 11 % of polymer of methylsiloxane	0 %	31.12.2018
ex 3208 90 19	50	Solution containing by weight:  — $(65 \pm 10)$ % of $\gamma$ -butyrolactone,  — $(30 \pm 10)$ % of polyamide resin,  — $(3,5 \pm 1,5)$ % of naphthoquinone ester derivative and  — $(1,5 \pm 0,5)$ % of arylsilicic acid	0 %	31.12.2018
ex 3208 90 19	60	Copolymer of hydroxystyrene with one or more of the following:  — styrene  — alkoxystyrene  — alkylacrylates dissolved in ethyl lactate	0 %	31.12.2016
ex 3208 90 19	75	Acenaphthalene copolymer in ethyl lactate solution	0 %	31.12.2017
ex 3208 90 99	10	Solution based on chemically modified natural polymers, containing two or more of the following dyes:  — methyl 8'-acetoxy-1,3,3,5,6-pentamethyl-2,3-dihydrospiro[1 <i>H</i> -indole-2,3'-naphtho[2,1- <i>b</i> ][1,4]oxazine]-9'-carboxylate,  — methyl 6-(isobutyryloxy)-2,2-diphenyl-2 <i>H</i> -benzo[ <i>h</i> ]chromene-5-carboxylate,	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		<ul> <li>— 13-isopropyl-3,3-bis(4-methoxyphenyl)-6,11-dimethyl-3,13-dihydrobenzo[h]indeno[2,1-f]chromen-13-ol,</li> <li>— ethoxycarbonylmethyl 8-methyl-2,2-diphenyl-2H-benzo[h]chromene-5-carboxylate,</li> <li>— 13-ethyl-3-[4-(morpholino)phenyl]-3-phenyl-3,13-dihydrobenzo[h]indeno[2,1-f]chromen-13-ol</li> </ul>		
ex 3215 11 00 ex 3215 19 00	10 10	Printing ink, liquid, consisting of a dispersion of a vinyl acrylate copolymer and colour pigments in isoparaffins, containing by weight not more than 13 % of vinyl acrylate copolymer and colour pigments	0 %	31.12.2018
ex 3215 19 00	20	Ink:  — consisting of a polyester polymer and a dispersion of silver (CAS RN 7440-22-4) and silver chloride (CAS RN 7783-90-6) in methyl propyl ketone (CAS RN 107-87-9),  — with a total solid content by weight of 55 % or more, but not more than 57 %, and  — with a specific gravity of 1,40 g/cm³ or more, but not more than 1,60 g/cm³, used to imprint electrodes	0 %	31.12.2017
ex 3215 90 00	10	Ink formulation, for use in the manufacture of ink-jet cartridges	0 %	31.12.2018
ex 3215 90 00	20	Heat sensitive ink fixed on a plastic film	0 %	31.12.2018
ex 3215 90 00	30	Disposable cartridge ink, containing by weight:  — 5 % or more, but not more than 10 % of amorphous silicon dioxide or  — 3,8 % or more of dye C.I. Solvent Black 7 in organic solvents for use in the marking of integrated circuits	0 %	31.12.2018
ex 3215 90 00	40	Dry ink powder with a base of hybrid resin (made from polystyrene acrylic resin and polyester resin) mixed with:  — wax;  — a vinyl-based polymer and — a colouring agent for use in the manufacture of toner bottles for photocopiers, fax machines, printers and multifunction devices	0 %	31.12.2015
3301 12 10		Essential oil of orange, not deterpenated	0 %	31.12.2018
ex 3402 11 90	10	Sodium lauroyl methyl isethionate	0 %	31.12.2015
ex 3402 13 00	10	Vinyl copolymer surface active agent based on polypropylene glycol	0 %	31.12.2018
ex 3402 13 00	20	Surfactant containing 1,4-dimethyl-1,4-bis(2-methylpropyl)-2-butyne-1,4-diyl ether, polymerised with oxirane, methyl terminated	0 %	31.12.2017
ex 3402 13 00	30	Polyoxyethylated-12-hydroxystearic acid (CAS RN 70142–34–6)	0 %	31.12.2018
ex 3402 90 10	20	Mixture of docusate sodium (INN) and sodium benzoate	0 %	31.12.2018
ex 3402 90 10	30	Surface-active preparation, consisting of a mixture of sodium docusate and ethoxylated 2,4,7,9-tetramethyldec-5-yne-4,7-diol (CAS RN 577-11-7 and 9014-85-1)	0 %	31.12.2015
ex 3402 90 10	50	Surface-active preparation, consisting of a mixture of polysiloxane and poly(ethylene glycol)	0 %	31.12.2015
ex 3402 90 10	60	Surface-active preparation, containing 2-ethylhexyloxymethyl oxirane	0 %	31.12.2014

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 3402 90 10	70	Surface-active preparation, containing ethoxylated 2,4,7,9-tetramethyl-5-decyne-4,7-diol (CAS RN 9014-85-1)	0 %	31.12.2014
ex 3403 99 00	10	Cutting-fluid preparation based on an aqueous solution of synthetic polypeptides	0 %	31.12.2018
ex 3504 00 90	10	Avidin (CAS RN 1405-69-2)	0 %	31.12.2014
ex 3505 10 50	20	O-(2-Hydroxyethyl)-derivative of hydrolysed maize starch (CAS RN 9005-27-0)	0 %	31.12.2018
ex 3506 91 00	10	Adhesive based on an aqueous dispersion of a mixture of dimerised rosin and a copolymer of ethylene and vinyl acetate (EVA)	0 %	31.12.2018
ex 3506 91 00	30	Two component microencapsulated epoxy adhesive dispersed in a solvent	0 %	31.12.2018
ex 3506 91 00	40	Acrylic pressure sensitive adhesive with a thickness of 0,076 mm or more but not more than 0,127 mm, put up in rolls of a width of 45,7 cm or more but not more than 132 cm supplied on a release liner with an initial peel adhesion release value of not less than 15 N/25 mm (measured according to ASTM D3330)	0 %	31.12.2014
ex 3601 00 00	10	Pyrotechnical powder in the form of granulate of cylindrical shape, composed of strontium nitrate or copper nitrate in the solution of nitroguanidine, binder and additives, used as a component of airbag inflators (1)	0 %	31.12.2016
ex 3701 30 00	10	Relief printing plate, of a kind used for printing on newsprint, consisting of a metal substrate coated with a photopolymer layer of a thickness of 0,2 mm or more but not more than 0,8 mm, not covered with a release film, of a total thickness of not more than 1 mm	0 %	31.12.2018
ex 3701 30 00	20	Photosensitive plate consisting of a photopolymer layer on a polyester foil of a total thickness of more than 0,43 mm but not more than 3,18 mm	0 %	31.12.2014
ex 3701 99 00	10	Plate of quartz or of glass, covered with a film of chromium and coated with a photosensitive or electron-sensitive resin, of a kind used forgoods of heading 8541 or 8542	0 %	01.07.2014
ex 3705 90 90	10	Photomasks for photographically transferring circuit diagram patterns onto semiconductor wafers	0 %	31.12.2014
ex 3707 10 00	10	Photosensitive emulsion for the sensitization of silicon discs (1)	0 %	31.12.2018
ex 3707 10 00	15	Sensitising emulsion consisting of:  — by weight not more than 12 % of diazooxonapthtalenesulphonic acid ester  — phenolic resins in a solution containing at least 2-methoxy-1-methylethyl acetate or ethyl lactate or methyl 3-methoxypropionate or 2-heptanone	0 %	31.12.2018
ex 3707 10 00	25	Sensitising emulsion containing:  — phenolic or acrylic resins  — a maximum 2 % by weight of light sensitive acid precursor, in a solution containing 2-methoxy-1-methylethyl acetate or ethyl lactate	0 %	31.12.2018
ex 3707 10 00	30	Preparation based on photosensitive acrylic containing polymer, containing colour pigments, 2-methoxy-1-methylethylacetate and cyclohexanone and whether or not containing ethyl-3-ethoxypropionate	0 %	31.12.2018
ex 3707 10 00 ex 3707 90 90	35 70	Sensitising emulsion or preparation containing one or more of:  — acrylate polymers,  — methacrylate polymers,  — derivatives of styrene polymers,  containing by weight not more than 7 % of photosensitive acid precursors, dissolved in an organic solvent containing at least 2-methoxy-1-methylethyl acetate	0 %	31.12.2016
ex 3707 10 00	40	Sensitising emulsion, containing:	0 %	31.12.2016

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		<ul> <li>not more than 10 % by weight of naphthoquinonediazide esters,</li> <li>2 % or more but not more than 20 % by weight of copolymers of hydroxystyrene</li> <li>not more than 7 % by weight of epoxy-containing derivatives dissolved in 1-ethoxy-2-propyl acetate and/or ethyl lactate</li> </ul>		
ex 3707 10 00	45	Photosensitive emulsion consisting of cyclized polyisoprene containing:  — 55 % or more but not more than 75 % by weight of xylene and  — 12 % or more but not more than 18 % by weight of ethylbenzene	0 %	31.12.2014
ex 3707 10 00	50	Photosensitive emulsion containing by weight:  — 20 % or more but not more than 45 % of copolymers of acrylates and/or methacrylates and hydroxystyrene derivatives,  — 25 % or more but not more than 50 % of organic solvent containing at least ethyl lactate and/or propylene glycolmethylether acetate,  — 5 % or more but not more than 30 % of acrylates,  — not more than 12 % of a photoinitiator	0 %	31.12.2014
ex 3707 10 00	55	Dielectric coating, buffering mechanical stress, consisting of a radically photopatternable polyamide-precursor with unsaturated carbon in the side-chains which is convertible into a polyimide, in form of a solution from N-methyl-2-pyrrolidone or N-ethyl-2-pyrrolidon with a polymer content by weight 10 % or more	0 %	31.12.2018
ex 3707 90 20	10	Dry ink powder or toner blend, consisting of a copolymer of styrene and butyl acrylate and either magnetite or carbon black, for use as a developer in the manufacture of cartridges for facsimile machines, computer printers or copiers (1)	0 %	31.12.2018
ex 3707 90 20	20	Dry ink powder or toner blend, based on a polyol resin, for use as a developer in the manufacture of cartridges for facsimile machines, computer printers or copiers	0 %	31.12.2018
ex 3707 90 20	40	Dry ink powder or toner blend, based on a polyester resin, manufactured by a polymerisation process, for use as a developer in the manufacture of cartridges for facsimile machines, computer printers or copiers (1)	0 %	31.12.2018
ex 3707 90 20	50	Dry ink powder or toner blend, consisting of:  — styrene acrylate/butadiene copolymer  — either carbon black or an organic pigment  — whether or not containing polyolefin or amorphous silica for use as a developer in the manufacturing of ink/toner filled bottles or cartridges for facsimile machines, computer printers and copiers	0 %	31.12.2017
ex 3707 90 90	10	Anti-reflection coating, consisting of a modified methacrylic polymer, containing by weight not more than 10 % of polymer, in a solution in two or three of the following substances:  — 2-methoxy-1-methylethyl acetate (CAS RN 108-65-6)  — 1-methoxypropan-2-ol (CAS RN 107-98-2)  — ethyl lactate (CAS RN 97-64-3)	0 %	31.12.2018
ex 3707 90 90	40	Anti-reflection coating, in the form of an aqueous solution, containing by weight not more than:  — 2 % of halogen-free alkyl sulphonic acid, and  — 5 % of a fluorinated polymer	0 %	31.12.2014
ex 3707 90 90	80	Anti-reflection coating, consisting of either a siloxane polymer or an organic polymer having a phenolic hydroxy group modified with a chromophore group, in the form of a solution of an organic solvent containing either 1-ethoxy-2-propanol or 2-methoxy-1-methylethyl acetate containing by weight not more than 10 % of polymer	0 %	31.12.2015
ex 3707 90 90	85	Rolls, containing:	0 %	31.12.2014

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		<ul> <li>a dry layer of a photosensitive acrylic resin,</li> <li>on one side a poly(ethylene terephthalate) protecting foil and</li> <li>on the other side a polyethylene protecting foil</li> </ul>		
ex 3801 90 00	10	Expandable graphite (CAS RN 90387-90-9 and CAS RN 12777-87-6)	0 %	31.12.2016
ex 3802 90 00	11	Soda flux calcinated diatomaceous earth, acid washed, for use as a filter aid in the manufacture of pharmaceutical and/or biochemical products	0 %	31.12.2017
3805 90 10		Pine oil	1.7 %	31.12.2018
ex 3806 10 00 ex 3909 40 00	20 50	Rosin modified phenolic resin, — containing 60 % or more but not more than 75 % by weight of rosin, — with an acid value of not more than 25, of a kind used in offset printing	0 %	31.12.2016
ex 3808 91 90	10	Indoxacarb (ISO) and its (R) isomer, fixed on a support of silicon dioxide	0 %	31.12.2018
ex 3808 91 90	30	Preparation containing endospores or spores and protein crystals derived from either:  — Bacillus thuringiensis Berliner subsp. aizawai and kurstaki or,  — Bacillus thuringiensis subsp. kurstaki or,  — Bacillus thuringiensis subsp. israelensis or,  — Bacillus thuringiensis subsp. aizawai or,  — Bacillus thuringiensis subsp. tenebrionis	0 %	31.12.2014
ex 3808 91 90	40	Spinosad (ISO)	0 %	31.12.2018
ex 3808 91 90	60	Spinetoram (ISO) (CAS RN 935545-74-7), preparation of two spinosyn components (3'-ethoxy-5,6-dihydro spinosyn J) and (3'-ethoxy- spinosyn L)	0 %	31.12.2017
ex 3808 92 90	10	Fungicide in the form of a powder, containing by weight 65 % or more but not more than 75 % of hymexazole (ISO), not put up for retail sale	0 %	31.12.2018
ex 3808 92 90	30	Preparation consisting of a suspension of pyrithione zinc (INN) in water, containing by weight:  — 24 % or more but not more than 26 % of pyrithione zinc (INN), or  — 39 % or more but not more than 41 % of pyrithione zinc (INN)	0 %	31.12.2018
ex 3808 92 90	50	Preparations based on copper pyrithione (CAS RN 14915-37-8)	0 %	31.12.2014
ex 3808 93 15	10	Preparation based on a concentrate containing by weight 45 % or more but not more than 55 % of the active herbicidal ingredient Penoxsulam as an aqueous suspension	0 %	31.12.2017
ex 3808 93 23	10	Herbicide containing flazasulfuron (ISO) as an active ingredient	0 %	31.12.2014
ex 3808 93 27	40	Preparation, consisting of a suspension of tepraloxydim (ISO), containing by weight:  — 30 % or more of tepraloxydim (ISO) and  — not more than 70 % of a petroleum fraction consisting of aromatic hydrocarbons	0 %	31.12.2016
ex 3808 93 90	10	Preparation, in the form of granules, containing by weight:  — 38,8 % or more but not more than 41,2 % of Gibberellin A3, or  — 9,5 % or more but not more than 10,5 % of Gibberellin A4 and A7	0 %	31.12.2014
ex 3808 93 90	20	Preparation consisting of benzyl(purin-6-yl)amine in a glycol solution, containing by weight:  — 1,88 % or more but not more than 2,00 % of benzyl(purin-6-yl)amine of a kind used in plant growth regulators	0 %	31.12.2015
ex 3808 93 90	30	Aqueous solution containing by weight:	0 %	31.12.2015

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		<ul> <li>1,8 % of sodium para-nitrophenolate,</li> <li>1,2 % of sodium ortho-nitrophenolate,</li> <li>0,6 % of sodium 5-nitroguaiacolate</li> <li>for use in the manufacture of a plant growth regulator</li> </ul>		
ex 3808 93 90	40	Mixed white powder containing by weight:  — 3 % or more but not more than 3,6 % of 1-methylcyclopropene with a purity more than 96 % and  — containing less than 0,05 % of each impurity of 1-chloro-2-methylpropene and 3-chloro-2-methylpropene for use in the manufacture of a growth regulator of post-harvest fruits, vegetables and ornamentals with a specific generator	0 %	31.12.2015
ex 3808 93 90	50	Preparation in the form of powder, containing by weight:  — 55 % or more of Gibberellin A4,  — 1 % or more but not more than 35 % of Gibberellin A7,  — 90 % or more of Gibberellin A4 and Gibberellin A7 combined  — not more than 10 % of a combination of water and other naturally occurring Gibberellins of a kind used in plant growth regulators	0 %	31.12.2015
ex 3808 99 90	10	Oxamyl (ISO) (CAS RN 23135-22-0) in a solution of cyclohexanone and water	0 %	31.12.2015
ex 3808 99 90	20	Abamectin (ISO) (CAS RN 71751-41-2)	0 %	31.12.2018
ex 3809 91 00	10	Mixture of 5-ethyl-2-methyl-2-oxo-1,3,2 $\lambda^5$ -dioxaphosphoran-5-ylmethyl methylphosphonate and bis(5-ethyl-2-methyl-2-oxo-1,3,2 $\lambda^5$ -dioxaphosphoran-5-ylmethyl) methylphosphonate	0 %	31.12.2018
ex 3809 92 00	20	Defoamer, consisting of a mixture of oxydipropanol and 2,5,8,11-tetramethyldodec-6-yn-5,8-diol	0 %	31.12.2014
ex 3810 10 00	10	Soldering or welding paste, consisting of a mixture of metals and resin containing by weight:  — 70 % or more, but not more than 90 % of tin  — not more than 10 % of one or more metals of silver, copper, bismuth, zinc, or indium for use in the electro technical industry	0 %	31.12.2018
ex 3811 19 00	10	Solution of more than 61% but not more than 63% by weight of methylcyclopentadienyl manganese tricarbonyl in an aromatic hydrocarbon solvent, containing by weight not more than:  — 4,9% of 1,2,4-trimethyl-benzene,  — 4,9% of naphthalene, and  — 0,5% of 1,3,5-trimethyl-benzene	0 %	31.12.2014
ex 3811 21 00	10	Salts of dinonylnaphthalenesulphonic acid, in the form of a solution in mineral oils	0 %	31.12.2018
ex 3811 21 00	20	Additives for lubricating oils, based on complex organic molybdenum compounds, in the form of a solution in mineral oil	0 %	31.12.2018
ex 3811 21 00	30	Additives for lubricating oils, containing mineral oils, consisting of calcium salts of reaction products of polyisobutylene substituted phenol with salicylic acid and formaldehyde, used as a concentrated additive for the manufacture of engine oils through a blending process	0 %	31.12.2017
ex 3811 21 00	40	Additives for lubricating oils, containing mineral oils, based on a mixture of dodecylphenol sulphide calcium salts (CAS RN 68784-26-9), used as a concentrated additive for the manufacture of engine oils through a blending process	0 %	31.12.2017
ex 3811 21 00	50	Additives for lubricating oils, — based on calcium C16-24 alkylbenzenesulphonates (CAS RN 70024-69-0),	0 %	31.12.2017

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		— containing mineral oils, used as a concentrated additive for the manufacture of engine oils through a blending process		
ex 3811 21 00	60	Additives for lubricating oils, containing mineral oils,  — based on calcium polypropylenyl substituted benzenesulphonate (CAS RN 75975-85-8) with a content by weight of 25 % or more but not more than 35 %,  — with a total base number (TBN) of 280 or more but not more than 320, used as a concentrated additive for the manufacture of engine oils through a blending process	0 %	31.12.2017
ex 3811 21 00	70	Additives for lubricating oils, — containing polyisobutylene succinimide derived from reaction products of polyethylenepolyamines with polyisobutenyl succinic anhydride (CAS RN 84605-20-9), — containing mineral oils, — with a chlorine content by weight of 0,05 % or more but not more than 0,25 %, — with a total base number (TBN) of more than 20, used as a concentrated additive for the manufacture of engine oils through a blending process	0 %	31.12.2017
ex 3811 29 00	20	Additives for lubricating oils, consisting of reaction products of bis(2-methylpentan-2-yl)dithiophosphoric acid with propylene oxide, phosphorus oxide, and amines with C12-14 alkyl chains, used as a concentrated additive for the manufacture of engine oils through a blending process	0 %	31.12.2017
ex 3811 29 00	30	Additives for lubricating oils, consisting of reaction products of butyl-cyclohex-3-enecarboxylate, sulphur and triphenyl phosphite (CAS RN 93925-37-2), used as a concentrated additive for the manufacture of engine oils through a blending process	0 %	31.12.2017
ex 3811 29 00	40	Additives for lubricating oils, consisting of reaction products of 2-methyl-prop-1-ene with sulphur monochloride and sodium sulphide (CAS RN 68511-50-2), with a chlorine content by weight of 0,05 % or more but not more than 0,5 %, used as a concentrated additive for the manufacture of engine oils through a blending process	0 %	31.12.2017
ex 3811 29 00	50	Additives for lubricating oils, consisting of a mixture of <i>N,N</i> -dialkyl -2-hydroxyacetamides with alkyl chain lengths between 12 and 18 carbon atoms (CAS RN 866259-61-2), used as a concentrated additive for the manufacture of engine oils through a blending process	0 %	31.12.2017
ex 3811 90 00	10	Dinonylnaphthylsulphonic acid salt, in a mineral oil solution	0 %	31.12.2018
ex 3811 90 00	40	Solution of a quaternary ammonium salt based on polyisobutenyl succinimide, containing by weight 20 % or more but not more than 29,9 % 2-ethylhexanol	0 %	31.12.2017
ex 3812 10 00	10	Rubber accelerator based on diphenyl guanidine granules (CAS RN 102-06-7)	0 %	31.12.2016
ex 3812 20 90	10	Plasticizer, containing:  — bis(2-ethylhexyl)-1,4-benzene dicarboxylate (CAS RN 6422-86-2)  — more than 10 % but not more than 60 % by weight of dibutylterephthalate (CAS RN 1962-75-0)	0 %	31.12.2018
ex 3812 30 80	20	Mixture containing predominantly bis(2,2,6,6-tetramethyl-1-octyloxy-4-piperidyl) sebacate	0 %	31.12.2018
ex 3812 30 80	25	UV photo stabiliser containing: $ -\alpha - [3-[3-(2H-Benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-\omega-hydroxypoly(oxy-1,2-ethanediyl) (CAS RN 104810-48-2);  -\alpha - [3-[3-(2H-Benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-\omega-[3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]poly (oxy-1,2-ethanediyl) (CAS RN 104810-47-1);  -\text{polyethylene glycol of a weight average molecular weight (Mw) of 300 (CAS RN 25322-68-3)}   -\text{bis } (1,2,2,6,6-\text{pentamethyl-4-piperidyl}) \text{sebacate } (CAS RN 41556-26-7), \text{ and } -\text{methyl-1},2,2,6,6-\text{pentamethyl-4-piperidyl} \text{ sebacate } (CAS RN 82919-37-7) $	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 3812 30 80	30	Compound stabilisers containing by weight 15 % or more but not more than 40 % of sodium perchlorate and not more than 70 % of 2-(2-methoxyethoxy)ethanol	0 %	31.12.2014
ex 3812 30 80	35	Mixture containing by weight:  — 25 % or more but not more than 50 % of a mixture of C15-18 tetramethylpiperidinyl esters (CAS RN 86403-32-9)  — not more than 20 % of other organic compounds  — on a carrier of polypropylene (CAS RN 9003-07-0)	0 %	31.12.2018
ex 3812 30 80	40	Mixture of:  — 80 % (± 10 %) by weight of 2-ethylhexyl 10-ethyl-4,4-dimethyl-7-oxo-8-oxa-3,5-dithia-4-stannatetradecanoate, and  — 20 % (± 10 %) by weight of 2-ethylhexyl 10-ethyl-4-[[2-[(2-ethylhexyl)oxy]-2-oxoethyl]thio]-4-methyl-7-oxo-8-oxa-3,5-dithia-4-stannatetradecanoate	0 %	31.12.2018
ex 3812 30 80	55	UV-stabilizer, containing:  — 2-(4,6-bis(2,4-dimethylphenyl)-1,3,5-triazin-2-yl)-5-(octyloxy)-phenol (CAS RN 2725-22-6) and  — either N,N'-bis(1,2,2,6,6-pentamethyl-4-piperidinyl)-1,6-hexanediamine, polymer with 2,4- dichloro-6-(4-morpholinyl)-1,3,5-triazine (CAS RN 193098- 40-7) or  — N,N'-bis(2,2,6,6-tetramethyl-4-piperidinyl)-1,6-hexanediamine, polymer with 2,4- dichloro-6-(4-morpholinyl)-1,3,5-triazine (CAS RN 82451-48-7)	0 %	31.12.2016
ex 3812 30 80	60	Light stabiliser, consisting of branched and linear alkyl esters of 3-(2H-Benzotriazolyl)-5-(1,1-di-methylethyl)-4-hydroxy-benzenepropanoic acid (CAS RN 127519-17-9)	0 %	31.12.2016
ex 3812 30 80	65	Stabiliser for plastic material containing:  — 2-ethylhexyl 10-ethyl-4,4-dimethyl-7-oxo-8-oxa-3,5-dithia-4-stannatetradecanoate (CAS RN 57583-35-4),  — 2-ethylhexyl 10-ethyl-4-[[2-[(2-ethylhexyl)oxy]-2-oxoethyl]thio]-4-methyl-7-oxo-8-oxa-3,5-dithia-4-stannatetradecanoate (CAS RN 57583-34-3), and  — 2-ethylhexyl mercaptoacetate (CAS RN 7659-86-1)	0 %	31.12.2016
ex 3812 30 80	70	Light stabiliser containing:  — branched and linear alkyl esters of 3-(2H-benzotriazolyl)-5-(1,1-dimethylethyl)-4-hydroxybenzenepropanoic acid (CAS RN 127519-17-9), and  — 1-methoxy-2-propyl acetate (CAS RN 108-65-6)	0 %	31.12.2016
ex 3812 30 80	75	<i>N,N'</i> -Bis(1,2,2,6,6-pentamethyl-4-piperidinyl)-1,6-hexanediamine, polymer with 2,4-dichloro-6-(4-morpholinyl)-1,3,5-triazine (CAS RN 193098-40-7)	0 %	31.12.2017
ex 3812 30 80	80	UV-stabilizer, consisting of:  — a hindered amine: <i>N,N'</i> -bis(1,2,2,6,6-pentamethyl-4-piperidinyl)-1,6-hexanediamine, polymer with 2,4- dichloro-6-(4-morpholinyl)-1,3,5-triazine (CAS RN 193098-40-7) and  — either an o-hydroxyphenyl triazine UV light absorber or  — a chemically modified phenolic compound	0 %	31.12.2017
ex 3814 00 90	20	Mixture containing by weight:  — 69 % or more but not more than 71 % of 1-methoxypropan-2-ol,  — 29 % or more but not more than 31 % of 2-methoxy-1-methylethyl acetate	0 %	31.12.2018
ex 3814 00 90	40	Azeotrope mixtures containing isomers of nonafluorobutyl methyl ether and/or nonafluorobutyl ethyl ether	0 %	31.12.2018
ex 3815 12 00	10	Catalyst, in the form of granules or rings of a diameter of 3 mm or more but not more than 10 mm, consisting of silver on an aluminium oxide support and containing by weight 8 % or more but not more than 40 % of silver	0 %	31.12.2018
ex 3815 19 90	10	Catalysts consisting of chromium trioxide, dichromium trioxide or organometallic compounds of chromium, fixed on a silicon dioxide support with a pore volume of 2 cm³/g or more (as determined by the nitrogen absorption method)	0 %	31.12.2016

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 3815 19 90	15	Catalyst, in the form of a powder, consisting of a mixture of metal oxides fixed on a support of silicon dioxide, containing by weight 20 % or more but not more than 40 % of molybdenum, bismuth and iron evaluated together, for use in the manufacture of acrylonitrile (1)	0 %	31.12.2018
ex 3815 19 90	25	Catalyst in the form of spheres of a diameter of 4,2 mm or more but not more than 9 mm, consisting of a mixture of metal oxides containing predominantly oxides of molybdenum, nickel, cobalt and iron, on a support of aluminium oxide, for use in the manufacture of acrylic aldehyde	0 %	31.12.2018
ex 3815 19 90	30	Catalyst containing titanium tetrachloride supported on magnesium dichloride, for use in the manufacture of polypropylene (1)	0 %	31.12.2018
ex 3815 19 90	40	Catalyst, in the form of spheres of a diameter of 4,2 mm or more but not more than 9 mm, consisting of a mixture of metals oxides containing predominantly oxides of molybdenum, vanadium and copper, on a support of silicon dioxide and/or aluminium oxide, for use in the manufacture of acrylic acid (1)	0 %	31.12.2018
ex 3815 19 90	60	Catalyst consisting of dichromium trioxide, fixed on a support of aluminium oxide	0 %	31.12.2014
ex 3815 19 90	65	Catalyst consisting of phosphoric acid chemically bonded to a support of silicon dioxide	0 %	31.12.2018
ex 3815 19 90	70	Catalyst consisting of organo-metallic compounds of aluminium and zirconium, fixed on a support of silicon dioxide	0 %	31.12.2018
ex 3815 19 90	75	Catalyst consisting of organo-metallic compounds of aluminium and chromium, fixed on a support of silicon dioxide	0 %	31.12.2018
ex 3815 19 90	80	Catalyst consisting of organo-metallic compounds of magnesium and titanium, fixed on a support of silicon dioxide, in the form of a suspension in mineral oil	0 %	31.12.2018
ex 3815 19 90	85	Catalyst consisting of organo-metallic compounds of aluminium, magnesium and titanium, fixed on a support of silicon dioxide, in the form of powder	0 %	31.12.2018
ex 3815 19 90	86	Catalyst containing titanium tetrachloride supported on magnesium dichloride, for use in the manufacture of polyolefins	0 %	31.12.2018
ex 3815 19 90 ex 8506 90 00	87 10	Cathode, in rolls, for air zinc button cell batteries (hearing aid batteries)	0 %	31.12.2016
ex 3815 90 90	16	Initiator based on dimethylaminopropyl urea	0 %	31.12.2017
ex 3815 90 90	18	Oxidation catalyst with an active ingredient of di[manganese (1+)], 1,2-bis(octahydro-4,7-dimethyl-1 $H$ -1,4,7-triazonine-1-yl- $k$ N $^1$ , $k$ N $^4$ , $k$ N $^7$ )ethane-di- $\mu$ -oxo- $\mu$ -(ethanoato- $k$ O, $k$ O $^3$ )-, di[chloride(1-)], used to accelerate chemical oxidation or bleaching (CAS RN 1217890-37-3)	0 %	31.12.2017
ex 3815 90 90	20	Catalyst, in powder form, consisting of a mixture of titanium trichloride and aluminium chloride, containing by weight:  — 20 % or more but not more than 30 % of titanium and  — 55 % or more but not more than 72 % of chlorine	0 %	31.12.2018
ex 3815 90 90	27	Catalyst, in the form of hollow cylinders with a length of 5 mm or more but not more than 9 mm, consisting of a mixture of metal oxides containing predominantly oxides of molybdenum, bismuth, iron and nickel, containing also a charge of silicon dioxide, for use in the manufacture of acrylic acid	0 %	31.12.2018
ex 3815 90 90	30	Catalyst, consisting of a suspension in mineral oil of:  — tetrahydrofuran complexes of magnesium chloride and titanium(III) chloride;	0 %	31.12.2015

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		and — silicon dioxide — containing 6,6 % (± 0,6 %) by weight of magnesium, and — containing 2,3 % (± 0,2 %) by weight of titanium		
ex 3815 90 90	33	Catalyst, consisting of a mixture of different alkylnaphthalene sulphonic acids, with aliphatic hydrocarbon chains, containing 12 – 56 carbon atoms	0 %	31.12.2018
ex 3815 90 90	50	Catalyst containing titanium trichloride, in the form of a suspension in hexane or heptane containing by weight, in the hexane- or heptane-free material, 9 % or more but not more than 30 % of titanium	0 %	31.12.2018
ex 3815 90 90	70	Catalyst, consisting of a mixture of (2-hydroxypropyl)trimethylammonium formate and dipropylene glycols	0 %	31.12.2014
ex 3815 90 90	71	Catalyst, containing <i>N</i> -(2-hydroxypropylammonium)diazabicyclo (2,2,2) octane-2-ethyl hexanoate, dissolved in ethane-1,2-diol	0 %	31.12.2016
ex 3815 90 90	80	Catalyst consisting predominantly of dinonylnaphthalenedisulphonic acid in the form of a solution in isobutanol	0 %	31.12.2014
ex 3815 90 90	81	Catalyst, containing by weight 69 % or more but not more than 79 % of (2-hydroxy-1-methylethyl)trimethylammonium 2-ethylhexanoate	0 %	31.12.2018
ex 3815 90 90	85	Catalyst based on aluminosilicate (zeolite), for the alkylation of aromatic hydrocarbons, for the transalkylation of alkylaromatic hydrocarbons or for the oligomerization of olefins	0 %	31.12.2017
ex 3815 90 90	86	Catalyst, in the form of rodlets, consisting of an aluminosilicate (zeolite), containing by weight 2 % or more but not more than 3 % of rare-earth metal oxides and less than 1 % of disodium oxide	0 %	31.12.2018
ex 3815 90 90	88	Catalyst, consisting of titanium tetrachloride and magnesium chloride, containing by weight on an oil- and hexane-free basis:  — 4 % or more but not more than 10 % of titanium and  — 10 % or more but not more than 20 % magnesium	0 %	31.12.2018
ex 3815 90 90	89	Rhodococcus rhodocrous J1 bacteria, containing enzymes, suspended in a polyacrylamide gel or in water, for use as a catalyst in the production of acrylamide by the hydration of acrylonitrile	0 %	31.12.2016
ex 3817 00 50	10	Mixture of alkylbenzenes (C14-26) containing by weight:  — 35 % or more but not more than 60 % of eicosylbenzene,  — 25 % or more but not more than 50 % of docosylbenzene,  — 5 % or more but not more than 25 % of tetracosylbenzene	0 %	31.12.2018
ex 3817 00 80	10	Mixture of alkylnaphthalenes, containing by weight:  — 88 % or more but not more than 98 % of hexadecylnaphthalene  — 2 % or more but not more than 12 % of dihexadecylnaphthalene	0 %	31.12.2018
ex 3817 00 80	20	Mixture of branched alkyl benzenes mainly containing dodecyl benzenes	0 %	31.12.2018
ex 3817 00 80	30	Mixed alkylnaphthalenes, modified with aliphatic chains, of a chain-length varying from 12 to 56 carbon atoms	0 %	31.12.2016
ex 3819 00 00	20	Fire resistant hydraulic fluid based on phosphate ester	0 %	31.12.2018
ex 3823 19 30	20	Palm fatty acid distillate, whether or not hydrogenated, with free fatty acid content 80 % or more for use in the manufacture of:  — industrial monocarboxylic fatty acids of subheading 3823,  — stearic acid of subheading 3823,  — stearic acid of subheading 2915,	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 3823 19 90	20	— palmitic acid of subheading 2915, or — animal feed preparations of subheading 2309  Palm acid oils from refining for use in the manufacture of: — industrial monocarboxylic fatty acids of subheading 3823 — stearic acid of subheading 3823 — stearic acid of subheading 2915 — palmitic acid of subheading 2915 — animal feed preparations of subheading 2309	0 %	31.12.2018
ex 3824 90 15	10	Acid aluminosilicate (artificial zeolite of the Y type) in the sodium form, containing by weight not more than 11 % of sodium evaluated as sodium oxide, in the form of rodlets	0 %	31.12.2018
ex 3824 90 97	05	Mixture of methylmethacrylate monomer and butylacrylate monomer in a solution of xylene and butylacetate, containing by weight more than 54 % but not more than 56 % of solvents	0 %	31.12.2014
ex 3824 90 97	06	Paraffin with a level of chlorination of 70 % or more	0 %	31.12.2014
ex 3824 90 97	07	Film containing oxides of barium or calcium combined with either oxides of titanium or zirconium, in an acrylic binding material	0 %	31.12.2014
ex 3824 90 97	08	Mixture of divinylbenzene-isomers and ethylvinylbenzene-isomers, containing by weight 56 % or more but not more than 85 % of divinylbenzene (CAS RN 1321-74-0)	0 %	31.12.2014
ex 3824 90 97	09	Anti-corrosion preparations consisting of salts of dinonylnaphthalenesulphonic acid, either:  — on a support of mineral wax, whether or not modified chemically, or  — in the form of a solution in an organic solvent	0 %	31.12.2018
ex 3824 90 97	10	Calcined bauxite (refractory grade)	0 %	31.12.2018
ex 3824 90 97	11	Mixture of phytosterols, not in powder form, containing by weight:  — 40 % or more but not more than 58 % of beta-sitosterols  — 20 % or more but not more than 28 % of campesterols  — 14 % or more but not more than 23 % of stigmasterols  — 0 % or more but not more than 15 % of other sterols	0 %	31.12.2014
ex 3824 90 97	12	Oligomer of tetrafluoroethylene, having one iodoethyl end-group	0 %	31.12.2018
ex 3824 90 97	13	Preparations containing not less than 92 % but not more than 96,5 % by weight of 1,3:2,4-bis-O-(4-methylbenzylidene)-D-glucitol and also containing carboxylic acid derivatives and an alkyl sulphate	0 %	31.12.2016
ex 3824 90 97	14	Calcium phosphonate phenate, dissolved in mineral oil	0 %	31.12.2016
ex 3824 90 97	15	Structured silica alumina phosphate	0 %	31.12.2014
ex 3824 90 97	16	Mixture of bis{4-(3-(3-phenoxycarbonylamino)tolyl)ureido}phenylsulphone, diphenyltoluene-2,4-dicarbamate and 1-[4-(4-aminobenzenesulphonyl)-phenyl]-3-(3-phenoxycarbonylamino-tolyl)-urea	0 %	31.12.2018
ex 3824 90 97	17	Mixture of acetates of 3-butylene-1,2-diol with a content by weight of 65 % or more but not more than 90 %	0 %	31.12.2018
ex 3824 90 97	18	Poly(tetramethylene glycol) bis[(9-oxo-9H-thioxanthen-1-yloxy)acetate] with an average polymer chain length of less than 5 monomer units (CAS RN 515136-48-8)	0 %	31.12.2014
ex 3824 90 97	20	Preparation consisting by weight of 83 % or more of 3a,4,7,7a-tetrahydro-4,7-methanoindene (dicyclopentadiene), a synthetic rubber, whether or not containing	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		by weight 7 % or more of tricyclopentadiene, and:  — either an aluminium-alkyl compound,  — or an organic complex of tungsten  — or an organic complex of molybdenum		
ex 3824 90 97	21	Mixture of 2-propenoic acid, (1-methylethylidene)bis(4,1-phenyleneoxy-2,1-ethanediyloxy-2,1-ethanediyl)ester with 2-propenoic acid, (2,4,6-trioxo-1,3,5-triazine-1,3,5(2 <i>H</i> ,4 <i>H</i> ,6 <i>H</i> )-triyl)tri-2,1-ethanediyl ester and 1-hydroxy-cyclohexylphenyl ketone in the solution of methyl ethyl ketone and toluene	0 %	31.12.2014
ex 3824 90 97	22	Preparations containing not less than 47 % by weight of 1,3:2,4-bis-O-benzylidene-D-glucitol	0 %	31.12.2016
ex 3824 90 97	23	Mixture of urethane acrylates, tripropylene glycoldiacrylate, ethoxylated bisphenol A acrylate and poly(ethyleneglycol) 400 diacrylate	0 %	31.12.2014
ex 3824 90 97	24	Solution of (chloromethyl)bis(4-fluorophenyl)methylsilane of a nominal concentration of 65 % in toluene	0 %	31.12.2015
ex 3824 90 97	26	Aqueous dispersion, containing by weight:  — 76 % (± 0,5 %) of silicon carbide (CAS RN 409-21-2)  — 4,6 % (± 0,05 %) of aluminium oxide (CAS RN 1344-28-1) and  — 2,4 % (± 0,05 %) of yttrium oxide (CAS RN 1314-36-9)	0 %	31.12.2016
ex 3824 90 97	27	Preparation, consisting of a mixture of 2,4,7,9-tetramethyldec-5-yne-4,7-diol and propan-2-ol	0 %	31.12.2015
ex 3824 90 97	28	Preparation containing by weight:  — 85 % or more but not more than 95 % of α-4-(2-cyano-2-butoxycarbonyl)vinyl- 2-methoxy-phenyl-ω-hydroxyhexa(oxyethylene), and  — 5 % or more but not more than 15 % of polyoxyethylene (20) sorbitan monopalmitate	0 %	31.12.2015
ex 3824 90 97	29	Preparation consisting predominantly of $\gamma$ -butyrolactone and quaternary ammonium salts, for the manufacture of electrolytic capacitors <sup>(1)</sup>	0 %	31.12.2018
ex 3824 90 97	30	2,4,7,9-Tetramethyldec-5-yne-4,7-diol, hydroxyethylated	0 %	31.12.2014
ex 3824 90 97	31	Diethylmethoxyborane (CAS RN 7397-46-8) in the form of a solution in tetrahydrofuran	0 %	31.12.2015
ex 3824 90 97	32	Mixture of:  — basic zirconium carbonate (CAS RN 57219-64-4) and  — cerium carbonate (CAS RN 537-01-9)	0 %	31.12.2016
ex 3824 90 97	33	Preparation, containing:  — trioctylphosphine oxide (CAS RN 78-50-2),  — dioctylhexylphosphine oxide (CAS RN 31160-66-4),  — octyldihexylphosphine oxide (CAS RN 31160-64-2) and  — trihexylphosphine oxide (CAS RN 9084-48-8)	0 %	31.12.2016
ex 3824 90 97	35	Mixture of:  — 3,3-bis(2-methyl-1-octyl-1H-indol-3-yl)phthalide (CAS RN 50292-95-0) and  — ethyl-6'-(diethylamino)-3-oxo-spiro-[isobenzofuran-1(3H),9'-[9H]xanthene]-2'-carboxylate (CAS RN 154306-60-2)	0 %	31.12.2017
ex 3824 90 97	36	Preparation based on 2,5,8,11-tetramethyl-6-dodecyn-5,8-diol ethoxylate (CAS RN 169117-72-0)	0 %	31.12.2017
ex 3824 90 97	37	Liquid crystal mixture for use in the manufacture of displays	0 %	31.12.2017
ex 3824 90 97	38	Alkyl carbonate-based preparation, also containing a UV absorber, for use in the manufacture of spectacle lenses	0 %	31.12.2017

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		(1)		
ex 3824 90 97	39	Mixture containing by weight 40 % or more but not more than 50 % of 2-hydroxyethyl methacrylate and 40 % or more but not more than 50 % of glycerol ester of boric acid	0 %	31.12.2018
ex 3824 90 97	40	Azelaic acid of a purity by weight of 75 % or more but not more than 85 %	0 %	31.12.2014
ex 3824 90 97	41	Preparation, consisting of:  — dipropylene glycol  — tripropylene glycol and  — pentapropylene glycol	0 %	31.12.2017
ex 3824 90 97	42	Mixed metals oxides, in the form of powder, containing by weight:  — either 5 % or more of barium, neodymium or magnesium and 15 % or more of titanium,  — or 30 % or more of lead and 5 % or more of niobium, for use in the manufacture of dielectric films or for use as dielectric materials in the manufacture of multilayer ceramic capacitors	0 %	31.12.2018
ex 3824 90 97	43	Nickel hydroxide, doped with 12 % or more but not more than 18 % by weight of zinc hydroxide and cobalt hydroxide, of a kind used to produce positive electrodes for accumulators	0 %	31.12.2017
ex 3824 90 97	44	Mixture of phytosterols, not in the form of powder, containing by weight:  — 75 % or more of sterols,  — not more than 25 % of stanols, for use in the manufacture of stanols/sterols or stanol/sterol esters  (1)	0 %	31.12.2017
ex 3824 90 97	45	Preparations consisting predominantly of ethylene glycol and:  — either diethylene glycol, dodecandioic acid and ammonia water,  — or N,N-dimethylformamide,  — or γ-butyrolactone,  — or silicon oxide,  — or ammonium hydrogen azelate,  — or ammonium hydrogen azelate and silicon oxide,  — or dodecandioic acid, ammonia water and silicon oxide,  for the manufacture of electrolytic capacitors	0 %	31.12.2018
ex 3824 90 97	47	Platinum oxide (CAS RN 12035-82-4) fixed on a porous support of aluminium oxide (CAS RN 1344-28-1), containing by weight:  — 0,1 % or more but not more than 1 % of platinum, and  — 0,5 % or more but not more than 5 % of ethylaluminium dichloride (CAS RN 563-43-9)	0 %	31.12.2017
ex 3824 90 97	49	Preparation containing:  — C,C'-azodi(formamide) (CAS RN 123-77-3),  — magnesium oxide (CAS RN 1309-48-4) and  — zinc bis(p-toluene sulphinate) (CAS RN 24345-02-6) in which the gas formation from C,C'-azodi(formamide) occurs at 135 °C	0 %	31.12.2017
ex 3824 90 97	50	Powder mixture containing by weight:  — 85 % or more of zinc diacrylate (CAS RN 14643-87-9)  — and not more than 5 % of 2,6-di-tert-butyl-alpha-dimethylamino-p-cresol (CAS RN 88-27-7)	0 %	31.12.2018
ex 3824 90 97	51	Diethylene glycol propylene glycol triethanolamine titanate complexes (CAS RN 68784-48-5) dissolved in diethylene glycol (CAS RN 111-46-6)	0 %	31.12.2017
ex 3824 90 97	52	Poly(tetramethylene glycol) bis[(2-benzoyl-phenoxy)acetate] with an average	0 %	31.12.2014

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		polymer chain length of less than 5 monomer units		
ex 3824 90 97	53	Poly(ethylene glycol) bis(p-dimethyl)aminobenzoate with an average polymer chain length of less than 5 monomer units	0 %	31.12.2014
ex 3824 90 97	54	2-Hydroxybenzonitrile, in the form of a solution in <i>N,N</i> -dimethylformamide, containing by weight 45 % or more but not more than 55 % of 2-hydroxybenzonitrile	0 %	31.12.2018
ex 3824 90 97	55	Preparation consisting of:  — 50 % (±2 %) by weight of bis-alkoxylated ethyl acetoacetate aluminium chelates,  — in an ink oil (white mineral) solvent with a boiling point of 160 °C or more but not more than 180 °C	0 %	31.12.2018
ex 3824 90 97	56	Potassium tert-butanolate (CAS RN 865-47-4) in the form of a solution in tetrahydrofuran	0 %	31.12.2018
ex 3824 90 97	58	N2-[1-(S)-Ethoxycarbonyl-3-phenylpropyl]-N6-trifluoroacetyl-L-lysyl-N2-carboxy anhydride in a solution of dichloromethane at 37 %	0 %	31.12.2015
ex 3824 90 97	59	3',4',5'-Trifluorobiphenyl-2-amine, in the form of a solution in toluene containing by weight 80 % or more but not more than 90 % of 3',4',5'-trifluorobiphenyl-2-amine	0 %	31.12.2015
ex 3824 90 97	60	α-Phenoxycarbonyl- $ω$ -phenoxypoly[oxy(2,6-dibromo-1,4-phenylene) isopropylidene(3,5-dibromo-1,4-phenylene)oxycarbonyl]	0 %	31.12.2018
ex 3824 90 97	62	Fused magnesia containing by weight 15 % or more of dichromium trioxide	0 %	31.12.2016
ex 3824 90 97	64	Aluminium sodium silicate, in the form of spheres of a diameter of:  — either 1,6mm or more but not more than 3,4mm,  — or 4mm or more but not more than 6mm	0 %	31.12.2018
ex 3824 90 97	65	Preparation containing by weight:  — 89 % or more but not more than 98,9 % of 1,2,3-trideoxy-4,6:5,7-bis-O-[(4-propylphenyl)methylene]-nonitol  — 0,1 % or more but not more than 1 % of colorants  — 1 % or more but not more than 10 % of fluoropolymers	0 %	31.12.2016
ex 3824 90 97	66	Mixture of primary tert-alkylamines	0 %	31.12.2014
ex 3824 90 97	78	Mixture of phytosterols derived from wood and wood based oils (tall oil), in the form of powder with a particle size not more than 300 μm, containing by weight:  — 60 % or more, but not more than 80 % of sitosterols,  — not more than 15 % of campesterols,  — not more than 5 % of stigmasterols,  — not more than 15 % of betasitostanols	0 %	31.12.2017
ex 3824 90 97	79	Mixture of 80 % ( $\pm$ 10 %) of 1-[2-(2-aminobutoxy)ethoxy]but-2-ylamine and 20 % ( $\pm$ 10 %) of 1-({[2-(2-aminobutoxy)ethoxy]methyl} propoxy)but-2-ylamine	0 %	31.12.2014
ex 3824 90 97	82	$\alpha\hbox{-}(2,4,6\hbox{-Tribromophenyl})\hbox{-}\omega\hbox{-}(2,4,6\hbox{-tribromophenoxy})poly[oxy(2,6\hbox{-dibromo-}1,4\hbox{-phenylene})isopropylidene(3,5\hbox{-dibromo-}1,4\hbox{-phenylene})oxycarbonyl]$	0 %	31.12.2018
ex 3824 90 97	84	Reaction product, containing by weight:  — 1 % or more but not more than 40 % of molybdenum oxide,  — 10 % or more but not more than 50 % of nickel oxide,  — 30 % or more but not more than 70 % of tungsten oxide	0 %	31.12.2014
ex 3824 90 97	87	Paste containing by weight:  — 75 % or more, but not more than 85 % of copper,  — inorganic oxides,  — ethyl cellulose, and	0 %	31.12.2017

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		— a solvent		
ex 3824 90 97	88	Oligomeric reaction product, consisting of bis(4-hydroxyphenyl) sulfone and 1,1'-oxybis(2-chloroethane)	0 %	31.12.2014
ex 3824 90 97	89	Oligomer of tetrafluoroethylene, having tetrafluoroiodoethyl end-groups	0 %	31.12.2018
ex 3824 90 97	90	Hollow spheres of fused aluminosilicate containing 65-80 % amorphous aluminosilicate, with the following characteristics:  — a melting point of between 1 600 °C and 1 800 °C,  — a density of 0,6 - 0,8 g/cm³, for use in the manufacture of particle filters in motor vehicles	0 %	31.12.2018
ex 3824 90 97	92	Preparation, consisting of 2,4,7,9-tetramethyldec-5-yne-4,7-diol and silicon dioxide	0 %	31.12.2014
ex 3824 90 97	94	Particles of silicon dioxide on which are covalently bonded organic compounds, for use in the manufacture of high performance liquid chromatography columns (HPLC) and sample preparation cartridges	0 %	31.12.2018
ex 3824 90 97	95	Mixture of phytosterols, in the form of flakes and balls, containing by weight 80 % or more of sterols and not more than 4 % of stanols	0 %	31.12.2014
ex 3824 90 97	97	Preparation containing by weight either 10 % or more but not more than 20 % of lithiumfluorophosphate or 5 % or more but not more than 10 % of lithium perchlorate in mixtures of organic solvents	0 %	31.12.2018
ex 3826 00 10 ex 3826 00 10	20 29	Mixture of fatty acid methyl esters containing by weight at least:  — 65 % or more but not more than 75 % of C12 FAME,  — 21 % or more but not more than 28 % of C14 FAME,  — 4 % or more but not more than 8 % of C16 FAME,  for use in the manufacture of detergents and home and personal care products	0 %	31.12.2018
ex 3826 00 10 ex 3826 00 10	30 39	Mixture of fatty acid methyl esters containing by weight at least:  — 50 % or more but not more than 58 % of C8-FAME  — 35 % or more but not more than 50 % of C10-FAME for use in the manufacture of agricultural chemistry, (animal and human) food ingredients, additives to lubricant, solvents, lamp oil and firelighter components  (1)	0 %	31.12.2018
ex 3826 00 10 ex 3826 00 10	40 49	Mixture of fatty acid methyl esters containing by weight at least:  — 15 % or more but not more than 32 % of C16 FAME  — 65 % or more but not more than 85 % of C18 FAME for use in the manufacture of detergents and home and personal cleaning products, agricultural chemistry, (animal and human) food ingredients, additives to lubricant, solvents, lamp oil and firelighter components (1)	0 %	31.12.2018
ex 3901 10 90	20	Polyethylene, in the form of granules, of a specific gravity of 0,925 ( $\pm$ 0,0015), a melt flow index of 0,3 g/10 min ( $\pm$ 0,05 g/10 min), for the manufacture of blown films of a haze value not more than 6 % and an elongation at break (MD/TD) of 210/340 $^{(1)}$	0 %	31.12.2018
ex 3901 10 90	30	Polyethylene granules, containing by weight 10 % or more but not more than 25 % of copper	0 %	31.12.2016
ex 3901 20 90	10	Polyethylene, in one of the forms mentioned in note 6 (b) to Chapter 39, of a specific gravity of 0,945 or more but not more than 0,985, for the manufacture of films for typewriter ribbon or similar ribbon (1)	0 %	31.12.2018
ex 3901 20 90	20	Polyethylene, containing by weight 35 % or more but not more than 45 % of mica	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 3901 30 00	80	Ethylene-vinyl acetate copolymer, — containing 27,8 % or more but not more than 29,3 % by weight of vinyl acetate — with a melt flow index of 22 g/10 min or more but no more than 28 g/10 min — containing not more than 15 mg/kg vinyl acetate monomer	0 %	31.12.2015
ex 3901 30 00	82	Ethylene-vinyl acetate copolymer, — containing 9,8 % or more but not more than 10,8 % by weight of vinyl acetate — with a melt flow index of 2,5 g/10 min or more but no more than 3,5 g/10 min — containing not more than 15 mg/kg vinyl acetate monomer	0 %	31.12.2015
ex 3901 90 90	80	Block copolymer of ethylene with octene in the form of pellets:  — with a specific gravity of 0,862 or more, but not more than 0,865,  — able to stretch to at least 200 % its original length,  — with a hysteresis of 50 % (±10 %),  — with permanent deformation of not more than 20 %, for use in the manufacture of napkin liners for babies	0 %	31.12.2015
ex 3901 90 90	82	Copolymer of ethylene and methacrylic acid	0 %	31.12.2015
ex 3901 90 90	91	Ionomer resin consisting of a salt of a copolymer of ethylene with methacrylic acid	4 %	31.12.2018
ex 3901 90 90	92	Chlorosulphonated polyethylene	0 %	31.12.2018
ex 3901 90 90	93	Copolymer of ethylene, vinyl acetate and carbon monoxide, for use as a plasticizer in the manufacture of roof sheets (1)	0 %	31.12.2018
ex 3901 90 90	94	Mixtures of A-B block copolymer of polystyrene and ethylene-butylene copolymer and A-B-A block copolymer of polystyrene, ethylene-butylene copolymer and polystyrene, containing by weight not more than 35 % of styrene	0 %	31.12.2018
ex 3901 90 90	97	Chlorinated polyethylene, in the form of powder	0 %	31.12.2018
ex 3902 10 00	10	Polypropylene containing no plasticizer and not more than:  — 7 mg/kg of aluminium,  — 2 mg/kg of iron,  — 1 mg/kg of magnesium,  — 8 mg/kg of chloride	0 %	31.12.2018
ex 3902 10 00	20	Polypropylene, containing no plasticiser,  — of a melting point of more than 150 °C (as determined by the ASTM D 3417 method),  — of a heat of fusion of 15 J/g or more but not more than 70 J/g,  — of an elongation at break of 1 000 % or more (as determined by the ASTM D 638 method),  — of a tensile modulus of 69 MPa or more but not more than 379 MPa (as determined by the ASTM D 638 method)	0 %	31.12.2018
ex 3902 10 00	30	Polypropylene, containing not more than 1 mg/kg of aluminium, 0,05 mg/kg of iron, 1 mg/kg of magnesium and 1 mg/kg of chloride, for use in the manufacture of packaging for disposable contact lenses (1)	0 %	31.12.2018
ex 3902 10 00	40	Polypropylene, containing no plasticizer:  — of a tensile strength: of 32-60 MPa (as determined by the ASTM D638 method);  — of a flexural strength of 50-90 MPa (as determined by the ASTM D790 method);  — of a Melt Flow Rate (MFR) at 230 °C/ 2,16 kg of 5-15 g/10 min (as determined by the ASTM D1238 method);  — with 40 % or more but not more than 80 % by weight of polypropylene,  — with 10 % or more but not more than 30 % by weight of glass fibre,  — with 10 % or more but not more than 30 % by weight of mica	0 %	31.12.2014
ex 3902 10 00	50	High isotactic polypropylene (HIPP), whether or not coloured, intended for the manufacture of plastic components for air freshener with the following properties:	0 %	31.12.2015

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		<ul> <li>a density of 0,880 g/cm³ or more but not more than 0,913 g/cm³ (as determined by test method ASTM D1505),</li> <li>a tensile strength at yield of 350 kg/cm² or more but not more than 390 kg/cm² (as determined by test method ASTM D638)</li> <li>a heat deflection temperature of 135 °C or more under load of 0,45 MPa (as determined by test method ASTM 648)</li> </ul>		
ex 3902 20 00	10	Polyisobutylene, of a number average molecular weight $(M_{\text{n}})$ of 700 or more but not more than $800$	0 %	31.12.2018
ex 3902 20 00	20	Hydrogenated polyisobutene, in liquid form	0 %	31.12.2018
ex 3902 30 00	91	A-B Block copolymer of polystyrene and an ethylene-propylene copolymer, containing by weight 40 % or less of styrene, in one of the forms mentioned in note 6 (b) to Chapter 39	0 %	31.12.2018
ex 3902 30 00	95	A-B-A block copolymer, consisting of:  — a copolymer of propylene and ethylene and  — 21 % (± 3 %) by weight of polystyrene	0 %	31.12.2016
ex 3902 30 00	97	Liquid ethylene-propylene-copolymer with:  — a flashpoint of 250 °C or more,  — a viscosity index of 150 or more,  — of a number average molecular weight (M <sub>n</sub> ) of 650 or more	0 %	31.12.2016
ex 3902 90 90	52	Amorphous poly-alpha-olefin copolymer blend of poly(propylene-co-1-butene) and petroleum hydrocarbon resin	0 %	31.12.2018
ex 3902 90 90	55	Thermoplastic elastomer, with an A-B-A block copolymer structure of polystyrene, polyisobutylene and polystyrene containing by weight 10 % or more but not more than 35 % of polystyrene	0 %	31.12.2018
ex 3902 90 90	60	Non-hydrogenated 100 % aliphatic resin (polymer), with the following characteristics:  — liquid at room temperature  — obtained by cationic polymerisation of C-5 alkenes monomers  — with a number average molecular weight (Mn) of 370 (± 50)  — with a weight average molecular weight (Mw) of 500 (± 100)	0 %	31.12.2014
ex 3902 90 90	84	Blend of hydrogenated styrenic block copolymer, polyethylene wax, and tackifier resin, in the form of pellets, containing by weight:  — 70 (±5) % of styrenic block copolymer,  — 15 (±5) % of polyethylene wax, and  — 15 (±5) % of tackifier resin with the following physical properties:  — able to stretch to at least 200 % of its original length  — with a hysteresis of 50 (± 10) %  — with a permanent deformation of no more than 20 % for use in the manufacture of napkins and napkin liners for babies	0 %	31.12.2015
ex 3902 90 90	92	Polymers of 4-methylpent-1-ene	0 %	31.12.2018
ex 3902 90 90	93	Synthetic poly-alpha-olefin having a viscosity of at least 38 x 10 <sup>-6</sup> m <sup>2</sup> s <sup>-1</sup> (38 centistokes) at 100°C measured using the ASTM D 445 method	0 %	31.12.2016
ex 3902 90 90	98	Synthetic poly-alpha-olefin with a viscosity at 100° Celsius (measured according to method ASTM D 445) ranging from 3 centistokes to 9 centistokes and obtained by polymerization of a mixture of dodecene and tetradecene, containing a maximum of 40 % of tetradecene	0 %	31.12.2016
ex 3903 11 00	10	White expandable polystyrene beads with a thermal conductivity of not more than 0,034 W/mK at a density of 14,0 kg/m $^3$ ( $\pm$ 1,5 kg/m $^3$ ), containing 50 % recycled material	0 %	31.12.2018
	L		l	l

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 3903 19 00	30	Crystalline polystyrene with a melting point of 268 °C or more but not more than 272 °C and a setting point of 232 °C or more but not more than 242 °C, whether or not containing additives and filling material	0 %	31.12.2016
ex 3903 90 90	10	Butadiene-styrene copolymer pellets or granules, with:  — a specific gravity of 1,05 (±0,02),  — a melt flow index at 200 °C/5 kg of 13 g/10 min (±1 g/10 min)	0 %	31.12.2016
ex 3903 90 90	15	Dry ink powder or toner blend, consisting of a copolymer of styrene, n-butyl acrylate, n-butyl methacrylate, methacrylic acid and polyolefin wax, for use as a developer in the manufacture of cartridges for facsimile machines, computer printers or copiers (1)	0 %	31.12.2016
ex 3903 90 90	20	Dry ink powder or toner blend, consisting of a copolymer of styrene, n-butyl acrylate, n-butyl methacrylate and polyolefin wax, for use as a developer in the manufacture of cartridges for facsimile machines, computer printers or copiers	0 %	31.12.2016
ex 3903 90 90	25	Dry ink powder or toner blend, consisting of a copolymer of styrene, n-butyl acrylate, methacrylic acid and polyolefin wax, for use as a developer in the manufacture of cartridges for facsimile machines, computer printers or copiers	0 %	31.12.2016
ex 3903 90 90	30	Butadiene-styrene copolymer pellets or granules with a melting point of 85 °C (±5 °C), containing by weight:  — 2 % or more but not more than 4 % of tris(tribromophenyl) triazine,  — 5 % or more but not more than 10 % of ethane-1,2-bis(pentabromophenyl),  — 3 % or more but not more than 5 % of antimony trioxide	0 %	31.12.2016
ex 3903 90 90 ex 3911 90 99	35 43	Copolymer of $\alpha$ -methylstyrene and styrene, having a softening point of more than 113 °C	0 %	31.12.2018
ex 3903 90 90 ex 3911 90 99	40 50	Copolymer of styrene with $\alpha$ -methylstyrene and acrylic acid, of a number average molecular weight $(M_n)$ of 500 or more but not more than 6000	0 %	31.12.2018
ex 3903 90 90	45	Styrene copolymer granules in primary forms, containing by weight:  — 91 % (± 0,5 %) of styrene,  — 8 % (± 0,8 %) of butadiene,  — 1 % (± 0,04 %) of additives (colorant)	0 %	31.12.2016
ex 3903 90 90	50	Crystalline copolymer of styrene and p-methylstyrene:  — with a melting point of 240 °C or more but not more than 260 °C,  — containing 5 % or more but not more than 15 % by weight of p-methylstyrene	0 %	31.12.2015
ex 3903 90 90 ex 3911 90 99	60 60	Copolymer of styrene with maleic anhydride, either partially esterified or completely chemically modified, of an average molecular weight $(M_n)$ of not more than 4500, in flake or powder form	0 %	31.12.2016
ex 3903 90 90	75	Copolymer of styrene and vinyl pyrrolidone, containing by weight not more than 1 % of sodium dodecyl sulphate, in the form of an aqueous emulsion, for the manufacture of goods of subheading 3305 20 00 or of hair dyes of subheading 3305 90 $^{(1)}$	0 %	31.12.2014
ex 3903 90 90	80	Granules of copolymer of styrene and divinylbenzene of a minimum diameter of 150 µm and a maximum diameter of 800 µm and containing by weight:  — minimum 65 % styrene,  — maximum 25 % divinylbenzene for use in the manufacture of ion exchange resins	0 %	31.12.2018
ex 3903 90 90	86	Mixture containing by weight:	0 %	31.12.2018
	ļ	1	L	L

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		<ul> <li>45 % or more but not more than 65 % of polymers of styrene</li> <li>35 % or more but not more than 45 % of poly(phenylene ether)</li> <li>not more than 10 % of other additives</li> <li>and with one or more of the following special colour effects:</li> <li>metallic or pearlescent with a visual angular metamerism caused by at least 0,3 % flake-based pigment</li> <li>fluorescent, as characterized by emitting light during absorption of ultraviolet radiation</li> <li>bright white, as characterized by L* not less than 92 and b* not more than 2 and a* between -5 and 7 on the CIELab colour scale</li> </ul>		
ex 3904 10 00	20	<ul> <li>Poly(vinyl chloride) powder, not mixed with any other substances or containing any vinyl acetate monomers, with:</li> <li>a degree of polymerisation of 1 000 (± 300) monomer units,</li> <li>a coefficient of heat transmission (K-value) of 60 or more, but not more than 70,</li> <li>a volatile material content of less than 2,00 % by weight,</li> <li>a sieve non-passing fraction at a mesh width of 120 μm of not more than 1 % by weight,</li> <li>for use in the manufacture of battery separators</li> </ul>	0 %	31.12.2014
ex 3904 30 00	20	Copolymer of vinyl chloride with vinyl acetate and maleic acid, containing by weight:  — 80,5 % or more but not more than 81,5 % of vinyl chloride,  — 16,5 % or more but not more than 17,5 % of vinyl acetate and  — 1,5 % or more but not more than 2,5 % of maleic acid, for use in the heat-sealing of plastics onto steel substrate for industrial uses	0 %	31.12.2014
ex 3904 30 00 ex 3904 40 00	30 91	Copolymer of vinyl chloride with vinyl acetate and vinyl alcohol, containing by weight:  — 87 % or more but not more than 92 % of vinyl chloride,  — 2 % or more but not more than 9 % of vinyl acetate and  — 1 % or more but not more than 8 % of vinyl alcohol, in one of the forms mentioned in note 6 (a) or (b) to Chapter 39, for the manufacture of goods of headings 3215 or 8523 or for use in the manufacture of coatings for containers and closures of a kind used for preserving food and drink  (1)	0 %	31.12.2018
ex 3904 40 00	93	Copolymer of vinyl chloride and methyl acrylate, containing by weight 80 % ( $\pm$ 1 %) of vinyl chloride and 20 % ( $\pm$ 1 %) of methyl acrylate, in the form of a aqueous emulsion	0 %	31.12.2018
ex 3904 50 90	92	Vinylidene-chloride methacrylate co-polymer for use in the manufacture of monofilaments	0 %	31.12.2014
ex 3904 61 00	20	Copolymer of tetrafluoroethylene and trifluoro(heptafluoropropoxy)ethylene, containing 3,2 % or more but not more than 4,6 % by weight of trifluoro(heptafluoropropoxy)ethylene and less than 1 mg/kg of extractable fluoride ions	0 %	31.12.2018
ex 3904 61 00	30	Polytetrafluoroethylene, in the form of powder, of a specific surface of 8 m²/g or more but not more than 12 m²/g, a particle size distribution of 10 % of less than 10 $\mu m$ and 90 % of less than 35 $\mu m$ and an average particle size of 20 $\mu m$	0 %	31.12.2018
ex 3904 69 80	81	Poly(vinylidene fluoride) (CAS RN 24937-79-9)	0 %	31.12.2015
ex 3904 69 80	85	Copolymer of ethylene with chlorotrifluoroethylene, whether or not modified with hexafluoroisobutylene, in powder, whether or not with fillers	0 %	31.12.2017
ex 3904 69 80	93	Copolymer of ethylene with chlorotrifluoroethylene, in one of the forms mentioned in note 6 (b) to Chapter 39	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 3904 69 80	94	Copolymer of ethylene and tetrafluoroethylene	0 %	31.12.2018
ex 3904 69 80	96	Polychlorotrifluoroethylene, in one of the forms mentioned in note 6 (a) and (b) to Chapter 39	0 %	31.12.2018
ex 3904 69 80	97	Copolymer of chlorotrifluoroethylene and vinylidene difluoride	0 %	31.12.2018
ex 3905 30 00	10	Viscous preparation, essentially consisting of poly(vinyl alcohol) (CAS RN 9002-89-5), an organic solvent and water for use as protective coating of wafers during the manufacturing of semiconductors	0 %	31.12.2017
ex 3905 91 00	20	Water soluble copolymer of ethylene and vinyl alcohol (CAS RN 26221-27-2), containing by weight not more than 13 % of the monomer unit ethylene	0 %	31.12.2017
ex 3905 99 90	92	Polymer of vinylpyrrolidone and dimethylaminoethyl methacrylate, containing by weight 97 % or more but not more than 99 % of vinylpyrrolidone, in the form of a solution in water	0 %	31.12.2018
ex 3905 99 90	95	Hexadecylated or eicosylated polyvinylpyrrolidone	0 %	31.12.2018
ex 3905 99 90	96	Polymer of vinyl formal, in one of the forms mentioned in note 6 (b) to Chapter 39, of a weight average molecular weight (M <sub>w</sub> ) of 25 000 or more but not more than 150 000 and containing by weight:  — 9,5 % or more but not more than 13 % of acetyl groups evaluated as vinyl	0 %	31.12.2018
		acetate and  — 5 % or more but not more than 6,5 % of hydroxy groups evaluated as vinyl alcohol		
ex 3905 99 90	97	Povidone (INN)-iodine (CAS RN 25655-41-8)	0 %	31.12.2018
ex 3905 99 90	98	Poly(vinyl pyrrolidone) partially substituted by triacontyl groups, containing by weight 78 % or more but not more than 82 % of triacontyl groups	0 %	31.12.2018
3906 90 60		Copolymer of methyl acrylate with ethylene and a monomer containing a non-terminal carboxy group as a substituent, containing by weight 50 % or more of methyl acrylate, whether or not mixed with silicon dioxide	0 %	31.12.2018
ex 3906 90 90	10	Polymerization product of acrylic acid with small quantities of a polyunsaturated monomer, for the manufacture of medicaments of heading 3003 or 3004 (1)	0 %	31.12.2018
ex 3906 90 90	15	Photosensitive resin consisting of modified acrylate, acrylic monomer, catalyst (photoinitiator) and stabilizer	0 %	31.12.2018
ex 3906 90 90	27	Copolymer of stearyl methacrylate, isooctyl acrylate and acrylic acid, dissolved in isopropyl palmitate	0 %	31.12.2017
ex 3906 90 90	30	Copolymer of styrene with hydroxyethyl methacrylate and 2-ethylhexyl acrylate, of a number average molecular weight $(M_n)$ of 500 or more but not more than 6 000	0 %	31.12.2018
ex 3906 90 90	35	White powder of 1,2-ethanediol dimethacrylate-methyl methacrylate copolymer of a particle size of not more than 18 $\mu m,$ insoluble in water	0 %	31.12.2018
ex 3906 90 90	40	Transparent acrylic polymer in packages of not more than 1 kg, and not for retail sale with:	0 %	31.12.2015
		<ul> <li>a viscosity of not more than 50000 Pa·s at 120 °C as determined by the test method ASTM D 3835</li> <li>a weight average molecular weight (M<sub>w</sub>) of more than 500 000 but not more than 1 200 000 according to the Gel Permeation Chromatography (GPC) test,</li> <li>a residual monomer content of less than 1 %</li> </ul>		
ex 3906 90 90	41	Poly(alkyl acrylate) with an ester alkyl chain of C10 to C30	0 %	31.12.2014
ex 3906 90 90	45	Acrylonitrile-butadiene-styrene-methylmethacrylate copolymer pellets with:	0 %	31.12.2016

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 3906 90 90	50	<ul> <li>a melting point of 96 °C (±3 °C),</li> <li>a specific gravity of 1,03 or more but not more than 1,07, and containing by weight:</li> <li>25 % or more but not more than 50 % of acrylonitrile-butadiene-styrene, and</li> <li>50 % or more but not more than 75 % of methylmethacrylate</li> <li>Polymers of esters of acrylic acid with one or more of the following monomers in the chain:</li> <li>chloromethyl vinyl ether,</li> <li>chloromethyl vinyl ether,</li> <li>vinyl chloroacetate,</li> <li>methacrylic acid,</li> <li>butenedioic acid monobutyl ester,</li> <li>containing by weight not more than 5 % of each of the monomeric units, in one of the forms mentioned in note 6 (b) to Chapter 39</li> </ul>	0 %	31.12.2018
ex 3906 90 90	65	Polyalkylacrylate, chemically modified with cobalt, with a melting temperature (Tm) of 65 °C (± 5 °C), measured with Differential Scanning Calorimetry (DSC)	0 %	31.12.2018
ex 3906 90 90	80	Polydimethylsiloxane-graft-(polyacrylates; polymethacrylates)	0 %	31.12.2018
ex 3906 90 90	85	Non aqueous dispersion type polymers of esters of acrylic acid with a hydrolyzable silyl group at one or both polymer ends	0 %	31.12.2014
ex 3907 20 11	10	Poly(ethylene oxide) of a number average molecular weight $(M_n)$ of 100 000 or more	0 %	31.12.2018
ex 3907 20 11	20	$Bis[Methoxypoly[ethyleneglycol)]-maleimidopropionamide, \ chemically \ modified \ with lysine, of a number average molecular weight (M_n) of 40 000$	0 %	31.12.2018
ex 3907 20 11	40	Polyethylene glycol with an ethylene oxide chain length of not more than 30, having butyl-2-cyano 3-(4-hydroxyphenyl) acrylate end groups, for use as a UV barrier in liquid masterbatches	0 %	31.12.2015
ex 3907 20 11	50	[3-[3-(2H-Benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropyl]-hydroxypoly(oxo-1,2-ethanediyl) (CAS RN 104810-48-2)	0 %	31.12.2016
ex 3907 20 11	60	Preparation containing: $ \begin{aligned} &-\alpha - [3-[3-(2H-Benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-\\ &-\alpha - [3-[3-(2H-Benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-\\ &-\alpha - [3-[3-(2H-Benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-\\ &-\alpha - [3-[3-(2H-Benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]poly(oxy-1,2-ethanediyl) (CAS RN 104810-47-1) \end{aligned} $	0 %	31.12.2016
ex 3907 20 20	20	Polytetramethylene ether glycol with a weight average molecular weight (Mw) of 2 700 or more but not more than 3 100 (CAS RN 25190-06-1)	0 %	31.12.2017
ex 3907 20 20	30	Mixture, containing by weight 70 % or more but not more than 80 % of a polymer of glycerol and 1,2-epoxypropane and 20 % or more but not more than 30 % of a copolymer of dibutyl maleate and <i>N</i> -vinyl-2-pyrrolidone	0 %	31.12.2018
ex 3907 20 20	40	Copolymer of tetrahydrofuran and tetrahydro-3-methylfuran with a number average molecular weight $(M_n)$ of 3 500 $(\pm100)$	0 %	31.12.2018
ex 3907 20 99	15	Poly(oxypropylene) having alkoxysilyl end-groups	0 %	31.12.2018
ex 3907 20 99	30	Homopolymer of 1-chloro-2,3-epoxypropane (epichlorohydrin)	0 %	31.12.2018
ex 3907 20 99	35	Polyethylene glycol chemically modified with an isocyanate group containing a carbodiimide group, in the form of a solution in 2-methoxy-1-methylethyl acetate	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 3907 20 99	45	Copolymer of ethylene oxide and propylene oxide, having aminopropyl and methoxy end-groups	0 %	31.12.2018
ex 3907 20 99	50	Vinyl-silyl terminated perfluoropolyether polymer or an assortment of two components consisting of the same type of vinyl-silyl terminated perfluoropolyether polymer as the main ingredient	0 %	31.12.2018
ex 3907 20 99	55	Succinimidyl ester of methoxy poly(ethylene glycol)propionic acid, of a number average molecular weight (Mn) of 5 000	0 %	31.12.2018
ex 3907 20 99	60	Polytetramethylene oxide di-p-aminobenzoate	0 %	31.12.2016
ex 3907 20 99	65	L-Lysine N-hydroxysuccinimidyl ester .alpha.,.epsilonbis(polyethylene glycol monomethylether carbamate) (CAS RN 266318-38-1) of a number average molecular weight (Mn) of 38 000 or more but not more than 40 000	0 %	31.12.2018
ex 3907 30 00 ex 3926 90 97	40 70	Epoxide resin, containing by weight 70 % or more of silicon dioxide, for the encapsulation of goods of headings 8533, 8535, 8536, 8541, 8542 or 8548 (1)	0 %	31.12.2018
ex 3907 30 00	50	Liquid epoxide resin of 2-propenenitrile/1,3-butadiene-epoxide copolymer, not containing any solvent, with:  — a zinc borate hydrate content of not more than 40 % by weight,  — a diantimony trioxide content of not more than 5 % by weight	0 %	31.12.2018
ex 3907 30 00	60	Polyglycerol polyglycidyl ether resin (CAS RN 105521-63-9)	0 %	31.12.2017
ex 3907 40 00	10	Polycarbonate pellets or granules:  — containing 7 % or more but not more than 15 % by weight of non halogen flame retardant, and  — with a specific gravity of 1,20 (± 0,01)	0 %	31.12.2016
ex 3907 40 00	20	Polycarbonate pellets or granules with a specific gravity of 1,32 ( $\pm$ 0,03), containing 20 % ( $\pm$ 5 %) of glass fibre	0 %	31.12.2016
ex 3907 40 00	30	Polycarbonate pellets or granules with a specific gravity of 1,18 or more but not more than 1,25, containing by weight:  — 77 % or more but not more than 90 % of polycarbonate,  — 8 % or more but not more than 20 % of phosphoric acid ester,  — 0,1 % or more but not more than 1 % of antioxidant, and whether or not containing 1 % or more but not more than 5 % of flame retardant	0 %	31.12.2016
ex 3907 40 00	40	Polycarbonate granules with:  — a melt flow rate of 18 g/10 min/300 °C/1,2 kg (according to ASTM D 1238)  — a tensile strength of 69 MPa according to ASTM D 638 and  — a flexural strength of 112 MPa according to ASTM D 790	0 %	31.12.2016
ex 3907 40 00	50	Polycarbonate resin, pellets or granules, with:  — a specific gravity of 1,20 (± 0,05),  — a heat deflection temperature of 146 °C (± 3 °C) at 4,6 kgf/cm², and  — a melt flow index of 20 (± 10) g/10 min at 300 °C/1,2 kg	0 %	31.12.2016
ex 3907 40 00	60	Polycarbonate acrylonitrile-butadiene-styrene pellets or granules with specific gravity of 1,20 (±0,05), containing by weight:  — 65 % or more but not more than 90 % of polycarbonate,  — 5 % or more but not more than 15 % of acrylonitrile-butadiene-styrene,  — 5 % or more but not more than 20 % of phosphoric acid ester and,  — 0,1 % or more but not more than 5 % of antioxidant	0 %	31.12.2016
ex 3907 60 80	10	Copolymer of terephthalic acid and isophthalic acid with ethylene glycol, butane-1,4-diol and hexane-1,6-diol	0 %	31.12.2018
ex 3907 60 80	30	Oxygen binding concentrate consisting of a blend of:  — a copolymer obtained from poly(ethylene terephthalate), pyromellitic dianhydride (PMDA) and a hydroxyl substituted polybutadiene	0 %	31.12.2014

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		a barrier co-polymer (as determined by the ASTM method F1115-95 (2001)) obtained from xylylene diamines and adipic acid, and — organic dyes and/or organic and inorganic pigments where the first co-polymer predominates		
ex 3907 60 80	40	Poly(ethylene terephthalate) pellets or granules:  — with a specific gravity of 1,23 or more but not more than 1,27 at 23° C, and  — containing not more than 10 % by weight of other modifiers or additives	0 %	31.12.2016
ex 3907 60 80	50	Flexible packages (for oxygen sensitive polymers) manufactured from a laminate of:  — not more than 75 μm of polyethylene, — not more than 50 μm of polyethylene terephthalate and — not more than 15 μm of aluminium with a tensile strength of more than 70 N/15 mm and oxygen transmission rate of less than 0,1 cm³/m²/24 hrs at 0,1 MPa	0 %	31.12.2017
3907 70 00		Poly(lactic acid)	0 %	31.12.2018
ex 3907 91 90	10	Diallyl phthalate prepolymer, in powder form	0 %	31.12.2014
ex 3907 99 90	10	Poly(oxy-1,4-phenylenecarbonyl) (CAS RN 26099-71-8), in the form of powder	0 %	31.12.2018
ex 3907 99 90	20	Liquid crystal copolyester with a melting point of not less than 270 °C, whether or not containing fillers	0 %	31.12.2018
ex 3907 99 90	25	Copolymer, containing 72 % by weight or more of terephthalic acid and/or isomers thereof and cyclohexanedimethanol	0 %	31.12.2017
ex 3907 99 90 ex 3913 90 00	30 20	Poly(hydroxyalkanoate), predominantly consisting of poly(3-hydroxybutyrate)	0 %	31.12.2015
ex 3907 99 90	60	Copolymer of terephthalic acid and isophthalic acid with bisphenol A	0 %	31.12.2017
ex 3907 99 90	70	Copolymer of poly(ethylene terephthalate) and cyclohexane dimethanol, containing more than 10 % by weight of cyclohexane dimethanol	0 %	31.12.2014
ex 3907 99 90	80	Copolymer, consisting of 72 % by weight or more of terephthalic acid and/ or derivatives thereof and cyclohexanedimethanol, completed with linear and/ or cyclic dioles	0 %	31.12.2015
ex 3908 90 00	10	Poly(iminomethylene-1,3-phenylenemethyleneiminoadipoyl), in one of the forms mentioned in note 6 (b) to Chapter 39	0 %	31.12.2018
ex 3908 90 00	30	Reaction product of mixtures of octadecanecarboxylic acids polymerised with an aliphatic polyetherdiamine	0 %	31.12.2018
ex 3908 90 00	50	Oxygen binding concentrate consisting of a blend of:  — a copolymer obtained from poly(ethyleneterephthalate), pyromellitic dianhydride (PMDA) and a hydroxyl substituted polybutadiene  — a barrier co-polymer (as determined by the ASTM method F1115-95 (2001)) obtained from xylylene diamines and adipic acid, and  — organic dyes and/or organic and inorganic pigments where the second co-polymer predominates	0 %	31.12.2014
ex 3908 90 00	60	Copolymer consisting of:  — hexanedioic acid  — 12-aminododecanoic acid  — hexahydro-2H-azepin-2-one, and  — 1,6-hexanediamine	0 %	31.12.2017
ex 3909 40 00	10	Polycondensation product of phenol with formaldehyde, in the form of hollow spheres of a diameter of less than 150 $\mu m$	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 3909 40 00	20	Powder of thermosetting resin in which magnetic particles have been evenly distributed, for use in the manufacture of ink for photocopiers, fax machines, printers and multifunction devices	0 %	31.12.2015
ex 3909 40 00	30	Mixture of:  — alkylphenol - formaldehyde resin, whether or not brominated, and  — zinc oxide	0 %	31.12.2017
ex 3909 40 00	40	Polymer in powder form with a content of:  — phenolic resin polymer (CAS RN 9003-35-4) with 80 % by weight or more but not more than 90 %  — phenol (CAS RN 108-95-2) with not more than 5 % and  — hexamethylenetetramine (CAS RN 100-97-0) with 5 % by weight or more but not more than 15 %	0 %	31.12.2018
ex 3909 50 90	10	UV curable water soluble liquid photopolymer consisting of a mixture by weight of — 60 % or more of two-functional acrylated polyurethane oligomers and — 30 % (± 8 %) of mono-functional and tri-functional (metha) acrylates, and — 10 % (± 3 %) of hydroxyl functionalized mono-functional (metha) acrylates	0 %	31.12.2014
ex 3910 00 00	20	Block copolymer of poly(methyl-3,3,3-trifluoropropylsiloxane) and poly[methyl(vinyl)siloxane]	0 %	31.12.2018
ex 3910 00 00	40	Biocompatible silicones for the manufacture of long term surgical implants (1)	0 %	31.12.2016
ex 3910 00 00	50	Silicone based pressure sensitive adhesive in solvent containing copoly(dimethylsiloxane/diphenylsiloxane) gum	0 %	31.12.2017
ex 3910 00 00	60	Polydimethylsiloxane, whether or not polyethylene glycol and trifluoropropyl substituted, with methacrylate end groups	0 %	31.12.2014
ex 3910 00 00	70	Passivating silicon coating in primary form, to protect edges and prevent short circuits in semiconductor devices	0 %	31.12.2018
ex 3911 10 00	81	Non-hydrogenated hydrocarbon resin, obtained by polymerization of more than 75 % by weight C-5 to C-12 cycloaliphatic alkenes and more than 10 % but not more than 25 % by weight aromatic alkenes yielding a hydrocarbon resin with:  — an iodine value of more than 120 and  — a Gardner Colour of more than 10 for the pure product or  — a Gardner Colour of more than 8 for a 50 % solution by weight in toluene (as determined by the ASTM method D6166)	0 %	31.12.2018
ex 3911 90 19	10	Poly(oxy-1,4-phenylenesulfonyl-1,4-phenyleneoxy-4,4'-biphenylene)	0 %	31.12.2018
ex 3911 90 19	30	Copolymer of ethyleneimine and ethyleneimine dithiocarbamate, in an aqueous solution of sodium hydroxide	0 %	31.12.2017
ex 3911 90 19	40	m- Xylene formaldehyde resin	0 %	31.12.2016
ex 3911 90 99	25	Copolymer of vinyltoluene and $\alpha$ -methylstyrene	0 %	31.12.2018
ex 3911 90 99	30	1,4:5,8- Dimethanonaphthalene, 2-ethylidene-1,2,3,4,4a,5,8,8a-octahydro-, polymer with 3a,4,7,7a- tetrahydro- 4,7-methano-1H-indene, hydrogenated	0 %	31.12.2015
ex 3911 90 99	31	Copolymers of butadiene and maleic acid, whether or not containing its ammonium salts	0 %	31.12.2014
ex 3911 90 99	35	Alternated copolymer of ethylene and maleic anhydride (EMA)	0 %	31.12.2015
ex 3911 90 99	40	Mixed calcium and sodium salt of a copolymer of maleic acid and methyl vinyl ether, having a calcium content of 9 % or more but not more than 16 % by weight	0 %	31.12.2018
ex 3911 90 99	45	Copolymer of maleic acid and methyl vinyl ether	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 3911 90 99	53	Hydrogenated polymer of 1,2,3,4,4a,5,8,8a-octahydro-1,4:5,8-dimethanonaphthalene with 3a,4,7,7a-tetrahydro-4,7-methano-1H-indene and 4,4a,9,9a-tetrahydro-1,4-methano-1H-fluorene (CAS RN 503442-46-4)	0 %	31.12.2017
ex 3911 90 99	57	Hydrogenated polymer of 1,2,3,4,4a,5,8,8a-octahydro-1,4:5,8-dimethanonaphthalene with 4,4a,9,9a-tetrahydro-1,4-methano-1H-fluorene (CAS RN 503298-02-0)	0 %	31.12.2017
ex 3911 90 99	65	Calcium zinc salt of a copolymer of maleic acid and methyl vinyl ether	0 %	31.12.2018
ex 3911 90 99	70	Aqueous solution containing by weight:  — 30 % or more but not more than 40 % of poly-4-vinylpyridine-N-oxide,  — 0,1 % or more but not more than 4 % of isonicotinic acid-N-oxide,  — 0,1 % or more but not more than 3,5 % of sodium sulphate,  — 0,1 % or more but not more than 2 % of 4-acetylpyridine-N-oxide	0 %	31.12.2016
ex 3911 90 99	86	Copolymer of methyl vinyl ether and maleic acid anhydride (CAS RN 9011-16-9)	0 %	31.12.2016
ex 3912 11 00	30	Cellulose triacetate (CAS RN 9012-09-3)	0 %	31.12.2016
ex 3912 11 00	40	Cellulose diacetate powder	0 %	31.12.2015
ex 3912 20 11	10	Nitrocellulose (CAS RN 9004-70-0)	0 %	31.12.2016
ex 3912 39 85	10	Ethylcellulose, not plasticized	0 %	31.12.2018
ex 3912 39 85	20	Ethylcellulose, in the form of an aqueous dispersion containing hexadecan-1-ol and sodium dodecyl sulphate, containing by weight 27 ( $\pm$ 3) % of ethylcellulose	0 %	31.12.2018
ex 3912 39 85	30	Cellulose, both hydroxyethylated and alkylated with alkyl chain-lengths of 3 or more carbon atoms	0 %	31.12.2018
ex 3912 39 85	40	Hypromellose (INN) (CAS RN 9004-65-3)	0 %	31.12.2016
ex 3912 90 10	10	Cellulose acetate propionate, non-plasticised, in the form of powder:  — containing by weight 25 % or more of propionyl (as determined by the ASTM D 817-72 method) and  — of a viscosity of not more than 120 poise (as determined by the ASTM D 817-72 method), for the manufacture of printing inks, paints, lacquers and other coatings, and reprographic coatings  (1)	0 %	31.12.2018
ex 3912 90 10	20	Hydroxypropyl methylcellulose phthalate	0 %	31.12.2018
ex 3913 90 00	85	Sterile sodium hyaluronate (CAS RN 9067-32-7)	0 %	31.12.2018
ex 3913 90 00	92	Protein, chemically modified by carboxylation and/or phthalic acid addition, having a weight average molecular weight ( $M_{\rm w}$ ) of 100 000 to 300 000	0 %	31.12.2018
ex 3913 90 00	94	Granules containing by weight:  — 35 % or more but less than 75 % of a high amylose extruded biopolymer produced from corn starch,  — 5 % or more but less than 16 % polyvinyl alcohol,  — 10 % or more but less than 46 % of polyol plasticisers,  — 0,25 % or more but less than 3 % of stearic acid,  — whether or not containing 30 % (± 10 %) of biodegradable polyester resin but never to a level that exceeds the amount of the high amylose biopolymer	0 %	31.12.2016
ex 3913 90 00	95	Chondroitinsulphuric acid, sodium salt (CAS RN 9082-07-9)	0 %	31.12.2018
ex 3913 90 00	96	Powder consisting of 90 % ( $\pm$ 5 %) by weight of a high amylose extruded biopolymer produced from corn starch, 10 % ( $\pm$ 5 %) by weight of a synthetic polymer and 0,5 % ( $\pm$ 0,25 %) of stearic acid	0 %	31.12.2016

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 3916 20 00	91	Profiles of poly(vinyl chloride) of a kind used in the manufacture of sheet pilings and facings, containing the following additives:  — titanium dioxide — poly(methyl methacrylate) — calcium carbonate — binding agents	0 %	31.12.2014
ex 3916 90 10	10	Rods with cellular structure, containing by weight:  — polyamide-6 or poly(epoxy anhydride)  — 7 % or more but not more than 9 % of polytetrafluorethylene if present  — 10 % or more but not more than 25 % of inorganic fillers	0 %	31.12.2018
ex 3917 32 00	91	Pipe consisting of a block copolymer of polytetrafluoroethylene and polyperfluoroalkoxytrifluoroethylene, of a length of not more than 600 mm, a diameter of not more than 85 mm and a wall-thickness of 30 $\mu m$ or more but not more than 110 $\mu m$	0 %	31.12.2018
ex 3917 40 00	91	Plastic connectors containing O-rings, a retainer clip and a release system for insertion into car fuel hoses	0 %	31.12.2014
ex 3919 10 19 ex 3919 10 80 ex 3919 90 00	10 25 31	Reflecting film, consisting of a layer of polyurethane, with, on one side, security imprints against counterfeiting, alteration or substitution of data or duplication, or an official mark for an intended use, and embedded glass beads and, on the other side, an adhesive layer, covered on one side or on both sides with a release film	0 %	31.12.2018
ex 3919 10 19	20	Rolls of two-sided adhesive tape:  — coated with non-vulcanised natural or synthetic rubber  — with a width of 20 mm or more but not more than 40 mm  — containing silicone, aluminium hydroxide, acryl and urethane	0 %	31.12.2018
ex 3919 10 80 ex 3919 90 00 ex 3920 61 00	21 21 20	Reflecting sheet, consisting of:  — a polycarbonate or acrylic polymer film totally embossed on one side in a regular shaped pattern,  — covered on both sides with one or more layers of plastic material,  — whether or not covered on one side with a self-adhesive layer and a release sheet	0 %	31.12.2018
ex 3919 10 80	23	Reflecting film, consisting of several layers including:  — poly(vinyl chloride);  — polyurethane with, on one side, imprints against counterfeiting, alteration or substitution of data or duplication, and on the other side, a layer of glass microspheres;  — a layer incorporating a security and/or official mark which changes appearance with angle of view;  — metallized aluminium;  — and adhesive, covered on one side with a release liner	0 %	31.12.2014
ex 3919 10 80 ex 3919 90 00	27 20	Polyester film:  — coated on one side with an acrylic thermal release adhesive that debonds at temperatures of 90 °C or more but not more than 200 °C, and a polyester liner, and  — on the other side not coated or coated with an acrylic pressure sensitive adhesive or with an acrylic thermal release adhesive that debonds at temperatures of 90 °C or more but not more than 200 °C, and a polyester liner	0 %	31.12.2014
ex 3919 10 80	30	Double-sided, self-adhesive modified epoxy resin foil, put up in rolls, 10 to 20 cm wide, 10 to 210 m long and with a total thickness of 10 to 50 $\mu$ m, not for retail sale	0 %	31.12.2016
ex 3919 10 80	32	Polytetrafluoroethylene film:  — with a thickness of 110 μm or more,  — with a surface resistance of between 10²-10¹⁴ ohms as determined by test method ASTM D 257,  — coated on one side with an acrylic pressure sensitive adhesive	0 %	31.12.2014

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 3919 10 80	35	Reflecting film, consisting of a layer of poly(vinyl chloride), a layer of alkyd polyester, with, on one side, security imprints against counterfeiting, alteration or substitution of data or duplication, or an official mark for an intended use, only visible by means of a retroreflecting lighting, and embedded glass beads and, on the other side, an adhesive layer, covered on one side or on both sides with a release film	0 %	31.12.2018
ex 3919 10 80	37	Polytetrafluoroethylene film:  — with a thickness of 100 μm or more,  — an elongation at break of not more than 100 %,  — coated on one side with a pressure sensitive silicon adhesive	0 %	31.12.2014
ex 3919 10 80 ex 3919 90 00	40 43	Black poly(vinyl chloride) film:  — with a gloss of more than 30 degrees according to ASTM D2457,  — whether or not covered on one side with a protective poly(ethyleneterephthalate) film, and on the other side with a pressure sensitive adhesive with channels and a release liner	0 %	31.12.2016
ex 3919 10 80 ex 3919 90 00	43 26	Ethylene vinyl acetate film:  — of a thickness of 100 μm or more,  — coated on one side with an acrylic pressure sensitive or UV-sensitive adhesive and a polyester liner	0 %	31.12.2014
ex 3919 10 80 ex 3919 90 00	45 45	Reinforced polyethylene foam tape, coated on both sides with an acrylic micro channelled pressure sensitive adhesive and on one side a liner, with an application thickness of 0,38 mm or more but not more than 1,53 mm	0 %	31.12.2017
ex 3919 10 80 ex 3919 90 00	47 32	Polyester, polyurethane or polycarbonate foil:  — with pressure sensitive silicone polymer adhesive,  — of a total thickness of not more than 0,7 mm,  — of a total width of 1 cm or more, but not more than 1 m,  — whether or not in rolls of a kind used for the protection of the surface of products of headings 8521 and 8528	0 %	31.12.2017
ex 3919 10 80 ex 3919 90 00 ex 3920 10 89	50 41 25	Adhesive film consisting of a base of a copolymer of ethylene and vinyl acetate (EVA) of a thickness of 70 $\mu$ m or more and an adhesive part of acrylic type of a thickness of 5 $\mu$ m or more, for use in the grinding and/or dicing process of silicon discs (1)	0 %	31.12.2018
ex 3919 10 80 ex 3919 90 00 ex 3920 10 28 ex 3920 10 89	53 34 93 50	Polyethylene foil:  — with pressure sensitive, non-rubber adhesive adhering solely to clean and smooth surfaces,  — of a total thickness of 0,025 mm or more, but not more than 0,7 mm, and  — of a total width of 6 cm or more, but not more than 1 m,  — whether or not in rolls, of a kind used for the protection of the surface of products of headings 8521 and 8528	0 %	31.12.2017
ex 3919 10 80 ex 3919 90 00	55 53	Acrylic foam tape, covered on one side with a heat activatable adhesive or an acrylic pressure sensitive adhesive and on the other side with an acrylic pressure sensitive adhesive and a release sheet, of a peel adhesion at an angle of 90 ° of more than 25 N/cm (as determined by the ASTM D 3330 method)	0 %	31.12.2017
ex 3919 10 80	60	Reflecting laminated sheet showing a regular pattern, consisting of a film of poly(methylmethacrylate), followed by a layer of acrylic polymer containing microprisms, a film of poly(methylmethacrylate), an adhesive layer and a release sheet	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 3919 10 80 ex 3919 90 00	65 57	Self-adhesive reflecting sheet whether or not in segmented pieces:  — showing a regular pattern,  — with or without an application tape layer,  — consisting of a film of acrylic polymer followed by a layer of poly(methyl methacrylate) containing microprisms,  — whether or not containing an additional layer of polyester and  — an adhesive with a final release sheet	0 %	31.12.2018
ex 3919 10 80 ex 3919 90 00	70 75	Rolls of polyethylene foil:  — self-adhesive on one side,  — of a total thickness of 0,025 mm or more, but not more than 0,09 mm,  — of a total width of 60 mm or more, but not more than 1 110 mm,  of a kind used for the protection of the surface of products of headings 8521 or  8528	0 %	31.12.2016
ex 3919 10 80 ex 3919 90 00	75 80	Self-adhesive reflecting film, consisting of several layers including:  — a copolymer of acrylic resin,  — polyurethane,  — a metalised layer with, on one side, laser imprints against counterfeiting, alteration or substitution of data or duplications, or an official mark for an intended use,  — glass microspheres, and  — an adhesive layer, with a release liner on one or both sides	0 %	31.12.2016
ex 3919 10 80 ex 3919 90 00	80 83	Acrylic tape put up in rolls:  — self-adhesive on both sides,  — of a total thickness of 0,04 mm or more, but not more than 1,25 mm,  — of a total width of 5 mm or more but not more than 1 205 mm for use in the manufacture of products of headings 8521 and 8528	0 %	31.12.2016
ex 3919 10 80 ex 3919 90 00	85 28	Poly(vinyl chloride) or polyethylene or any other polyolefine film:  — of a thickness of 65 µm or more,  — coated on one side with an acrylic UV-sensitive adhesive and a polyester liner	0 %	31.12.2014
ex 3919 90 00	19	Transparent poly(ethylene terephthalate) self-adhesive film:  — free from impurities or faults,  — coated on one side with an acrylic pressure sensitive adhesive and a protective liner, and on the other side with an antistatic layer of ionic organic choline compound,  — whether or not with a printable dust-proof layer of modified long chain alkyl organic compound,  — with a total thickness without the liner of 54 μm or more but not more than 64 μm, and  — a width of more than 1 295 mm but not more than 1 305 mm	0 %	31.12.2018
ex 3919 90 00	22	Black polypropylene film:  — with a gloss of more than 20 degrees as determined by test method ASTM D2457,  — whether or not covered on one side with a protective poly(ethylene terephthalate) film and on the other side with a pressure sensitive adhesive with channels and a release liner	0 %	31.12.2014
ex 3919 90 00	23	Film consisting of 1 to 3 laminated layers of poly(ethylene terephthalate) and a copolymer of terephthalic acid, sebacic acid and ethylene glycol, coated on one side with an acrylic abrasion resistant coating and on the other side with an acrylic pressure sensitive adhesive, a water soluble methylcellulose coating and a poly(ethylene terephthalate) protective liner	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 3919 90 00	24	Reflecting laminated sheet:  — consisting of an epoxy acrylate layer embossed on one side in a regular shaped pattern,  — covered on both sides with one or more layers of plastic material and  — covered on one side with an adhesive layer and a release sheet	0 %	31.12.2014
ex 3919 90 00	25	Film consisting of a multi-layer construction of poly(ethylene terephthalate) and copolymer of butylacrylate and methylmethacrylate, coated on one side with an acrylic abrasion resistant coating incorporating nanoparticles of antimony tin oxide and carbon black, and on the other side with an acrylic pressure sensitive adhesive and a silicone-coated poly(ethylene terephthalate) protective liner	0 %	31.12.2017
ex 3919 90 00	27	Poly(ethylene terephthalate) film, with an adhesive strength of not more than 0,147 N/25 mm and an electrostatic discharge of not more than 500 V	0 %	31.12.2018
ex 3919 90 00	29	Polyester film coated on both sides with an acrylic and/or rubber (pressure sensitive) adhesive put up in rolls of a width of 45,7 cm or more but not more than 132 cm (supplied with a release liner)	0 %	31.12.2014
ex 3919 90 00	33	Transparent poly(ethylene) self-adhesive film, free from impurities or faults, coated on one side with an acrylic pressure sensitive adhesive, with a thickness of 60 $\mu m$ or more, but not more than 70 $\mu m$ , and with a width of more than 1 245 mm but not more than 1 255 mm	0 %	31.12.2018
ex 3919 90 00	35	Reflecting layered sheet on rolls, with a width of more than 20 cm, showing an embossed regular pattern, consisting of poly(vinyl chloride) film coated on one side with:  — a layer of polyurethane containing glass micro beads, — a layer of poly(ethylene vinyl acetate), — an adhesive layer, and — a release sheet	0 %	31.12.2018
ex 3919 90 00 ex 3920 49 10	36 95	Printed laminated sheet with a central layer of poly(vinyl chloride), coated on both sides with a layer of poly(vinyl fluoride)  — whether or not with a pressure or heat sensitive adhesive layer  — whether or not with a release film  — with a toxicity (as determined by test method ABD 0031) of not more than 70 ppm hydrogen fluoride, not more than 120 ppm hydrogen chloride, not more than 10 ppm hydrogen cyanide, not more than 10 ppm nitrogen oxides, not more than 300 ppm carbon monoxide and not more than 10 ppm dihydrogen sulphide and sulphur dioxide taken together  — with a flammability within 60 seconds of not more than 130 mm (as determined by test method FAR 25 App.F Pt. I Amdt.83)  — with a weight (without release film) of 240 g/m² (± 30 g/m²) without adhesive layer, of 340 g/m² (± 40 g/m²) with heat sensitive adhesive layer or of 330 g/m² (± 40 gm²) with pressure sensitive layer	0 %	31.12.2017
ex 3919 90 00	37	UV-absorbing film of poly (vinyl chloride):  — with a thickness of 78 μm or more,  — covered on one side with an adhesive layer and with a release sheet,  — with an adhesive strength of 1 764 mN / 25 mm or more	0 %	31.12.2014
ex 3919 90 00	38	Self-adhesive film composed of:  — a top layer predominantly of polyurethane mixed with acrylic polymer emulsions and titanium dioxide,  — whether or not containing a second layer of a mixture of vinyl acetate-ethylene copolymer and cross-linkable vinyl acetate polymer emulsions,  — not more than 6 % by weight of other additives,  — a pressure sensitive adhesive; and  — covered on one side with a release liner,  — whether or not with a separate self-adhesive over laminate protective film,  — of a total thickness of not more than 400 μm	0 %	31.12.2017
ex 3919 90 00	39	Poly(vinyl chloride) sheeting, of a thickness of less than 1 mm, coated with an adhesive in which are embedded glass balls of a diameter of not more than 100 $\mu$ m	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 3919 90 00	40	Film, with a total thickness of 40 μm or more, consisting of one or more layers of transparent polyester film:  — containing at least one infrared reflective layer with a total normal reflectance according to EN 12898 of 80 % or more  — having on one side a layer with a normal emissivity according to EN 12898 of not more than 0,2  — coated on the other side with a pressure sensitive adhesive and a release liner	0 %	31.12.2017
ex 3919 90 00	42	Self-adhesive film composed of:  — a first layer containing a mixture of thermoplastic polyurethane and antiblocking agent,  — a second layer containing a maleic anhydride copolymer,  — a third layer containing a mixture of low density polyethylene, titanium dioxide and additives,  — a fourth layer containing a mixture of low density polyethylene, titanium dioxide, additives and colour pigment,  — a pressure sensitive adhesive; and  — covered on one side with a release liner  — whether or not with a separate self-adhesive over laminate protective film  — of a total thickness of not more than 400 μm	0 %	31.12.2017
ex 3919 90 00 ex 3921 90 60	44 95	Printed laminated sheet  with a core layer of glass fabric, coated on each side with a layer of poly(vinyl chloride),  on one side covered with a layer of poly(vinyl fluoride),  whether or not with a pressure sensitive adhesive layer and a release film on the other side,  with a toxicity (as determined by test method ABD 0031) of not more than 50 ppm hydrogen fluoride, not more than 85 ppm hydrogen chloride, not more than 10 ppm hydrogen cyanide, not more than 10 ppm nitrogen oxides, not more than 300 ppm carbon monoxide and not more than 10 ppm dihydrogen sulphide and sulphur dioxide taken together,  with a flammability within 60 seconds of not more than 110 mm (as determined by test method FAR 25 App.F Pt. I Amdt.83), and  with a weight (without release film) of 490 g/m² (± 45 g/m²) without adhesive layer or of 580 g/m² (± 50 g/m²) with pressure sensitive layer	0 %	31.12.2017
ex 3919 90 00 ex 9001 20 00	47 40	Polariser film, in rolls, consisting of a multilayered polyvinyl alcohol film, supported on either side by a triacetyl cellulose film, with a pressure sensitive adhesive and release film on one side	0 %	31.12.2017
ex 3919 90 00	49	Reflecting laminated sheet consisting of a film of poly(methyl methacrylate) embossed on one side in a regular shaped pattern, a film of a polymer containing glass microspheres, an adhesive layer and a release sheet	0 %	31.12.2018
ex 3919 90 00	51	Biaxially-oriented film of poly(methyl methacrylate), of a thickness of 50 $\mu$ m or more but not exceeding 90 $\mu$ m, covered on one side with an adhesive layer and a release sheet	0 %	31.12.2018
ex 3919 90 00	60	Reflecting film containing:  — a poly(vinyl chloride) layer,  — a polyurethane layer,  — a glass microspheres layer,  — a layer whether or not incorporating a security and/or official mark which changes appearance with angle of view,  — a metallised aluminium layer, and  — an adhesive, covered on one side with a release liner	0 %	31.12.2015
ex 3919 90 00	63	Co-extruded trilayer film,  — each layer containing a mixture of polypropylene and polyethylene,  — containing not more than 3 % by weight of other polymers,  — whether or not containing titanium dioxide in the core layer,  — coated with an acrylic pressure sensitive adhesive and  — with a release liner	0 %	31.12.2015

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		— of an overall thickness of not more than 110 μm		
ex 3919 90 00	65	Self-adhesive film with a thickness of 40 $\mu m$ or more, but not more than 400 $\mu m$ , consisting of one or more layers of transparent, metallised or dyed poly(ethylene terephthalate), covered on one side with a scratch resistant coating and on the other side with a pressure sensitive adhesive and a release liner	0 %	31.12.2015
ex 3919 90 00	70	Self-adhesive polishing discs of microporous polyurethane, whether or not coated with a pad	0 %	31.12.2015
ex 3919 90 00	81	Film of a minimum thickness of 0,36 mm, consisting of the following:  — an embossed polyester layer,  — a caprolactone-cyclohexylene isocyanate copolymer layer,  — a pressure sensitive adhesive and covered on one side with a release liner	0 %	31.12.2018
ex 3919 90 00	85	Multi-layered film of poly(methyl methacrylate) and metallised layers of silver and copper:  — having a minimum reflectance of 93,5 % as determined by ASTM G173-03,  — covered on one side with a removable layer of polyethylene,  — covered on the other side with an acrylic pressure sensitive adhesive and a siliconised polyester liner	0 %	31.12.2016
ex 3919 90 00	87	Self-adhesive transparent film, having a transmittance of more than 90 % and a haze of less than 3 % (as determined by ASTM D1003), consisting of several layers including: — an acrylic adhesive layer with a thickness of 20 $\mu m$ or more but not more than 70 $\mu m$ , — a polyurethane based layer with a thickness of 100 $\mu m$ or more but not more than 300 $\mu m$	0 %	31.12.2016
ex 3920 10 25 ex 3920 10 89	10 20	Film of a thickness of not more than 0,20 mm, of a blend of polyethylene and a copolymer of ethylene with oct-1-ene, embossed in a regular rhomboidal pattern, for coating both sides of a layer of unvulcanized rubber (1)	0 %	31.12.2018
ex 3920 10 25	20	Film of polyethylene, of a kind used for typewriter ribbon	0 %	31.12.2018
ex 3920 10 28	91	Poly(ethylene) film printed with a graphic design, which is achieved by using four base colours in ink plus specialist colours, to achieve multiple colours in ink on one side of the film, and one colour on the opposite side, the graphic design also has the following characteristics:  — is repetitive and equally spaced along the length of the film  — is equally and visibly aligned when viewed from the back or front of the film	0 %	31.12.2018
ex 3920 10 40	30	Co-extruded seven to nine layered film predominately of copolymers of ethylene or functionalized polymers of ethylene, consisting of:  — a tri-layer barrier with a core layer predominantly of ethylene vinyl alcohol covered on either side with a layer predominantly of cyclic olefin polymers,  — covered on either side with two or more layers of polymeric material, and having an overall total thickness of not more than 110 µm	0 %	31.12.2017
ex 3920 10 89	30	Ethylene vinyl acetate (EVA) film with:  — a raised relief surface with embossed undulations, and  — a thickness of more than 0,125 mm	0 %	31.12.2016
ex 3920 10 89	40	Composite sheet containing an acrylic coating and laminated to a high-density polyethylene layer, of a total thickness of 0,8 mm or more but not more than 1,2 mm	0 %	31.12.2016
ex 3920 20 21	30	Biaxially oriented polypropylene film with a coextruded layer of polyethylene on one side and a total thickness of 11,5 μm or more but not more than 13,5 μm	0 %	31.12.2018
ex 3920 20 21	40	Sheets of biaxially - oriented polypropylene film:  — with the thickness of not more than 0,1 mm,	0 %	31.12.2016

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 3920 20 29 ex 8507 90 30	50 95	<ul> <li>— printed on both sides with specialised coatings to allow banknote security printing</li> <li>Sheet of polypropylene in the form of a roll:         <ul> <li>— with a thickness of not more than 30 μm,</li> <li>— of a width of not more than 210 mm,</li> <li>— conforming to ASTM D882,</li> <li>for use in the manufacture of separators for lithium-ion electric vehicle batteries</li> </ul> </li> </ul>	0 %	31.12.2016
ex 3920 20 29 ex 3920 20 80	55 93	Co-extruded seven to nine layered film predominately of copolymers of propylene, consisting of:  — a tri-layer barrier with a core layer predominantly of ethylene vinyl alcohol covered on either side with a layer predominantly of cyclic olefin polymers,  — covered on either side with two or more layers of polymeric material, and having an overall total thickness of not more than 110 µm	0 %	31.12.2017
ex 3920 20 29	92	Mono-axial oriented film, of a total thickness of not more than 75 μm, consisting of two or three layers, each layer containing a mixture of polypropylene and polyethylene, with a core layer whether or not containing titanium dioxide, having:  — a tensile strength in the machine direction of 140 MPa or more but not more than 270 MPa and  — a tensile strength in the transverse direction of 20 MPa or more but not more than 40 MPa as determined by test method ASTM D882/ISO 527-3	0 %	31.12.2018
ex 3920 20 29	93	<ul> <li>Mono-axial oriented film, consisting of three layers, each layer consisting of a mixture of polypropylene and a copolymer of ethylene and vinyl acetate, having:         <ul> <li>a thickness of 55 μm or more but not more than 97 μm,</li> <li>a tensile modulus in the machine direction of 0,75 GPa or more but not more than 1,45 GPa, and</li> <li>a tensile modulus in the transverse direction of 0,20 GPa or more but not more than 0,55 GPa</li> </ul> </li> </ul>	0 %	31.12.2014
ex 3920 20 29	94	Co-extruded trilayer film,  — each layer containing a mixture of polypropylene and polyethylene,  — containing not more than 3 % by weight of other polymers,  — whether or not containing titanium dioxide in the core layer,  — of an overall thickness of not more than 70 µm	0 %	31.12.2016
ex 3920 20 80	92	Laminated sheet or strip, consisting of a film of a thickness of 181 $\mu m$ or more but not more than 223 $\mu m$ composed of a blend of a copolymer of propylene with ethylene and a copolymer of styrene-ethylene-butylene-styrene (SEBS) coated or covered on one side with a layer of a copolymer of styrene-ethylene-butylene-styrene (SEBS) and a layer of polyester	0 %	31.12.2018
ex 3920 20 80	95	Polypropylene sheet, put up in rolls, with:  — flame retardant level of UL 94 V-0 for material thicknesses of 0,25 mm or more and level UL 94 VTM-0 for material thicknesses of 0,05 mm or more but not more than 0,25 mm (as determined by Flammability Standard UL-94)  — dielectric breakdown of 13,1 kV or more but not more than 60,0 kV(as determined by ASTM D149)  — tensile yield in a machine direction of 30 MPa or more but not more than 33 MPa (as determined by ASTM D882)  — tensile yield in a transverse direction of 22 MPa or more but not more than 25 MPa (as determined by ASTM D882)  — density range of 0,988 g/cm³ or more but not more than 1,035 g/cm³ (as determined by ASTM D792)  — moisture absorption of 0,01 % or more but not more than 0,06 % (as determined by ASTM D570)  for use in the manufacture of insulators used in the electronics and electrical industries (1)	0 %	31.12.2017
ex 3920 43 10	92	Sheeting of poly(vinyl chloride), stabilized against ultraviolet rays, without any	0 %	31.12.2018

	1			
CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 3920 43 10 ex 3920 49 10	94 93	holes, even microscopic, of a thickness of $60~\mu m$ or more but not more than $80~\mu m$ , containing $30$ or more but not more than $40$ parts of plasticizer to $100$ parts of poly(vinyl chloride)  Film of a specular gloss of $70$ or more, measured at an angle of $60~^{\circ}$ using a glossmeter (as determined by the ISO $2813:2000$ method), consisting of one or two layers of poly(vinyl chloride) coated on both sides with a layer of plastic, of a thickness of $0.26$ mm or more but not more than $1.0$ mm, covered on the gloss surface with a protective film of polyethylene, in rolls of a width of $1~000$ mm or more but not more than $1~450$ mm, for use in the manufacture of goods of heading $9403~^{(1)}$	0 %	31.12.2018
		neading 9403		
ex 3920 43 10	95	Reflecting laminated sheet, consisting of a film of poly(vinyl chloride) and a film of an other plastic totally embossed in a regular pyramidal pattern, covered on one side with a release sheet	0 %	31.12.2018
ex 3920 49 10	30	Film of a (polyvinyl)chloride-copolymer  — containing by weight 45 % or more of fillers  — on a support	0 %	31.12.2018
ex 3920 51 00	20	Plate of poly(methyl methacrylate) containing aluminium trihydroxide, of a thickness of 3,5 mm or more but not more than 19 mm	0 %	31.12.2018
ex 3920 51 00	30	Biaxially-oriented film of poly(methyl methacrylate), of a thickness of 50 $\mu m$ or more but not exceeding 90 $\mu m$	0 %	31.12.2018
ex 3920 51 00	40	Sheets of polymethylmethacrylate conforming to standard EN 4366 (MIL-PRF-25690)	0 %	31.12.2018
ex 3920 59 90	10	Non-cellular and non-laminated sheet of modified copolymer of acrylonitrile-methyl acrylate with a thickness of 1,0 mm or more but not more than 1,3 mm, put up in rolls	0 %	31.12.2016
ex 3920 59 90	20	Reflecting laminated sheet, consisting of an epoxy acrylate layer embossed on one side in a regular shaped pattern, covered on both sides with one or more layers of plastic material	0 %	31.12.2014
ex 3920 59 90	30	Non-self-adhesive reflecting film, consisting of several layers including:  — a copolymer of acrylic resin  — polyurethane  — a metallised layer with, on one side, laser imprints against counterfeiting, alteration or substitution of data or duplications, or an official mark for an intended use  — glass microspheres, and  — a permanent liner of poly(ethyleneterephthalate)	0 %	31.12.2016
ex 3920 62 19	02	Coextruded opaque sheet of poly(ethylene terephthalate), of a thickness of 50 $\mu m$ or more but not more than 350 $\mu m$ , consisting especially of a layer containing carbon black	0 %	31.12.2018
ex 3920 62 19	08	Poly(ethylene terephthalate) film, not coated with an adhesive, of a thickness of not more than 25 µm, either:  — only dyed in the mass, or  — dyed in the mass and metallised on one side	0 %	31.12.2018
ex 3920 62 19	12	Film of poly(ethylene terephthalate) only, of a total thickness of not more than 120 $\mu$ m, consisting of one or two layers each containing a colouring and/or UV-absorbing material throughout the mass, uncoated with an adhesive or any other material	0 %	31.12.2018
ex 3920 62 19	18	Laminated film of poly(ethylene terephthalate) only, of a total thickness of not more than 120 $\mu m$ , consisting of one layer which is metallised only and one or two layers each containing a colouring and/or UV-absorbing material throughout the	0 %	31.12.2018
	l		l	

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		mass, uncoated with an adhesive or any other material		
ex 3920 62 19	20	Reflecting polyester sheeting embossed in a pyramidal pattern, for the manufacture of safety stickers and badges, safety clothing and accessories thereof, or of school satchels, bags or similar containers (1)	0 %	31.12.2018
ex 3920 62 19	25	Film of poly(ethylene terephthalate) of a thickness of 186 $\mu$ m or more but not more than 191 $\mu$ m coated on one side with an acrylic layer in a matrix pattern	0 %	31.12.2014
ex 3920 62 19	38	Poly(ethylene terephthalate) film, of a thickness of not more than 12 $\mu$ m, coated on one side with a layer of aluminium oxide of a thickness of not more than 35 nm	0 %	31.12.2018
ex 3920 62 19	48	Sheets or rolls of poly(ethylene terephthalate):  — coated on both sides with a layer of epoxy acrylic resin,  — of a total thickness of 37 μm (± 3 μm)	0 %	31.12.2015
ex 3920 62 19	52	Film of poly(ethylene terephthalate), poly(ethylene naphthalate) or similar polyester, coated on one side with metal and/or metal oxides, containing by weight less than 0,1 % of aluminium, of a thickness of not more than 300 $\mu m$ and having a surface resistivity of not more than 10 000 ohms (per square) (as determined by the ASTM D 257-99 method)	0 %	31.12.2018
ex 3920 62 19 ex 3920 69 00	73 40	Iridescent film of polyester and poly(methyl methacrylate)	0 %	31.12.2018
ex 3920 62 19	76	Transparent poly(ethylene terephthalate) film:  — coated on both sides with layers of organic substances on the basis of acryl of a thickness of 7 nm or more but not more than 80 nm,  — with a surface tension of 36 Dyne/cm or more but not more than 39 Dyne/cm,  — with a light transmission of more than 93 %,  — with a haze value of not more than 1,3 %,  — with a total thickness of 10 μm or more but not more than 350 μm,  — with a width of 800 mm or more but not more than 1 600 mm	0 %	31.12.2018
ex 3920 62 19	81	Poly(ethylene terephthalate) film:  — of a thickness of not more than 20 μm,  — coated on at least one side with a gas barrier layer consisting of a polymeric matrix in which silica has been dispersed and of a thickness of not more than 2 μm	0 %	31.12.2017
ex 3920 69 00	20	Film of poly(ethylene naphthalene-2,6-dicarboxylate)	0 %	31.12.2018
ex 3920 91 00	51	Poly(vinyl butyral) film containing by weight 25 % or more but not more than 28 % of tri-isobutyl phosphate as a plasticizer	0 %	31.12.2014
ex 3920 91 00	52	Poly(vinyl butyral) film:  — containing by weight 26 % or more but not more than 30 % of triethyleneglycol bis(2-ethyl hexanoate) as a plasticizer,  — with a thickness of 0,73 mm or more but not more than 1,50 mm	0 %	31.12.2014
ex 3920 91 00	91	Poly(vinyl butyral) film having a graduated coloured band	3 %	31.12.2018
ex 3920 91 00	92	Plasticised film of polyvinyl butyral, containing by weight:  — either 14,5 % or more but not more than 17,5 % of dihexyl adipate,  — or 14,5 % or more but not more than 28,5 % of dibutyl sebacate	0 %	31.12.2014
ex 3920 91 00	93	Film of poly(ethylene terephthalate), whether or not metallised on one or both sides, or laminated film of poly(ethylene terephthalate) films, metallised on the external sides only, and having the following characteristics:  — a visible light transmission of 50 % or more,  — coated on one or both sides with a layer of poly(vinyl butyral) but not coated with an adhesive or any other material except poly(vinyl butyral),  — a total thickness of not more than 0,2 mm without taking the presence of poly(vinyl butyral) into account and a thickness of poly(vinyl butyral) of more than 0,2 mm	0 %	31.12.2014

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		for use in the manufacture of heat-reflecting or decorative laminated glass		
ex 3920 91 00	95	Co-extruded trilayer poly(vinyl butyral) film with a graduated colour band containing by weight 29 % or more but not more than 31 % of 2,2'-ethylenedioxydiethyl bis(2-ethylhexanoate) as a plasticiser	0 %	31.12.2018
ex 3920 92 00	30	Polyamide film:  — of a thickness of not more than 20 μm,  — coated on at least one side with a gas barrier layer which consists of a polymeric matrix in which silica has been dispersed and of a thickness of not more than 2 μm	0 %	31.12.2018
ex 3920 99 28	35	<ul> <li>Polyether imide sheets, in rolls, with <ul> <li>a thickness of 5 μm or more, but not more than 14 μm,</li> <li>a width of 478 mm or more, but not more than 532 mm,</li> <li>a tensile strength at break of 78 MPa or more (as determined by JIS C-2318 for a film thickness of 50 μm),</li> <li>an elongation at break of 50 % or more (as determined by JIS C-2318 for a film thickness of 50 μm),</li> <li>a glass transition point (Tg) of 226 °C,</li> <li>a continuous service temperature of 180 °C (as determined by UL-746 B for a film thickness of 50 μm),</li> <li>a flammability of VTM-0 (as determined by UL 94 for a film thickness of 25 μm)</li> </ul> </li> </ul>	0 %	31.12.2018
ex 3920 99 28	40	Polymer film containing the following monomers:  — poly (tetramethylene ether glycol),  — bis (4-isocyanotocyclohexyl) methane,  — 1,4-butanediol or 1,3-butanediol,  — with a thickness of 0,25 mm or more but not more than 5,0 mm,  — embossed with a regular pattern on one surface,  — and covered with a release sheet	0 %	31.12.2018
ex 3920 99 28	45	Transparent polyurethane film metallised on one side:  — with a gloss of more than 90 degrees according to ASTM D2457  — covered on the metalized side with a heat bonding adhesive layer consisting of polyethylene/polypropylene copolymer  — covered on the other side with a protective poly(ethylene terephthalate) film  — with a total thickness of more than 204 μm but not more than 244 μm	0 %	31.12.2018
ex 3920 99 28	50	Thermoplastic polyurethane film, of a thickness of 250 $\mu m$ or more but not more than 350 $\mu m$ , covered on one side with a removable protective film	0 %	31.12.2016
ex 3920 99 28	55	Thermoplastic polyurethane film extruded, with:  — not self-adhesive,  — an index of yellow lower of more than 1,0 but not more than 2,5 for 10 mm stacked films (as determined by test method ASTM E 313-10),  — a light transmission higher to 87 % for 10 mm stacked films (as determined by test method ASTM D 1003-11),  — a total thickness of 0,38 mm or more, but not more than 7,6 mm,  — a width of 99 cm or more, but not more than 305 cm, of a kind used in the production of laminated safety glass	0 %	31.12.2017
ex 3920 99 28	60	Silicone tape, plate or strip:  — of a total thickness of 2 mm or more, but not more than 9 mm,  — of a total width of 12 mm or more, but not more than 65 mm, for use in the manufacture of products of headings 8521 or 8528	0 %	31.12.2016
ex 3920 99 28	70	Sheets on rolls, consisting of epoxy resin, with conducting properties, containing:  — microspheres with a coating of metal, whether or not alloyed with gold,  — an adhesive layer,  — with a protective layer of silicone or poly(ethylene terephthalate) on one side,  — with a protective layer of poly(ethylene terephthalate) on the other side, and  — with a width of 5 cm or more but not more than 100 cm  — with a length of not more than 2 000 m	0 %	31.12.2016

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 3920 99 59	25	Poly(1-chlorotrifluoroethylene) film	0 %	31.12.2018
ex 3920 99 59	50	Polytetrafluoroethylene film, non-microporous, in the form of rolls, of a thickness of 0,019 mm or more but not more than 0,14 mm, impermeable to water vapour	0 %	31.12.2018
ex 3920 99 59	55	Ion-exchange membranes of fluorinated plastic material	0 %	31.12.2018
ex 3920 99 59	60	Film of a vinyl alcohol copolymer, soluble in cold water, of a thickness of 34 $\mu m$ or more but not more than 90 $\mu m$ , a tensile strength at break of 20 MPa or more but not more than 45 MPa and an elongation at break of 250 % or more but not more than 900 %	0 %	31.12.2018
ex 3920 99 90	20	Anisotropic conductive film, in rolls, of a width of 1,5 mm or more but not more than 3,15 mm and a maximum length of 300 m, used for joining electronic components in the production of LCD or plasma displays	0 %	31.12.2018
ex 3921 13 10	10	Sheet of polyurethane foam, of a thickness of 3 mm ( $\pm$ 15 %) and of a specific gravity of 0,09435 or more but not more than 0,10092	0 %	31.12.2018
ex 3921 13 10	20	Rolls of open-cell polyurethane foam:  — with a thickness of 2,29 mm (± 0,25 mm),  — surface-treated with a foraminous adhesion promoter, and  — laminated to a polyester film and a layer of textile material	0 %	31.12.2017
ex 3921 19 00	30	Blocks with cellular structure, containing by weight:  — polyamide-6 or poly(epoxy anhydride)  — 7 % or more but not more than 9 % of polytetrafluorethylene if present  — 10 % or more but not more than 25 % of inorganic fillers	0 %	31.12.2018
ex 3921 19 00	91	Microporous polypropylene film of a thickness of not more than 100 μm	0 %	31.12.2018
ex 3921 19 00	93	Strip of microporous polytetrafluoroethylene on a support of a non-woven, for use in the manufacture of filters for kidney dialysis equipment (1)	0 %	31.12.2018
ex 3921 19 00	95	Film of polyethersulfone, of a thickness of not more than 200 $\mu m$	0 %	31.12.2018
ex 3921 19 00	96	Cellular film, consisting of a layer of polyethylene of a thickness of 90 $\mu m$ or more but not more than 140 $\mu m$ and a layer of regenerated cellulose of a thickness of 10 $\mu m$ or more but not more than 40 $\mu m$	0 %	31.12.2018
ex 3921 90 10	10	Composite plate of poly(ethylene terephthalate) or of poly(butylene terephthalate), reinforced with glass fibres	0 %	31.12.2018
ex 3921 90 10	20	Poly(ethylene terephthalate) film, laminated on one side or on both sides with a layer of unidirectional nonwoven poly(ethylene terephthalate) and impregnated with polyurethane or epoxide resin	0 %	31.12.2018
ex 3921 90 55	20	Pre-impregnated reinforced fibreglass containing cyanate ester resin or bismaleimide (B) triazine (T) resin mixed with epoxide resin, measuring:  — 469,9 mm (± 2 mm) × 622,3 mm (± 2 mm), or  — 469,9 mm (± 2 mm) × 414,2 mm (± 2 mm), or  — 546,1 mm (± 2 mm) × 622,3 mm (± 2 mm) for use in the manufacture of printed circuit boards	0 %	31.12.2018
ex 3921 90 55 ex 7019 40 00	25 20	Prepreg sheets or rolls containing polyimide resin	0 %	31.12.2014
ex 3921 90 55	30	Prepreg sheets or rolls containing brominated epoxy resin reinforced with glass fabric, having  — a flow of not more than 3,6 mm (as determined by IPC-TM 650.2.3.17.2), and  — a glass transition temperature (Tg) of more than 170 °C (as determined by IPC-TM 650.2.4.25)  for use in the manufacture of printed circuit boards	0 %	31.12.2014

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 3921 90 60 ex 5407 71 00 ex 5903 90 99	91 20 10	Woven polytetrafluoroethylene fabric, coated or covered with a copolymer of tetrafluoroethylene and trifluoroethylene having perfluorinated alkoxy side-chains ending in carboxylic acid or sulphonic acid groups, whether or not in the potassium or sodium salt form	0 %	31.12.2018
ex 3921 90 60	93	Film, of a specular gloss of 30 or more but not more than 60 measured at an angle of 60 ° using a glossmeter (as determined by the ISO 2813:2000 method), consisting of a layer of poly(ethylene terephthalate) and a layer of coloured poly(vinyl chloride), joined by a metallised adhesive coating, for coating panels and doors of a kind used in the manufacture of domestic appliances (1)	0 %	31.12.2018
ex 3921 90 90 ex 8507 90 80	10 50	Roll of polymer-metal laminate comprising:  — a layer of poly(ethylene terephthalate),  — a layer of aluminium,  — a layer of polypropylene,  — with a width of not more than 275 mm,  — a total thickness of not more than 165 µm, and  — conforming to ASTM D1701-91 and ASTM D882-95A for use in the manufacture of lithium-ion electric vehicle batteries	0 %	31.12.2016
ex 3923 10 00	10	Photomask or wafer compacts:  — consisting of antistatic materials or blended thermoplastics proving special electrostatic discharge (ESD) and outgassing properties,  — having non porous, abrasion resistant or impact resistant surface properties,  — fitted with a specially designed retainer system that protects the photomask or wafers from surface or cosmetic damage and  — with or without a gasket seal, of a kind used in the photolithography or other semiconductor production to house photomasks or wafers	0 %	31.12.2016
ex 3923 30 90	10	Polyethylene container, for compressed hydrogen:  — with aluminium bosses at both ends,  — wholly embedded in an overwrap of carbon fibres impregnated with epoxide resin,  — of a diameter of 213 mm or more, but not more than 368 mm,  — a length of 860 mm or more, but not more than 1 260 mm and  — a capacity of 18 litres or more, but not more than 50 litres	0 %	31.12.2018
ex 3926 90 92	20	Reflecting sheeting or tape, consisting of a facing-strip of poly(vinyl chloride) embossed in a regular pyramidal pattern, heat-sealed in parallel lines or in a grid-pattern to a backing-strip of plastic material, or of knitted or woven fabric covered on one side with plastic material	0 %	31.12.2018
ex 3926 90 97	10	Microspheres of a polymer of divinylbenzene, of a diameter of 4,5 $\mu m$ or more but not more than 80 $\mu m$	0 %	31.12.2018
ex 3926 90 97	15	Glass fibre reinforced plastic traverse leaf spring for use in the manufacture of motor vehicle suspension systems	0 %	31.12.2018
ex 3926 90 97	25	Unexpansible microspheres of a copolymer of acrylonitrile, methacrylonitrile and isobornyl methacrylate, of a diameter of 3 $\mu m$ or more but not more than 4,6 $\mu m$	0 %	31.12.2018
ex 3926 90 97	55	Flat product of polyethylene, perforated in opposing directions, of a thickness of 600 $\mu m$ or more but not more than 1 200 $\mu m$ and of a weight of 21 g/m² or more but not more than 42 g/m²	0 %	31.12.2018
ex 3926 90 97	65	Die-cast decoration element made of polycarbonate resin, coated with  — a silver-colour acrylic paint, and  — a transparent scratch-resistant paint of a kind used in the manufacture of car radio front panels	0 %	31.12.2018
ex 3926 90 97	80	Parts of car radio front panels — of acrylonitrile-butadiene-styrene with or without polycarbonate,	0 %	31.12.2016

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		<ul> <li>coated with a copper, a nickel and a chrome layers,</li> <li>with a total thickness of coating of 5,54 μm or more but not more than 22,3 μm</li> </ul>		
ex 4007 00 00	10	Siliconated vulcanised rubber thread and cord	0 %	31.12.2018
ex 4016 99 97	20	Soft rubber sealing stoppers for the manufacture of electrolytic capacitors (1)	0 %	31.12.2018
ex 4016 99 97	30	Tyre moulding bladder	0 %	31.12.2016
ex 4104 41 19	10	Buffalo leather, split, chrome tanned synthetic retanned ("crust"), dry	0 %	31.12.2017
4105 10 00 4105 30 90		Sheep or lamb skin leather, without wool on, tanned or retanned but not further prepared, whether or not split, other than leather of heading 4114	0 %	31.12.2018
4106 21 00 4106 22 90		Goat or kid skin leather, without hair on, tanned or retanned but not further prepared, whether or not split, other than leather of heading 4114	0 %	31.12.2018
4106 31 00 4106 32 00 4106 40 90 4106 92 00		Leather of other animals, without hair on, not further prepared than tanned, other than leather of heading 4114	0 %	31.12.2018
ex 5004 00 10	10	Silk yarn (other than yarn spun from silk waste) not put up for retail sale, unbleached, scoured or bleached, entirely of silk	0 %	31.12.2016
ex 5005 00 10 ex 5005 00 90	10 10	Yarn spun entirely from silk waste (noil), not put up for retail sale	0 %	31.12.2018
ex 5205 31 00	10	Six ply yarn of bleached cotton, measuring 925 dtex or more but not more than 989 dtex per single yarn, for the manufacture of tampons	0 %	31.12.2018
5208 11 10		Fabrics for the manufacture of bandages, dressings and medical gauzes	5.2 %	31.12.2018
ex 5402 45 00	20	Yarn of synthetic textile fibres solely of aromatic polyamides obtained by the polycondensation of <i>m</i> -phenylenediamine and isophthalic acid	0 %	31.12.2018
ex 5402 47 00	10	Synthetic bicomponent filament yarn, not textured, untwisted, measuring 1 650 decitex or more but not more than 1 800 decitex, consisting of 110 filaments or more but not more than 120 filaments, each having a core of poly(ethylene terephthalate) and a skin of polyamide-6, containing by weight 75 % or more but not more than 77 % of poly(ethylene terephthalate), for use in the manufacture of roofings (1)	0 %	31.12.2016
ex 5402 47 00	20	Bicomponent monofilament yarn of not more than 30 dtex, consisting of:  — a poly(ethylene terephthalate) core, and  — an outer layer of a copolymer of poly(ethyleneterephthalate) and poly(ethyleneisophthalate), for use in the manufacture of filtration fabrics	0 %	31.12.2015
ex 5402 49 00	30	Yarn of a copolymer of glycollic acid with lactic acid, for the manufacture of surgical sutures (1)	0 %	31.12.2018
ex 5402 49 00	50	Non-textured filament yarn of poly(vinyl alcohol)	0 %	31.12.2018
ex 5402 49 00	70	Synthetic filament yarn, single, containing by weight 85 % or more of acrylonitrile, in the form of a wick containing 1 000 continuous filaments or more but not more than 25 000 continuous filaments, of a weight per metre of 0,12 g or more but not more than 3,75 g and of a length of 100 m or more, for the manufacture of carbon-fibre yarn (1)	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 5404 19 00	20	Monofilament of poly(1,4-dioxanone)	0 %	31.12.2018
ex 5404 19 00	30	Unsterilised monofilament of a copolymer of 1,3-dioxan-2-one with 1,4-dioxan-2,5-dione, for the manufacture of surgical sutures (1)	0 %	31.12.2014
ex 5404 19 00	50	Monofilaments of polyester or poly(butylene terephthalate), with cross-sectional dimension of 0,5 mm or more but not more than 1 mm, for use in the manufacture of zippers	0 %	31.12.2018
ex 5404 90 90	20	Strip of polyimide	0 %	31.12.2018
ex 5407 10 00	10	Textile fabric, consisting of warp filament yarns of polyamide-6,6 and weft filament yarns of polyamide-6,6, polyurethane and a copolymer of terephthalic acid, <i>p</i> -phenylenediamine and 3,4'-oxybis (phenyleneamine)	0 %	31.12.2017
ex 5503 11 00 ex 5601 30 00	10 40	Synthetic staple fibres of a copolymer of terephthalic acid, <i>p</i> -phenylenediamine and 3,4'-oxybis(phenyleneamine), of a length of not more than 7 mm	0 %	31.12.2018
ex 5503 40 00	10	Hollow polypropylene staple fibres:  — measuring 6 decitex or more but not more than 10 decitex,  — of a strength of 3,5 cN/dtex or more  — of a diameter of 30 µm or more for use in the manufacture of napkins and napkin liners for babies and other sanitary products  (1)	0 %	31.12.2016
ex 5503 90 00 ex 5506 90 00 ex 5601 30 00	20 10 10	Poly(vinyl alcohol) fibres, whether or not acetalized	0 %	31.12.2018
ex 5603 11 10 ex 5603 11 90 ex 5603 12 10 ex 5603 12 90 ex 5603 91 10 ex 5603 91 90 ex 5603 92 10 ex 5603 92 90	10 10 10 10 10 10 10	Poly(vinyl alcohol) non-wovens, in the piece or cut into rectangles:  — of a thickness of 200µm or more but not more than 280µm and  — of a weight of 20g/m² or more but not more than 50g/m²	0 %	31.12.2018
ex 5603 11 10 ex 5603 11 90	20 20	Non-wovens, not weighing more than $20~g/m^2$ , containing spunbonded and meltblown filaments put together in a sandwich way with the two outer layers containing fine endless filaments (not less than $10~\mu m$ but not more than $20~\mu m$ in diameter) and the inner layer containing super-fine endless filaments (not less than $1~\mu m$ but not more than $5~\mu m$ in diameter), for the manufacture of napkins and napkin liners for babies and similar sanitary napkins $^{(1)}$	0 %	31.12.2017
ex 5603 12 90 ex 5603 13 90 ex 5603 14 90 ex 5603 92 90 ex 5603 93 90 ex 5603 94 90	30 30 10 60 40 30	Non-wovens of aromatic polyamide fibres obtained by polycondensation of <i>m</i> -phenylenediamine and isophthalic acid, in the piece or cut into rectangles	0 %	31.12.2018
ex 5603 12 90	50	Non-woven:  — weighing 30 g/m² or more, but not more than 60 g/m²,  — containing fibres of polypropylene or of polypropylene and polyethylene,  — whether or not printed, with:  — on one side, 65 % of the total surface area having circular bobbles of 4mm in diameter, consisting of anchored, elevated un-bonded curly fibres, suitable for the engagement of extruded hook materials, and the remaining 35 % of the surface area being bonded,  — and on other side a smooth untextured surface,	0 %	31.12.2017

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		for use in the manufacture of napkins and napkin liners for babies and similar sanitary articles		
ex 5603 12 90 ex 5603 13 90	60 60	Non-woven of spunbonded polyethylene, of a weight of more than 60 g/m² but not more than 80 g/m² and an air resistance (Gurley) of 8 s or more but not more than 36 s (as determined by the ISO 5636/5 method)	0 %	31.12.2018
ex 5603 12 90 ex 5603 13 90 ex 5603 92 90 ex 5603 93 90	70 70 40 10	Non-wovens of polypropylene,  — with a melt blown layer, laminated on each side with spunbonded filaments of polypropylene,  — with a weight of not more than 150 g/m²,  — in the piece or simply cut into squares or rectangles, and  — not impregnated	0 %	31.12.2018
ex 5603 13 10 ex 5603 14 10	10 10	Electrically nonconductive nonwovens, consisting of a central film of poly(ethylene terephthalate) laminated on each side with unidirectionally aligned fibres of poly(ethylene terephthalate), coated on both sides with high grade temperature resistant electrical nonconductive resin, weighing 147 g/m² or more but not more than 265 g/m², with non-isotropic tensile strength on both directions, to be used as electrical insulation material	0 %	31.12.2018
ex 5603 13 10	20	Non-woven of spunbonded polyethylene, with a coating, — of a weight of more than 80 g/m² but not more than 105 g/m² and — an air resistance (Gurley) of 8 seconds or more but not more than 75 seconds (as determined by the ISO 5636/5 method)	0 %	31.12.2015
ex 5603 14 90	40	Non-wovens, consisting of poly(ethylene terephthlate) spun bonded media:  — of weight of 160 g/m² or more but not more than 300 g/m²,  — whether or not laminated on one side with a membrane or a membrane and aluminium  of a kind used for the manufacture of industrial filters	0 %	31.12.2018
ex 5603 92 90 ex 5603 93 90	20 20	Non-wovens consisting of a meltblown central layer of a thermoplastic elastomer laminated on each side with spunbonded filaments of polypropylene	0 %	31.12.2018
ex 5603 92 90 ex 5603 94 90	70 40	Non-wovens, consisting of multiple layers of a mixture of meltblown fibres and staple fibres of polypropylene and polyester, whether or not laminated on one side or on both sides with spunbonded filaments of polypropylene	0 %	31.12.2018
ex 5603 92 90 ex 5603 93 90	80 50	Non-woven polyolefin fabric, consisting of an elastomeric layer, laminated on each side with polyolefin filaments:  — a weight of 25 g/m² or more but not more than 150 g/m²,  — in the piece or simply cut into squares or rectangles,  — not impregnated,  — with cross-directional or machine-directional stretch properties for use in the manufacture of infant/child care products	0 %	31.12.2016
ex 5603 94 90	20	Acrylic fibre rods, having a length of not more than 50 cm, for the manufacture of pen tips (1)	0 %	31.12.2018
ex 5607 50 90	10	Unsterilised twine of poly(glycolic acid) or of poly(glycolic acid) and its copolymers with lactic acid, plaited or braided, with an inner core, for the manufacture of surgical sutures (1)	0 %	31.12.2014
ex 5803 00 10	91	Gauze of cotton, of a width of less than 1 500 mm	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 5903 10 90 ex 5903 20 90 ex 5903 90 99	10 10 20	Knitted or woven fabrics, coated or covered on one side with artificial plastic material in which are embedded microspheres	0 %	31.12.2018
ex 5906 99 90	10	Rubberised textile fabric, consisting of warp yarns of polyamide-6,6 and weft yarns of polyamide-6,6, polyurethane and a copolymer of terephthalic acid, <i>p</i> -phenylenediamine and 3,4'-oxybis(phenyleneamine)	0 %	31.12.2018
ex 5907 00 00	10	Textile fabrics, coated with adhesive in which are embedded spheres of a diameter of not more than 150 $\mu m$	0 %	31.12.2016
ex 5911 10 00	10	Needle-punched synthetic-fibre felts, not containing polyester, whether or not containing catalytic particles entrapped within the synthetic fibres, coated or covered on one side with polytetrafluoroethylene film, for the manufacture of filtration products (1)	0 %	31.12.2018
ex 5911 90 90 ex 8421 99 00	30 92	Parts of equipment for the purification of water by reverse osmosis, consisting essentially of plastic-based membranes, supported internally by woven or non-woven textile materials which are wound round a perforated tube, and enclosed in a cylindrical plastic casing of a wall-thickness of not more than 4 mm, whether or not housed in a cylinder of a wall-thickness of 5 mm or more	0 %	31.12.2018
ex 5911 90 90	40	Multi-layered non-woven polyester polishing pads, impregnated with polyurethane	0 %	31.12.2014
ex 6813 89 00	10	Friction material, of a thickness of less than 20 mm, not mounted, for the manufacture of friction components of a kind used in automatic transmissions and clutches (1)	0 %	31.12.2018
ex 6814 10 00	10	Agglomerated mica with a thickness of not more than 0,15 mm, on rolls, whether or not calcined, whether or not reinforced with aramid fibres, for use in the manufacture of insulation products for high voltage applications	0 %	31.12.2018
ex 6903 90 90	20	Silicon carbide reactor tubes and holders, of a kind used for insertion into diffusion and oxidation furnaces for production of semiconductor materials	0 %	31.12.2018
ex 6909 19 00	15	Ceramic ring with rectangular transversal section having an external diameter of 19 mm or more (+ 0,00 mm/- 0,10 mm) but not more than 29 mm (+ 0,00 mm/- 0,20 mm), an internal diameter of 10 mm or more (+ 0,00 mm/- 0,20 mm) but not more than 19 mm (+ 0,00 mm/- 0,30 mm), a thickness variable from 2 mm (± 0,10 mm) to 3,70 mm (± 0,20 mm) and heat resistance 240 °C or more, containing by weight: — 90 % (± 1,5 %) of aluminium oxide — 7 % (± 1 %) of titanium oxide	0 %	31.12.2017
ex 6909 19 00	20	Silicon nitride (Si <sub>3</sub> N <sub>4</sub> ) rollers or balls	0 %	31.12.2015
ex 6909 19 00	30	Supports for catalysts, consisting of porous cordierite or mullite ceramic pieces, of an overall volume of not more than 65 l, having, per cm <sup>2</sup> of the cross-section, not less than one continuous channel which may be open at both ends or stopped at one end	0 %	31.12.2018
ex 6909 19 00 ex 6914 90 00	50 20	Ceramic articles made of continuous filaments of ceramic oxides, containing by weight:  — 2 % or more of diboron trioxide,  — 28 % or less of silicon dioxide and  — 60 % or more of dialuminium trioxide	0 %	31.12.2018
ex 6909 19 00	60	Supports for catalysts, consisting of porous ceramic pieces, of a blend of silicon carbide and silicon, with a hardness of less than 9 on the Mohs scale, with a total volume of not more than 65 litres, having, per cm² of the surface of the cross section one or more closed channels at the tail end	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 6909 19 00	70	Supports for catalysts or filters, consisting of porous ceramics made primarily from oxides of aluminium and titanium; with a total volume of not more than 65 litres and at least one duct (open on one or both ends) per cm <sup>2</sup> of cross section	0 %	31.12.2018
ex 6909 19 00	80	Ceramic heat sinks, containing by weight:  — 66 % or more of silicon carbide,  — 15 % or more of aluminium oxide for maintaining the operating temperature of transistors, diodes and integrated circuits in products of headings 8521 or 8528  (1)	0 %	31.12.2016
ex 6914 90 00	30	Ceramic microspheres, transparent, obtained from silicon dioxide and zirconium dioxide, of a diameter of more than 125 $\mu m$	0 %	31.12.2018
ex 7005 10 30	10	Float glass:  — of a thickness of 4,0 mm or more but not more than 4,2 mm,  — with a light transmission of 91 % or more measured using a D-type light source,  — coated on one surface with a fluorine doped tin dioxide reflective layer	0 %	31.12.2017
ex 7006 00 90	70	Float glass:  — with a thickness of 1,7 mm or more but not more than 1,9 mm,  — with light transmission of 91 % or more, measured with a D-type light source,  — coated on one side with fluorine-doped tin dioxide as a reflecting layer,  — with worked edges	0 %	31.12.2016
ex 7007 19 20	10	Glass plate of a diagonal size of 81,28 cm (± 1,5 cm) or more, but not more than 185,42 cm (± 1,5 cm), consisting of tempered glass; provided either with a mesh film and a near-infrared absorbing film or a sputtered conductive layer, with optional additional anti-reflex layer on one or both sides, for use in the manufacture of products falling within heading 8528 (1)	0 %	31.12.2018
ex 7007 29 00	10	Glass plate of a diagonal size of $81,28~\rm cm~(\pm 1,5~\rm cm)$ or more, but not more than $185,42~\rm cm~(\pm 1,5~\rm cm)$ , consisting of 2 sandwich plates laminated together; provided either with a mesh film and a near-infrared absorbing film or a sputtered conductive layer, with optional additional anti-reflex layer on one or both sides	0 %	31.12.2018
ex 7009 10 00	10	Electro-cromic auto-dimming glass for motor vehicle mirrors:  — whether or not equipped with plastic backing plate,  — whether or not equipped with a heating element,  — whether or not equipped with Blind Spot Module (BSM) display	0 %	31.12.2017
ex 7009 91 00	10	Unframed glass mirrors with:  — a length of 1516 mm (± 1 mm);  — a width of 553 mm (± 1 mm);  — a thickness of 3 mm (± 0,1 mm);  — the back of the mirror covered with protective polyethylene (PE) film, with a thickness of 0,11 mm or more but not more than 0,13 mm;  — a lead content of not more than 90 mg/kg and  — a corrosion resistance of 72 hours or more according to ISO 9227 salt spray test	0 %	31.12.2015
7011 20 00		Glass envelopes (including bulbs and tubes), open, and glass parts thereof, without fittings, for cathode ray tubes	0 %	31.12.2018
ex 7014 00 00	10	Optical elements of glass (other than those of heading 7015), not optically worked, other than signalling glassware	0 %	31.12.2018
ex 7019 12 00 ex 7019 12 00	01 21	Rovings, measuring 2 600 tex or more but not more than 3 300 tex and of a loss on ignition of 4 % or more but not more than 8 % by weight (as determined by the ASTM D 2584-94 method)	0 %	31.12.2018
ex 7019 12 00 ex 7019 12 00	02 22	Rovings, measuring 650 tex or more but not more than 2 500 tex, coated with a layer of polyurethane whether or not mixed with other materials	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 7019 12 00 ex 7019 12 00	03 23	Rovings, measuring 392 tex or more but not more than 2 884 tex, coated with a layer of an acrylic copolymer	0 %	31.12.2018
ex 7019 12 00 ex 7019 12 00	05 25	Rovings ranging from 1 980 to 2 033 tex, composed of continuous glass filaments of 9 $\mu m$ (± 0,5 $\mu m$ )	0 %	31.12.2017
ex 7019 19 10	10	Yarn of 33 tex or a multiple thereof ( $\pm$ 7,5 %), obtained from continuous spun-glass filaments of a nominal diameter of 3,5 $\mu$ m or of 4,5 $\mu$ m, in which filaments of a diameter of 3 $\mu$ m or more but not more than 5,2 $\mu$ m predominate, other than those treated so as to improve their adhesion to elastomers	0 %	31.12.2018
ex 7019 19 10	15	S-glass yarn of 33 tex or a multiple of 33 tex ( $\pm$ 13 %) made from continuous spunglass filaments with fibres of a diameter of 9 $\mu$ m (- 1 $\mu$ m / + 1,5 $\mu$ m)	0 %	31.12.2017
ex 7019 19 10	20	Yarn of 10,3 tex or more but not more than 11,9 tex, obtained from continuous spun-glass filaments, in which filaments of a diameter of 4,83 $\mu$ m or more but not more than 5,83 $\mu$ m predominate	0 %	31.12.2015
ex 7019 19 10	25	Yarn of 5,1 tex or more but not more than 6,0 tex, obtained from continuous spunglass filaments, in which filaments of a diameter of 4,83 $\mu m$ or more but not more than 5,83 $\mu m$ predominate	0 %	31.12.2015
ex 7019 19 10	30	Yarn of E-glass of 22 tex ( $\pm$ 1,6 tex), obtained from continuous spun-glass filaments of a nominal diameter of 7 $\mu$ m, in which filaments of a diameter of 6,35 $\mu$ m or more but not more than 7,61 $\mu$ m predominate	0 %	31.12.2014
ex 7019 19 10	50	Yarn of 11 tex or a multiple thereof ( $\pm$ 7,5 %), obtained from continuous spun-glass filaments, containing 93 percent by weight or more of silicon dioxide, of a nominal diameter of 6 $\mu$ m or 9 $\mu$ m, other than those treated	0 %	31.12.2016
ex 7019 19 10	55	Glass cord impregnated with rubber or plastic, obtained from K- or U-glass filaments, made up of:  — 9 % or more but not more than 16 % of magnesium oxide,  — 19 % or more but not more than 25 % of aluminium oxide,  — 0 % or more but not more than 2 % of boron oxide,  — without calcium oxide, coated with a latex comprising at least a resorcinol- formaldehyde resin and chlorosulphonated polyethylene	0 %	31.12.2014
ex 7019 19 10 ex 7019 90 00	60 30	High modulus glass cord (K) impregnated with rubber, obtained from twisted high modulus glass filament yarns, coated with a latex comprising a resorcinol-formaldehyde resin with or without vinylpyridine and/or hydrogenated acrylonitrile-butadiene rubber (HNBR)	0 %	31.12.2018
ex 7019 19 10 ex 7019 90 00	70 20	Glass cord impregnated with rubber or plastic, obtained from twisted glass filament yarns, coated with a latex comprising at least a resorcinol-formaldehyde-vinylpyridine resin and an acrylonitrile-butadiene rubber (NBR)	0 %	31.12.2018
ex 7019 19 10 ex 7019 90 00	80 40	Glass cord impregnated with rubber or plastic, obtained from twisted glass filament yarns, coated with a latex comprising at least a resorcinol-formaldehyde resin and chlorosulphonated polyethylene	0 %	31.12.2018
ex 7019 39 00	50	Non-woven product of non-textile glass fibre, for the manufacture of air filters or catalysts (1)	0 %	31.12.2016
ex 7019 40 00	10	Woven fabrics of rovings, impregnated with epoxy resin, with a coefficient of thermal expansion between 30°C and 120°C (measured according to IPC-TM-650) of:  — 10ppm per°C or more but not more than 12ppm per°C in the length and width, and	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		— 20ppm per°C or more but not more than 30ppm per°C in the thickness, with a glass transition temperature of 152°C or more but not more than 153°C (measured according IPC-TM-650)		
ex 7019 90 00	10	Non-textile glass fibres in which fibres of a diameter of less than 4,6 $\mu m$ predominate	0 %	31.12.2018
ex 7020 00 10 ex 7616 99 90	10 77	Television pedestal stands with or without bracket for fixation to and stabilization of television cabinet case/body	0 %	31.12.2016
ex 7201 10 11	10	Pig iron ingots with a length of not more than 350 mm, a width of not more than 150 mm, a height of not more than 150 mm	0 %	31.12.2016
ex 7201 10 30	10	Pig iron ingots with a length of not more than 350 mm, a width of not more than 150 mm, a height of not more than 150 mm, containing by weight not more than 1 % of silicon	0 %	31.12.2016
7202 50 00		Ferro-silico-chromium	0 %	31.12.2018
ex 7202 99 80	10	Ferro-dysprosium, containing by weight:  — 78 % or more of dysprosium, and  — 18 % or more but not more than 22 % of iron	0 %	31.12.2015
ex 7318 14 99 ex 7318 14 99	20 29	Rock bolt:  — being a self-tapping screw,  — with a length of more than 300 mm, of a kind used for support of mines	0 %	31.12.2016
ex 7320 90 10	91	Flat spiral spring of tempered steel, with:  — a thickness of 2,67 mm or more, but not more than 4,11 mm,  — a width of 12,57 mm or more, but not more than 16,01 mm,  — a torque of 18,05 Nm or more, but not more than 73,5 Nm  — an angle between the free position and the nominal position in exercise of 76° or more, but not more than 218° for use in the manufacture of tensioners for power transmission belts, for internal combustion engines  (1)	0 %	31.12.2018
ex 7325 99 10	20	Anchor head of hot dipped galvanized ductile cast iron of the kind used in the production of earth anchors	0 %	31.12.2014
ex 7326 20 00	20	Metal fleece, consisting of a mass of stainless steel wires of diameters of 0,017 mm or more but not more than 0,070 mm, compacted by sintering and rolling	0 %	31.12.2016
ex 7410 11 00 ex 8507 90 80 ex 8545 90 90	10 60 30	Roll of laminate foil of graphite and copper, with:  — a width of 610 mm or more but not more than 620 mm, and  — a diameter of 690 mm or more but not more than 710 mm, for use in the manufacture of lithium-ion electric vehicle batteries  (1)	0 %	31.12.2016
ex 7410 21 00	10	Sheet or plate of polytetrafluoroethylene, containing aluminium oxide or titanium dioxide as filler or reinforced with glass-fibre fabric, covered on both sides with copper foil	0 %	31.12.2018
ex 7410 21 00	30	Film of polyimide, whether or not containing epoxide resin and/or glass fibre, covered on one side or on both sides with a copper foil	0 %	31.12.2018
ex 7410 21 00	40	Sheet or plates:  — consisting of at least a central layer of paper or one central sheet of any type of nonwoven fibre, laminated on each side with glass-fibre fabric and impregnated with epoxide resin, or  — consisting of multiple layers of paper, impregnated with phenolic resin, coated on one or both sides with a copper film with a maximum thickness of 0,15	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 7410 21 00	50	Plates:  — consisting of at least one layer of fibreglass fabric impregnated with epoxide resin,  — covered on one or both sides with copper foilwith a thickness of not more than 0,15mm and  — with a dielectric constant (DK) of less than 3,9 and a loss factor (Df) of less than 0,015 at a measuring frequency of 10GHz, as measured according to IPC-TM-650	0 %	31.12.2018
ex 7410 21 00	60	Plates, rolls and sheets of synthetic or artificial resin:  — with a maximum thickness of not more than 25μm,  — coated on both sides with a copper film with a maximum thickness of 0,15mm,  — with a minimum capacitance of 1,09pF/mm², for use in the manufacture of circuit boards	0 %	31.12.2018
ex 7410 21 00	70	Plates, rolls or sheets:  — with at least one layer of woven glass fibre, impregnated with a fire-retardant artificial or synthetic resin with a glass transition temperature (Tg) of more than 170 °C (according to IPC-TM-650, method 2.4.25),  — coated on one or both sides with a copper film with a thickness of not more than 0,15 mm, for use in the manufacture of circuit boards	0 %	31.12.2018
ex 7419 99 90 ex 7616 99 90	91 60	Disc (target) with deposition material, consisting of molybdenum silicide:  — containing 1mg/kg or less of sodium and  — mounted on a copper or aluminium support	0 %	31.12.2018
7601 20 20		Slabs and billets of unwrought aluminium alloys	4 %	31.12.2018
ex 7601 20 20	10	Slabs and billets of aluminium alloy containing lithium	0 %	31.12.2017
ex 7604 21 00 ex 7604 29 90	10 30	Profiles made of aluminium alloy conforming to EN standard AW-6063 T5  — anodized  — whether or not lacquered  — with a wall thickness of 0,5 mm (± 1,2 %) or more but not more than 0,8 mm (± 1,2 %)  for use in the manufacture of goods of heading 8302	0 %	31.12.2018
ex 7604 29 10 ex 7606 12 99	10 20	Sheets and bars of aluminium-lithium alloys	0 %	31.12.2015
ex 7605 19 00	10	Not alloyed aluminium wire, of a diameter of 2 mm or more but not more than 6 mm, covered with a layer of copper of a thickness of 0,032 mm or more but not more than 0,117 mm	0 %	31.12.2018
ex 7606 12 92 ex 7607 11 90	20 20	Aluminium and magnesium alloy strip:  — in rolls,  — of a thickness of 0,14 mm or more but not more than 0,40 mm,  — a width of 12,5 mm or more but not more than 359 mm,  — a tensile strength of 285 N/mm² or more, and  — an elongation at break of 1 % or more, and containing by weight:  — 93,3 % or more of aluminium,  — 2,2 % or more but not more than 5 % of magnesium, and  — not more than 1,8 % of other elements	0 %	31.12.2017

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 7607 11 90	10	Plain aluminium foil with the following parameters:  — an aluminium content of 99,98 % or more  — a thickness of 0,070 mm or more but not more than 0,125 mm  — with a cubic texture of a kind used for high voltage etching	0 %	31.12.2016
ex 7607 11 90	40	Aluminium foil in rolls:  — having a purity of 99,99 % by weight,  — of a thickness of 0,021 mm or more but not more than 0,2 mm,  — with a width of 500 mm,  — with a surface oxide layer by 3 to 4 nm thick,  — and with a cubic texture of more than 95 %	0 %	31.12.2016
ex 7607 19 90 ex 8507 90 80	10 80	Sheet in the form of a roll consisting of a laminate of lithium and manganese bonded to aluminium, with:  — a width of 595 mm or more but not more than 605 mm, and  — a diameter of 690 mm or more but not more than 710 mm, for use in the manufacture of cathodes for lithium-ion electric vehicle batteries	0 %	31.12.2016
ex 7607 20 90	10	Aluminium laminated film of a total thickness of not more than 0,123 mm, comprising of a layer of aluminium of a thickness of not more than 0,040 mm, polyamide and polypropylene base films, and a protective coating against corrosion by hydrofluoric acid, for use in the manufacture of lithium polymer batteries	0 %	31.12.2017
ex 7607 20 90	20	<ul> <li>Lubricating entry sheet of a total thickness of not more than 350 μm, comprising of:</li> <li>— a layer of aluminium foil of a thickness of 70 μm or more but not more than 150 μm,</li> <li>— a water soluble lubricant of a thickness of 20 μm or more but not more than 200 μm and solid at room temperature</li> </ul>	0 %	31.12.2015
ex 7613 00 00	20	Aluminium container, seamless, for compressed natural gas or compressed hydrogen, wholly embedded in an overwrap of epoxy-carbon fibres composite, of a storage capacity of 172 l ( $\pm$ 10 %) and an unfilled weight of not more than 64 kg	0 %	31.12.2018
ex 7616 99 90	15	Honeycomb aluminium blocks of the type used in the manufacture of aircraft parts	0 %	31.12.2018
ex 7616 99 90 ex 8482 80 00 ex 8803 30 00	70 10 40	Connecting components for use in the production of helicopter tail rotor shafts	0 %	31.12.2016
ex 7616 99 90	75	Parts in the shape of a rectangular frame:  — of painted aluminium,  — with a length of 1 011 mm or more but not more than 1 500 mm,  — with a width of 622 mm or more but not more than 900 mm,  — with a thickness of 0,6 mm (± 0,1 mm),  of a kind used in the manufacture of TV sets	0 %	31.12.2017
ex 8102 10 00	10	Molybdenum powder with:  — a purity by weight of 99 % or more and  — a particle size of 1,0 μm or more, but not more than 5,0 μm	0 %	31.12.2017
8104 11 00		Unwrought magnesium, containing at least 99,8 % by weight of magnesium	0 %	31.12.2018
ex 8104 30 00	30	Magnesium powder:  — of purity by weight of 99,5 % or more,  — with a particle size of 0,2 mm or more but not more than 0,8 mm	0 %	31.12.2015
ex 8104 90 00	10	Ground and polished magnesium sheets, of dimensions not more than $1500 \text{ mm} \times 2000 \text{ mm}$ , coated on one side with an epoxy resin insensitive to light	0 %	31.12.2018
ex 8105 90 00	10	Bars or wires made of cobalt alloy containing, by weight:	0 %	31.12.2017

25 % (42 %) color.	CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 8108 20 00   30   Titanium powder of which 90 % by weight or more passes through a sieve with an			- 25 % (± 1 %) nickel, - 19 % (± 1 %) chromium and - 7 % (± 2 %) iron conforming to the material specifications AMS 5842, of a kind used in the		
aperture of 0,224 mm	ex 8108 20 00	10	Titanium sponge	0 %	31.12.2018
1 % or more but not more than 2 % of aluminium	ex 8108 20 00	30		0 %	31.12.2018
cx 8108 90 30   20   Bars, rods and wire of alloy of titanium and aluminium, containing by weight 1 % or more but not more than 2 % of aluminium, for use in the manufacture of silencers and exhaust pipes of subheadings 8708 92 or 8714 10 00   31.12.2015	ex 8108 30 00	10		0 %	31.12.2018
cx 8108 90 30   30   Titanium-aluminium-vanadium alloy (TiAl6V4) wire, complying with AMS standards 4928 and 4967   31.12.2015	ex 8108 90 30	10	Titanium alloy rods complying with standard EN 2002-1, EN 4267 or DIN 65040	0 %	31.12.2014
AMS standards 4928 and 4967   Wire of an titanium alloy containing by weight:	ex 8108 90 30	20	or more but not more than 2 % of aluminium, for use in the manufacture of silencers and exhaust pipes of subheadings 8708 92 or 8714 10 00	0 %	31.12.2017
= 22 % (± 3 %) of vanadium and	ex 8108 90 30	30		0 %	31.12.2015
than 2 % of aluminium, in sheets or rolls, of a thickness of 0.49 mm or more but not more than 3.1 mm, of a width of 1 000 mm or more but not more than 1 254 mm, for the manufacture of goods of subheading 8714 10 00 (1)  8 Alloy of titanium and silicon, containing by weight 0.15 % or more but not more than 0.60 % of silicon, in sheets or rolls, for use in the manufacture of:  — exhaust systems for internal combustion engines or — tubes and pipes of subheading 8108 90 60  8 Plates, sheets, strips and foils of an alloy of titanium, copper and niobium, containing by weight 0.8 % or more but not more than 1.2 % of copper and 0.4 % or more but not more than 0.6 % of niobium  8 ex 8108 90 50  9 Plates, sheets, strips and foils of an alloy of titanium, aluminium, silicon and niobium, containing by weight:  — 0.4 % or more but not more than 0.55 % of silicon and — 0.1 % or more but not more than 0.55 % of silicon and — 0.1 % or more but not more than 0.35 % of niobium  8 ex 8108 90 50  70 Strip of an alloy of titanium, containing by weight: — 1.5 % (± 1 %) of vanadium — 3 % (± 0.5 %) of chromium — 3 % (± 0.5 %) of aluminium  8 strips and foil of titanium alloy, containing by weight: — 0.3 % or more but not more than 0.7 % of aluminium and — 0.25 % or more but not more than 0.6 % of silicon  8 ex 8108 90 50  8 plates, sheets, strips and foil of non-alloyed titanium  9 cx 8108 90 50  9 Plates, sheets, strip and foil of non-alloyed titanium  9 cx 8108 90 90  10 Parts of spectacle frames and mountings, including bolts of the kind used for 0 %  11.12.2016	ex 8108 90 30	40	— 22 % (± 3 %) of vanadium and	0 %	31.12.2016
than 0,60 % of silicon, in sheets or rolls, for use in the manufacture of:  — exhaust systems for internal combustion engines or — tubes and pipes of subheading 8108 90 60  ex 8108 90 50  Plates, sheets, strips and foils of an alloy of titanium, copper and niobium, containing by weight 0,8 % or more but not more than 1,2 % of copper and 0,4 % or more but not more than 0,6 % of niobium  ex 8108 90 50  Plates, sheets, strips and foils of an alloy of titanium, aluminium, silicon and niobium, containing by weight: — 0,4 % or more but not more than 0,6 % of aluminium, — 0,35 % or more but not more than 0,55 % of silicon and — 0,1 % or more but not more than 0,3 % of niobium  ex 8108 90 50  Strip of an alloy of titanium, containing by weight: — 15 % (± 1 %) of vanadium — 3 % (± 0,5 %) of chromium — 3 % (± 0,5 %) of aluminium  ex 8108 90 50  Plates, sheets, strips and foil of titanium alloy, containing by weight: — 0,3 % or more but not more than 0,7 % of aluminium and — 0,25 % or more but not more than 0,6 % of silicon  ex 8108 90 50  Plates, sheets, strips and foil of non-alloyed titanium  9 % 31.12.2016  20 Parts of spectacle frames and mountings, including bolts of the kind used for 0 % 31.12.2016	ex 8108 90 50	10	than 2 % of aluminium, in sheets or rolls, of a thickness of 0,49 mm or more but not more than 3,1 mm, of a width of 1 000 mm or more but not more than 1 254 mm,	0 %	31.12.2018
containing by weight 0,8 % or more but not more than 1,2 % of copper and 0,4 % or more but not more than 0,6 % of niobium  ex 8108 90 50  60  Plates, sheets, strips and foils of an alloy of titanium, aluminium, silicon and niobium, containing by weight:  — 0,4 % or more but not more than 0,6 % of aluminium,  — 0,35 % or more but not more than 0,55 % of silicon and  — 0,1 % or more but not more than 0,3 % of niobium  ex 8108 90 50  70  Strip of an alloy of titanium, containing by weight:  — 15 % (± 1 %) of vanadium  — 3 % (± 0,5 %) of chromium  — 3 % (± 0,5 %) of tin and  — 3 % (± 0,5 %) of aluminium  ex 8108 90 50  75  Plates, sheets, strips and foil of titanium alloy, containing by weight:  — 0,3 % or more but not more than 0,7 % of aluminium and  — 0,25 % or more but not more than 0,6 % of silicon  ex 8108 90 50  85  Plates, sheets, strip and foil of non-alloyed titanium  ex 8108 90 90  20  Parts of spectacle frames and mountings, including bolts of the kind used for 0 %  31.12.2016	ex 8108 90 50	30	than 0,60 % of silicon, in sheets or rolls, for use in the manufacture of:  — exhaust systems for internal combustion engines or  — tubes and pipes of subheading 8108 90 60	0 %	31.12.2017
niobium, containing by weight:  - 0,4 % or more but not more than 0,6 % of aluminium, - 0,35 % or more but not more than 0,55 % of silicon and - 0,1 % or more but not more than 0,3 % of niobium  8 Strip of an alloy of titanium, containing by weight: - 15 % (± 1 %) of vanadium - 3 % (± 0,5 %) of chromium - 3 % (± 0,5 %) of tin and - 3 % (± 0,5 %) of faluminium  9 Plates, sheets, strips and foil of titanium alloy, containing by weight: - 0,3 % or more but not more than 0,7 % of aluminium and - 0,25 % or more but not more than 0,6 % of silicon  10 %  11.12.2016  12.2016  13.112.2016  13.112.2017  13.112.2017  14.11	ex 8108 90 50	50	containing by weight 0,8 % or more but not more than 1,2 % of copper and 0,4 %	0 %	31.12.2017
ex 8108 90 50  To Plates, sheets, strips and foil of titanium alloy, containing by weight:	ex 8108 90 50	60	niobium, containing by weight:  — 0,4 % or more but not more than 0,6 % of aluminium,  — 0,35 % or more but not more than 0,55 % of silicon and	0 %	31.12.2018
ex 8108 90 50 85 Plates, sheets, strip and foil of non-alloyed titanium 0 % 31.12.2017 ex 8108 90 90 20 Parts of spectacle frames and mountings, including bolts of the kind used for 0 % 31.12.2016	ex 8108 90 50	70	- 15 % (± 1 %) of vanadium - 3 % (± 0,5 %) of chromium - 3 % (± 0,5 %) of tin and	0 %	31.12.2016
ex 8108 90 90 20 Parts of spectacle frames and mountings, including bolts of the kind used for 0 % 31.12.2016	ex 8108 90 50	75	— 0,3 % or more but not more than 0,7 % of aluminium and	0 %	31.12.2016
	ex 8108 90 50	85	Plates, sheets, strip and foil of non-alloyed titanium	0 %	31.12.2017
				0 %	31.12.2016

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 8109 20 00	10	Non-alloy zirconium sponges or ingots, containing by weight more than 0,01 % of hafnium for use in the manufacture of tubes, bars or ingots enlarged by remelting for the chemical industry	0 %	31.12.2018
ex 8110 10 00	10	Antimony in the form of ingots	0 %	31.12.2018
ex 8112 99 30	10	Alloy of niobium (columbium) and titanium, in the form of bars and rods	0 %	31.12.2018
ex 8113 00 20	10	Cermet blocks containing by weight $60\%$ or more of aluminium and $5\%$ or more of boron carbide	0 %	31.12.2016
ex 8113 00 90	10	Carrier plate of aluminium silicon carbide (AlSiC-9) for electronic circuits	0 %	31.12.2017
ex 8207 30 10	10	Set of transfer and/or tandem press tools for cold-forming, pressing, drawing, cutting, punching, bending, calibrating, bordering and throating of metal sheets, for use in the manufacture of frame parts of motor vehicles	0 %	31.12.2017
ex 8301 60 00 ex 8413 91 00 ex 8419 90 85 ex 8438 90 00 ex 8468 90 00 ex 8476 90 00 ex 8479 90 80 ex 8481 90 00 ex 8503 00 99 ex 8515 90 00 ex 8531 90 85 ex 8536 90 85 ex 8543 90 00 ex 8708 91 99 ex 8708 99 97 ex 9031 90 85	10 20 20 10 10 10 87 20 45 20 20 96 50 10 30	Keypads, wholly of either silicone or polycarbonate, including printed keys with electrical contacting elements	0 %	31.12.2015
ex 8309 90 90	10	Aluminium can ends with so-called "ring pull" full aperture with a diameter of 136,5 mm ( $\pm$ 1 mm)	0 %	31.12.2018
ex 8401 30 00	20	Non-irradiated hexagonal fuel modules (elements) for use in nuclear reactors (1)	0 %	31.12.2018
ex 8405 90 00 ex 8708 21 10 ex 8708 21 90	10 10 10	Metal casing for automobile safety belt pre-tension gas generators	0 %	31.12.2014
ex 8407 33 00 ex 8407 90 80 ex 8407 90 90	10 10 10	Spark-ignition reciprocating or rotary internal combustion piston engines, having a cylinder capacity of not less than 300 cm³ and a power of not less than 6 kW but not exceeding 20,0 kW, for the manufacture of:  — self-propelled lawn mowers with a seat of subheading 8433 11 51, and hand-operated lawn mowers of heading 8433 11 90,  — tractors of subheading 8701 90 11, whose main function is that of a lawn mower,  — four stroke mowers with motor of a cylinder capacity of not less than 300 cc of subheading 8433 20 10 or  — snowploughs and snow blowers of subheading 8430 20	0 %	31.12.2017
ex 8407 90 10	10	Four-stroke petrol engines of a cylinder capacity of not more than 250 cm³ for use in the manufacture of lawnmowers of subheading 8433 11, mowers with motor of subheading 8433 20 10, rotovators of subheading 8432 29 50, garden shredders of subheading 8436 80 90 or scarifiers of subheading 8432 29 10 (1)	0 %	31.12.2016
ex 8407 90 90	20	Compact Liquid Petroleum Gas (LPG) Engine System, with:  — 6 cylinders,  — an output of 75 kW or more, but not more than 80 kW,  — inlet and exhaust valves modified to operate continuously in heavy duty	0 %	31.12.2015

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		applications, for use in the manufacture of vehicles of heading 8427		
ex 8408 90 41	20	Diesel engines of a power of not more than 15 kW, with 2 or 3 cylinders, for use in the manufacture of vehicle mounted temperature control systems (1)	0 %	31.12.2018
ex 8408 90 43	20	Diesel engines of a power of not more than 30 kW, with 4 cylinders, for use in the manufacture of vehicle mounted temperature control systems	0 %	31.12.2018
ex 8408 90 43 ex 8408 90 45 ex 8408 90 47	30 20 30	4 Cylinder, 4 cycle, liquid cooled, compression-ignition engine having:  — a capacity of not more than 3850 cm³, and  — a rated output of 15 kW or more but not more than 55 kW, for use in the manufacture of vehicles of heading 8427	0 %	31.12.2017
ex 8408 90 47	40	4 Cylinder, 4 cycle, liquid cooled, compression-ignition engine having:  — a capacity of not more than 3 850 cm³,  — a rated output of 55 kW or more but not more than 85 kW, for use in the manufacture of vehicles of heading 8427	0 %	31.12.2018
ex 8409 91 00 ex 8409 99 00	10 20	Exhaust manifold complying with standard DIN EN 13835, whether or not with turbine housing, with four inlet ports, for use in the manufacture of exhaust manifold that is turned, milled, drilled and/or processed by other means (1)	0 %	31.12.2016
ex 8409 99 00 ex 8479 90 80	10 85	Injectors with solenoid valve for optimised atomisation in the engine combustion chamber	0 %	31.12.2016
ex 8411 99 00	30	Wheel-shaped gas turbine component with blades, of a kind used in turbochargers:  — of a precision-cast nickel based alloy complying with standard DIN G-NiCr13Al16MoNb or DIN NiCo10W10Cr9AlTi or AMS AISI:686,  — with a heat-resistance of not more than 1 100 °C;  — with a diameter of 30 mm or more, but not more than 80 mm;  — with a height of 30 mm or more, but not more than 50 mm	0 %	31.12.2017
ex 8411 99 00	40	Spiral-shaped gas turbine turbocharger component:  — of a stainless alloy,  — with a heat-resistance of not more than 1 050 °C,  — with a diameter of 100 mm or more, but not more than 200 mm,  — with a height of 100 mm or more, but not more than 150 mm,  — whether or not with an engine exhaust manifold	0 %	31.12.2018
ex 8411 99 00	50	Actuator for a single-stage turbocharger:  — with a built-in conducting horn and connecting sleeve,  — of a stainless steel alloy,  — with conducting horns having an operating distance of 20 mm,  — with a length of not more than 350 mm,  — with a diameter of not more than 75 mm,  — with a height of not more than 50 mm	0 %	31.12.2018
ex 8413 70 35	20	Single phase centrifugal pump:  — discharging at least 400 cm³ fluid per minute,  — with a noise level limited to 6 dBA,  — with the inside diameter of the suction opening and discharge outlet of not more than 15 mm, and  — working at ambient temperatures down to -10°C	0 %	31.12.2015
ex 8414 30 81	50	Hermetic or semi-hermetic variable-speed electric scroll compressors, with a nominal power rating of 0,5 kW or more but not more than 10 kW, with a displacement volume of not more than 35 cm <sup>3</sup> , of the type used in refrigeration equipment	0 %	31.12.2014

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 8414 30 89	20	Vehicle air conditioning system part, consisting of an open shaft reciprocating compressor of a power of more than 0,4 kW but not more than 10 kW	0 %	31.12.2018
ex 8414 59 20	30	Axial fan:  — with an electric motor,  — of an output of not more than 125 W for use in the manufacture of computers	0 %	31.12.2018
ex 8414 59 20	40	Axial fan with an electric motor, of an output of not more than 2 W, for use in the manufacture of products of heading 8521 or 8528	0 %	31.12.2015
ex 8414 59 80 ex 8414 90 00	40 60	Cross-flow fan with:  — a height of 575 mm (± 1,0 mm) or more, but not more than 850 mm (± 1,0 mm),  — a diameter of 95mm (± 0,6 mm) or 102 mm (± 0,6 mm),  — an anti-static, anti-bacterial and heat-resistant, 30 % glass fibre reinforced plastic raw material that has a minimum temperature resistance of 70°C (±5°C), for use in the manufacture of indoor units of split-type air conditioning machines	0 %	31.12.2016
ex 8414 90 00	20	Aluminium pistons, for incorporation into compressors of air conditioning machines of motor vehicles (1)	0 %	31.12.2014
ex 8414 90 00	30	Pressure-regulating system, for incorporation into compressors of air conditioning machines of motor vehicles (1)	0 %	31.12.2018
ex 8414 90 00	40	Drive part, for compressors of air conditioning machines of motor vehicles (1)	0 %	31.12.2018
ex 8415 90 00	20	Evaporator made of aluminium for use in the manufacture of air conditioning machines for automobiles (1)	0 %	31.12.2016
ex 8418 99 10	50	Evaporator composed of aluminium fins and a copper coil of the kind used in refrigeration equipment	0 %	31.12.2014
ex 8418 99 10	60	Condenser composed of two concentric copper tubes of the kind used in refrigeration equipment	0 %	31.12.2014
ex 8421 99 00	91	Parts of equipment, for the purification of water by reverse osmosis, consisting of a bundle of hollow fibres of artificial plastic material with permeable walls, embedded in a block of artificial plastic material at one end and passing through a block of artificial plastic material at the other end, whether or not housed in a cylinder	0 %	31.12.2018
ex 8421 99 00	93	Components of separators for the separation or purification of gases from gas mixtures, consisting of a bundle of permeable hollow fibres enclosed within a container, whether or not perforated, of an overall length of 300 mm or more but not more than 3 700 mm and a diameter of not more than 500 mm	0 %	31.12.2018
ex 8422 30 00 ex 8479 89 97	10 30	Machines and apparatus, other than injection moulding machines, for the manufacture of ink-jet printer cartridges (1)	0 %	31.12.2018
ex 8424 90 00	30	Containers of poly(ethylene terephthalate), with a content of 50 ml or more but not more than 600 ml, equipped with a nozzle, of a kind used as a part of mechanical appliances for spraying liquids	0 %	31.12.2018
ex 8431 20 00	30	Drive axle assembly containing differential, reduction gears, crown wheel, drive shafts, wheel hubs, brakes and mast mounting arms for use in the manufacture of vehicles in heading 8427	0 %	31.12.2017
ex 8439 99 00	10	Suction-roll shells, produced by centrifugal casting, not drilled, in the form of alloy-	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 8467 99 00 ex 8536 50 11	10 35	steel tubes, of a length of 3 000 mm or more and an external diameter of 550 mm or more  Mechanical switches for connecting electrical circuits, with:  — a voltage of 14,4 V or more but not more than 42 V,  — an amperage of 10 A or more but not more than 42 A, for use in the manufacture of machines falling within heading 8467	0 %	31.12.2014
ex 8477 80 99	10	Machines for casting or for surface modification of plastic membranes of heading 3921	0 %	31.12.2018
ex 8479 89 97	40	Isobaric pressure exchanger with a flow rate of not more than 50 m³/h, whether or not with a booster pump	0 %	31.12.2014
ex 8479 89 97 ex 8479 90 80	50 80	Machinery, being components of a production line for the manufacture of lithium ion batteries for passenger electric motor vehicles, for the construction of such a production line	0 %	31.12.2015
ex 8481 30 91	91	Steel check (non-return) valves with:  — an opening pressure of not more than 800 kPa  — an external diameter not more than 37 mm	0 %	31.12.2014
ex 8481 80 59	10	Air control valve, consisting of a stepping motor and a valve pintle, for the regulation of idle air flow in fuel injection engines	0 %	31.12.2018
ex 8481 80 69	60	Four-way reversing valve for refrigerants, consisting of:  — a solenoid pilot valve  — a brass valve body including valve slider and copper connections with a working pressure up to 4,5 MPa	0 %	31.12.2017
ex 8481 80 79	20	Solenoid valve device that can withstand a pressure of 875 bar	0 %	31.12.2018
ex 8481 80 99	50	Service valve, consisting a combination of a two way valve on the liquid line and a three way valve on the gas line with:  — a minimum enclosing pressure of 30 kgf/cm²,  — a minimum withstanding pressure of 45 kgf/cm², for use in the manufacture of outdoor air conditioning units	0 %	31.12.2016
ex 8481 80 99	60	Four way valve, consisting of:  — a core plunger,  — a sealing plunger,  — a 220 V-240 V AC 50/60 Hz solenoid coil,  — a working pressure up to 4,3 MPa,  — a housing for directing the flow of the refrigerant, for use in the manufacture of outdoor air conditioning units  (1)	0 %	31.12.2016
ex 8483 30 38	30	Cylindrical bearing housing:  — of precision-cast grey cast iron complying with standard DIN EN 1561,  — with oil chambers,  — without bearings,  — with a diameter of 60 mm or more, but not more than 180 mm,  — with a height of 60 mm or more, but not more than 120 mm,  — whether or not with water chambers and connectors	0 %	31.12.2017
ex 8483 40 29	50	Gear set of cycloid gear type with:  — a rated torque of 50 Nm or more but not more than 7 000 Nm,  — standard ratios of 1:50 or more but not more than 1:270,  — lost motion of not more than one arc minute,  — an efficiency of more than 80 %,	0 %	31.12.2016

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		of a kind used in robot arms		
ex 8483 40 29	60	Epicyclic gearing, of a kind used in driving hand-held power tools with:  — a rated torque of 25 Nm or more, but not more than 70 Nm,  — standard gear ratios of 1:12.7 or more, but not more than 1:64.3	0 %	31.12.2018
ex 8483 40 51	20	Gear box, having a differential with wheel axle, for use in the manufacture of self-propelled lawnmowers with a seat of subheading 8433 11 51	0 %	31.12.2018
ex 8483 40 59	20	Hydrostatic speed changer, having a hydro pump and a differential with wheel axle, for use in the manufacture of self-propelled lawnmowers with a seat of subheading 8433 11 51 (1)	0 %	31.12.2018
ex 8483 40 90	80	Transmission gearbox, with:  — not more than 3 gears, — an automatic deceleration system and — a power reversal system, for use in the manufacture of goods of heading 8427	0 %	31.12.2015
ex 8501 10 99	54	DC motor, brushless, with an external diameter of not more than 25,4 mm, a rated speed of 2 260 (±15 %) rpm or 5 420 (±15 %) rpm, a supply voltage of 1,5 V or 3 V	0 %	31.12.2018
ex 8501 10 99	60	DC motor:  — with a rotor speed of 3 500 rpm or more but not more than 5 000 rpm loaded and not more than 6 500 rpm when not loaded  — with a power supply voltage of 100 V or more but not more than 240 V for use in the manufacture of electric fryers	0 %	31.12.2017
ex 8501 10 99	79	DC motor with brushes and an internal rotor with a three-phase winding, whether or not equipped with a worm, of a specified temperature range covering at least - $20 ^{\circ}\text{C}$ to + $70 ^{\circ}\text{C}$	0 %	31.12.2018
ex 8501 10 99	80	DC stepping motor, with:  — an angle of step of 7,5° (± 0,5°),  — a pull-out torque at 25 °C of 25 mNm or more,  — a pull-out pulse rate of 1 960 pps or more,  — a two-phase winding, and  — a rated voltage of 10,5 V or more, but not more than 16,0 V	0 %	31.12.2018
ex 8501 10 99	81	DC stepping motor, with an angle of step of 18 $^{\circ}$ or more, a holding torque of 0,5 mNm or more, a coupling bracket the exterior dimensions of which do not exceed 22 mm $\times$ 68 mm, a two phase winding and an output of not more than 5 W	0 %	31.12.2018
ex 8501 10 99	82	DC motor, brushless, with an external diameter of not more than 29 mm, a rated speed of 1 500 (±15 %) rpm or 6 800 (±15 %) rpm, a supply voltage of 2 V or 8 V	0 %	31.12.2014
ex 8501 31 00	30	DC motor, brushless, with a three-phase winding, an external diameter of 85 mm or more, but not more than 115 mm, a nominal torque of 2,23 Nm (± 1,0 Nm), of an output of more than 120 W but not more than 520 W, calculated with 1 550 rpm (± 350 rpm) at a supply voltage of 12 V equipped with electronic circuit with sensors using the Hall effect, for use with an electric power steering control module (power steering motor) (1)	0 %	31.12.2016
ex 8501 31 00	40	Permanently excited DC motor with  — a multiple-phase winding,  — an external diameter of 30 mm or more but not more than 80 mm,  — a rated speed of not more than 15 000 rpm,  — an output of 45 W or more but not more than 300 W and  — a supply voltage of 9 V or more but not more than 25 V	0 %	31.12.2014
ex 8501 31 00	45	DC motors, brushless, with:  — an external diameter of 90 mm or more, but not more than 110 mm,	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		<ul> <li>a rated speed of not more than 3 680 rpm,</li> <li>an output of 600 W or more but not more than 740 W at 2 300 rpm and at 80 °C,</li> <li>a supply voltage of 12 V,</li> <li>a torque of not more than 5,67 Nm,</li> <li>a rotor position sensor,</li> <li>an electronic star-point relay, and</li> <li>for use with an electric power steering control module</li> </ul>		
ex 8501 31 00	55	DC motor with commutator, with  — an external diameter of 27.5 mm or more, but not more than 45 mm,  — a rated speed of 11 000 rpm or more, but not more than 23 200 rpm,  — a rated supply voltage of 3.6 V or more, but not more than 230 V,  — an output power of not more than 529 W,  — a free load current of not more than 3.1 A,  — a maximum efficiency of 54 % or more, for driving hand-held power tools	0 %	31.12.2018
ex 8501 31 00	60	Brushless DC motor that can revolve counter clockwise (CCW), with:  — an input voltage of 264 V or more, but not more than 391 V,  — an external diameter of 81 mm (± 2,5 mm) or more, but not more than 150 mm (± 0,8 mm),  — an output power of not more than 125 W,  — E or B class winding insulation, for use in the manufacture of indoor or outdoor units of split-type air conditioning machines  (1)	0 %	31.12.2016
ex 8501 31 00	65	Fuel cell module containing at least polymer electrolyte membrane fuel cells in a housing with an integrated cooling system, for use in the manufacture of motor vehicle propulsion systems	0 %	31.12.2018
ex 8501 31 00	70	DC motors, brushless, with:  — an external diameter of 80 mm or more, but not more than 100 mm,  — a supply voltage of 12 V,  — an output at 20 °C of 300 W or more, but not more than 550 W,  — a torque 20 °C of 2,90 Nm or more, but not more than 5,30 Nm,  — a rated speed at 20 °C of 600 rpm or more, but not more than 1 200 rpm,  — equipped with the rotor angle position sensor of resolver type or Hall effect type,  of the kind used in power steering systems for cars	0 %	31.12.2017
ex 8501 33 00 ex 8501 40 80 ex 8501 53 50	30 50 10	Electric drive for motor vehicles, with an output of not more than 315 kW, with:  — an AC or DC motor whether or not with transmission,  — power electronics	0 %	31.12.2016
ex 8501 51 00 ex 8501 52 20	30 50	AC synchronous servo motor with resolver and brake for a maximum speed of not more than 6 000 rpm, with:  — an output of 340 W or more but not more than 7,4 kW,  — a flange of dimensions of not more than 180 mm × 180 mm, and  — a length from flange to extreme end of resolver of not more than 271 mm	0 %	31.12.2016
ex 8501 62 00	30	Fuel cell system  — consisting of at least phosphoric acid fuel cells,  — in a housing with integrated water management and gas treatment,  — for permanent, stationary energy supply	0 %	31.12.2017
ex 8503 00 91 ex 8503 00 99	31 32	Rotor, at the innerside provided with one or two magnetic rings whether or not incorporated in a steel ring	0 %	31.12.2018
ex 8503 00 99	31	Stamped collector of an electric motor, having an external diameter of not more than 16 mm	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 8503 00 99	33	Stator for brushless motor of electrical power steering with a roundness tolerance of 50 $\mu m$	0 %	31.12.2016
ex 8503 00 99	34	Rotor for brushless motor of electrical power steering with a roundness tolerance of 50 $\mu m$	0 %	31.12.2016
ex 8503 00 99	35	Transmitter resolver for brushless motors of electrical power steering	0 %	31.12.2014
ex 8503 00 99	40	Fuel cell membrane, in rolls or sheets, with a width of not more than 150 cm, of a kind used for manufacture of fuel cells in heading 8501	0 %	31.12.2017
ex 8504 31 80	20	Transformer for use in the manufacture of inverters in LCD modules	0 %	31.12.2017
ex 8504 31 80	30	Switching transformers, having a power handling capacity of not more than 1 kVA for use in the manufacture of static converters	0 %	31.12.2018
ex 8504 31 80	40	Electrical transformers:  — with a capacity of 1 kVA or less  — without plugs or cables, for internal use in the manufacture of set top boxes and TVs	0 %	31.12.2017
ex 8504 40 82	40	Printed circuit board equipped with a bridge rectifier circuit and other active and passive components:  — with two output connectors  — with two input connectors which are available and useable in parallel  — able to switch between bright and dimmed operation mode  — with an input voltage of 40 V (+ 25 % -15 %) or 42 V (+ 25 % -15 %) in bright operation mode, with an input voltage of 30 V (± 4 V) in dimmed operation mode, or  — with an input voltage of 230 V (+20 % -15 %) in bright operation mode, with an input voltage of 160 V (± 15 %) in dimmed operation mode, or  — with an input voltage of 120 V (15 % -35 %) in bright operation mode, with an input voltage of 60 V (± 20 %) in dimmed operation mode  — with an input current reaching 80 % of its nominal value within 20 ms  — with an input frequency of 45 Hz or more, but not more than 65 Hz for 42 V and 230 V, and 45-70 Hz for 120 V versions  — with an maximum inrush current overshoot of not more than 250 % of the input current  — with a period of the inrush current overshoot of not more than 100 ms  — with an input current undershoot of not less than 50 % of the input current  — with a period of the inrush current undershoot of not more than 20 ms  — with an output current reaching 90 % of its nominal pre-set value within 50 ms  — with an output current reaching zero within 30 ms after removal of the input voltage  — with an defined failure status in case of no-load or too-high load (end-of-life function)	0 %	31.12.2017
ex 8504 40 82	50	Rectifier in a housing with  — a rated power of not more than 250 W  — an input voltage of 90 V or more, but not more than 305 V  — a certified input frequency of 47 Hz or more, but not more than 440 Hz  — a constant current output of 350 mA or more, but not more than 15 A  — an inrush current of not more than 10 A  — an operating temperature range of -40 °C or more, but not more than +85 °C,  — suitable for driving of LED-illuminants	0 %	31.12.2017
ex 8504 40 90	20	Direct current to direct current converter	0 %	31.12.2018
ex 8504 40 90	30	Static converter comprising a power switch with insulated-gate bipolar transistors (IGBTs), contained in a housing, for use in the manufacture of microwave ovens of subheading 8516 50 00 $^{(1)}$	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 8504 40 90	40	Semiconductor power modules comprising:  — power transistors,  — integrated circuits,  — whether or not containing diodes and with or without thermistors,  — an operating voltage of not more than 600 V,  — not more than three electrical outputs each containing two power switches (whether MOSFET (Metal Oxide Semiconductor Field-Effect Transistor) or IGBT (Insulated Gate Bi-polar Transistors)) and internal drives, and  — a rms (root mean square) current rating of not more than 15,7 A	0 %	31.12.2018
ex 8504 40 90	50	Drive unit for industrial robot with:  — one or six 3-phase motor outputs with maximum 3 x 32 A,  — a main power input of 220 V AC or more, but not more than 480 V AC, or 280 V DC or more, but not more than 800 V DC  — a logic power input of 24 V DC,  — an EtherCat communication interface,  — and a dimension of 150 x 140 x 120 mm or more, but not more than 335 x 430 x 179 mm	0 %	31.12.2018
ex 8504 40 90	60	Transfer moulded semiconductor power module comprising:  — power transistors, — integrated circuits, — whether or not containing diodes and with or without thermistors, — a circuit configuration, — either containing a direct drive stage with an operating voltage of more than 600 V, — or containing a direct drive stage with an operating voltage of not more than 600 V and a rms current of more than 15,7 A, — or including one or more power factor correction modules	0 %	31.12.2018
ex 8504 50 95	20	Inductor with an inductance of not more than 62 mH	0 %	31.12.2018
ex 8504 50 95	40	Coil choke with:  — an inductance of 4,7 µH (± 20 %),  — a DC resistance of not more than 0,1 Ohms,  — an insulation resistance of 100 MOhms or more at 500 V (DC) for use in the manufacture of LCD and LED module power boards  (1)	0 %	31.12.2015
ex 8504 50 95	50	Solenoid coil with  — a power consumption of not more than 6 W,  — an insulation resistance of more than 100 M ohms, and  — an insert hole of 11,4 mm or more, but not more than 11,8 mm	0 %	31.12.2017
ex 8504 90 11	10	Ferrite cores, other than for deflection yokes	0 %	31.12.2018
ex 8505 11 00	31	Permanent magnet having a remanence of 455 mT (±15 mT)	0 %	31.12.2018
ex 8505 11 00	33	Permanent magnets consisting of an alloy of neodymium, iron and boron, either in the shape of a rounded rectangle with measurements of not more than 15 mm $\times$ 10 mm $\times$ 2 mm, or in the shape of a disc with a diameter of not more than 90mm, whether or not containing a hole in the centre	0 %	31.12.2018
ex 8505 11 00	35	Permanent magnets of an alloy of either neodymium, iron and boron, or samarium and cobalt coated having undergone inorganic passivation (inorganic coating) using zinc phosphate for the industrial manufacture of products in motor or sensory applications	0 %	31.12.2017
ex 8505 11 00	50	Bars specifically shaped, intended to become permanent magnets after magnetization, containing neodymium, iron and boron, with dimensions:  — a length of 15 mm or more but not more than 52 mm,  — a width of 5 mm or more but not more than 42 mm, of a kind to be used in the manufacture of electric servomotors for industrial automation	0 %	31.12.2017

Ex 8505 11 00 06 Rings, tubes, bushings or collars made from an alloy of neodynnium, iron and of organization of the control o		I			
boron, with  a diameter of not more than 45 mm, a height of not more than 45 mm, a height of not more than 45 mm, of a kind used in the manufacture of permanent magnets after magnetisation  70  Disc:  with a diameter of not more than 90 mm, whether or not containing a hole in the centre, consisting of an ailuty of neodynium, mor and boron, covered with nickel, that after magnetisation is intended to become permanent magnet, of a kind used in car brubspealers  of a kind used in car brubspealers  Articles in the form of a fatingule, square or rectangle, intended to become permanent magnets after magnetization, containing neodynium, iron and boron, a with dimensions.  a length of 15 mm or more but not more than 105 mm, a width of 5 mm or more but not more than 105 mm, a height of 3 mm or more but not more than 105 mm, a height of 3 mm or more but not more than 105 mm, a height of 15 mm or more but not more than 105 mm, a height of 3 mm or more but not more than 55 mm a length of 15 mm or more but not more than 55 mm a length of 15 mm or more but not more than 55 mm because the magnetization with a remanence between 350 mT and 470 mT  ex 8505 20 00  30  Electromagnetic clutch, for use in the manufacture of compressors of air conditioning machines of motor vehicles  ex 8505 50 90  10  Lithium iodine single cell battery the dimensions of which do not exceed 9 mm 0 % 31.12.2018  ex 8506 50 90  20  Lithium iodine single cell battery the dimensions of which do not exceed 9 mm 0 % 31.12.2018  ex 8507 50 90  30  Lithium-iodine or lithium-silver vanadium oxide single cell battery of dimensions of not more than 2.8 vm was a manufacture of products alling within heading 8517 vii  ex 8507 50 90  30  Cylindrical nickel-eadmium accumulator, with a length of 65.3 mm (±1,5 mm) and of not more than 28 mm × 45 mm × 15 mm and a capacity of not less than 1,05 Ah  1.2018  ex 8507 50 90  30  Cylindrical nickel-eadmium accumulator, with a length of 65.3 mm (±1,5 mm) and of a diameter of 14,5 mm (a mm), having a nominal copuration of 100	CN code	TARIC	Description	autonomous	foreseen for mandatory
- with a diameter of not more than 90 mm, - whether or not containing a hole in the centre, - consisting of an alloy of neodynnium, iron and boron, covered with nickel, that after magnetisation is intended to become permanent magnet, of a kind used in car loudspeakers - a length of 15 mm or more but not more than 105 mm, - a width of 5 mm or more but not more than 105 mm, - a width of 5 mm or more but not more than 105 mm, - a width of 5 mm or more but not more than 105 mm, - a length of 15 mm or more but not more than 105 mm, - a length of 15 mm or more but not more than 105 mm, - a length of 15 mm or more but not more than 105 mm, - a length of 15 mm or more but not more than 105 mm, - a length of 15 mm or more but not more than 105 mm, - a length of 15 mm or more but not more than 105 mm, - a length of 15 mm or more but not more than 105 mm, - a length of 15 mm or more but not more than 105 mm, - a length of 15 mm or more but not more than 105 mm, - a length of 15 mm or more but not more than 105 mm, - a length of 15 mm or more but not more than 105 mm, - a length of 15 mm or more but not more than 105 mm, - a length of 15 mm or more but not more than 105 mm, - a length of 15 mm or more but not more than 105 mm, - a length of 15 mm or more but not more than 105 mm, - a length of 15 mm or more but not more than 105 mm, - a length of 15 mm or more but not more than 105 mm, - a length of 15 mm or more but not more than 105 mm or more products falling within heading 8517.60  Ex 8506 50 90  20  Lithium-iodine single cell battery the dimensions of which do not exceed 9 mm or with a length of 100 mm or than 20 mm or with a length of 100 mm or than 20 mm or with a length of 100 mm or than 20 mm or with a length of 100 mm or than 20 mm or with a length of 100 mm or than 20 mm or with a length of 100 mm or than 100 mm or with high repencative alternative or products and a capacity of 1000 mAh or more, for use in the manufacture of passenger cars and light commercial vehicles employing high regenerative alternator cont	ex 8505 11 00	60	boron, with  — a diameter of not more than 45 mm,  — a height of not more than 45 mm,	0 %	31.12.2017
permanent magnets after magnetization, containing neodymium, iron and boron, with dimensions:  — a length of 15 mm or more but not more than 105 mm, — a width of 5 mm or more but not more than 105 mm, — a height of 3 mm or more but not more than 105 mm, — a height of 3 mm or more but not more than 105 mm, — a height of 3 mm or more but not more than 105 mm, — a height of 3 mm or more but not more than 105 mm, — a height of 3 mm or more but not more than 105 mm, — a height of 3 mm or more but not more than 55 mm  Articles of agglomerated ferrite in the shape of a disc with a diameter of not more than 120 mm, containing a hole in the centre intended to become permanent magnets after magnetization with a remanence between 50 mT and 470 mT  ex 8505 20 00 30 Electromagnetic clutch, for use in the manufacture of compressors of air conditioning machines of motor vehicles  of conditioning machines of motor vehicles of products falling within heading 8517 (0)  of conditioning machines of motor vehicles  of conditioning machines of motor vehicles of products falling within heading 8517 (0)  of conditioning machines of motor or dan 2.8 V  Unit consisting of not more than 2.8 this machines of the conditioning machines of the machines of the machines of the machines of the more than 100 more than 100 m	ex 8505 11 00	70	<ul> <li>— with a diameter of not more than 90 mm,</li> <li>— whether or not containing a hole in the centre,</li> <li>— consisting of an alloy of neodymium, iron and boron, covered with nickel, that after magnetisation is intended to become permanent magnet,</li> </ul>	0 %	31.12.2018
than 120 mm, containing a hole in the centre intended to become permanent magnets after magnetization with a remanence between 350 mT and 470 mT  Electromagnetic clutch, for use in the manufacture of compressors of air conditioning machines of motor vehicles  ex 8505 90 20 91 Solenoid with a plunger, operating at a nominal supply voltage of 24 V at a nominal DC of 0,08 A, for use in the manufacture of products falling within heading 8517 (1)  ex 8506 50 90 10 Lithium iodine single cell battery the dimensions of which do not exceed 9 mm × 23 mm × 45 mm and a voltage of not more than 2,8 V  ex 8506 50 90 20 Unit consisting of not more than 2 lithium batteries embedded in a socket for integrated circuits (battery-buffered socket), with not more than 32 connections and incorporating a control circuit  ex 8506 50 90 30 Lithium-iodine or lithium-silver vanadium oxide single cell battery of dimensions of not more than 28 mm × 45 mm × 15 mm and a capacity of not less than 1,05 Ah  ex 8507 10 20 80 Lead acid starter battery, with:  — a charge acceptance capacity of 200 % or more of the level of an equivalent conventional flooded battery during the first 5 seconds of charge.  — a liquid electrolyte, for use in the manufacture of passenger cars and light commercial vehicles employing high regenerative alternator controls or start/stop systems with high regenerative alternator controls  ex 8507 50 00 20 Rectangular accumulator, with a length of 65,3 mm (±1,5 mm) and a diameter of 14,5 mm (±1 mm), having a nominal capacity of 1 000 mAh or more, for use in the manufacture of rechargeable batteries (1)  ex 8507 50 00 20 Rectangular accumulator, with a length of not more than 14,5 mm, of we should be a diameter of rechargeable batteries (1)  ex 8507 50 00 30 Cylindrical nickel-hydride accumulator, of a diameter of not more than 14,5 mm, of we manufacture of rechargeable batteries (1)  ex 8507 60 00 25 Rectangular modules for incorporation in lithium-ion rechargeable batteries, with:  — a width of 352,5 mm (±1 mm) or 367,1 mm (	ex 8505 11 00	80	permanent magnets after magnetization, containing neodymium, iron and boron, with dimensions:  — a length of 15 mm or more but not more than 105 mm,  — a width of 5 mm or more but not more than 105 mm,	0 %	31.12.2018
ex 8505 90 20 91 Solenoid with a plunger, operating at a nominal supply voltage of 24 V at a nominal DC of 0,08 A, for use in the manufacture of products falling within heading 8517 (1) 0 % 31.12.2018 ex 8506 50 90 10 Lithium iodine single cell battery the dimensions of which do not exceed 9 mm × 23 mm × 45 mm and a voltage of not more than 2,8 V 23 mm × 45 mm and a voltage of not more than 2,8 V 23 mm × 45 mm and a voltage of not more than 2,8 V 25 mm × 45 mm and a voltage of not more than 32 connections and incorporating a control circuit ex 8506 50 90 20 Unit consisting of not more than 2 lithium batteries embedded in a socket for integrated circuits (battery-buffered socket), with not more than 32 connections and incorporating a control circuit ex 8507 10 20 80 Lithium-iodine or lithium-silver vanadium oxide single cell battery of dimensions of not more than 28 mm × 45 mm × 15 mm and a capacity of not less than 1,05 Ah 0 % 31.12.2018 ex 8507 10 20 80 Lead acid starter battery, with:  — a charge acceptance capacity of 200 % or more of the level of an equivalent conventional flooded battery during the first 5 seconds of charge, — a liquid electrolyte, for use in the manufacture of passenger cars and light commercial vehicles employing high regenerative alternator controls or start/stop systems with high rege	ex 8505 19 90	30	than 120 mm, containing a hole in the centre intended to become permanent	0 %	31.12.2018
ex 8506 50 90  10  Lithium iodine single cell battery the dimensions of which do not exceed 9 mm	ex 8505 20 00	30	conditioning machines of motor vehicles	0 %	31.12.2018
x 23 mm x 45 mm and a voltage of not more than 2,8 V  Unit consisting of not more than 2 lithium batteries embedded in a socket for integrated circuits (battery-buffered socket), with not more than 32 connections and incorporating a control circuit  ex 8506 50 90  30 Lithium-iodine or lithium-silver vanadium oxide single cell battery of dimensions of not more than 28 mm x 45 mm x 15 mm and a capacity of not less than 1,05 Ah  ex 8507 10 20  80 Lead acid starter battery, with:  — a charge acceptance capacity of 200 % or more of the level of an equivalent conventional flooded battery during the first 5 seconds of charge, — a liquid electrolyte, for use in the manufacture of passenger cars and light commercial vehicles employing high regenerative alternator controls or start/stop systems with high regenerative alternator controls  ex 8507 30 20  30 Cylindrical nickel-cadmium accumulator, with a length of 65,3 mm (±1,5 mm) and a diameter of 14,5 mm (±1 mm), having a nominal capacity of 1 000 mAh or more, for use in the manufacture of rechargeable batteries (1)  ex 8507 50 00  20 Rectangular accumulator, with a length of not more than 69 mm, a width of not more than 36 mm and a thickness of not more than 12 mm, for use in the manufacture of rechargeable batteries (1)  ex 8507 50 00  30 Cylindrical nickel-hydride accumulator, of a diameter of not more than 14,5 mm, for the manufacture of rechargeable batteries (1)  ex 8507 60 00  25 Rectangular modules for incorporation in lithium-ion rechargeable batteries, with: — a width of 352,5 mm (±1 mm) or 367,1 mm (±1 mm)  31.12.2017	ex 8505 90 20	91	Solenoid with a plunger, operating at a nominal supply voltage of 24 V at a nominal DC of 0,08 A, for use in the manufacture of products falling within heading 8517 (1)	0 %	31.12.2018
integrated circuits (battery-buffered socket), with not more than 32 connections and incorporating a control circuit  ex 8506 50 90 30 Lithium-iodine or lithium-silver vanadium oxide single cell battery of dimensions of not more than 28 mm × 45 mm × 15 mm and a capacity of not less than 1,05 Ah  ex 8507 10 20 80 Lead acid starter battery, with:  — a charge acceptance capacity of 200 % or more of the level of an equivalent conventional flooded battery during the first 5 seconds of charge, — a liquid electrolyte, for use in the manufacture of passenger cars and light commercial vehicles employing high regenerative alternator controls or start/stop systems with high regenerative alternator or start/stop syste	ex 8506 50 90	10	Lithium iodine single cell battery the dimensions of which do not exceed 9 mm $\times$ 23 mm $\times$ 45 mm and a voltage of not more than 2,8 V	0 %	31.12.2018
of not more than 28 mm × 45 mm × 15 mm and a capacity of not less than 1,05 Ah  Lead acid starter battery, with:  — a charge acceptance capacity of 200 % or more of the level of an equivalent conventional flooded battery during the first 5 seconds of charge, — a liquid electrolyte, for use in the manufacture of passenger cars and light commercial vehicles employing high regenerative alternator controls or start/stop systems with high regenerative alternator controls  ex 8507 30 20  30  Cylindrical nickel-cadmium accumulator, with a length of 65,3 mm (±1,5 mm) and a diameter of 14,5 mm (±1 mm), having a nominal capacity of 1 000 mAh or more, for use in the manufacture of rechargeable batteries (1)  ex 8507 50 00  ex 8507 60 00  20  Rectangular accumulator, with a length of not more than 69 mm, a width of not more than 36 mm and a thickness of not more than 12 mm, for use in the manufacture of rechargeable batteries (1)  ex 8507 50 00  30  Cylindrical nickel-hydride accumulator, of a diameter of not more than 14,5 mm, for the manufacture of rechargeable batteries (1)  ex 8507 60 00  25  Rectangular modules for incorporation in lithium-ion rechargeable batteries, with: — a width of 352,5 mm (±1 mm) or 367,1 mm (±1 mm)  0 %  31.12.2017	ex 8506 50 90	20	integrated circuits (battery-buffered socket), with not more than 32 connections and	0 %	31.12.2018
- a charge acceptance capacity of 200 % or more of the level of an equivalent conventional flooded battery during the first 5 seconds of charge,  — a liquid electrolyte, for use in the manufacture of passenger cars and light commercial vehicles employing high regenerative alternator controls or start/stop systems with high regenerative alternator controls  Cylindrical nickel-cadmium accumulator, with a length of 65,3 mm (±1,5 mm) and a diameter of 14,5 mm (±1 mm), having a nominal capacity of 1 000 mAh or more, for use in the manufacture of rechargeable batteries (1)  Exercise 8507 50 00 20 Rectangular accumulator, with a length of not more than 69 mm, a width of not more than 36 mm and a thickness of not more than 12 mm, for use in the manufacture of rechargeable batteries (1)  Exercise 8507 50 00 30 Cylindrical nickel-hydride accumulator, of a diameter of not more than 14,5 mm, for the manufacture of rechargeable batteries (1)  Exercise 8507 60 00 25 Rectangular modules for incorporation in lithium-ion rechargeable batteries, with:  — a width of 352,5 mm (±1 mm) or 367,1 mm (±1 mm)	ex 8506 50 90	30		0 %	31.12.2018
a diameter of 14,5 mm (±1 mm), having a nominal capacity of 1 000 mAh or more, for use in the manufacture of rechargeable batteries (1)  ex 8507 50 00  ex 8507 60 00  20  Rectangular accumulator, with a length of not more than 69 mm, a width of not more than 36 mm and a thickness of not more than 12 mm, for use in the manufacture of rechargeable batteries (1)  ex 8507 50 00  30  Cylindrical nickel-hydride accumulator, of a diameter of not more than 14,5 mm, for the manufacture of rechargeable batteries (1)  ex 8507 60 00  25  Rectangular modules for incorporation in lithium-ion rechargeable batteries, with:  — a width of 352,5 mm (±1 mm) or 367,1 mm (±1mm)	ex 8507 10 20	80	<ul> <li>a charge acceptance capacity of 200 % or more of the level of an equivalent conventional flooded battery during the first 5 seconds of charge,</li> <li>a liquid electrolyte,</li> <li>for use in the manufacture of passenger cars and light commercial vehicles employing high regenerative alternator controls or start/stop systems with high regenerative alternator controls</li> </ul>	0 %	31.12.2015
ex 8507 60 00 20 more than 36 mm and a thickness of not more than 12 mm, for use in the manufacture of rechargeable batteries (1)  ex 8507 50 00 30 Cylindrical nickel-hydride accumulator, of a diameter of not more than 14,5 mm, for the manufacture of rechargeable batteries (1)  ex 8507 60 00 25 Rectangular modules for incorporation in lithium-ion rechargeable batteries, with:  — a width of 352,5 mm (± 1 mm) or 367,1 mm (±1mm)	ex 8507 30 20	30	a diameter of 14,5 mm (±1 mm), having a nominal capacity of 1 000 mAh or more,	0 %	31.12.2018
for the manufacture of rechargeable batteries (1)  ex 8507 60 00  25  Rectangular modules for incorporation in lithium-ion rechargeable batteries, with:  — a width of 352,5 mm (± 1 mm) or 367,1 mm (±1mm)  31.12.2017			more than 36 mm and a thickness of not more than 12 mm, for use in the	0 %	31.12.2018
— a width of 352,5 mm (± 1 mm) or 367,1 mm (±1mm)	ex 8507 50 00	30	Cylindrical nickel-hydride accumulator, of a diameter of not more than 14,5 mm, for the manufacture of rechargeable batteries (1)	0 %	31.12.2018
— a depth of 300 mm (± 2 mm) or 272,6 mm (± 1 mm)	ex 8507 60 00	25	— a width of 352,5 mm (± 1 mm) or 367,1 mm (±1mm)	0 %	31.12.2017

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		— a height of 268,9 mm (± 1,4 mm) or 229,5 mm (± 1mm) — a weight of 45,9 kg or 46,3 kg — a rating of 75 Ah and — a nominal voltage of 60 V		
ex 8507 60 00	30	Cylindrical lithium-ion accumulator, with a length of 63 mm or more and a diameter of 17,2 mm or more, having a nominal capacity of 1 200 mAh or more, for use in the manufacture of rechargeable batteries (1)	0 %	31.12.2014
ex 8507 60 00	35	Lithium-ion rechargeable batteries, with:  — a length of 1 475 mm or more, but not more than 2 200 mm  — a width of 935 mm or more, but not more than 1 400 mm  — a height of 260 mm or more, but not more than 310 mm  — a weight of 320 kg or more, but not more than 390 kg  — a nominal capacity of 18,4 Ah or more, but not more than 130 Ah,  — put up in packs of 12 or 16 modules	0 %	31.12.2017
ex 8507 60 00	40	Batteries of ion-lithium electric accumulators rechargeable with:  — a length of 1 203 mm or more, but not more than 1 297 mm,  — a width of 282 mm or more, but not more than 772 mm,  — a height of 792 mm or more, but not more than 839 mm,  — a weight of 260 kg or more, but not more than 293 kg,  — power of 22 kWh or 26 kWh, and  — constituted of 24 or 48 modules	0 %	31.12.2017
ex 8507 60 00	50	Modules for the assembly of batteries of ion lithium electric accumulators with:  — a length of 298 mm or more, but not more than 408 mm,  — a width of 33,5 mm or more, but not more than 209 mm,  — a height of 138 mm or more, but not more than 228 mm,  — a weight of 3,6 kg or more, but not more than 17 kg, and  — a power of 458 kWh or more, but not more than 2 158 kWh	0 %	31.12.2017
ex 8507 60 00	55	Lithium-ion accumulator in cylindrical form, with:  — a base similar to an ellipse squeezed in the middle,  — a length of 49 mm or more (not including terminals),  — a width of 33,5 mm or more,  — a thickness of 9,9 mm or more,  — a rated capacity of 1,75 Ah or more, and  — a rated voltage of 3,7 V,  for the manufacture of rechargeable batteries  (1)	0 %	31.12.2017
ex 8507 60 00	57	Lithium-ion accumulator, cuboid in shape, with:  — some of the corners rounded off,  — a length of 76 mm or more (not including terminals),  — a width of 54,5 mm or more,  — a thickness of 5,2 mm or more,  — a rated capacity of 3 100 mAh or more, and  — a rated voltage of 3,7 V,  for the manufacture of rechargeable batteries  (1)	0 %	31.12.2017
ex 8507 60 00	60	Lithium-ion rechargeable batteries, with:  — a length of 1 213 mm or more, but not more than 1 575 mm,  — a width of 245 mm or more but not more than 1 200 mm,  — a height of 265 mm or more, but not more than 755 mm,  — a weight of 265 kg or more but not more than 294 kg,  — a nominal capacity of 66,6 Ah, put up in packs of 48 modules	0 %	31.12.2015
ex 8507 60 00	65	Cylindrical Lithium Ion Cell with  — 3,5 VDC to 3,8 VDC,  — 300 mAh to 900 mAh and  — a diameter of 10,0 mm to 14,5 mm	0 %	31.12.2016
ex 8507 60 00	70	Rectangular modules for incorporation in lithium-ion rechargeable batteries:  — of a length of 350 mm or 312 mm,	0 %	31.12.2015

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 8507 60 00	75	<ul> <li>of a width of 79,8 mm or 225 mm,</li> <li>of a height of 168 mm or 35 mm,</li> <li>of a weight of 6,2 kg or 3,95 kg,</li> <li>with a rating of 129 Ah or 66,6 Ah</li> </ul> Rectangular lithium-ion-accumulator, with <ul> <li>a metal casing,</li> <li>a length of 173 mm (± 0,15 mm),</li> </ul>	0 %	31.12.2016
		- a relight of 175 mm (± 0,13 mm), - a width of 21 mm (± 0,15 mm), - a height of 91 mm (± 0,15 mm), - a nominal voltage of 3,3 V and, - a nominal capacity of 21 Ah or more		
ex 8507 60 00	80	Rectangular lithium-ion-accumulator, with  — a metal casing,  — a length of 171 mm (± 3 mm),  — a width of 45,5 mm (± 1 mm),  — a height of 115 mm (± 1 mm),  — a nominal voltage of 3,75 V and  — a nominal capacity of 50 Ah for use in the manufacture of rechargeable batteries for motor vehicles  (1)	0 %	31.12.2015
ex 8507 90 80	70	Cut plate of nickel-plated copper foil, with:  — a width of 70 mm (± 5 mm),  — a thickness of 0,4 mm (± 0,2 mm),  — a length of not more than 55 mm, for use in the manufacture of lithium-ion electric vehicle batteries  (1)	0 %	31.12.2016
ex 8508 70 00 ex 8537 10 99	10 96	Electronic circuit card without separate housing for actuating and controlling vacuum cleaner brushes powered by not more than 300 W	0 %	31.12.2015
ex 8508 70 00 ex 8537 10 99	20 98	Electronic circuit cards that:  — are connected by wire or radio frequency to each other and the motor controller card, and  — regulate the functioning (switching on or off and suction capacity) of vacuum cleaners according to a stored program,  — whether or not fitted with indicators that display the functioning of the vacuum cleaner (suction capacity and/or dust bag full and/or filter full)	0 %	31.12.2015
ex 8512 40 00 ex 8516 80 20	10 20	Car door mirror heating foil:  — with two electrical contacts,  — with an adhesive layer on both sides (on the side of the plastic holder of the mirror and on the side of the mirror glass),  — with a protective paper film on both sides	0 %	31.12.2018
ex 8516 90 00	60	Ventilation sub-assembly of an electric deep-fat fryer:  — fitted with a motor having a power rating of 8 W at 4 600 rpm,  — governed by an electronic circuit,  — operating at ambient temperatures above 110 °C,  — fitted with a thermoregulator	0 %	31.12.2014
ex 8516 90 00	70	Inner pot:  — containing side and central openings,  — of annealed aluminium,  — with a ceramic coating, heat resistant to more than 200° C for use in the manufacture of an electric fryer	0 %	31.12.2017
ex 8518 29 95	30	Loudspeakers of:  — an impedance of 4 Ohm or more, but not more than 16 Ohm,	0 %	31.12.2017

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		<ul> <li>a nominal power of 2 W or more, but not more than 20 W,</li> <li>with or without plastic bracket, and</li> <li>with or without electric cable fitted with connectors,</li> <li>of a kind used for TV sets and video monitors manufacture</li> </ul>		
ex 8518 30 95	20	Headphone and earphone for hearing aids, contained in a housing the exterior dimensions of which, excluding connecting points, do not exceed 5 mm × 6 mm × 8 mm	0 %	31.12.2018
ex 8518 40 80	91	Circuit board sub-assembly, comprising digital audio signal decoding, audio signal processing and amplification with dual and/or multi-channel functionality	0 %	31.12.2014
ex 8518 40 80	92	Circuit board sub-assembly, comprising power supply, active equalizer and power amplifier circuits	0 %	31.12.2015
ex 8518 90 00	91	Integrally cold-upsetted steel coreplate, in the form of a disk on one side provided with a cylinder, for use in the manufacture of loudspeakers (1)	0 %	31.12.2018
ex 8521 90 00	20	Digital video recorder:  — without a hard disk drive,  — with or without a DVD-RW drive,  — with either motion detection or capability of motion detection through IP connectivity via LAN connector  — with or without a USB serial port, for use in the manufacture of Closed-circuit television (CCTV) surveillance systems (1)	0 %	31.12.2014
ex 8522 90 49	50	Electronic assembly for a laser read-head of a compact disc player, comprising:  — a printed circuit,  — a photo-detector, in the form of a monolithic integrated circuit, contained in a housing,  — not more than 3 connectors,  — not more than 1 transistor,  — not more than 3 variable and 4 fixed resistors,  — not more than 5 capacitors, the whole mounted on a support	0 %	31.12.2018
ex 8522 90 49 ex 8527 99 00 ex 8529 90 65	60 10 25	Printed circuit board assembly comprising:  — a radio tuner (capable of receiving and decoding radio signals and transmitting those signals within the assembly) without signal processing capabilities,  — a microprocessor capable of receiving remote control messages and controlling the tuner chipset,  for use in the manufacture of home entertainment systems	0 %	31.12.2014
ex 8522 90 49 ex 8527 99 00 ex 8529 90 65	65 20 40	Printed circuit board subassembly, comprising:  — a radio tuner, capable of receiving and decoding radio signals and transmitting those signals within the assembly, with a signal decoder,  — a radio frequency (RF) remote control receiver,  — an infrared remote control signal transmitter,  — a SCART signal generator  — a TV state sensor for use in the manufacture of home entertainment systems	0 %	31.12.2014
ex 8522 90 49	70	Assembly, comprising at least a flexible printed circuit, a laser driver integrated circuit and a signal converter integrated circuit	0 %	31.12.2018
ex 8522 90 80	15	Heat sinks and cooling fins of aluminium, for maintaining the operating temperature of transistors and/or integrated circuits in products of heading 8521	0 %	31.12.2017
ex 8522 90 80 ex 8529 90 92	30 30	Holder, fixing item or internal stiffener of metal, for use in the manufacture of televisions, monitors and video players (1)	0 %	31.12.2016
ex 8522 90 80	65	Assembly for optical discs, comprising at least an optical unit and DC motors,	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		whether or not capable of double layer recording		
ex 8522 90 80	70	Video tape recording/reproducing assembly comprising at least a motor and a printed circuit board containing integrated circuits with driver or control functions, whether or not incorporating a transformer, for use in the manufacture of products falling within heading 8521	0 %	31.12.2018
ex 8522 90 80	75	Optical reading head for CD player, consisting of one laser diode, one photo detector integrated circuit and one beam splitter	0 %	31.12.2018
ex 8522 90 80	80	Laser optical drive unit assembly (so called mecha units) for the recording and/or reproduction of digital video and/or audio signals, comprising at least a laser optical reading and/or writing unit, one or more DC motors and not containing a printed circuit board or containing a printed circuit board not capable of signal processing for sounds and images, for use in the manufacture of products falling within headings 8519, 8521, 8526, 8527, 8528 or 8543	0 %	31.12.2018
ex 8522 90 80	81	Laser optical pick up unit for the reproduction of optical signals from CD or DVD and the recording of optical signal on DVD, comprising at least  — a laser diode,  — a laser driver integrated circuit,  — a photo detector integrated circuit,  — a front monitor integrated circuit and an actuator, for use in the manufacture of products falling within heading 8521	0 %	31.12.2016
ex 8522 90 80	83	Blu-ray optical pick-up unit, whether or not recordable, for use with Blu-ray, DVD and CD discs, comprising at least:  — laser diodes operating at three different wavelengths,  — a photo detector integrated circuit and  — an actuator, for the manufacture of products falling within heading 8521	0 %	31.12.2018
ex 8522 90 80	84	Blu-ray drive mechanism, whether or not recordable, for use with Blu-ray, DVD and CD discs, comprising at least:  — an optical pick up unit with laser diodes operating at three different wavelengths,  — a spindle motor,  — a stepping motor	0 %	31.12.2018
ex 8522 90 80	85	Video head drum, with video heads or with video and audio heads and an electric motor, for use in the manufacture of products falling within heading 8521 (1)	0 %	31.12.2018
ex 8522 90 80	96	Hard disk drive, for incorporation in products of heading 8521	0 %	31.12.2017
ex 8522 90 80 ex 8529 90 65	97 50	Tuner transforming high-frequency signals into mid-frequency signals, for use in the manufacture of products falling under headings 8521 and 8528 (1)	0 %	31.12.2016
ex 8525 80 19	20	Assembly for television cameras of dimensions of not more than 10 mm $\times$ 15 mm $\times$ 18 mm, comprising an image sensor, an objective and a color processor, having an image resolution of not more than 1024 $\times$ 1280 pixels, whether or not fitted with cable and/or housing, for the manufacture of goods of subheading 8517 12 00 $^{(1)}$	0 %	31.12.2018
ex 8525 80 19	25	Long wavelength infrared camera (LWIR camera) (according to ISO/TS 16949), with:  — a sensitivity in the wavelength area of 8 µm or more, but not more than 14 µm,  — a resolution of 324 × 256 pixels,  — a weight of not more than 400 g,  — measurements of not more than 70 mm × 67 mm × 75 mm,  — a waterproof housing and an automotive- qualified plug and	0 %	31.12.2014

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		— a deviation of the output signal over the entire work temperature range of not more than 20 $\%$		
ex 8525 80 19 ex 8525 80 91	31 10	Closed circuit television (CCTV) camera:  — of a weight of not more than 5,9 kg,  — without a housing,  — of dimensions of not more than 405 mm × 315 mm,  — with a single Charge-Couple-Device (CCD) or Complementary Metal–Oxide–Semiconductor (CMOS) sensor,  — with effective pixels of not more than 5 megapixels,  for use in CCTV surveillance systems	0 %	01.07.2014
ex 8525 80 19	35	Image scanning cameras, using:  — a "Dynamic overlay lines" system,  — an output NTSC video signal,  — a voltage of 6,5 V,  — an illuminance of 0,5 lux or more	0 %	31.12.2014
ex 8525 80 19	40	Assembly for cameras used in computer notebooks of dimensions of not more than 15 mm $\times$ 25 mm, comprising an image sensor, an objective and a colour processor, having an image resolution of not more than 1600 $\times$ 1200 pixels, whether or not fitted with cable and/or housing, whether or not mounted on a base and containing a LED chip $^{(1)}$	0 %	31.12.2016
ex 8525 80 19	45	Camera module with a resolution of 1 280 * 720 P HD, with two microphones, for use in the manufacture of products of heading 8528	0 %	31.12.2017
ex 8526 91 20 ex 8527 29 00	80 10	Integrated audio module (IAM) with a digital video output for connection to an LCD touch screen monitor, interfaced over the Media Oriented Systems Transport (MOST) network and transported over the MOST High protocol, with or without  — a printed circuit board (PCB) containing a Global Positioning System (GPS) receiver, a gyroscope, and a Traffic Message Channel (TMC) tuner,  — a hard disk drive supporting multiple maps,  — a HD radio,  — a voice recognition system,  — a CD and DVD drive, and including  — Bluetooth, MP3 and USB input connectivity,  — a voltage of 10 V or more but not more than 16 V, for the use in the manufacture of vehicles in Chapter 87	0 %	31.12.2015
ex 8527 91 99 ex 8529 90 65	10 35	Assembly consisting of at least:  — an audio frequency amplifier unit, comprising at least an audio frequency amplifier and a sound generator,  — a transformer and  — a radio broadcast receiver	0 %	31.12.2014
ex 8528 49 10	10	Video monitor comprising:  — a flat screen monochrome cathode-ray tube with a diagonal measurement of the screen of not more than 110 mm and equipped with a deflector yoke, and  — a printed circuit on which are mounted a deflection unit, a video-amplifier and a transformer, the whole mounted or not on a chassis, for the manufacture of video entry-phones, video telephones or surveillance apparatus  (1)	0 %	31.12.2018
ex 8528 59 70	10	Liquid crystal display colour video monitors, excluding those combined with other apparatus, having a DC input voltage of 7 V or more but not more than 30 V, with a diagonal measurement of the screen of 33,2 cm or less,  — without a housing, with back cover and mounting frame,	0 %	30.06.2014

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		— or with a housing, used for permanent incorporation or permanent mounting, during industrial assembly, into goods of Chapters 84 to 90 and 94		
ex 8529 10 80	20	Ceramic filter package comprising 2 ceramic filters and 1 ceramic resonator for a frequency of 10,7 MHz (±30 kHz), contained in a housing	0 %	31.12.2018
ex 8529 10 80	50	Ceramic filter for a centre frequency of 450 kHz (±1,5 kHz) or 455 kHz (±1,5 kHz), with a bandwidth of not more than 30 kHz at 6 dB and not more than 70 kHz at 40 dB, contained in a housing	0 %	31.12.2018
ex 8529 10 80	60	Filters, excluding surface acoustic wave filters, for a center frequency of 485 MHz or more but not more than 1 990 MHz with an insertion loss of not more than 3,5 dB, contained in a housing	0 %	31.12.2018
ex 8529 90 65 ex 8548 90 90	30 44	Parts of TV-apparatus, having micro-processor and video-processor functions, comprising at least a micro-controller and a video-processor, mounted on a leadframe and contained in a plastic housing	0 %	31.12.2018
ex 8529 90 65	45	Satellite radio receiver module transforming satellite high frequency signals to digital audio coded signal, for use in the manufacture of products falling within heading 8527 (1)	0 %	31.12.2014
ex 8529 90 65	55	Ambient light LED board to be incorporated in goods of heading 8528 (1)	0 %	31.12.2015
ex 8529 90 65	60	Tuner transforming high frequency signals to mid frequency signals for use in the manufacture of satellite or terrestrial TV receivers for set-top boxes (1)	0 %	31.12.2016
ex 8529 90 65	65	Printed circuit board for distributing supply voltage and control signals directly to a control circuit on a TFT glass panel of a LCD module	0 %	31.12.2015
ex 8529 90 65	70	Unit driver consisting of an electronic integrated circuit and a flexible printed circuit, for use in the manufacture of LCD modules (1)	0 %	31.12.2016
ex 8529 90 65	75	Modules comprising at least semiconductor chips for:  — the generation of driving signals for pixel addressing, or  — driving addressing pixels	0 %	31.12.2017
ex 8529 90 92	25	LCD modules, not combined with touch screen facilities, solely consisting of:  — one or more TFT glass or plastic cells,  — a die cast heat sink,  — a backlight unit,  — one printed circuit board with micro controller, and  — LVDS (Low Voltage Differential Signalling) interface, for use in the manufacture of radios for motor vehicles	0 %	31.12.2015
ex 8529 90 92	32	Optical unit for video projection, comprising a colour separation system, a positioning mechanism and lenses, for use in the manufacture of products falling within heading 8528 (1)	0 %	31.12.2018
ex 8529 90 92	40	Assembly comprising prisms, digital micromirror device (DMD) chips and electronic control circuits, for the manufacture of television projection equipments or video projectors (1)	0 %	31.12.2018
ex 8529 90 92	41	Digital micromirror device (DMD)-chips, for use in the manufacture of video projectors (1)	0 %	31.12.2018
ex 8529 90 92	42	Heat sinks and cooling fins of aluminium, for maintaining the operating temperature of transistors and integrated circuits in television sets	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 8529 90 92	43	Plasma display module incorporating only address and display electrodes, with or without driver and/or control electronics for pixel address only and with or without a power supply	0 %	31.12.2018
ex 8529 90 92	44	LCD modules, solely consisting of one or more TFT glass or plastic cells, not combined with touch screen facilities, with or without backlight unit, with or without inverters and one or more printed circuit boards with control electronics for pixel addressing only		31.12.2018
ex 8529 90 92	45	Integrated circuit package with TV reception functionality containing a channel decoder die, tuner die, power management die, GSM filters and discrete as well as embedded passive circuit elements for reception of digitally broadcasting videosignals of DVB-T and DVB-H formats	0 %	31.12.2018
ex 8529 90 92	47	Area image sensors ("progressive scan" Interline CCD-Sensor or CMOS-Sensor) or digital video cameras in the form of analogue or digital, monolithic integrated circuit with pixels of not more than $12  \mu m \times 12  \mu m$ in monochromic version with microlenses applied to each individual pixel (microlens array) or in bolychromic version with a colour filter, whether or not with a lenslet (micro lens) array with one lenslet mounted on each individual pixel		31.12.2014
ex 8529 90 92	48	Aluminium die cast heat sink, for maintaining the operating temperature of transistors and integrated circuits, for use in the manufacture of products falling within heading 8527 (1)	0 %	31.12.2014
ex 8529 90 92 ex 8536 69 90	49 83	AC socket with a noise filter, composed of:  — AC socket (for power cord connection) of 230 V,  — integrated noise filter composed of capacitors and inductors,  — cable connector for connecting an AC socket with the PDP (Plasma display panel) power supply unit,  whether or not equipped with a metal support, which joins the AC socket to the PDP TV set	0 %	31.12.2014
ex 8529 90 92	50	Colour LCD display panel for LCD monitors of heading 8528:  — with a diagonal measurement of the screen of 14,48 cm or more but not more than 31,24 cm,  — with backlight, micro-controller,  — with a CAN (Controller area network)-controller with LVDS (Low-voltage differential signalling) interface and CAN/power supply socket or with an APIX (Automotive Pixel Link) controller with APIX interface,  — in a housing with or without a heat sink at the back of the housing,  — without a signal-processing module, for use in the manufacture of vehicles of chapter 87	0 %	31.12.2015
ex 8529 90 92	70	Rectangular fastening and covering frame:  — of an aluminium alloy containing silicon and magnesium,  — with a length of 900 mm or more but not more than 1 500 mm,  — with a width of 600 mm or more but not more than 950 mm,  of a kind used for the production of TV sets	0 %	31.12.2017
ex 8531 80 95	40	Electro-accoustic transducer	0 %	31.12.2018
ex 8535 90 00	20	Printed circuit board in the form of plates consisting of isolating material with electrical connections and solder points, for use in the manufacture of back light units for LCD modules		31.12.2018
ex 8535 90 00 ex 8536 50 80	30 83	Semiconductor module switch in a casing:  — consisting of an IGBT transistor chip and a diode chip on one or more lead frames,  — for a voltage of 600 V or 1 200 V	0 %	31.12.2015

-	ı			
CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 8536 30 30	11	Thermo-electric switch with a cut-off current of 50 A or more, comprising a snap action switch, for direct mounting on an electric motor coil, contained in a hermetically sealed housing	0 %	31.12.2018
ex 8536 49 00	91	Thermal relays contained in a hermetically sealed glass cartridge of not more than 35 mm in length excluding wires, with a maximum leakage rate of 10-6 cm³ He/sec at one bar in the temperature range 0 °C to 160 °C, to be incorporated into compressors for refrigerating equipment (1)	0 %	31.12.2018
ex 8536 50 11	31	Switch of the printed circuit mount type, operating at a force of 4,9 N ( $\pm$ 0,9 N), contained in a housing	0 %	31.12.2018
ex 8536 50 11	32	Mechanical tact switch for connecting electronic circuits, operating at a voltage of not more than 60V and at a current strength of not more than 50mA, for use in the manufacture of products of headings 8521 or 8528	0 %	31.12.2018
ex 8536 50 19	91	Hall effect switch, comprising 1 magnet, 1 Hall effect sensor and 2 capacitors, contained in a housing with 3 connections	0 %	31.12.2018
ex 8536 50 19 ex 8536 50 80	93 97	Devices, having adjustable controller and switching functions, comprising one ore more monolithic integrated circuits whether or not combined with semiconductor elements, mounted together on a leadframe and contained in a plastic housing	0 %	31.12.2018
ex 8536 50 80	81	Mechanical speed governer switches for connecting electrical circuits, with:  — a voltage of 240 V or more but not more than 250 V,  — an amperage of 4 A or more but not more than 6 A, for use in the manufacture of machines falling within heading 8467		31.12.2014
ex 8536 50 80	82	Mechanical switches for connecting electrical circuits, with:  — a voltage of 240 V or more but not more than 300 V,  — an amperage of 3 A or more but not more than 15 A, for use in the manufacture of machines falling within heading 8467	0 %	31.12.2014
ex 8536 50 80	93	Switch unit for coaxial cable, comprising 3 electromagnetic switches, with a switching time of not more than 50 ms and an actuating current of not more than 500 mA at a voltage of 12 V	0 %	31.12.2018
ex 8536 50 80	98	Mechanical push-button switch for connecting electronic circuits, operating at a voltage of 220 V or more but not more than 250 V and at a current strength of not more than 5 A, for use in the manufacture of products of headings 8521 or 8528 (1)	0 %	31.12.2018
ex 8536 69 90	51	SCART type connectors, built into a plastic or metal housing, with 21 pins in 2 rows, for use in the manufacture of products falling within headings 8521 and 8528	0 %	31.12.2017
ex 8536 69 90	81	Pitch connector for use in the manufacture of LCD television reception apparatus	0 %	31.12.2017
ex 8536 69 90	82	Modular socket or plug for local area networks, whether or not combined with other sockets, integrating at least:  — a pulse transformer, including a wide-band ferrite core,  — a common mode coil,  — a resistor,  — a capacitor, for use in the manufacture of products falling within headings 8521 or 8528	0 %	31.12.2014
ex 8536 69 90	84	Universal serial bus (USB) socket or plug in a single or multiple form for connecting with other USB devices, for use in the manufacture of goods falling within headings 8521 or 8528	0 %	31.12.2015

CN code	TARIC	Description		Date foreseen for mandatory review
		(1)		
ex 8536 69 90	85	Socket or plug, built into a plastic or metal housing, with no more than 8 pins, for use in the manufacture of products falling within headings 8521 or 8528	0 %	31.12.2016
ex 8536 69 90	86	High-Definition Multimedia Interface (HDMI) type socket or plug, built into a plastic or metal housing, with 19 pins or 20 pins in 2 rows, for use in the manufacture of products falling within headings 8521 or 8528	0 %	31.12.2016
ex 8536 69 90	87	D-Subminiature (D-sub) type socket or plug, built into a plastic or metal housing, with 15 pins in 3 rows, for use in the manufacture of products falling within headings 8521 or 8528	0 %	31.12.2016
ex 8536 69 90	88	Secure Digital (SD), CompactFlash, "Smart Card" and 64- pin PC-card female connectors, of a kind used for soldering on printed circuit boards, for connecting electrical apparatus and circuits and switching or protecting electrical circuits with a voltage of not more than 1 000 V	0 %	31.12.2017
ex 8536 70 00	10	Optical socket or plug, for use in the manufacture of goods falling within headings 8521 or 8528	0 %	31.12.2016
ex 8536 70 00	20	Metal plugs, sockets and connectors in plastic or metal housing for optically and mechanically aligning optical fibre cables:  — having an operating temperature of -20 °C or more, but not more than 70 °C,  — having a signal transmission speed of not more than 25 Mbps,  — having a supply voltage of -0,5 V or more, but not more than 7 V,  — having an input voltage of -0,5 V or more, but not more than 7,5 V,  — without an integrated circuit,  for use in the manufacture of products of headings 8521 and 8528		31.12.2016
ex 8536 90 85	92	Metallic stamped frame with connections	0 %	31.12.2018
ex 8536 90 85 ex 8544 49 93	94 10	Elastomeric connector, of rubber or silicone, consisting of one or more conductor elements	0 %	31.12.2018
ex 8536 90 85	97	Secure Digital (SD) type memory card slot, push-push or push-pull type, for use in the manufacture of goods falling within headings 8521 or 8528	0 %	31.12.2016
ex 8537 10 91	30	Data processing and evaluation vehicle dashboard control module, operating through the CAN - bus protocol, containing at least:  — microprocessor relays,  — a stepper motor,  — Electrically Erasable Programmable Read-Only (EEPROM) memory, and  — other passive components (such as connectors, diodes, voltage stabilizer, resistors, capacitors, transistors), with a voltage of 13,5 V		31.12.2017
ex 8537 10 99	92	Touch sensitive screen panel, consisting of a conductive grid between two glass or plastic plates or sheets, fitted with electric conductors and connectors	0 %	31.12.2018
ex 8537 10 99	93	Electronic control units for a voltage of 12 V, for use in the manufacture of vehicle mounted temperature control systems (1)	0 %	31.12.2018
ex 8537 10 99 ex 8543 70 90	94 20	Unit consisting of two junction field effect transistors contained in a dual lead frame housing	0 %	31.12.2018
ex 8537 10 99	97	Electronic controller card for actuating and controlling of a single-phase electric	0 %	31.12.2015

CN code	TARIC	Description		Date foreseen for mandatory review
		AC commutator motor, with an output of 750 W or more and an input power of more than 1 600 W but not more than 2 700 W		
ex 8538 90 99	92	Part of an electrothermal fuse, consisting of a tin coated copper wire attached to a cylindrical casing, the exterior dimensions of which do not exceed 5 mm $\times$ 48 mm	0 %	31.12.2018
ex 8538 90 99	95	Copper base plate, of a kind used as a heatsink in the manufacture of IGBT modules of heading 8535 or 8536 with a voltage of 650 V or more but not more than $1200V_{(1)}$	0 %	31.12.2018
ex 8539 39 00	20	Cold cathode (CCFL) or external electrode (EEFL) fluorescent lamps, of a diameter of not more than 5 mm and with a length of more than 120 mm but not more than 1570 mm	0 %	31.12.2016
ex 8540 11 00	93	Colour cathode-ray tube equipped with electron guns placed side by side (in-line technology), with a diagonal measurement of the screen of 79 cm or more	0 %	31.12.2016
ex 8540 20 80	91	Photomultiplier	0 %	31.12.2016
ex 8540 71 00	20	Continuous wave magnetron with a fixed frequency of 2 460 MHz, packaged magnet, probe output, for use in the manufacture of products falling within subheading 8516 50 00 (1)	0 %	31.12.2018
ex 8540 89 00	91	Displays in the form of a tube consisting of a glass housing mounted on a board the dimensions of which do not exceed 300 mm × 350 mm excluding leads. The tube contains one or more rows of characters or lines arranged in rows, each character or line consisting of fluorescent or phosphorescent elements. These elements are mounted on a metallised base which is covered with fluorescent substances or phosphorescent salts which give off light when bombarded with electrons		31.12.2018
ex 8540 89 00	92	Vacuum fluorescent display tube		31.12.2018
ex 8543 70 90 ex 9405 40 39 ex 9405 40 99	23 50 03	Semiconductor device for the conversion of electrical energy into visible, infra-red or ultra-violet rays:  — whether or not with a housing  — with electrical leads,  — including one or more light-emitting semiconductor chips which may be electrically connected among each other and which may be furnished for their protection with one or multiple protective diodes,  — formed/shaped as an indivisible entity  — for use in the manufacture of lighting gear employed for solid state lighting / for general lighting purposes		31.12.2018
ex 8543 70 90	30	Amplifier, consisting of active and passive elements mounted on a printed circuit, contained in a housing	0 %	31.12.2018
ex 8543 70 90	35	Radio frequency (RF) modulator, operating with a frequency range of 43 MHz or more but not more than 870 MHz, capable of switching VHF and UHF signals, consisting of active and passive elements mounted on a printed circuit, contained in a housing		31.12.2018
ex 8543 70 90	40	High-frequency amplifier comprising one or more integrated circuits and discrete capacitor chips on a metal flange in a housing	0 %	31.12.2015
ex 8543 70 90	45	Piezo-electric crystal oscillator with a fixed frequency, within a frequency range of 1,8 MHz to 67 MHz, contained in a housing		31.12.2018
ex 8543 70 90	55	Opto-electronic circuit comprising one or more light-emitting diodes (LEDs), whether or not equipped with an integrated driving circuit, and one photodiode with amplifier circuit, whether or not with an integrated logic gate arrays circuit or one or more light-emitting diodes and at least 2 photodiodes with an amplifier circuit, whether or not with an integrated logic gate arrays circuit or other integrated	0 %	31.12.2018

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
		circuits, contained in a housing		
ex 8543 70 90	60	Oscillator, with a centre frequency of 20 GHz or more but not more than 42 GHz, consisting of active and passive elements not mounted on a substrate, contained in a housing	0 %	31.12.2018
ex 8543 70 90	65	Audio recording and reproducing circuit, capable of stereo audio data storage and simultaneous record and playback, comprising 2 or 3 monolithic integrated circuits mounted on a printed circuit or a lead frame, contained in a housing	0 %	31.12.2018
ex 8543 70 90	80	Temperature compensated oscillator, comprising a printed circuit on which are mounted at least a piezo-electric crystal and an adjustable capacitor, contained in a housing	0 %	31.12.2018
ex 8543 70 90	85	Voltage controlled oscillator (VCO), other than temperature compensated oscillators, consisting of active and passive elements mounted on a printed circuit, contained in a housing	0 %	31.12.2018
ex 8543 70 90	95	Mobile telephone view and control module comprising of:  — a mains power/ CAN (Controller area network) output socket,  — a universal serial bus (USB) and audio IN/OUT ports and  — incorporating a video switching device for the interface of smart phone operating systems with the Media Orientated Systems Transport network (MOST),  for use in the manufacture of vehicles of Chapter 87	0 %	31.12.2015
ex 8543 90 00	20	Stainless steel cathode in the form of a plate with a hanger bar, whether or not with plastic side strips	0 %	31.12.2014
ex 8543 90 00	30	Assembly of products falling within heading 8541 or 8542 mounted on a printed circuit, contained in a housing	0 %	31.12.2018
ex 8543 90 00	40	Part of an electrolysis device, consisting of a pan of nickel equipped with a wire mesh of nickel, fixed via ribs of nickel, and a pan of titanium equipped with a wire mesh of titanium, fixed via ribs of titanium, of which both pans are fixed together back to back	0 %	31.12.2017
ex 8544 20 00 ex 8544 42 90 ex 8544 49 93 ex 8544 49 95	10 20 20 10	PET/PVC insulated flexible cable with:  — a voltage of not more than 60 V,  — a current of not more than 1 A,  — a heat resistance of not more than 105 °C,  — individual wires of a thickness of not more than 0,1 mm (± 0,01 mm) and a width of not more than 0,8 mm (± 0,03 mm),  — a distance between conductors of not more than 0,5 mm and  — a pitch (distance from centreline to centreline of conductors) of not more than 1,25 mm	0 %	31.12.2018
ex 8544 42 90	10	Data transmission cable capable of a bit rate transmission of 600 Mbit/s or more, with:  — a voltage of 1,25 V (± 0,25 V)  — connectors fitted at one or both ends, at least one of which contains pins with a pitch of 1 mm,  — outer screening shielding, used solely for communication between LCD, PDP or OLED panel and video processing electronic circuits	0 %	31.12.2018
ex 8544 42 90	30	PET insulated electric conductor with:  — 10 or 80 individual wires,  — a length of 50 mm or more, but not more than 800 mm,  — connector(s) and/or plug(s) fitted at one or both ends, for use in the manufacture of products falling within headings 8521 and 8528	0 %	31.12.2017

CN code	TARIC	Description		Date foreseen for mandatory review
ex 8545 19 00	20	Carbon electrodes, for use in the manufacture of zinc-carbon batteries	0 %	31.12.2018
ex 8545 90 90	20	Carbon fibre paper of a kind used for gas diffusion layers in fuel cell electrodes	0 %	31.12.2015
ex 8547 10 00	10	Insulated fitting of ceramics, containing by weight 90 % or more of aluminium oxide, metallised, in the form of a hollow cylindrical body of an external diameter of 20 mm or more but not more than 250 mm, for the manufacture of vacuum interrupters (1)	0 %	31.12.2018
ex 8548 10 29	10	Spent lithium-ion or nickel metal hydride electric accumulators	0 %	31.12.2016
ex 8548 90 90	41	Unit, consisting of a resonator operating within a frequency range of 1,8 MHz or more but not more than 40 MHz and a capacitor, contained in a housing	0 %	31.12.2018
ex 8548 90 90	43	Contact image sensor	0 %	31.12.2018
ex 8548 90 90	47	Unit consisting of two or more light emitting diode chips operating at a typical wavelength of 440 nm or more but not more than 660 nm, contained in a lead frame housing whose exterior dimensions - without fittings - do not exceed $12 \text{ mm} \times 12 \text{ mm}$	0 %	31.12.2018
ex 8548 90 90	48	Optical unit, consisting at least of a laserdiode and a photodiode operating at a typical wavelength of 635 nm or more but not more than 815 nm	0 %	31.12.2018
ex 8548 90 90	49	LCD modules, solely consisting of one or more TFT glass or plastic cells, combined with touch screen facilities, with or without backlight unit, with or without inverters and one or more printed circuit boards with control electronics for pixel addressing only	0 %	31.12.2018
ex 8548 90 90	50	Filters with a ferromagnetic core, used to suppress high frequency noise in electronic circuits, for the manufacture of TV sets and monitors of heading 8528	0 %	31.12.2017
ex 8704 23 91	20	Motor chassis with a self-ignition capacity of at least 8 000 cm <sup>3</sup> , fitted with a cabin on either 3, 4 or 5 wheels having a wheelbase of at least 480 cm, not containing working machinery, to be built into special purpose motor vehicles with a width of at least 300 cm (1)	0 %	31.12.2017
ex 8708 30 91	10	Drum type parking brake:  — operating within the service brake disk,  — with a diameter of 170 mm or more but not more than 175 mm, for use in the manufacture of motor vehicles	0 %	31.12.2015
ex 8708 99 97	20	Metal housing caps for incorporation into balancing-arms or spherical bearings used in the suspension systems for the front wheels of motor vehicles (1)	0 %	31.12.2016
ex 8803 30 00	50	Pre-formed helicopter rotor shafts:  — of circular cross-section,  — with a length of 1 249,68 mm or more, but not more than 1 496,06 mm,  — of an external diameter of 81,356 mm or more, but not more than 82,2198 mm,  — swaged on both ends to an external diameter of 63,8683 mm or more, but not more than 66,802 mm,  — heat treated according to standards MIL-H-6088, AMS 2770 or AMS 2772	0 %	31.12.2016
ex 9001 10 90	10	Image reverser made up from an assembly of optical fibres	0 %	31.12.2018
ex 9001 10 90	30	Polymer optical fibre with:  — a poly(methyl methacrylate) core,  — a cladding of fluorinated polymer,  — a diameter of not more than 3,0 mm, and  — a length of more than 150 m, of a kind used in the manufacture of polymer fibre cables	0 %	31.12.2016

CN code	TARIC	Description	Rate of autonomous duty	Date foreseen for mandatory review
ex 9001 20 00	10	Material consisting of a polarising film, whether or not on rolls, supported on one or both sides by transparent material, whether or not with an adhesive layer, covered on one side or on both sides with a release film	0 %	31.12.2017
ex 9001 20 00 ex 9001 90 00	20 55	Optical, diffuser, reflector or prism sheets, unprinted diffuser plates, whether or not possessing polarising properties, specifically cut	0 %	31.12.2018
ex 9001 90 00	21	Multi-Optical-Path (MOP) film, in rolls, based on poly(ethylene terephthalate) 0 (PET) material:  — having a total thickness of 100 μm or more, but not more than 240 μm,  — having a total transmittance of more than 55 % but not more than 65 %, determined by standard method JIS K7105 related to ASTM D1003 and  — haze more than 70 % but not more than 80 %, determined by standard method JIS K7105 related to ASTM D1003		31.12.2014
ex 9001 90 00	25	Unmounted optical elements made from moulded infrared transmitting chalcogenide glass, or a combination of infrared transmitting chalcogenide glass and another lens material	0 %	31.12.2017
ex 9001 90 00	35	Rear projection screen, comprising a lenticular plastic plate	0 %	31.12.2018
ex 9001 90 00	45	Rod of neodymium-doped yttrium-aluminium garnet (YAG) material, polished at both ends	0 %	31.12.2018
ex 9001 90 00	60	Reflector or diffuser sheets in rolls	0 %	31.12.2018
ex 9001 90 00	65	Optical film with a minimum of 5 multi-layer structures, including a back side reflector, a front side coating and a contrast filter with a pitch of not more than 0,65 $\mu$ m, for use in the manufacture of front projection screens <sup>(1)</sup>	0 %	31.12.2014
ex 9001 90 00	70	Poly(ethylene terephthalate) film with a thickness of less than 300 $\mu m$ according to ASTM D2103, having on one side prisms of acrylic resin with a prism angle of 90° and a prism pitch of 50 $\mu m$	0 %	31.12.2016
ex 9001 90 00	75	Front filter comprising glass panels with special printing and film coating, for use in the manufacture of plasma display modules	0 %	31.12.2017
ex 9001 90 00	85	Light guide panel made of poly(methyl methacrylate):  — whether or not cut,  — whether or not printed, for use in the manufacture of backlight units for flat screen TVs	0 %	31.12.2015
ex 9002 11 00	10	Adjustable lens unit, having a focal length of 90 mm or more but not more than 180 mm and comprising a combination of between 4 and 8 glass or methacrylic lenses with a diameter of 120 mm or more but not more than 180 mm, each lens coated on at least one side with a magnesium fluoride layer, for use in the manufacture of video projectors (1)	0 %	31.12.2018
ex 9002 11 00	20	Lenses  — measuring not more than 80 mm x 55 mm x 50 mm,  — with a resolution of 160 lines/mm or better, and  — with a zoom ratio of 18 times, of a kind used for the production of visualizers or live image cameras	0 %	31.12.2017
ex 9002 11 00	30	Lenses  — measuring not more than 180 mm x 100 mm x 100 mm at a maximum focal length of more than 200 mm,  — with a resolution of 130 lines/mm or better, and  — with a zoom ratio of 18 times of a kind used for the production of visualizers or live image cameras	0 %	31.12.2017
ex 9002 11 00	40	Lenses	0 %	31.12.2017
-	-			-

CN code	TARIC	Description		Date foreseen for mandatory review
		— measuring not more than 125 mm x 65 mm x 65 mm,  — with a resolution of 125 lines/mm or better, and  — with a zoom ratio of 16 times of a kind used for the production of visualizers or live image cameras		
ex 9002 11 00	50	Lens unit, having a focal length of 25 mm or more but not more than 150 mm, consisting of glass or plastic lenses, with a diameter of 60 mm or more but not more than 190 mm	0 %	31.12.2018
ex 9002 11 00	70	Lenses  — measuring not more than 180 mm×100 mm×100 mm at a maximum focal length of more than 200 mm,  — with an etendue of 7 steradian mm² or better, and  — with a zoom ratio of 16 times of a kind used for the production of visualizers or live image cameras	0 %	31.12.2017
ex 9002 20 00	10	Filter, consisting of a plastic polarising membrane, a glass plate and a transparent protective film, mounted on a metal frame, for use in the manufacture of products falling within heading 8528 (1)	0 %	31.12.2018
ex 9002 90 00	20	Lens, mounted, having a fixed focal length of 3,8 mm ( $\pm 0,19$ mm) or 8 mm ( $\pm 0,4$ mm), with a relative aperture of F2.0 and a diameter of not more than 33 mm, for use in the manufacture of charged-coupled (CCD) cameras <sup>(1)</sup>	0 %	31.12.2018
ex 9002 90 00	30	Optical unit, comprising 1 or 2 rows of optical glass fibres in the form of lenses and with a diameter of 0,85 mm or more but not more than 1,15 mm, embedded between 2 plastic plates	0 %	31.12.2018
ex 9002 90 00	40	Mounted lenses made from infrared transmitting chalcogenide glass, or a combination of infrared transmitting chalcogenide glass and another lens material	0 %	31.12.2017
ex 9012 90 90	10	Energy filters, to be installed on the column of electron microscopes	0 %	31.12.2016
ex 9013 20 00	10	Carbon dioxide laser, stimulated by high frequency, having an output power of 12 W or more, but not more than 200 W	0 %	31.12.2018
ex 9013 20 00	20	Laser head assemblies for use in the manufacture of measuring or checking machines for semiconductor wafers or devices	0 %	31.12.2018
ex 9013 20 00	30	Laser for use in the manufacture of measuring or checking machines for semiconductor wafers or devices	0 %	31.12.2018
ex 9022 90 00	10	Panels for x-ray apparatus (x-ray flat panel sensors/x-ray sensors) consisting of a glass plate with a matrix of thin-film transistors, covered with a film of amorphous silicon, coated with a scintillator layer of caesium iodide and a metallised protective layer, with an active surface of 409,6 mm² $\times$ 409,6 mm² and a pixel size of 200 $\mu$ m² $\times$ 200 $\mu$ m²	0 %	31.12.2018
ex 9025 80 40	30	Electronic barometric semiconductor pressure sensor in a housing, mainly consisting of  — a combination of one or more monolithic application-specific integrated circuits (ASIC) and  — at least one or more microelectromechanical sensor elements (MEMS) manufactured with semiconductor technology, with mechanical components arranged in three-dimensional structures on the semiconductor material	0 %	31.12.2018
ex 9027 10 90	10	Sensor element for gas or smoke analysis in motor vehicles, essentially consisting of a zirconium-ceramic element in a metal housing	0 %	31.12.2018
ex 9029 10 00	20	Device for measuring wheel speed in vehicles (semi-conductor wheel speed sensor), consisting of:  — a monolithic integrated circuit in a housing, and  — one or more discrete SMD capacitors connected in parallel to the integrated	0 %	31.12.2018

CN code	TARIC	Description		Date foreseen for mandatory review
		circuit  — whether or not with integrated permanent magnets for detecting the movement of a pulse generator		
ex 9031 80 34	30	Apparatus for measuring the angle and direction of rotation of motor vehicles, consisting of at least one yaw rate sensor in the form of a monocrystalline quartz, whether or not combined with one or more measuring sensors, the whole contained in a housing	0 %	31.12.2018
ex 9031 80 38	10	Acceleration measurement device for automotive applications, comprising one or more active and/or passive elements and one or more sensors, the whole contained in a housing	0 %	31.12.2018
ex 9031 80 38	20	Electronic semiconductor accelerometer in a housing, mainly consisting of  — a combination of one or more monolithic application-specific integrated circuits (ASIC) and  — one or more microelectromechanical sensor elements (MEMS) manufactured with semiconductor technology, with mechanical components arranged in three-dimensional structures on the semiconductor material to be fitted in products under chapter 84 - 90 and 94	0 %	31.12.2018
ex 9031 90 85	20	Assembly for a laser align sensor, in the form of a printed circuit comprising optical filters and a charge-coupled image (CCD) sensor, the whole contained in a housing	0 %	31.12.2018
ex 9032 89 00	20	Automotive airbag shock-sensor, comprising a contact capable of switching a current of 12 A at a voltage of 30 V, having a typical contact resistance of 80 mOhm	0 %	31.12.2018
ex 9032 89 00	30	Electronic controller of electric power steering (EPS controller)	0 %	31.12.2018
ex 9032 89 00	40	Digital valve controller for controlling liquids and gases	0 %	31.12.2017
ex 9401 90 80	10	Ratchet disk of a kind used in the manufacture of reclining car seats		31.12.2015
ex 9401 90 80	20	Sidemember with a thickness of 0,8 or more but not more than 3,0 mm, used in the manufacture of reclining car seats		31.12.2018
ex 9401 90 80	30	Steel bracket for mounting safety features seats with thickness of 1 mm or more but not more than 2.5 mm used in the manufacture of reclining car seats		31.12.2018
ex 9401 90 80	40	Steel handles for controlling the seat adjustment mechanism used in the manufacture of reclining car seats	0 %	31.12.2018
ex 9405 40 35	10	Electric light assembly of synthetic material containing 3 fluorescent tubes (RBG) of a diameter of 3,0 mm ( $\pm$ 0,2 mm), of a length of 420 mm ( $\pm$ 1 mm) or more but not more than 600 mm ( $\pm$ 1 mm), for the manufacture of goods of heading 8528 <sup>(1)</sup>	0 %	31.12.2018
ex 9405 40 39	10	Ambient light module with a length of 300 mm or more but not more than 600 mm, based on a light engine of a series of 3 or more but not more than 9 specific one chip red green and blue light emitting diodes mounted on a PCB, with light coupled to the front and/or back of the flat TV set	0 %	31.12.2018
ex 9405 40 39	20	LED array of white silicone, containing:  — an LED matrix module measuring 38,6 mm × 20,6 mm (±0,1 mm), equipped with 128 red and green LED chips, and  — a flexible printed circuit board, equipped with a Negative Temperature Coefficient Thermistor	0 %	31.12.2018
ex 9405 40 39	60	LED components (equipped with light emitting diodes) fitted with  — a plastic casing,  — one or more light emitting diode chips either chips manufactured using thin-	0 %	31.12.2018

CN code	TARIC	Description		Date foreseen for mandatory review
ex 9405 40 99	06	film technology or so-called sapphire emitter chips and  — one or more optional semiconductor chips with electric protection function.  — for use in the manufacture of lighting gear employed for general lighting purposes  (1)  LED components (equipped with light emitting diodes) fitted with  — a casing made of ceramic or circuit board material,  — one or more light emitting diode chips either chips manufactured using thin-film technology or so-called sapphire emitter chips  — one or more optional semiconductor chips with electric protection function  — for use in the manufacture of lighting gear employed for general lighting purposes  (1)		31.12.2018
ex 9503 00 75 ex 9503 00 95	10 10	Plastic cable car scale models, whether or not with a motor, for printing (1)		31.12.2015
ex 9608 91 00	10	Non-fibrous plastic pen-tips with an internal canal		31.12.2018
ex 9608 91 00	20	Felt tips and other porous-tips for markers, without internal canal		31.12.2018
ex 9612 10 10	10	Ribbons of plastic with segments of different colours, providing the penetration of dyes by heat into a support (so called dye-sublimation)		31.12.2018

<sup>(1)</sup> Suspension of duties is subject to Articles 291 to 300 of Commission Regulation (EEC) No 2454/93 (OJ L 253 11.10.1993, p. 1).

<sup>(2)</sup> However, the measure is not allowed where processing is carried out by retail or catering undertakings.

<sup>(3)</sup> The specific duty shall apply.

A surveillance of imports of goods covered by this tariff suspension shall be established in accordance with the procedure laid down in Article 308d of the Commission Regulation (EEC) No 2454/93.

CUS (Customs Union and Statistics Number) is assigned to each ECICS record (product). ECICS (European Customs Inventory of Chemical Substances) is an information tool managed by the European Commission, General Directorate for Taxation and Customs Union. More information can be found via the following link: http://ec.europa.eu/taxation\_customs/common/databases/ecics/index\_en.htm

## **ANNEX II**

ex 6909 19 00	15	Number of Items
		(p/st)
ex 7020 00 10	10	p/st
ex 7616 99 90	77	p/st
ex 7326 90 98	40	p/st
ex 6909 19 00	80	p/st
ex 7006 00 90	70	p/st
ex 7009 91 00	10	p/st
ex 7011 10 00	10	p/st
7011 20 00		p/st
ex 7320 90 10	91	p/st
ex 7325 99 10	20	p/st
ex 7604 21 00 ex 7604 29 90	10 30	p/st p/st
ex 7613 00 00	20	p/st
ex 7616 99 90	15	p/st
ex 7616 99 90	70	p/st
ex 8482 80 00	10	p/st
ex 8803 30 00	40	p/st
ex 7616 99 90	75	p/st
ex 8108 90 90	20	p/st
ex 9003 90 00	10	p/st
ex 8207 30 10	10	p/st
ex 8301 60 00 ex 8413 91 00	10 20	p/st
ex 8419 90 85	20	p/st
ex 8438 90 00 ex 8468 90 00	10 10	p/st
ex 8476 90 00	10	p/st
ex 8479 90 80 ex 8481 90 00	87 20	p/st
ex 8503 00 99	45	
ex 8515 90 00 ex 8531 90 85	20 20	p/st
ex 8536 90 85 ex 8543 90 00	96 50	p/st
ex 8708 91 99	50 10	p/st
ex 8708 99 97	30	p/st
ex 9031 90 85	30	p/st
		p/st
		p/st

CN code	TARIC	Supplementary unit
		p/st
ex 8309 90 90	10	p/st
ex 8405 90 00	10	p/st
ex 8409 91 00	10	p/st
ex 8409 99 00	20	p/st
ex 8409 99 00 ex 8479 90 80	10 85	p/st
		p/st
ex 8411 99 00	30	p/st
ex 8414 90 00	20	p/st
ex 8414 90 00	30	p/st
ex 8414 90 00	40	p/st
ex 8415 90 00	20	p/st
ex 8418 99 10	50	p/st
ex 8418 99 10	60	p/st
ex 8421 99 00	91	p/st
ex 8421 99 00	93	p/st
ex 8422 30 00 ex 8479 89 97	10 30	p/st
CX 6477 67 77	30	p/st
ex 8431 20 00	30	p/st
ex 8439 99 00	10	p/st
ex 8467 99 00	10	p/st
ex 8536 50 11	35	p/st
ex 8477 80 99	10	p/30
		p/st
ex 8479 89 97	40	p/st
ex 8479 89 97 ex 8479 90 80	50 80	p/st
		p/st
ex 8481 30 91	91	p/st
ex 8481 80 59	10	p/st
ex 8481 80 69	60	p/st
ex 8481 80 79	20	p/st
ex 8481 80 99	50	p/st
ex 8481 80 99	60	p/st

CN code	TARIC	Supplementary unit
ex 8483 30 38	30	p/st
ex 8483 40 29	50	p/st
ex 8483 40 51	20	p/st
ex 8483 40 59	20	p/st
ex 8483 40 90	80	p/st
ex 8503 00 91 ex 8503 00 99	31 32	p/st
		p/st
ex 8503 00 99	31	p/st
ex 8503 00 99	33	p/st
ex 8503 00 99	34	p/st
ex 8503 00 99	35	p/st
ex 8503 00 99	40	p/st
ex 8504 40 82	40	p/st
ex 8504 40 82	50	p/st
ex 8504 40 90	20	p/st
ex 8504 40 90	30	p/st
ex 8504 40 90	40	p/st
ex 8504 50 95	20	p/st
ex 8504 50 95	30	p/st
ex 8504 50 95	40	p/st
ex 8504 50 95	50	p/st
ex 8504 90 11	10	p/st
ex 8505 11 00	31	p/st
ex 8505 11 00	33	p/st
ex 8505 11 00	35	p/st
ex 8505 11 00	40	p/st
ex 8505 11 00	50	p/st
ex 8505 20 00	30	p/st
ex 8505 90 20	91	p/st
ex 8507 90 80	70	p/st
ex 8508 70 00	10	p/st
ex 8537 10 99	96	p/st
		l

CN code	TARIC	Supplementary unit
ex 8516 90 00	60	p/st
ex 8516 90 00	70	p/st
ex 8518 30 95	20	p/st
ex 8518 90 00	91	p/st
ex 8522 90 49	50	p/st
ex 8522 90 49 ex 8529 90 65	60 25	p/st
		p/st
ex 8522 90 49 ex 8529 90 65	65 40	p/st
		p/st
ex 8522 90 49	70	p/st
ex 8522 90 80	15	p/st
ex 8522 90 80 ex 8529 90 92	30 30	p/st
		p/st
ex 8522 90 80	65	p/st
ex 8522 90 80	70	p/st
ex 8522 90 80	75	p/st
ex 8522 90 80	80	p/st
ex 8522 90 80	81	p/st
ex 8522 90 80	83	p/st
ex 8522 90 80	84	p/st
ex 8522 90 80	85	p/st
ex 8522 90 80	95	p/st
ex 8522 90 80	96	p/st
ex 8522 90 80 ex 8529 90 65	97 50	p/st
		p/st
ex 8529 10 80	20	p/st
ex 8529 10 80	35	p/st
ex 8529 10 80	50	p/st
ex 8529 10 80	60	p/st
ex 8529 90 65 ex 8548 90 90	30 44	p/st
3.1 00 10 70 70		p/st
ex 8529 90 65	45	p/st
ex 8529 90 65	55	p/st

CN code ex 8529 90 65	TARIC	Supplementary unit
	60	p/st
ex 8529 90 65	65	p/st
ex 8529 90 65	70	p/st
ex 8529 90 65	75	p/st
ex 8529 90 92	25	p/st
ex 8529 90 92	32	p/st
ex 8529 90 92	40	p/st
ex 8529 90 92	41	p/st
ex 8529 90 92	42	p/st
ex 8529 90 92	43	p/st
ex 8529 90 92	44	p/st
ex 8529 90 92	45	p/st
ex 8529 90 92	46	p/st
ex 8529 90 92	47	p/st
ex 8529 90 92	48	p/st
ex 8529 90 92	49	p/st
ex 8536 69 90	83	
		p/st
ex 8529 90 92	50	p/st
ex 8529 90 92	70	p/st
ex 8529 90 92	80	p/st
ex 9405 40 39	40	p/st
ex 8529 90 97	60	p/st
ex 8531 80 95	40	p/st
ex 8535 90 00	20	p/st
ex 8535 90 00 ex 8536 50 80	30 83	p/st
		p/st
ex 8536 30 30	11	p/st
ex 8536 49 00	91	p/st
ex 8536 50 11	31	p/st
ex 8536 50 11	32	p/st
ex 8536 50 19	91	p/st
ex 8536 50 19 ex 8536 50 80	93 97	p/st
		p/st
1		1

CN code	TARIC	Supplementary unit
ex 8536 50 80	81	p/st
ex 8536 50 80	82	p/st
ex 8536 50 80	93	p/st
ex 8536 50 80	95	p/st
ex 8536 50 80	98	p/st
ex 8536 69 90	51	p/st
ex 8536 69 90	81	p/st
ex 8536 69 90	82	p/st
ex 8536 69 90	84	p/st
ex 8536 69 90	85	p/st
ex 8536 69 90	86	p/st
ex 8536 69 90	87	p/st
ex 8536 69 90	88	p/st
ex 8536 70 00	10	p/st
ex 8536 70 00	20	p/st
ex 8536 90 85	92	p/st
ex 8536 90 85	94	n/at
ex 8544 49 93	10	p/st p/st
ex 8536 90 85	97	p/st
ex 8537 10 91	30	p/st
ex 8537 10 99	92	p/st
ex 8537 10 99	93	p/st
ex 8537 10 99	94	
ex 8543 70 90	20	p/st p/st
ex 8537 10 99	95	
ex 8543 70 90	25	p/st p/st
ex 8537 10 99	97	p/st
ex 8538 90 99	92	p/st
ex 8540 91 00	32	p/st
ex 8540 91 00	40	p/st
ex 8540 91 00	50	p/st
ex 8540 91 00	96	p/st
		F. Se

CN code ex 8543 70 90	TARIC	Supplementary unit
	30	p/st
ex 8543 70 90	35	p/st
ex 8543 70 90	40	p/st
ex 8543 70 90	45	p/st
ex 8543 70 90	55	p/st
ex 8543 70 90	60	p/st
ex 8543 70 90	65	p/st
ex 8543 70 90	80	p/st
ex 8543 70 90	85	p/st
ex 8543 70 90	90	p/st
ex 8543 70 90	95	p/st
ex 8543 90 00	20	p/st
ex 8543 90 00	30	p/st
ex 8543 90 00	40	p/st
ex 8544 42 90	10	p/st
ex 8545 19 00	20	p/st
ex 8547 10 00	10	p/st
ex 8548 90 90	41	p/st
ex 8548 90 90	43	p/st
ex 8548 90 90	47	p/st
ex 8548 90 90	48	p/st
ex 8548 90 90	49	p/st
ex 8548 90 90	50	p/st
ex 8708 30 91	10	p/st
ex 8708 99 97	20	p/st
ex 8803 30 00	50	p/st
ex 9001 90 00	75	p/st
ex 9002 90 00	20	p/st
ex 9002 90 00	30	p/st
ex 9002 90 00	40	p/st
ex 9012 90 90	10	p/st
ex 9013 20 00	10	p/st
ex 9013 20 00	20	p/st
		•

CN code	TARIC	Supplementary unit
ex 9013 20 00	30	p/st
ex 9022 90 00	10	p/st
ex 9031 80 34	30	p/st
ex 9031 80 38	10	p/st
ex 9031 90 85	20	p/st
ex 9032 89 00	20	p/st
ex 9032 89 00	30	p/st
ex 9032 89 00	40	p/st
ex 9401 90 80	10	p/st
ex 9405 40 35	10	p/st
ex 9405 40 39	10	p/st
ex 9405 40 39	20	p/st
ex 9503 00 75 ex 9503 00 95	10 10	p/st
		p/st
ex 3919 90 00	36	Square meter (m <sup>2</sup> )
ex 3919 90 00	44	m <sup>2</sup>
ex 3920 49 10	95	m <sup>2</sup>
ex 3921 90 60	95	m <sup>2</sup>
ex 5603 11 10	10	m <sup>2</sup>
ex 5603 11 10	20	m <sup>2</sup>
ex 5603 11 90	10	m <sup>2</sup>
ex 5603 11 90	20	m <sup>2</sup>
ex 5603 12 10	10	m <sup>2</sup>
ex 5603 12 90	10	$m^2$
ex 5603 12 90	50	m <sup>2</sup>
ex 5603 12 90	60	m <sup>2</sup>
ex 5603 12 90	70	$m^2$
ex 5603 13 10	10	m <sup>2</sup>
ex 5603 13 10	20	m <sup>2</sup>
ex 5603 13 90	60	m <sup>2</sup>
ex 5603 13 90	70	m <sup>2</sup>
ex 5603 14 10	10	m <sup>2</sup>

CN code	TARIC	Supplementary unit
ex 5603 14 90	30	m <sup>2</sup>
ex 5603 91 10	10	$m^2$
ex 5603 91 90	10	m <sup>2</sup>
ex 5603 92 10	10	m <sup>2</sup>
ex 5603 92 90	10	m <sup>2</sup>
ex 5603 92 90	40	m <sup>2</sup>
ex 5603 92 90	80	m <sup>2</sup>
ex 5603 93 90	10	m <sup>2</sup>
ex 5603 93 90	50	m <sup>2</sup>
ex 3824 90 97	90	Cubic Metre (m³)
ex 3901 10 90	20	m <sup>3</sup>
ex 3901 20 90	10	m <sup>3</sup>
ex 3902 10 00	50	m <sup>3</sup>
ex 3903 11 00	10	m <sup>3</sup>
ex 3903 90 90	10	m <sup>3</sup>
ex 3907 40 00	50	m <sup>3</sup>
ex 3907 40 00	60	m <sup>3</sup>
ex 3907 60 80	40	m <sup>3</sup>
ex 3920 20 80	95	m <sup>3</sup>
ex 5402 49 00	70	Metre (m)
ex 3215 19 00	20	Litre (l)
ex 3824 90 97	46	1